



# دهانات الجوهرة

## ALJAWHARA PAINTS

### EXTERIOR SEALER

It is Super Sealer suitable for exterior use and based on styrene binder that provides extra strength and adhesion to the paint on the surfaces. It is easy to apply on concrete, gypsum & bricks.

### PHYSICAL DATA

Appearance	: Matt white emulsion Sealer
Binder	: Styrene acrylic
Specific Gravity	: 1.45 Kg / Ltr.
Drying Time	{ Dust Dry: 45 min. } { Hard Dry: 2 hours } Depends on Temperature & Humidity
Flammability	: Non-Flammable
Coverage	: 10- 12 sq.m / Ltr. (at 30 microns Dft)

### PHYSICAL DATA

Tools	: Roller, brush or air spray
Dilution	: Add water
Dilution %	: About 5%
Storage Period	: 18 months in a cool place away from heat sources & direct sunshine.

### BEFORE PAINTING OPERATION:

- The surface to be painted must be clean, non-crusty and free from dirt, loose materials, dust and grease
- To ensure good results, apply several layers
- Prepare perfectly the surface to be painted before painting operation
- Cleaning of used Tools By Water.



الشركة الكيماوية للتشكيلات الملونة المحدودة  
Chemical Company for Colour Assortement LTD.



[www.aljawharapaints.com](http://www.aljawharapaints.com)

[info@aljawharapaints.com](mailto:info@aljawharapaints.com)

Kingdom of Saudi Arabia TollFree 920000008

المملكة العربية السعودية الرقم الموحد: ٩٢٠٠٠٠٠٠٨