# ColorWorks® C7500G Inkjet label printer





## High-speed, batch near-prime color label printer, for on-demand gloss labels.

**Reliable performance** — rugged design means minimal maintenance and a low overall cost of ownership; ideal for busy, on-demand environments

**Astounding image quality** — PrecisionCore® inkjet technology and UltraChrome® DL inks from Epson; delivers vibrant, accurate colors, smooth gradations, precise barcodes and ultra sharp text

**High-speed, on-demand color printing** — speed through multiple full-color labels with variable data up to 11.8" per second<sup>1</sup>

**Powerful productivity** — Just in Time Color<sup>™</sup> printing for high-volume glossy labeling applications

**Low cost of labeling** — up to 50 percent lower printing costs than with laser and thermal transfer printers for high-durability color labels<sup>2</sup>

**Seamless integration** — built-in ZPL-II emulation with the ability to automatically merge color artwork from memory eliminates the need for pre-printed labels in traditional thermal transfer applications

**Highly efficient** — high-yield ink cartridges mean fewer user interventions and less waste than most thermal transfer printers; easy to change, so there's less downtime

Contact Us: 855-848-4332 sales@vividdatallc.com VividDataGroup.com





### ColorWorks® C7500G Inkjet label printer

#### **Printer**

Print method: PrecisionCore TFP® with Nozzle Verification

echnology

Ink type: UltraChrome DL, 4 individual CMYK cartridges

Print resolution: 1200 x 600 dpi Print speed: 300 mm/s Print width: 4.25" (108 mm) max.

**Media types:** Roll-fed or fan-fold, die cut; single layer or adhesive labels on liner; plain paper, fine paper, PET film,

synthetic

#### **Media Dimensions**

**Width:** 1.97" (50 mm) minimum -4.41" (112 mm) maximum **Thickness:** .005" -.009" (0.129-0.236 mm) **Roll size 0.D.:** Maximum label length 23.6" (1600 mm)

Core diameter: 3" (76 mm) Media sensors: Gap, black mark Die-cut label gap: Min. 0.12" (3.0 mm)

**Black mark size:** Min. 1.1" x 0.2" (28 mm x 5 mm) (W x H)

#### General

Interfaces: USB 2.0 High-speed, Ethernet 10/100 BASE-T Operating system: Microsoft® Windows® 8.1 (32-bit, 64-bit), Windows 8 (32-bit, 64-bit), Windows 7 SP1 (32-bit, 64-bit), Windows Vista® SP2 (32-bit, 64-bit), Windows XP SP3 (32-bit), Windows Server® 2012 R2, Windows Server 2012, Windows Server 2008 R2, Windows 20

**Direct command based printing:** Zebra® ZPL II™ native language support; plus command extensions to allow for colorization of data. Epson ESC/Label color command language.

#### **General (continued)**

Barcode font: UPC-A, UPC-E, JAN13(EAN), JAN8(EAN), Code39, ITF, Codabar, Code93, Code128, GS1-128, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded

Two-dimensional code printing: PDF417, QR Code, Maxi Code, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded Stacked, DataMatrix, Aztec Code, MicroPDF417, Micro QR Code

**Operating temperature** 

5 to 35  $^{\circ}$ C  $^{-}$  / 20  $^{-}$  80% RH humidity

Storage temperature

-20 to 60 °C / 5 - 85% RH humidity

**Overall dimensions** 

15.4" x 23.5" x 15.5" (W x D x H)

Weight

Approximately 37.0 kg (81.57 lb) (without ink)

Power consumption

50 – 60 W Printing (average printing) 4.1 – 4.4 W Standby 0.2 – 0.5 W Power Off state

Rated voltage AC 100 - 240 VAC

Rated frequency

50 - 60 Hz

Acoustic noise approx.

55 dBA

**EMI** 

FCC / ICES-003 Class B

Safety standards

UL60950-1/CSA C22.2 No.60950-1

**Printer durability** 

Printhead 5 years

Feeding mechanism 500 Km before major service

Warranty

One year depot repair

#### What's in the Box

ColorWorks C7500G printer, AC power cord, full capacity ink cartridges, sample label roll, instruction sheet, CD with utilities and manuals

#### **Ordering Information**

 TM-C7500-011 4 inch-color label printer- Gloss
 C31CD64311

 TU-RC7508-471 Take Up Unit Option for C7500 / C7500G
 C32C8154471

 SUIC30P (B) Black Ink — Gloss
 C33S020635

 SUIC30P (C) Cyan Ink — Gloss
 C33S020636

 SUIC30P (M) Magenta Ink — Gloss
 C33S020637

 SUIC30P (Y) Yellow Ink — Gloss
 C33S020638

 SUMB7500 Maintenance Box
 C33S020596

	C7500	C7500G
Ink Type	SJIC26P DURABrite® Ultra	SJIC30P UltraChrome DL
Media		
Plain paper – uncoated	Richer image – darker black	Good image – sharp colors
Matte paper – coated	Richer image – darker black	Good image – sharp colors
Matte synthetic – coated	Richer image – darker black – BS5609	Good image – sharp colors
Low gloss paper – coated	Good image – sharp colors	Best image
Semi-gloss paper – coated	Not supported	Best image
High gloss paper – coated	Not supported	Best image
High gloss synthetic – coated	Not supported	Best image

1 Printing in full 1200 x 600 resolution with Flush-onto-Paper mode enabled. With Flush-onto-Paper mode disabled, print speed is up to 10.4" per second. | 2 Up to 50 percent lower printing cost than competitive color laser printers and thermal transfer printers using full resin ribbons available in July 2014. Calculation based on continuous printing of GHS-certified color labels using the suite of ISO/IEC 24712 text and graphics images, with highest-capacity cartridges purchased at MSRP. Actual costs will vary based on print task and use conditions.







**Epson America, Inc.**Sepson Canada Limited

Sepson Canada Limited

185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON, ColorWorks, DURABrite, Precision Core, TFP and UltraChrome are registered trademarks and EPSON Exceed Your Vision is a registered logomark of Seiko Epson Corporation. Just in Time Color is a trademark of Epson America, Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2016, Epson America, Inc. CPD-51160 1/16

