



دهانات الجوهرة ALJAWHARA PAINTS

JAWHARA STUCCO

High quality putty suitable for interior use on gypsum, wood and cement surfaces. It makes a very smooth finish, and gives a silky, blinking texture surface. No maintenance needed, and it is not over painted.

PHYSICAL DATA

Appearance	: Dense thick paste.
Color	: All colors available.
Binder	: Copolymer, and special resins.
Specific Gravity	: About 1.35 Kg / Ltr
Drying Time	{ Dust dry: 45 mins. } { Hard dry: 2 hour. } Depends on Temperature & Humidity
Flammability	: Non - Flammable

APPLICATION DATA

Tools	: Putty knife or trowel.
Dilution	: With water.
Dilution %	: As required.
Coverage	: 5 m ² / 20 kg. : (at 400 microns. DFT)
Storage	: 18 months in a cool, Dry Place Away from heat Sources & Direct Sunshine

BEFORE PAINTING OPERATION:

- The surface to be painted must be clean, non-crusty and free from dirt, loose materials, dust and grease.
- Suitable for use on all cement and wooden surfaces.
- To ensure good results, apply several layers.
- Prepare perfectly the surface to be with sealer before painting operation.
- Cleaning of used tools By water.



الشركة الكيماوية للتشكيلات الملونة المحدودة
Chemical Company for Colour Assortement LTD.



www.aljawharapaints.com

info@aljawharapaints.com

Kingdom of Saudi Arabia TollFree 920000008

المملكة العربية السعودية الرقم الموحد: ٩٢٠٠٠٠٠٠٨