

Rev.date: 28.10.2015

Rev. N.: 0

Mod: 4.1.2. UK

**1. TRADE NAME: ECOTRAP QUADRO + TUNNEL FOR ECOTRAP QUADRO**

Monitoring device for the following target pests: *Mus musculus musculus*, *Mus musculus domesticus* and other small rodents.

Monitoring device for the IPM application complying with UNI EN 16636:2015 Regulation, that must be applied to control regularly the pests presence in a specific place for a defined time.

**2. CODE: P-02013 + P-02047****3. PICTURES:****4. TECHNICAL SPECIFICATIONS:**

Ecotrap Quadro is a monitoring device (glue trap)

It is composed of:

- Black thermoformed plastic tray;
- Banana flavored glue;
- Thermoformed plastic tunnel (optional) for protecting Ecotrap Quadro from dust and water.

**Trap size:**

- **Length:** 126 mm
- **Width:** 120 mm
- **Heigh:** 12 mm

**Tunnel size:**

- **Length:** 128 mm
- **Width:** 123 mm
- **Heigh:** 50 mm

Rev.date: 28.10.2015

Rev. N.: 0

Mod: 4.1.2. UK

**Glue Quantity in Ecotrap Quadro:** 18 g**Colour:** As in the picture

## 5. HOW TO USE:

**Place Ecotrap Quadro in the following places:**

- Near cable trough and electric boards, dishwashers, doors and slots, lofts, storehouses, producing departments, cellars, garages, workshops, etc.;
- Along the rooms perimeters to be disinfested and along the rodent habitual paths, which can be identified through excrements, fur, dens, paw prints, etc..
- Along the walls.

We suggest you to give a number to each trap and indicate its placement in the monitored area plan, in order to facilitate the check during the periodic monitoring.

**Theoretical covered area:** at a distance of 5-10 meters the one from the other, according to the assumed pest infestation.

**Suggested monitoring period:** all the year long, especially in the period between October and April, in which it is registered peaks due to the external temperature reduction.

**Suggested frequency of the controls:** weekly. Change the trap after two months (at the latest) or before according to the pest infestation or the presence of dust and water in the environment.

The use of the trap in a dusty place could reduce the product functionality over time. For this reason we suggest its use with Tunnel for Ecotrap Quadro (code P-02047).

**Storage conditions:** in a cool and dry room, temperature below 25°C and R.H. below 55%.  
If well stored (intact packaging), the product shell life is 3 years.

## 6. PACKAGING AND SPARE PARTS:

*Ecotrap Quadro:*

Case: 50 packs (sales unit). Every pack contains 4 pieces, for a total of 200 traps/case.

Pallet: 6.400 pc/pallet; 32 cases/pallet; pallet dimension: 80 x 120 x 175 cm (h)

Rev.date: 28.10.2015

Rev. N.: 0

Mod: 4.1.2. UK

*Tunnel for Ecotrap Quadro:*

Pack: bulk

Case: 100 pieces (sales unit).

Pallet: 3.200 pc/pallet; 32 cases/pallet; pallet dimension: 80 x 120 x 175 cm (h)

## 7. DISPOSAL CONSIDERATIONS

Waste disposal should be in accordance with existing Community, National and local regulations.