

Product Data Sheet: SphereCel GF



SPHERE CEL[®]

LAMINATE BULKER

- ◆ Fiberglass-based laminate bulker

CHARACTERISTICS

- ◆ Very fast resin absorption
- ◆ Jointless overlapping
- ◆ For flat and two-dimensional laminates
- ◆ Outstanding surface quality
- ◆ Excellent bonding with covering fiberglass layers

INDUSTRIES

- ◆ Marine: hulls, decks and structures of boats and yachts
- ◆ Transportation: parts and panels of cars, trailers, trucks and RVs
- ◆ Mass transit: interior and exterior of trains, light rail, buses, ferry
- ◆ Leisure: kayaks, surfboards, pools, bath tubs
- ◆ Industrial: architectural panels, fans, containers, tanks

PROCESSING

- ◆ Hand lay up
- ◆ Wet pressing
- ◆ Panel production

Product Data Sheet: SphereCel GF

Product Description:	Non-woven core material				
Base material:	Glass veil, volumized with thermoplastic microspheres				
Thickness: (+/- 10%)	1.2 mm	2 mm	3 mm	4 mm	5 mm
Weight: (+/- 15%)	55 g/m ²	65 g/m ²	80 g/m ²	95 g/m ²	110 g/m ²
Width: (+ 40 / - 20 mm) <i>Up to 300 cm possible</i>	100 cm	100 cm	100 cm	100 cm	100 cm
Roll length:	100 m	70 m	50 m	40 m	35 m
Weight per roll: (approx.)	5.5 kg	4.6 kg	4.0 kg	3.8 kg	3.9 kg
Packaging:	Plastic bag				
Storage:	To be stored in original packaging, in well-ventilated rooms, at moderate temperature. Keep away from humidity.				