



دهانات الجوهرة

ALJAWHARA PAINTS

SUPER FLAT ENAMEL

it is super matt paint based on modified resin to give good coverage & climatic resistance it is used for interior & exterior application it is easy to apply on concrete, wood, steel and gypsum surfaces.

PHYSICAL DATA

| | |
|------------------|--|
| Appearance | : flat enamel paint |
| Color | : White color and other colors. |
| Binder | : Modified alkyd and some solvents |
| Specific Gravity | : Approx: 1.38 kg / Ltr. |
| Drying Time | { Dust Dry: 2 hours } { Hard Dry: 6 hours } Depends on Temperature & Humidity |
| Next Coat: | after one day |
| Flammability | : Flammable |
| Coverage | : 10 - 12 sq.m / Ltr. (at 30 microns DFT) |

APPLICATION DATA

| | |
|----------------|---|
| Tools | : Roller, brush or air spray gun. |
| Dilution | : With white spirit. |
| Dilution % | : 5 - 10% |
| Storage Period | : 18 months in a cool place away from heat sources. |

BEFORE PAINTING OPERATION:

- The surface to be painted must be clean and free from dirt, loose materials, dust and grease
- Ensure adequate ventilation during painting
- This paint can be used as primer for wood surfaces, but for metal surfaces you must apply a layer of red iron oxide primer
- Avoid contact with eyes .
- Cleaning of used tools by thinner.



الشركة الكيماوية للتشكيلات الملونة المحدودة
Chemical Company for Colour Assortement LTD.

www.aljawharapaints.com

info@aljawharapaints.com

Kingdom of Saudi Arabia TollFree 920000008

المملكة العربية السعودية الرقم الموحد: ٩٢٠٠٠٠٠٠٨

