



دهانات الجوهرة

ALJAWHARA PAINTS

JAWHARA FIX

Jawhara fix is a special product, based on styrene acrylic, designed to strengthen the traditional mud houses against rubbing and rains, it has a good resistance to damp and moisture, also it could be over painted to give a nice, sleek look to those mud houses.

PHYSICAL DATA

Appearance	: White emulsion (Transparent)
Binder	: styrene acrylic emulsion
Specific Gravity	: About 0.98 kg / Ltr.
Drying Time	{ Dust dry: 45 mins. } { Hard dry: 1 hour } Depends on Temperature & Humidity
Next coat after	2hours
Flammability	: Non-Flammable

APPLICATION DATA

Tools	: spray gun or roller.
Dilution	: With water.
Dilution %	:10- 15%.
Coverage	: about 5 m2/ kg (two layers).
Thickness	: 100 microns DFT.
Storage	: 18 months in a cool, Dry Place Away From heat sources & Direct sun shine

BEFORE PAINTING OPERATION:

- The surface to be sprayed, to be rubbed with a piece of tissue
- Surfaces should be free of dust, though spraying water and to be left to dry.

Note:

- As it is desired to apply paint as a top coat, putty for walls could be applied to prepare the surface and make it smooth before applying the finish coat.



الشركة الكيماوية للتشكيلات الملونة المحدودة
Chemical Company for Colour Assortement LTD.

www.aljawharapaints.com

info@aljawharapaints.com



Kingdom of Saudi Arabia TollFree 920000008

المملكة العربية السعودية الرقم الموحد: ٩٢٠٠٠٠٠٠٨