

Rev.date: 29.10.2015

Rev. N.: 3

Mod: 4.1.2. UK

1. TRADE NAME: ECOTRAP RATS PLUS + TUNNEL FOR ECOTRAP RATS

Monitoring device for the following target pests: *Rattus rattus* (black rat or roof rat), *Rattus norvegicus* (common rat) and other big rodents. It can monitor even small rodents. Protection tunnel: optional.

Monitoring device for the IPM application complying with UNI EN 16636:2015 Regulation, that must be applied to control regularly the pests presence in a specific place for a defined time.

1. CODE: P-02004G40 (black tray version) + P-02004G40B (white tray version) + P-02020 (tunnel)**2. PICTURES:****3. TECHNICAL SPECIFICATIONS:**

Ecotrap Rats Plus (both colours) is a monitoring device (glue trap).

It is composed of:

- Black or white thermoformed plastic tray;
- Glue;
- Thermoformed plastic tunnel (optional) for protecting Ecotrap Rats Plus from dust and water.

The glue used for Ecotrap Rats Plus works perfectly even at very cold environmental conditions.

Trap size:

- **Length:** 252 mm
- **Width:** 122 mm
- **Height:** 12 mm

Rev.date: 29.10.2015

Rev. N.: 3

Mod: 4.1.2. UK

Tunnel size:

- **Length:** 250 mm
- **Width:** 120 mm
- **Height:** 75 mm

Glue Quantity in Ecotrap Rats Plus: 40 g**Colour:** as in the picture.**4. HOW TO USE:****Place Ecotrap Rats Plus in the following places:**

- Near cable trough and electric boards, dishwashers, doors and slots, lofts, storehouses, producing departments, cellars, garages, workshops, etc.;
- Along the rooms perimeters to be disinfested and along the rodent habitual paths, which can be identified through excrements, fur, dens, paw prints, etc..
- Along the walls.

We suggest you to give a number to each trap and indicate its placement in the monitored area plan, in order to facilitate the check during the periodic monitoring.

Theoretical covered area: at a distance of 5-10 meters the one from the other, according to the assumed pest infestation.

Suggested monitoring period: all the year long, especially in the period between October and April, in which it is registered peaks due to the external temperature reduction.

Suggested frequency of the controls: weekly. Change the trap after two months (at the latest) or before according to the pest infestation or the presence of dust and water in the environment.

The use of the trap in a dusty place could reduce the product functionality over time. For this reason we suggest its use with Tunnel for Ecotrap Rats (code P-02020).

Storage conditions: in a cool and dry room, temperature below 25°C and R.H. below 55%.
If well stored (intact packaging), the product shell life is 3 years.

Rev.date: 29.10.2015

Rev. N.: 3

Mod: 4.1.2. UK

5. PACKAGING AND SPARE PARTS:

Ecotrap Rats Plus:

Case: 50 packs (sales unit). Every pack contains 2 pieces, for a total of 100 traps/case.

Pallet: 3.200 pc/pallet; 32 cases/pallet; pallet dimension: 80 x 120 x 175 cm (h)

Tunnel for Ecotrap Rats:

Pack: bulk

Case: 100 pieces (sales unit).

Pallet: 3.200 pc/pallet; 32 cases/pallet; pallet dimension: 80 x 120 x 175 cm (h)

6. DISPOSAL CONSIDERATIONS

Waste disposal should be in accordance with existing Community, National and local regulations.