



## SPECIFICATION

## ELEPAQ CONSTANT

Model		SV28000E2	SV28000E2
Generator	Starting Watts	13000W/13.0KW = 16.25KVA @50Hz	
	Running Watts	12000W/12.0KW = 15KVA @50Hz	
	Rated AC Voltage	220,230,240V	
	Phase	Single Phase	
	Voltage regulator	AVR	
	Power Factor	1W - KW, 0.8KW - KVA	
	Alternator Type	Brush	
Engine	Engine Model	GX440	GX440
	Engine Type	Single Cylinder, 4-Stroke OHV Air Cooled	
	Displacement	440cc	
	Maximum output	15HP	
	Ignition System	Breakless Ignition Type, Flywheel Magneto	
	Starting System	Recoil/Electric	Recoil/Electric/Remote
	Fuel	Unleaded Automotive Gasoline	
	Capacity Fuel Tank	25 Litres	
	Lubricating Oil Capacity	1.1 L	
	Noise Level	82 dB @ 7 Meters	
	Air Cleaner	Polyurethane Type	
	P.T.O. shaft rotation	Counter Clockwise (Facing P.T.O.)	
Dimension	L X W X H	820 X 560 X 580 mm.	
	Dry Weight	101KG	101KG