



دهانات الجوهرة

ALJAWHARA PAINTS

SOFT TEXTURE

High quality soft texture based on acrylic, mica, quartz and titanium dioxide. Suitable for exterior and interior use to hide cracks and other defects on wall surfaces. It is easy to use on cement, concrete, Gypsum Surfaces.

PHYSICAL DATA

Appearance	: Matt Dense Paste.
Binder	: Acrylic Copolymer.
Color	: All colors
Specific Gravity	: 1.7 Kg / Ltr.
Drying Time	{ Dust Dry: 4 hours. } { Hard Dry: 10 hours } Depends on Temperature & Humidity
Flammability	: Non-Flammable
Coverage	: Approx 1.5 - 2 sq.m/ltr. (at 250 microns DFT) according to desired pattern and nature of the surface

APPLICATION DATA

Tools	: Air spray, Roller
Dilution	: Add water
Dilution %	: Max. 5%
Storage	: 18 months in a cool place away from Direct Sunshine & heat

BEFORE PAINTING OPERATION:

- The surface to be painted must be clean, non-crusty and free from dirt, loose materials, dust and grease
- Apply a coat of sealer before painting the texture coat and a gloss coat as a top coat to add shining & protection to the surface.
- Cleaning of used tools by water.



الشركة الكيماوية للتشكيلات الملونة المحدودة
Chemical Company for Colour Assortement LTD.

www.aljawharapaints.com

info@aljawharapaints.com

Kingdom of Saudi Arabia TollFree 920000008

المملكة العربية السعودية الرقم الموحد: ٩٢٠٠٠٠٠٠٨

