



دهانات الجوهرة

ALJAWHARA PAINTS

CLEAR GLOSS EMULSION

Clear gloss emulsion coat based on soft acrylic polymer, resistant to climatic factors, anti crust and easy to clean. This paint is used as a protective coat for exterior and interior white and color textures.

PHYSICAL DATA

Appearance	: Clear emulsion
Binder	: Strong bonding, clear acrylic (transparent).
Specific Gravity	: Approx 0.96 kq / Ltr.
Drying Time	{ Dust Dry: 45 minutes } { Hard Dry: 2 hours } Depends on Temperature & Humidity
Flammability	: Non-Flammable
Coverage	: 15 sq.m. / Ltr. (at 30 microns DFT)

APPLICATION DATA

Tools	: Roller, brush or air spray gun.
Dilution	: With water
Dilution %	: 5%
Storage Period	: 18 months in a cool, dry place away from heat sources & direct sunshine

BEFORE PAINTING OPERATION:

- The surface to be painted must be clean and free from dirt, loose materials, dust and grease .
- Ensure adequate ventilation during painting .
- Cleaning of used tools by water.



الشركة الكيماوية للتشكيلات الملونة المحدودة
Chemical Company for Colour Assortement LTD.

www.aljawharapaints.com

info@aljawharapaints.com

Kingdom of Saudi Arabia TollFree 920000008

المملكة العربية السعودية الرقم الموحد: ٩٢٠٠٠٠٠٠٨

