



دهانات الجوهرة

ALJAWHARA PAINTS

TORATH TEXTURE COAT

it is super texture coat, based on a strong styrene acrylic binder for exterior and interior use to mud hide the cracks and other defects on walls, also it gives the desired traditional environmental turath effect for the old-time MUD- HOUSES.

PHYSICAL DATA

Appearance	: Dens paste.
Binder	: Acrylic emulsion.
Color	: brown.
Specific Gravity	: 1.5 kg / Ltr.
Drying Time	{ Dust dry: 4 hours. } { Hard dry: 18 hours. } Depends on Temperature & Humidity Next coat after 12 hours.
Flammability	: Non-Flammable

APPLICATION DATA

Tools	: Rubber gloves.
Dilution	: With water.
Dilution %	: 5%
Coverage	: Approx. 6m ² / 25Kg. durm.
Dry layer thickness	: 200- 300 microns.
Storage	: 18 months on cool place away from direct sunshine & heat sources.

BEFORE PAINTING OPERATION:

- The surface to be covered must be clean, non-crusty and free from dirt, loose materials, dust and grease.
- Sanding is not required.
- It could be mixed with {straw pack} - included by the drum.
- Cleaning of used tools by water.



الشركة الكيماوية للتشكيلات الملونة المحدودة
Chemical Company for Colour Assortement LTD.

www.aljawharapaints.com

info@aljawharapaints.com



Kingdom of Saudi Arabia TollFree 920000008

المملكة العربية السعودية الرقم الموحد: ٩٢٠٠٠٠٠٠٨