



# دهانات الجوهرة

## ALJAWHARA PAINTS

### EXTERIOR EMULSION%100

It is High Quality Exterior Emulsion Specially Formulated to Enhance Excellent Washability & Weathering Resistance. It is Easy to Apply on All Exterior Surfaces Like Cement, Concrete Bricks.

### PHYSICAL DATA

Appearance	: Matt emulsion
Color	: White & Other Colors
Specific Gravity	: 1.45 Kg / ltr.
Drying Time:	{ Dust Dry: 45 min. } { Hard Dry: 1 hour } Depends on Temperature & Humidity
	Second coat after 2 hours
Flammability	: Non-Flammable
Coverage	: 10- 12 sq. m / Ltr. (At 30 microns Dft)

### PHYSICAL DATA

Tools	: Roller, brush or air spray
Dilution	: Add water
Dilution %	: 5 - 10%
Storage Period	: 18 months in a cool place away from Direct Sunshine

### BEFORE PAINTING OPERATION:

- The surface to be painted must be clean and free from dirt, loose materials, dust and Grease
- Apply putty & a sealer coat before painting the exterior Emulsion as a top coat.
- Cleaning of used Tools By Water.



الشركة الكيماوية للتشكيلات الملونة المحدودة  
Chemical Company for Colour Assortement LTD.



[www.aljawharapaints.com](http://www.aljawharapaints.com)

[info@aljawharapaints.com](mailto:info@aljawharapaints.com)

Kingdom of Saudi Arabia TollFree 920000008

المملكة العربية السعودية الرقم الموحد: ٩٢٠٠٠٠٠٠٨