



دهانات الجوهرة

ALJAWHARA PAINTS

SEMI GLOSS ENAMEL

This paint is based on modified alkyd and titanium dioxide and other substances. It is suitable for interior and exterior use, soft, durable and resistant to climatic factors it is easy to apply on steel, concrete, cementitious surfaces and wood.

PHYSICAL DATA

Appearance	: semi gloss enamel
Color	: White and other colors.
Base	: Modified alkyd Resin
Specific Gravity	: Approx: 1.25 Kg/Ltr.
Drying Time	{ Dust Dry: 2 hours } { Hard Dry: 4 hours } Depends on Temperature & Humidity
	Next Coat: after one day
Flammability	: Flammable
Coverage	: 12 - 13 sq.m/Litr. (at 30 microns DFT)

APPLICATION DATA

Tools	: Roller, brush or air spray
Dilution	: Use whitespirit
Dilution %	: 5 - 10%
Storage Period	: 18 months in a cool place away from Direct Flame. & Heat

BEFORE PAINTING OPERATION:

- The surface to be painted must be clean and free from dirt, loose materials, dust and grease
- Apply a primer coat for cement walls, but for metal surfaces apply a coat of red iron oxide primer
- Ensure adequate ventilation during painting.
- Cleaning of used tools by thinner.



الشركة الكيماوية للتشكيلات الملونة المحدودة
Chemical Company for Colour Assortement LTD.

www.aljawharapaints.com

info@aljawharapaints.com

Kingdom of Saudi Arabia TollFree 920000008

المملكة العربية السعودية الرقم الموحد: ٩٢٠٠٠٠٠٠٨

