# SUPER GLOSS ENAMEL

It is premium Quality top coat gloss enamel with superior opacity and durabitity, it is smooth and easy to apply for interior & exterior surfaces for all steel, wood, bricks, cementinous surfaces it has good scratch resistance.

## PHYSICAL DATA

| | |
|---|---|
| Appearance | : glossy enamel |
| Color | : White and other colors are available: |
| Specific Gravity | : Approx. 1.1 Kg/L |
| Drying Time | Dust Dry: 2 hours<br>8 hours<br>Depends on Temperature & Humidity |
| Next Coat | Next Coat: after one day |
| Coverage | : 16 sq.m/ltr (at 30 microns) DFT |
| Flammability | : Flammable |

## APPLICATION DATA

| | |
|---|---|
| Tools | : Roller, brush or air spray |
| Dilution | : Use white spirit |
| Dilution % | : 5 - 10 % |
| Storage | : 18 months in a cool place away from direct flame & Heat |

## BEFORE PAINTING OPERATION:

- The surface must be dry and free from dirt, dust and grease.
- Apply a primer coat on wood and cement surfaces before painting enamel paint.
- Apply a primer coat of on metal surfaces redoxide primer.
- Ensure adequate ventilation and use mask during painting operation.
- Cleaning of used tools by thinner.