

Product Data Sheet: SphereCel HX



SPHERE CEL®

LAMINATE BULKER

Hexagonal structure

CHARACTERISTICS

- Fast resin impregnation
- Suitable for complex geometries
- More pressure resistant than fiberglass based laminate bulker
- Compatible with all regular types of resins, incl. polyester, epoxy, vinylester

INDUSTRIES

- Marine: hulls, decks and structures of boats and yachts
- <u>Transportation</u>: parts and panels of cars, trailers, trucks and RVs
- Mass transit: trains, light rail, buses, ferry
- <u>Leisure</u>: kayaks, bath tubs
- <u>Industrial</u>: fans, containers, tanks, pipes

PROCESSING

- Hand lay up
- Winding



Product Data Sheet: SphereCel HX

| Product Description: | Non-woven core material | | |
|---|---|----------|----------|
| Base material: | Proprietary veil, volumized with thermoplastic microspheres | | |
| Thickness: (+/- 10%) | 1.5 mm | 2 mm | 3 mm |
| Weight: (+/- 15%) | 95 g/m² | 105 g/m² | 120 g/m² |
| Width: (+ 40 / - 20 mm) Up to 300 cm possible | 100 cm | 100 cm | 100 cm |
| Roll length: | 90 m | 70 m | 50 m |
| Weight per roll: (approx.) | 8.6 kg | 7.4 kg | 6.0 kg |
| Packaging: | Plastic bag | | |
| Storage: | To be stored in original packaging, in well-ventilated rooms, at moderate temperature. Keep away from humidity. | | |