



دهانات الجوهرة ALJAWHARA PAINTS

IRON OXIDE PRIMER

It is Primer for wood and steel surfaces, specially formulated to enhance anti corrosive & anti rust properties.

PHYSICAL DATA

Appearance	: flat-red Primer
Color	: RED oxide
Specific Gravity	: About 1.6 Kg/Ltr.
Drying Time	{ Dust Dry: 1 hours. } { Hard Dry: 4 hours } } Depends on Temperature & Humidity Next coat after 24 hours
Flammability	: Flammable
Coverage	: About 10 - 12 sq.m / ltr (at 50 ,microns) DFT

APPLICATION DATA

Tools	: Roller, brush or air spray
Dilution	: Add white spirit.
Dilution %	: 5%
Storage Period	: 18 months in a cool place away from fire sources

BEFORE PAINTING OPERATION:

- The surface to be painted must be clean, free from dirt, loose materials, dust and grease
- For best results apply several coats
- Suitable for use on all metal surfaces & wood.
- Clean all tools and equipment with thinner after application.
- Surfaces to be primed should be prepared by apply sand paper to remove any rust might be there.



الشركة الكيماوية للتشكيلات الملونة المحدودة
Chemical Company for Colour Assortement LTD.



www.aljawharapaints.com
Kingdom of Saudi Arabia TollFree 920000008

info@aljawharapaints.com

المملكة العربية السعودية الرقم الموحد: ٩٢٠٠٠٠٠٠٨