



Unix/Linux Command Reference

File commands

<code>ls</code>	Directory listing
<code>ls -al</code>	Formatted listing with hidden files
<code>cd dir</code>	Change directory to dir
<code>cd</code>	Change to home
<code>pwd</code>	Show current directory
<code>mkdir dir</code>	Create a directory dir
<code>rm file</code>	Delete file
<code>rm -r dir</code>	Delete directory dir
<code>rm -f file</code>	Force remove file
<code>rm -rf dir</code>	For remove directory dir
<code>cp file1 file2</code>	Copy file1 to file2
<code>cp -r dir1 dir2</code>	Copy dir1 to dir2; create dir2 if it doesn't exist
<code>mv file1 file2</code>	Rename or move file1 to file2. If file2 is an existing directory, moves file1 into directory file2
<code>ln -s file link</code>	Create symbolic link link to file
<code>touch file</code>	Create or update file
<code>cat > file</code>	Places standard input into file
<code>more file</code>	Output the contents of file
<code>head file</code>	Output the first 10 lines of file
<code>tail file</code>	Output the last 10 lines of file
<code>tail -f file</code>	Output the contents of file as it grows, starting with the last 10 lines

System Info

<code>date</code>	show the current date and time
<code>cal</code>	show this month's calendar
<code>uptime</code>	show current uptime
<code>w</code>	display who is online
<code>whoami</code>	who you are logged in as
<code>finger user</code>	display information about user
<code>uname -a</code>	show kernel information
<code>cat /proc /cpuinfo</code>	cpu information
<code>cat /proc /meminfo</code>	memory information
<code>man command</code>	show the manual for command
<code>df</code>	show disk usage
<code>du</code>	show directory space usage
<code>free</code>	show memory and swap usage
<code>whereis app</code>	show possible locations of app
<code>which app</code>	show which app will be run by default

Compression

<code>tar cf file.tar files</code>	create a tar named file.tar containing files
<code>tar xf file.tar</code>	extract the files from file.tar
<code>tar czf file.tar.gz files</code>	create a tar with Gzip compression
<code>tar xzf file.tar.gz</code>	extract a tar using Gzip
<code>tar cjf file.tar.bz2</code>	create a tar with Bzip2 compression
<code>tar xjf file.tar.bz2</code>	extract a tar using Bzip2
<code>gzip file</code>	compresses file and renames it to file.gz
<code>gzip -d file.gz</code>	decompresses file.gz back to file

Process Management

<code>ps</code>	display all currently active processes
<code>top</code>	display all running processes
<code>kill pid</code>	kill process id pid
<code>killall proc</code>	kill all processes named proc *
<code>bg</code>	lists stopped or background jobs; resume a stopped job in the background
<code>fg</code>	Brings the most recent job to the foreground
<code>fg a</code>	brings job a to the foreground

Network

<code>ping host</code>	ping host and output results
<code>whois domain</code>	get whois information for domain
<code>dig domain</code>	get DNS information for domain
<code>dig -x host</code>	reverse lookup host
<code>wget file</code>	download file
<code>wget -c file</code>	continue a stopped download

File Permissions

<code>chmod octal file</code>	change the permissions of file to octal, which can be found separately for user, group, and world by adding: <ul style="list-style-type: none"> • 4 – read (r) • 2 – write (w) • 1 – execute (x) Examples: chmod 777 – read, write, execute for all chmod 755 – rwx for owner, rx for group and world. For more options, see man chmod .
-------------------------------	---

Installation

<i>Install from source:</i>	
<code>./configure</code>	
<code>make</code>	
<code>make install</code>	
<code>dpkg -i pkg.deb</code>	install a package (Debian)
<code>rpm -Uvh pkg.rpm</code>	install a package (RPM)

SSH

<code>ssh user@host</code>	connect to host as user
<code>ssh -p port user@host</code>	connect to host on port port as user
<code>ssh-copy-id user@host</code>	add your key to host for user to enable a keyed or passwordless login

Shortcuts

<code>Ctrl+C</code>	halts the current command
<code>Ctrl+Z</code>	stops the current command, resume with fg in the foreground or bg in the background
<code>Ctrl+D</code>	log out of current session, similar to exit
<code>Ctrl+W</code>	erases one word in the current line
<code>Ctrl+U</code>	erases the whole line
<code>Ctrl+R</code>	type to bring up a recent command
<code>!!</code>	repeats the last command
<code>exit</code>	log out of current session
<code>*</code>	use with extreme caution

Searching

<code>grep pattern files</code>	search for pattern in files
<code>grep -r pattern dir</code>	search recursively for pattern in dir
<code>command grep pattern</code>	search for pattern in the output of command
<code>locate file</code>	find all instances of file


makeuseof.com

Did you like this CheatSheet? Then why not visit MakeUseOf.com for daily posts on cool websites, free software and internet tips.

If you want more great CheatSheets and MakeUseOf Guides join using the link below.

<http://www.makeuseof.com/pages/>

Over 50 Free Downloadable PDF Guides



Download 50+ MakeUseOf Guides on a wide range of subjects. More than a million downloads so far. All free. Enjoy and share!

Free Printable Cheat Sheets



Get printable cheat sheets and shortcuts for your favorite programs and sites. These cheat sheets will make you more productive!