




Product selector

2020-01-22 23:36:07



Video Intercoms			
Image	 VTO2111D-WP-S1	 VTO3211D-P-S1/P2-S1/P4-S1	 VTO2202F-P
Properties			
Image Sensor	1/4" 1MP CMOS	1/2.8" 2MP CMOS	2.0MP
Lens	2.2mm	1.9mm	1.95
Angle of View	D:125° H:105°	D:158° H:140°	H:160°
Day/Night	ICR	ICR	ICR
LCD Screen	-	-	-
Reader	Mifare Card	Mifare Card	-
Proximity Sensor	-	-	-
Keypad	Mechanical Button	Mechanical Button	Mechanical Button
RS485	1	1	1
Door Control	1 Relay Out 1 Feedback 1 Exit Button	1 Relay Out 1 Feedback 1 Exit Button	1 Relay Out 1 Feedback 1 Exit Button
Alarm In/Out	-	-	1
Ingress Protection	IP65	IP65, IK08	IP55, IK07
Tamper Switches	1	1	1
Memory Slot	Micro SD, Max 32G	-	Micro SD, Max 64GB
Wi-Fi	IEEE802.11b/g/n, 2.4GHZ	-	-
433	-	-	-
Ethernet	10M/100Mbps	10M/100Mbps	10M/100Mbps
Installation	Surface	Surface	Surface & Flush
Material	Plastic	Aluminum	Aluminum
Working Temperature	-30°C~+60°C (-22°F~+140°F)	-40°C~+60°C (-40°F~+140°F)	30°C~+60°C (-22°F~+140°F)
Power Supply	DC 12, PoE(802.3af), Max 10W	DC 12, PoE(802.3af), Max 10W	DC 12, PoE(802.3af)
Relative Humidity	10~95%RH	10~95%RH	10~90%RH
Dimensions	135mm×70.4mm×34.4mm	182mm×30mm×101mm	130 mm×96 mm×28.5 mm
Weight	0.4kg	0.8kg	0.35kg