

BEST TIPS FOR RAY-BAN SUNGLASSES BROKEN HINGE REPAIR



Sunglasses hinge breaking is a common phenomenon. If this happens, you have a few options to fix this problem. You can change the complete set of sunglasses with the help of an optometrist or as a functional substitute, change the hinge. After changing the hinge of the Ray-Ban sunglasses, you can use it as earlier.

During the time of [Ray-Ban Hinge Repair](#), an optometrist uses small brass hinge, leather-man pliers, super glue, BIC lighter, etc. So here we discuss the hinge repair steps below:

1 Remove the broken Hinge

In most of the cases, broken hinges are fixed by using heat. In this case, original pieces of hinges are inserted into the frame. For removing the broken hinges:

- ✓ Give heat properly to the metal part so that the surrounding part of plastic becomes soften.
- ✓ Collect the metal hinges which are stick out from the frame of sunglasses.
- ✓ Different types of heat sources are used to remove the hinges like soldering iron, BIC lighter, etc.

2 New hinge preparation

Usually, the brass hinge is used. It is small, decorative in nature and usually used on jewelry boxes or small wooden crafts.

- ✓ Two hinges are given in a packet including small brad nails.
- ✓ The size of this hinge is generally $\frac{5}{8}$ " x $2\text{-}\frac{3}{4}$ ".
- ✓ As per the requirement, you can cut this hinge for better fitting with leatherman jaws.

3 Insertion of new Hinge

- ✓ Though the plastic surface is a nonporous part, rub the area properly.
- ✓ After the trimming and cleaning of hinges, apply the glue to set properly.

4 Finishing touch

- ✓ Let the glue dry for some time.
- ✓ A light scar may be observed after repairing the hinge but the sunglass is ready for further use.

