

## T300e WALK-BEHIND FLOOR SCRUBBER

	SINGLE DISK		SINGLE DISK		DUAL DISK	CYLINDRICAL	ORBITAL
	17 IN/430 MM PAD ASSIST	17 IN/430 MM SELF-PROPEL	20 IN/500 MM PAD ASSIST	20 IN/500 MM SELF-PROPEL	24 IN/600 MM PROPEL	20 IN/500 MM SELF-PROPEL	20 IN/500 MM SELF-PROPEL
<b>Productivity (per hour)</b>							
Theoretical Max	17,000 ft <sup>2</sup> /1,579 m <sup>2</sup>		20,000 ft <sup>2</sup> /1,858 m <sup>2</sup>		24,000 ft <sup>2</sup> /2,230 m <sup>2</sup>	20,000 ft <sup>2</sup> /1,858 m <sup>2</sup>	20,000 ft <sup>2</sup> /1,858 m <sup>2</sup>
<b>Estimated Coverage*</b>							
Conventional	9,340 ft <sup>2</sup> /868 m <sup>2</sup>	12,453 ft <sup>2</sup> /1,157 m <sup>2</sup>	11,208 ft <sup>2</sup> /1,041 m <sup>2</sup>	14,943 ft <sup>2</sup> /1,388 m <sup>2</sup>	18,264 ft <sup>2</sup> /1,697 m <sup>2</sup>	14,943 ft <sup>2</sup> /1,388 m <sup>2</sup>	14,943 ft <sup>2</sup> /1,388 m <sup>2</sup>
<b>BRUSH DRIVE SYSTEM</b>							
Scrub motor	24 VDC, 1 hp/0.230 rpm		24 VDC, 1 hp/0.75 kW 230 rpm		24 VDC, 1 hp/0.75 kW 285 rpm	24 VDC, 1 hp/0.75 kW 1,065 rpm	0.6 hp/0.45 kW 2,200 rpm
Brush/pad RPM	47 lbs/21 kg		51 lbs/23 kg		57 lbs/26 kg	53 lbs/24 kg	63 lbs/29 kg
Brush/pad pressure	Optional 86 lbs/39 kg		Optional 90 lbs/41 kg		Optional 97 lbs/44 kg	Optional 64 lbs/29 kg	Optional 109 lbs/49 kg
<b>SOLUTION/RECOVERY SYSTEM</b>							
Solution tank capacity	11 gal/42 L		11 gal/42 L		11 gal/42 L	11 gal/42 L	11 gal/42 L
Recovery tank capacity	14 gal/53 L		14 gal/53 L		14 gal/53 L	14 gal/53 L	14 gal/53 L
Vacuum motor	24 VDC, 0.6 hp/0.47 kW		24 VDC, 0.6 hp/0.47 kW		24 VDC, 0.6 hp/ 0.47 kW	24 VDC, 0.6 hp/ 0.47 kW	24 VDC, 0.6 hp/ 0.47 kW
Vacuum waterlift	34.5 in / 876 mm		34.5 in / 876 mm		34.5 in / 876 mm	34.5 in / 876 mm	34.5 in / 876 mm
<b>BATTERY SYSTEM</b>							
System voltage	24 volt		24 volt		24 volt	24 volt	24 volt
Battery types (Wet 105AH, Wet 130AH, Wet 150AH, Sealed AGM 140AH)	2 required		2 required		2 required	2 required (150AH wet & 140AH sealed only)	2 required
Battery run time (up to hours)	3.4	3.1	2.8	2.6	2.9	2.5	3.8
On-board charger	Standard		Standard		Standard	Standard	Standard
Off-board charger	Optional		Optional		Optional	Optional	Optional
<b>MACHINE SPECIFICATIONS</b>							
Length	51.25 in/1,302 mm		54 in/1,372 mm		51.75 in/1,314 mm	50.50 in/1,283 mm	49 in/1,245 mm
Width	20 in/500 mm		22 in/559 mm		26 in/660 mm	25 in/635 mm	20.5 in/521 mm
Height	43.10 in/1,095 mm		43.10 in/1,095 mm		43.10 in/1,095 mm	43.10 in/1,095 mm	43.10 in/1,095 mm
Weight (without batteries)	220 lbs/98 kg	230 lbs/104 kg	230 lbs/104 kg	240 lbs/109 kg	250 lbs/113 kg	250 lbs/113 kg	255 lbs/116 kg
Weight (with batteries)	366 lbs/166 kg	390 lbs/177 kg	376 lbs/171 kg	400 lbs/181 kg	410 lbs/186 kg	410 lbs/186 kg	415 lbs/188 kg
Sound level (operator's ear)	67 dBA		67 dBA		67.7 dBA	68.7 dBA	67.5 dBA
<b>WARRANTY</b>							
See your local representative for warranty information							

\* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

\*\* Run times are based on Continuous Scrubbing Run Times.

\*\*\* Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA.

Specifications subject to change without notice.

### SEEING IS BELIEVING

For a demonstration or additional information,  
send an email to [info@tenantco.com](mailto:info@tenantco.com)

Tennant  
701 North Lilac Drive  
Minneapolis, MN 55422 USA

USA: +1.800.553.8033  
Overseas: +1.763.540.1315

T300e Brochure 5/17

©2017 The Tennant Company logo and other trademarks designated with the symbol "®" are trademarks of Tennant Company registered in the United States and/or other countries. Tennant Company's products are sold and serviced through subsidiaries of Tennant Company and distributors. All rights reserved.

[www.tennantco.com](http://www.tennantco.com)  
[info@tenantco.com](mailto:info@tenantco.com)



CREATING A CLEANER, SAFER, HEALTHIER WORLD.

EQUIPMENT



# T300e

## WALK-BEHIND FLOOR SCRUBBER

Delivering high performance, consistent results for virtually any hard surface condition while lowering cleaning costs

Scan this cover for virtual demo or download App

