ALPHA PROSPECTS AND DERLITE PRESENTS

ATOMIC ENERGY FROM WATER PLASMOID PROTIUM POWER

FOR INTERNAL COMBUSTION ENGINES USING WATER AS AN ATOMIC FUEL.

Proprietary Confidential Information

Inventor - Malcolm Bendall

Version 4.0 - December 25th 2017

WELCOME TO THE IMPLOSIVE ENERGY REVOLUTION

- Malcolm Bendall has invented a proprietary plasmoid-induced atomic fusion process which allows water to be used as the atomic fuel.
- Using this novel technology, conventional engines and generators can be retrofitted to run on a combination of water and fossil fuels, producing negligible toxic emissions when compared to current outputs.
- Existing hydrocarbon fossil fuels, (petrol, diesel & gas), are only used during the start-up to achieve the initial operating temperatures and vacuum. This is required to begin the creation, capture and harvesting of the stored atomic fusion energy contained within the plasmoids.

EXPLOSIVE vs **IMPLOSIVE TECHNOLOGY**

- Bendall's proprietary device, once attached to an internal combustion engine generates energy from a combination of HHO, plasma, preconditioned water, the original fossil fuel, the motor's vacuum and the recovered exhaust gases.
- Using current combustion engine technology ≥30% of all hydrocarbon fuel is wasted as heat. The Bendall plasmoid energy retrofit utlilises this loss, whilst improving efficiency by orders of magnitude.
- Tests perfomed on a working plasmoid energy engine prototype have proven the utility and efficiency of the engine, heralding the start of a new sustainable industrial revolution.

DERLITE FACTORY - PLASMOID GENERATOR PROTOTYPING



Drone view of the Derlite facility



The expansive facility covers 3,600 sqm



Malcolm Bendall overseeing construction of the Thunderstorm Generator



Malcolm testing and documenting results

EXECUTIVE SUMMARY - MARKET VALUATION

- Traditional internal combustion engine efficiency is $\leq 45\%$
- Using water as an atomic fuel reduces the engine's consumption of fossil fuels, as the energy consumed is derived from Protium, (an isotope of Hydrogen).
- Retrofitting the Bendall Engine technology to an existing engine increases the efficiency by ≥ 90%. This is because the by-product of burning water as an atomic fuel is water, which is continuously recirculated inside our closed fuel system.
- Market Segment Roll-Out:

Phase 1: Retrofit of Diesel, Petrol & Gas powered generators Market Size: 14,000,000 gensets in operation 10% market penetration revenues: \$2.1bn

Phase 2: Retrofit of Diesel, Petrol & Gas powered vehicles Market Size: 1.25bn vehicles in operation 10% market penetration license revenues: \$12.5bn

HOW IT WORKS - WATER TO HYDROGEN (H) & OXYGEN (O) TO WATER

H₂O liquid pulled apart

CATALYSTS INDUCE DISASSOCIATION OF H₂O LIQUID

Water Vapour Plasmoids Iron Chrome Platinum Shockwave Heat Exhaust Pulse Vacuum Plasma Spark Hydrogen & Oxygen HHO gas

LIQUID TO GAS

The disassembled water seperates into two parts ionised Hydrogen gas and one part Oxygen gas.

=>

=>

These gases are highly flammable.

Burning HHO gas reverts to H₂O liquid

GAS TO LIQUID

When HHO is exposed to a positively charged plasma it ignites and returns to a liquid H2O.

Liquid

Gas

HOW IT WORKS - SCHEMATIC OF THE BENDALL ENGINE



HOW IT WORKS - THUNDERSTORM ELECTRON GENERATION





- The exhaust gases, which are introduced at an angle, first expand anti-clockwise and then contract clockwise as they pass through the cavity between two spheres.
 This creates opposing tornadoes within both the outer and inner spheres.
- These expanding and then contracting tornadoes strip electrons and lay a positive charge on the outside surface of the inner sphere.
- The atomised water on the inside of the inner sphere lays a negative charge. This creates a potential difference across the stainless steel, charging the plasmoids.

HOW IT WORKS - RANQUE-HILSCH VORTEX TUBE



The vortex tube, also known as the Ranque-Hilsch vortex tube, is a mechanical device that separates a compressed gas into hot and cold streams. The gas emerging from the "hot" end can reach temperatures of 200 °C (392 °F), and the gas emerging from the "cold end" can reach –50 °C (–58 °F).[1] It has no moving parts.

Pressurised gas is injected tangentially into a swirl chamber and accelerated to a high rate of rotation. Due to the conical nozzle at the end of the tube, only the outer shell of the compressed gas is allowed to escape at that end. The remainder of the gas is forced to return in an inner vortex of reduced diameter within the outer vortex.

HOW IT WORKS - INJECTOR FOR FUEL, PLASMOIDS AND PLASMA



Proprietary Fuel, Plasmoid and Plasma Injector vs. Bosch Platinum Fusion standard sparkplug



Injector without insulator with fuel and plasmoid inlet



Injector expanded view without insulator with connected fuel and plasmoid inlet



Injector expanded view without insulator or connected fuel and plasmoid inlet

HOW IT WORKS - PLASMA ELECTRONICS AND 555 TIMER



The Test Rig for a standard car coil retrofit conversion from a normal high voltage spark plug igniting petrol to an injected plasma invoking an atomic fusion based plasmoid discharge and the separation of water into hydrogen and oxygen.

HOW IT WORKS - PLASMOID DISCHARGE TEST PLATFORM



Electronic control panel with variac, modified car coils and plasma generator. Designer piston, plasma discharge and fuel testing infrastructure. High voltage distribution panel, also showing massive structural steel components to safely deal with the atomic forces being generated.

HOW IT WORKS - DESIGNER PISTONS FOR PLASMOID DISCHARGE



Implosive cylinder head concentrating force into a central tungsten carbide sphere. Implosive piston with rings, hydraulic dampener and cylinder head. Cylinder with 4 platinum fusion spark plugs. The design for one injector to generate an implosion at the central tungsten carbide sphere. Implosive piston with rings, hydraulic dampener and cylinder head designed for plasma injector.

HOW IT WORKS - NESTED CYLINDER HHO GENERATOR





HHO Generator distributing H to the air intake ionizer and O to the carburetor intake.



Nested stainless steel cylinders creating a resonant octave 16 part chord giving the maximum reactive HHO generative surface area within a minimal space.

WHAT IS A PLASMOID EVO (Exotic Vacuum Occurrence)? How is it created?



CREATION OF A VACUUM BUBBLE

A vacuum applied to a body of water creates bubbles from the dissolved gases within the water itself.

CREATION OF PLASMOID EVO

The core pressure (up to 100,000 psi) and temperature (up to 10 million degrees celsius) creates enough energy to establish the first electron spin on the toruscreating a plasmoid EVO

WHAT IS A PLASMOID EVO ? - How is it charged & discharged?





PLASMOID EVO WITHSTANDS BUBBLE BURST

Bubble bursts leaving a stable plasmoid EVO.

PLASMOID IS NEGATIVELY CHARGED BY THE THUNDERSTORM ELECTRON GENERATOR

The Plasmoid grows in size from 10⁻¹² Microns to 100 Microns.

PLASMOID IS PROPORTIONALLY DISCHARGED BY A POSITIVELY CHARGED PLASMA

The Plasmoid reduces in size from 100 Microns to 10⁻¹² Microns .

PLASMOID'S EFFECT ON WATER

 \cap

0

Plasmoids cause the separation of Hydrogen & Oxygen

Plasmoids cause disintegration of Hydrogen & Oxygen into their component parts

H

Plasmoid absorbs all Protons & Electrons within its immediate sphere of influence

Plasmoid in its fully charged state has a diameter of 100 Microns

WATER H₂0

HOW IT WORKS - PRECONDITIONED WATER FOR THE PLASMOID GENERATOR

REGULAR WATER



Water contains dissolved gases which through diffusion equalize with the atmospheric gases.



The dissolved gases are extracted from the water by applying a vacuum increasing the available energy per volume.

DESIGNER GAS ADDED



A Hydrogen based gas is introduced to the water further increasing the available energy per volume.

TEST RESULTS - BENDALL ENGINE WITH PLASMOIDS IN OPERATION



- The Bendall engine ignition begins with the use of a fossil fuel in order to heat the Thunderstorm Generator to operational temperatures.
- Once the Thunderstorm generator has reached its operating temperature (around 300°C) our plasmoid fuel is introduced where it is charged.
- The hybrid fuel (water vapor and plasmoids) is created when a preconditioned water and ionised air mix is passed through the Plasmoid generator. This generator vaporises water and produces plasmoids from collapsing cavitation bubbles. Stainless steel is used as the catalyst along with the plasmoids to produce hydrogen and oxygen by disassembling the water.
- A plasmoid is a coherent toroidal structure of plasma confined by magnetic fields. It is a self structuring, self regulating, homeostatic system.

TEST RESULTS - PLASMOID DISCHARGE



- The Thunderstorm generator facilitates an atomic restructuring action that increases the size of the plasmoids by adding electrons and protons to them.
- The plasmoids harvest the electrons and protons from the protium (H) contained within the water as a result of disassembly caused by the forces applied by the plasmoids.
- The energy harvested from the electron enhanced plasmoids significantly increases the engines energy output, efficiency and thereby reduces the toxicity of the exhaust.
- The normal operating temperature of the Thunderstorm generator is between 700°C and 1,000°C with a 300°C exhaust gas input.

TEST RESULTS - THERMOCOUPLE READINGS



Jan Tue 31 2017									
T1 MAX	767.6@31/01/2017 17:17:19	MIN	27.5@31/01/2017 17:05:12	AVG	363.911	-			
T2 MAX	145.4@31/01/2017 17:20:57	MIN	-40.6@31/01/2017 17:17:07	AVG	63.910				
T3 MAX	76.7@31/01/2017 17:20:29	MIN	-86.3@31/01/2017 17:17:17	AVG	30.984	-			
T4 MAX	422.2@31/01/2017 17:08:33	MIN	32.3@31/01/2017 17:03:58	AVG	274.531	-			

- Maximum Exhaust Temperature Measured on the outside sphere was +767.6°c
- Minimum Vacuum Temperature Measured on the Plasmoid Generator outlet was -86.3°c
- Max Inner Sphere Core Temperature Calculated by the fail-safe allowing melting & deformation of the stainless steel and welds +1500°c

Thermal Equation

By measuring temperatures & exhaust gas volumes we have calculated a 2x increase of the output energy of the engine due to the plasmoid discharge.

TEST RESULTS - THERMAL EQUATION BASED ON EMPIRICAL DATA

The energy (in Kwh) in a gas stream = the weight in Kilograms per second (A) multiplied by the specific heat (B) mulitplied by the temperature difference (x - y) in Kelvin (C) = Kilo Joules per second (1 Joule per second = 1 watt per second).



Result based on empirical measured temperatures 0.0157 kg/sec (A) × 0.812 Kj (B) × 800 K (C) = 10.198 Kwh (14 hp)	~ Two times motor output (5.5Kw)
Result based on empirical melting point of 304 stainless steel 0.0157 kg/sec (A) × 0.812 Kj (B) × 1726 K (C) = 22.000 Kwh (30 hp)	~ Four times motor output (5.5Kw)

ACTION PLAN

- Expand the dedicated R & D facility and increase the team of development engineers and associated support staff.
- Expand worldwide patents for the concepts and ideas used in the product.
- Continue to develop working prototypes demonstrating the use of this technology as related to diesel, petrol and gas-powered engines.
- Determine the most beneficial licensing arrangements.
- Negotiate licensing agreements and manage royalty fees and intellectual property.

MONETISATION - GENERATOR RETROFIT

Estimated Units of Portable Generators in Use, by Generator kW Ratings, 2004 - 2012 % 2-3.49 kW % 5-6.49 kW % 6.5-7.99 kW % 8 kW + %

- -

Year	< 2 kW	%	2—3.49 kW	%	3.5—4.99 kW	%	5—6.49 kW	%	6.5—7.99 kW	%	8 kW +	%	Total
2004	1,164,937	11.8%	1,514,418	15.3%	2,003,691	20.2%	3,307,573	33.4%	1,125,797	11.4%	785,440	7.9%	9,901,855
2005	1,169,828	11.2%	1,507,610	14.5%	2,052,923	19.7%	3,620,229	34.8%	1,218,983	11.7%	843,880	8.1%	10,413,454
2006	1,138,111	10.9%	1,494,780	14.3%	2,026,543	19.4%	3,684,521	35.3%	1,234,027	11.8%	865,844	8.3%	10,443,826
2007	1,138,122	10.8%	1,507,516	14.3%	2,019,291	19.2%	3,721,225	35.3%	1,246,975	11.8%	908,152	8.6%	10,541,281
2008	1,225,495	11.2%	1,657,508	15.2%	2,029,573	18.6%	3,804,931	34.8%	1,246,355	11.4%	965,614	8.8%	10,929,475
2009	1,382,555	12.3%	1,945,110	17.3%	2,006,405	17.8%	3,755,195	33.4%	1,189,234	10.6%	966,810	8.6%	11,245,308
2010	1,565,789	13.5%	2,278,780	19.6%	2,001,427	17.2%	3,686,827	31.7%	1,133,894	9.8%	962,137	8.3%	11,628,854
2011	1,724,038	14.4%	2,579,743	21.6%	1,988,252	16.6%	3,641,605	30.4%	1,071,810	9.0%	961,550	8.0%	11,966,999
2012	1,906,637	15.3%	2,943,773	23.6%	2,001,557	16.1%	3,626,361	29.1%	1,012,496	8.1%	968,748	7.8%	12,459,571
9-Year Average	1,379,501	12.5%	1,936,582	17.5%	2,014,407	18.2%	3,649,830	33.0%	1,164,397	10.5%	914,242	8.3%	11,058,958

Source: CPSC Directorate for Economic Analysis, based on Product Population Model evaluation of estimated historical sales.

- The table alongside shows the number of portable generators in use worldwide.
- Today we estimate there are
 14 million portable genera tors in use globally.
- Consider a license fee and retrofit kit costing US\$1,500.
- Potential revenue from this with a 10% global market penetration is US\$2.1 Billion.

MONETISATION - MOTOR VEHICLES RETROFIT



- The table alongside shows the number of cars and commercial vehicles in use worldwide.
- Today we estimate there are 1.25 Billion cars and commercial vehicles in use globally.
- Consider a license fee of say US\$100 per vehicle.
- Potential revenue from
 this source alone with a
 10% global market pene tration is US\$12.5 Billion.

TIMETABLE

	Year 1				Year 2		Year 3	
	Q1	Q2	Q3	Q4	H1	H2	H1	H2
Establish Team								
File Patents								
Design and build prototypes								
Determine licensing model								
Establish marketing team								
Set up licensees								
Units Sold							50,000	100,000
Royalty Revenue							\$5.0m	\$10.0m
Capex (\$000)	50	120	120	120	-	100		
Expenses (\$000)	150	350	350	350	1,020	1,020	1,120	1,120

OTHER CONSIDERATIONS

Economic

Worldwide annual expenditure on generator and motor vehicle fuel is estimated at well over USD one trillion dollars. The new Bendall Plasmoid technology has the potential to save more than USD 400 million a year in fuel costs.

Environmental

The effect on the environment will be dramatic. A primary source of pollution is motor vehicle exhaust gases. There will be significant reduction in carbon emissions from implementing this technology.

Devolution of the discovery

The science behind these inventions will challenge the current thinking. The knowledge of how and why these units work will need to be disseminated to the widest possible global audience.

Energy Security

A significant component of the economic activity in the world relates to energy production. International conflict is often caused by concerns about the security regarding sources of energy - consider the benefits of what could be almost free and storable energy.

CONCLUSION - RESULTS

Test Results

Based on the results documented on page 19, the thermal equation on page 20 confirms the effectiveness and compatibility of the plamoid system when integrated with existing internal combustion engines.

Retrofit Kit

New technology can be retrofitted to existing diesel, petrol and gas driven internal combustion technologies.

Smooth Transition From Fossil Fuel to Atomic Power

The Bendall Engine technology will enable the smooth transition from fossil fuels to clean atomic power, making use of all existing legacy infrastructure and support industries, thereby ensuring continuity of employment.

Competitive Advantage

The advantage is that water is available in every house and business. The overall weight of the vehicle is also reduced and the range of the vehicle is extended by orders of magnitude.

CONCLUSION- IN SUMMARY

- Over the last 200 years we have witnessed several fundamental changes to society.
 - Discovery of the wheel
 - Agricultural Revolution
 - Industrial Revolution
 - Invention of the Computer
 - Information Revolution

This is a unique opportunity to participate in what is the next industrial revolution.

Plasmoid Protium Energy Revolution

DISCLAIMER

DISCLAIMER: This confidential investor presentation is being made by Malcolm Bendall to certain investors residing in the United Kingdom, other European countries, Asia and the United States in accordance with the restrictions set forth in this presentation.

The directors of the Company have taken all reasonable care to ensure that the information contained in this investor presentation is in accordance with the facts as known to them and as reasonably investigated by them. The opinions expressed in this investor presentation are those of the directors, based on their knowledge and experience of the markets which they describe. Financial projections have been properly prepared, but are, by their nature, subject to change as the business develops. The directors do not, however, accept responsibility for this document and accordingly shall not be responsible for any incorrect or misleading information contained in, or any information omitted from, this investor presentation.

This investor presentation sets out certain basic information relating to the Company. This investor presentation is not exhaustive and should not be regarded as such, nor relied on in any way. The information contained in it has not been verified independently of the directors. The investor presentation does not constitute an offer in any form for shares in the Company. The contents of this investor presentation are the property of the Company and are confidential. They may not be disclosed without the prior consent of the Company, save where they are in the public domain without breach of any obligation of confidentiality by the recipient of this investor presentation. Recipients of this investor presentation should make their own independent assessment of the merits or otherwise of the Company or the acquisition, holding or disposal of shares in the Company and should not construe the contents of this investor presentation or the documents referred to in it as advice on legal, taxation or investment matters.

The distribution of this investor presentation in certain jurisdictions may be restricted. The recipient of this document is not to send or send a copy of this document to any person other than its directors or employees whose business is to consider it on behalf of the recipient. This investor presentation and the information contained herein has been prepared and is intended for use on a confidential basis solely by the small number of persons to whom it is sent on behalf of the Company. It may not be reproduced, redistributed or passed on to any other person or published in whole or in part for any purpose. It does not constitute an invitation to the public or any section thereof to subscribe for or purchase any shares or other securities in any company and accordingly is not a prospectus within the meaning of the Companies Act of the United Kingdom or of the European Communities (Transferable Securities and Stock Exchange Regulations).

Investment in the Company involves significant risk. This document includes certain statements, estimates and forward-looking projections of the Company with respect to the anticipated future performance of the Company. The Company's independent auditors have neither examined nor compiled the estimates or projections and accordingly do not express an opinion or any other form of assurance with respect thereto. The statements, estimates and projections are based upon various assumptions by management that may not prove to be correct. Such assumptions are inherently subject to significant economic and competitive uncertainties and contingencies, many of which are beyond the control of the Company, and upon assumptions with respect to the future performance of the Company that may be subject to change because of circumstances beyond the control of the directors and or the Company. The Company believes that such estimates and other assumptions are reasonable under the circumstances, but no representation, warranty or other assurance is given that such statements, estimates and projections and actual events and results, and such variations will likely be material.

The forward-looking statements contained herein are made as of the date of this document, and the Company accepts no obligation to update such forward-looking statements or to update the reasons why actual results could differ materially from those anticipated in such forward-looking statements.