

RETAILER BOOK

2017 BIKES



TABLE OF CONTENTS

WOMEN'S TURBO LEVO FSR	1	ROCKHOPPER	125
WOMEN'S TURBO LEVO HT	3	PITCH	131
TURBO LEVO FSR	5	HARDROCK	135
TURBO LEVO FAT	9	DEMO	137
TURBO LEVO HT	11	FATBOY	143
ERA	13	P.SERIES	151
WOMEN'S EPIC HARDTAIL	17	VENGE	155
JETT	19	TARMAC	161
RHYME	23	ALLEZ	179
WOMEN'S CAMBER	29	ROUBAIX	187
		SHIV	191
RUZE	33	SHIV TT	195
JYNX	35	CRUX	197
MYKA	39	LANGSTER	203
HELLGA	41	DIVERGE	207
AMIRA	45	SEQUOIA	213
RUBY	51	AWOL	217
DOLCE	55	TURBO	221
VITA	61	SIRRUS	225
ARIEL	71	CROSSTRAIL	235
EPIC	79	CROSSROADS	241
EPIC HT	87	ALIBI	247
CAMBER FSR	91	ROLL	253
STUMPJUMPER FSR	103	RIPROCK	265
FUSE	119	HOTROCK	273



WOMEN'S TURBO LEVO FSR COMP 6FATTIE



TARBLK/HYP

The Women's Turbo Levo FSR Comp 6Fattie has the perfect blend of trail performance, proper handling, technology, and durability. This means that you get a roomy top tube for an easy fit, ultra-short chainstays for nimble handling, and a low bottom bracket that makes the bike feel glued to the trail.

- The frame was constructed from our M5 Premium Aluminum, which is equal parts strong, lightweight, and incredibly responsive. The design of the frame itself revolves around our Trail Geometry that includes all of our trail hallmarks, like a low-slung bottom bracket, roomy top tube, and ultra-short chainstays. Cable routing is all internal, including that of the Command Post IR, while the battery and motor is fully integrated in the down tube.
- The RockShox Yari RC fork takes aesthetic and performance cues from the much heralded Pike and Lyric models, offering top features like Fast Black upper tubes, Motion Control™ IS damper, and the Solo AIRcc™ spring. So you get a stiff 35mm chassis and a smooth 140mm of travel.
- SRAM's Guide R brakes provide powerful, precise, and highly adjustable braking. They're based on a four-piston caliper design that puts out smooth, dependable stopping power, while the Reach Adjust feature allows you to customize the position for easy, one-finger lever pulls. And with SRAM's SwingLink technology, the cam system minimizes deadband without sacrificing modulation.

LEVO FSR WMN			
SIZE	S	M	L
Seat Tube Length, Center to Top (mm)	396	435	468
Top Tube Length, Horizontal (mm)	555	585	615
Bottom Bracket Drop (mm)	21	21	21
Bottom Bracket Height (mm)	342	342	342
Chainstay Length (mm)	459	459	459
Seat Tube Angle, Actual (deg)	69.3	69.3	69.3
Seat Tube Angle, Effective (deg)	74.5	74.2	73.9
Head Tube Angle (deg)	66.5	66.5	66.5
Wheel Base (mm)	1154	1181	1212
Standover Height (mm)	755	763	773
Head Tube Length (mm)	95	100	130
Stack (mm)	596	600	628
Reach (mm)	389	415	434
Handlebar Width (mm)	720	720	720
Stem Length (mm)	45	60	60
Saddle Width (mm)	155	155	155
Seat Post Length (mm)	390	390	430
Crank Length (mm)	165	165	170

SPECS	All specs are subject to change without notice.
FRAME	Specialized M5 Premium Aluminum, Trail Geometry, integrated down tube battery, enclosed internal cable and Command Post IR routing, 148mm spacing, fully sealed cartridge bearings, 140mm of travel
REAR SHOCK	FOX FLOAT Performance, Women's Rx Tune, AUTOSAG, DPS damper, rebound and 3-position compression adjust, 197x47.6mm
FORK	RockShox Yari RC 29/27.5+, Solo Air spring, adjustable compression and rebound, 15x110mm Maxle Ultimate thru-axle, 51mm offset, 140mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width
GRIPS	Specialized Sip Grip, lock-on, half-waffle, regular thickness
FRONT BRAKE	SRAM Guide R, hydraulic disc, metallic pads, Guide S4 4-piston caliper, 200mm rotor
REAR BRAKE	SRAM Guide R, hydraulic disc, metallic pads, Guide S4 4-piston caliper, 200mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM GX, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PCX1, 11-speed w/PowerLink
CRANKSET	Custom alloy crankarms
CHAINRINGS	32T
BOTTOM BRACKET	Integrated in motor
RIMS	Roval Traverse 650b, hookless alloy, 38mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 110x15mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless
FRONT TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Command Post IRoc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel
MOTOR	Exclusive custom tune and software, Trail Tune, 250W
USER INTERFACE	Integrated Trail display, 10-LED battery display, Mission Control iOS/Android App
BATTERY	Custom Levo Battery, 460Wh, 40x3.2Ah, ANT+/Bluetooth® connectivity, IP 67
CHARGER	Custom charger, 42V4A w/Rosenberger plug
WIRING HARNESS	Custom harness w/ Rosenberger plug

PART NO.	DESCRIPTION	COLOR	SIZE
96416-5002	LEVO WMN FSR COMP 6FATTIE	TARBLK/HYP	S
96416-5003			M

WOMEN'S TURBO LEVO SHORT TRAVEL FSR 6FATTIE



RFBLKTNT/METWHTSIL



CLGRY/LTTUR

The Women's Turbo Levo Short Travel FSR 6Fattie was designed for all those that count speed among the top traits on the performance pyramid. Along these lines, you'll find that this model features 120mm of travel at the front and rear, compared to the 140 found on the "standard" Levo FSR.

- The frame was constructed from our M5 Premium Aluminum, which is equal parts strong, lightweight, and incredibly responsive. The design of the frame itself revolves around our Trail Geometry that includes all of our trail hallmarks, like a low-slung bottom bracket, roomy top tube, and ultra-short chainstays. Cable routing is all internal, including that of the Command Post IR, while the battery and motor is fully integrated in the down tube.
- A RockShox Revelation RL fork was developed to deliver 120mm of plush, trail taming travel, while accommodating a 15x110mm Maxle Stealth thru-axle for reliable handling and durability over rough, bumpy, or loose terrain.
- SRAM DB5 brakes feature a high-volume reservoir and a custom four-piston design in order to provide you with heaps of stopping power for hard and steep riding.

LEVO FSR WMN ST			
SIZE	S	M	L
Seat Tube Length, Center to Top (mm)	396	435	468
Top Tube Length, Horizontal (mm)	552.6	577	612
Bottom Bracket Drop (mm)	28	28	28
Bottom Bracket Height (mm)	345	345	345
Chainstay Length (mm)	459	459	459
Seat Tube Angle, Actual (deg)	70.9	70.2	70.2
Seat Tube Angle, Effective (deg)	75.4	75	74.8
Head Tube Angle (deg)	67.4	67.4	67.4
Wheel Base (mm)	1146	1174	1204
Standover Height (mm)	757	767	775
Head Tube Length (mm)	95	100	130
Stack (mm)	589	594	621
Reach (mm)	399	424	443
Handlebar Width (mm)	720	720	720
Stem Length (mm)	45	60	60
Saddle Width (mm)	155	155	155
Seat Post Length (mm)	350	350	400
Crank Length (mm)	165	165	170

SPECS	All specs are subject to change without notice.
FRAME	Specialized M5 Premium Aluminum, Trail Geometry, integrated down tube battery, enclosed internal cable and Command Post IR routing, 148mm spacing, fully sealed cartridge bearings, 140mm of travel
REAR SHOCK	FOX FLOAT Performance, Women's Rx Tune, AUTOSAG, DPS damper, rebound and 3-position compression adjust, 197x47.6mm
FORK	RockShox Revelation RL 29/27.5+, Solo Air spring, lockout and rebound adjust, 15x110mm Maxle Lite thru-axle, 51mm offset, 120mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width
GRIPS	Specialized Sip Grip, lock-on, half-waffle, regular thickness
FRONT BRAKE	SRAM DB5, hydraulic disc, custom 4-piston caliper, semi-organic pads, 200mm rotor
REAR BRAKE	SRAM DB5, hydraulic disc, 2-piston caliper, semi-organic pads, 200mm rotor
REAR DERAILLEUR	SRAM NX, long cage, 11-speed
SHIFT LEVERS	SRAM NX, 11-speed, trigger
CASSETTE	SRAM PG-1130, 11-speed, 11-42t
CHAIN	SRAM PC1130, 11-speed w/PowerLink
CRANKSET	Custom alloy crankarms
CHAINRINGS	32T
BOTTOM BRACKET	Integrated in motor
RIMS	Roval Traverse 650b, hookless alloy, 38mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 110x15mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless
FRONT TIRE	Fast Trak, GRID casing, 650bx2.8", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Fast Trak, GRID casing, 650bx2.8", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Alloy, 2-bolt clamp, 12.5mm offset, 30.9mm, anti-corrosion hardware
MOTOR	Exclusive custom tune and software, Trail Tune, 250W
USER INTERFACE	Integrated Trail display, 10-LED battery display, Mission Control iOS/Android App
BATTERY	Custom LEVO battery, 460Wh, 40x3.2Ah, ANT+/Bluetooth connectivity, IP 67
CHARGER	Custom charger, 42V4A w/Rosenberger plug
WIRING HARNESS	Custom harness w/ Rosenberger plug

PART NO.	DESCRIPTION	COLOR	SIZE
96417-7002	LEVO WMN FSR ST 6FATTIE	RFBLKTNT/METWHTSIL	S
96417-7003			M
96417-7102	LEVO WMN FSR ST 6FATTIE	CLGRY/LTTUR	S
96417-7103			M

WOMEN'S TURBO LEVO HARDTAIL COMP 6FATTIE



BLK/LTTUR

The Women's Turbo Levo Hardtail Comp 6Fattie has all of the speed and nimble handling that our hardtail trail bikes are known for—only with a boost of Turbo technology. Then comes the efficient and powerful Turbo technology, mating the battery and motor into the M5 frame in a new way.

- M5 Premium Aluminum construction is paired with our Women's Trail Geometry and a hardtail design to support a ride that provides slack, confident handling, maximum efficiency, and tons of speed. The frame also features an integrated battery and motor mount at the down tube for fast and easy battery removal. This keeps the aesthetic streamlined and the weight distribution perfectly balanced. Lastly, you'll find enclosed internal cable routing for a clean look and even cleaner cables, and internal routing for a dropper post.
- A RockShox Recon Silver RL fork delivers plush, trail-taming travel, while accommodating 15x110mm thru-axles for reliable handling and durability over rough, bumpy, or loose terrain.
- SRAM DB5 brakes feature a high-volume reservoir and a custom four-piston design in order to provide you with heaps of stopping power for hard and steep riding.

LEVO HARDTAIL WOMEN			
SIZE	S	M	L
Seat Tube Length, Center to Top (mm)	390	425	450
Top Tube Length, Horizontal (mm)	568	588	619
Bottom Bracket Drop (mm)	55	55	55
Bottom Bracket Height (mm)	308	308	308
Chainstay Length (mm)	450	450	450
Seat Tube Angle, Effective (deg)	74	73	73
Head Tube Angle (deg)	67	67	67
Wheel Base (mm)	1121	1144	1177
Standover Height (mm)	688	710	723
Head Tube Length (mm)	100	100	120
Stack (mm)	598	616	635
Reach (mm)	385	400	425
Fork Length (full) (mm)	510	530	530
Handlebar Width (mm)	720	720	720
Stem Length (mm)	45	60	60
Saddle Width (mm)	155	155	155
Seat Post Length (mm)	328	328	370
Crank Length (mm)	165	165	170

SPECS	All specs are subject to change without notice.
FRAME	Specialized M5 Premium Aluminum, Women's Trail HT Geometry, integrated down tube battery, enclosed internal cable and Command Post IR routing, 148mm spacing
FORK	RockShox Reba RL 29/27.5+, Solo Air spring, 15x110mm Maxle Lite thru-axle, compression and lockout adjust, 100/120mm of travel (size specific), 51mm offset
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width
GRIPS	Specialized Body Geometry XCT Women's, lock-on
FRONT BRAKE	SRAM DB5, hydraulic disc, custom 4-piston caliper, semi-organic pads, 200mm rotor
REAR BRAKE	SRAM DB5, hydraulic disc, 2-piston caliper, semi-organic pads, 200mm rotor
REAR DERAILLEUR	SRAM GX, Type 2.1, long cage, 10-speed
SHIFT LEVERS	SRAM GX, 10-speed, trigger
CASSETTE	Sunrace, 10-speed, 11-40t
CHAIN	SRAM PC1031, 11-speed w/PowerLink
CRANKSET	Custom alloy crankarms
CHAINRINGS	32T
BOTTOM BRACKET	Integrated in motor
RIMS	Roval Traverse 650b, hookless alloy, 38mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 110x15mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless
FRONT TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	TranzX dropper, internal cable routing, remote lever, 30.9mm, S/M: 80mm, L: 100mm travel
MOTOR	Exclusive custom tune and software, Trail Tune, 250W
USER INTERFACE	Integrated Trail display, 10-LED battery display, Mission Control iOS/Android App
BATTERY	Custom LEVO battery, 460Wh, 40x3.2Ah, ANT+/Bluetooth connectivity, IP 67
CHARGER	Custom charger, 42V4A w/Rosenberger plug
WIRING HARNESS	Custom harness w/ Rosenberger plug

PART NO.	DESCRIPTION	COLOR	SIZE
96416-7002	LEVO WMN HT COMP 6FATTIE	BLK/LTTUR	S
96416-7003			M

S-WORKS TURBO LEVO FSR 6FATTIE



BLK/FLORED

The S-Works Turbo Levo FSR 6Fattie is a trail bike with all of the hallmarks that our mountain bikes are known for. This means that you get a roomy top tube for an easy fit, ultra-short chainstays for nimble handling, and a low bottom bracket that makes the bike feel glued to the trail.

- The frame was constructed from our M5 Premium Aluminum, which is equal parts strong, lightweight, and incredibly responsive. The design of the frame itself revolves around our Trail Geometry that includes all of our trail hallmarks, like a low-slung bottom bracket, roomy top tube, and ultra-short chainstays. Cable routing is all internal, including that of the Command Post IR, while the battery and motor is fully integrated in the down tube.
- RockShox Pike RCT3 fork features a 15x110mm Maxle Ultimate thru-axle and 140mm of plush travel to take on big hits and bumpy terrain with supreme speed and efficiency.
- SRAM Guide RS Carbon brakes offer the "ultimate" in adjustability and sheer power. They feature a four-piston design and the latest SwingLink™ lever cam, which leads to a svelte overall weight, heat management, and smooth, consistent modulation.

PART NO.	DESCRIPTION	COLOR	SIZE
95216-0002	SW LEVO FSR 6FATTIE	BLK/FLORED	S
95216-0003			M
95216-0004			L
95216-0005			XL

LEVO FSR					
SIZE	S	M	L	XL	
Seat Tube Length, Center to Top (mm)	396	435	468	520	
Top Tube Length, Horizontal (mm)	555	585	615	650	
Bottom Bracket Drop (mm)	21	21	21	21	
Bottom Bracket Height (mm)	342	342	342	342	
Chainstay Length (mm)	459	459	459	459	
Seat Tube Angle, Actual (deg)	69.3	69.3	69.3	69.3	
Seat Tube Angle, Effective (deg)	74.5	74.2	73.9	73.6	
Head Tube Angle (deg)	66.5	66.5	66.5	66.5	
Wheel Base (mm)	1154	1181	1212	1246	
Standover Height (mm)	755	763	773	781	
Head Tube Length (mm)	95	100	130	150	
Stack (mm)	596	600	628	646	
Reach (mm)	389	415	434	460	
Handlebar Width (mm)	750	750	750	750	
Stem Length (mm)	50	60	60	60	
Saddle Width (mm)	143	143	143	143	
Seat Post Length (mm)	390	430	430	430	
Crank Length (mm)	165	170	170	170	

SPECS	All specs are subject to change without notice.
FRAME	Specialized M5 Premium Aluminum, Trail Geometry, integrated down tube battery, enclosed internal cable and Command Post IR routing, 148mm spacing, fully sealed cartridge bearings, 120mm travel
REAR SHOCK	FOX FLOAT Factory, Rx Trail Tune, AUTOSAG, DPS damper, Kashima coating, rebound and 3-position compression and Open adjust, 197x47.6mm
FORK	RockShox Pike RCT3 29/27.5+, Solo Air, compression and rebound and threshold adjust, tapered steerer, 15x110mm Maxle Stealth thru-axle, 51mm offset, 140mm travel
STEM	Syntax F109, 6-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Trail, FACT carbon, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width, 31.8mm
GRIPS	Specialized Sjp Grip, light lock-on, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide RS carbon, hydraulic disc, organic pads, carbon lever, Guide S4 4-piston caliper, 200mm rotor
REAR BRAKE	SRAM Guide RS carbon, hydraulic disc, organic pads, carbon lever, Guide S4 4-piston caliper, 200mm rotor
REAR DERAILLEUR	SRAM XX1 Type 2.1, 11-speed
SHIFT LEVERS	SRAM XX1, 11-speed, trigger
CASSETTE	SRAM XX1, 11-speed, 10-42t
CHAIN	SRAM XX1, 11-speed w/PowerLink
CRANKSET	Custom alloy crankarms
CHAINRINGS	32T
BOTTOM BRACKET	Integrated in motor
RIMS	Roval Traverse SL 38 650b, hookless carbon, 38mm inner width, 24/28h, tubeless ready
FRONT HUB	Roval Traverse, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
REAR HUB	Roval Traverse SL, DT Swiss Star Ratchet, 54t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
SPOKES	DT Swiss Revolution
FRONT TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Expert, hollow titanium rails, 143mm
SEATPOST	Command Post IRcc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel
MOTOR	Exclusive custom tune and software, Trail Tune, 250W
USER INTERFACE	Integrated Trail display, 10-LED battery display, Mission Control iOS/Android App
BATTERY	Custom Levo Battery, 460Wh, 40x3.2Ah, ANT+/Bluetooth® connectivity, IP 67
CHARGER	Custom charger, 42V4A w/Rosenberger plug
WIRING HARNESS	Custom harness w/ Rosenberger plug

TURBO LEVO FSR EXPERT 6FATTIE



WRMCHAR/CYN



MXORG/BLK

When designing the Turbo Levo FSR Expert 6Fattie, we started by building a trail bike with all the hallmarks that our mountain bikes are known for, while streamlining the design for full integration of our Turbo technology.

- The frame was constructed from our M5 Premium Aluminum, which is equal parts strong, lightweight, and incredibly responsive. The design of the frame itself revolves around our Trail Geometry that includes all of our trail hallmarks, like a low-slung bottom bracket, roomy top tube, and ultra-short chainstays. Cable routing is all internal, including that of the Command Post IR, while the battery and motor is fully integrated in the down tube.
- RockShox Pike RC fork features a 15x110mm Maxle Ultimate thru-axle and 140mm of plush travel to take on big hits and bumpy terrain with supreme speed and efficiency.
- SRAM Guide RS brakes offer the most adjustability and power in their class. They feature a four-piston design and the latest SwingLink™ lever cam, which leads to a respectable overall weight, top-of-the-line heat management, and smooth, consistent modulation.

PART NO.	DESCRIPTION	COLOR	SIZE
95216-3002	LEVO FSR EXPERT 6FATTIE	WRMCHAR/CYN	S
95216-3003			M
95216-3004			L
95216-3005			XL
95217-3102	LEVO FSR EXPERT 6FATTIE	MXORG/BLK	S
95217-3103			M
95217-3104			L
95217-3105			XL

LEVO FSR					
SIZE	S	M	L	XL	
Seat Tube Length, Center to Top (mm)	396	435	468	520	
Top Tube Length, Horizontal (mm)	555	585	615	650	
Bottom Bracket Drop (mm)	21	21	21	21	
Bottom Bracket Height (mm)	342	342	342	342	
Chainstay Length (mm)	459	459	459	459	
Seat Tube Angle, Actual (deg)	69.3	69.3	69.3	69.3	
Seat Tube Angle, Effective (deg)	74.5	74.2	73.9	73.6	
Head Tube Angle (deg)	66.5	66.5	66.5	66.5	
Wheel Base (mm)	1154	1181	1212	1246	
Standover Height (mm)	755	763	773	781	
Head Tube Length (mm)	95	100	130	150	
Stack (mm)	596	600	628	646	
Reach (mm)	389	415	434	460	
Handlebar Width (mm)	750	750	750	750	
Stem Length (mm)	45	60	60	60	
Saddle Width (mm)	143	143	143	143	
Seat Post Length (mm)	390	430	430	430	
Crank Length (mm)	165	170	170	170	

SPECS	All specs are subject to change without notice.
FRAME	Specialized M5 Premium Aluminum, Trail Geometry, integrated down tube battery, enclosed internal cable and Command Post IR routing, 148mm spacing, fully sealed cartridge bearings, 120mm travel
REAR SHOCK	FOX FLOAT Factory, Rx Trail Tune, AUTOSAG, DPS damper, Kashima coating, rebound and 3-position compression and Open adjust, 197x47.6mm
FORK	RockShox Pike RC 29/27.5+, Solo Air, compression and rebound adjust, tapered steerer, 15x110mm Maxle Stealth thru-axle, 51mm offset, 140mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 25mm rise, 750mm width, 31.8mm
GRIPS	Specialized Sip Grip, light lock-on, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide RS carbon, hydraulic disc, organic pads, carbon lever, Guide S4 4-piston caliper, 200mm rotor
REAR BRAKE	SRAM Guide RS, hydraulic disc, organic pads, Guide S4 4-piston caliper, 200mm rotor
REAR DERAILLEUR	SRAM XO1, carbon cage, 11-speed
SHIFT LEVERS	SRAM X1, 11-speed, trigger
CASSETTE	SRAM XG-1180, 11-speed, 10-42t
CHAIN	SRAM PCX1, 11-speed w/PowerLink
CRANKSET	Custom alloy crankarms
CHAINRINGS	32T
RIMS	Roval Traverse 650b, hookless alloy, 38mm inner width, 24/28h, tubeless ready
FRONT HUB	Roval Traverse, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
REAR HUB	Roval Traverse, DT Swiss internals, sealed cartridge bearings, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
SPOKES	DT Swiss Revolution
FRONT TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Command Post IRcc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel
MOTOR	Exclusive custom tune and software, Trail Tune, 250W
USER INTERFACE	Integrated Trail display, 10-LED battery display, Mission Control iOS/Android App
BATTERY	Custom Levo Battery, 460Wh, 40x3.2Ah, ANT+/Bluetooth® connectivity, IP 67
CHARGER	Custom charger, 42V4A w/Rosenberger plug
WIRING HARNESS	Custom harness w/ Rosenberger plug

TURBO LEVO FSR COMP 6FATTIE



CNDYRED/HYP



MONGRN/BLK



BLK/CHAR

The Turbo Levo FSR Comp 6Fattie has the perfect blend of trail performance, proper handling, technology, and durability.

- The frame was constructed from our M5 Premium Aluminum, which is equal parts strong, lightweight, and incredibly responsive. The design of the frame itself revolves around our Trail Geometry that includes all of our trail hallmarks, like a low-slung bottom bracket, roomy top tube, and ultra-short chainstays. Cable routing is all internal, including that of the Command Post IR, while the battery and motor is fully integrated in the down tube.
- RockShox Yari RC fork features a 15x110mm Maxle Ultimate thru-axle, a Solo Air™ spring, and 140mm of plush travel to take on big hits and bumpy terrain with supreme speed and efficiency.
- SRAM Guide R brakes offer the most adjustability and power in their class. They feature a four-piston design, which leads to a respectable overall weight and consistent modulation.

PART NO.	DESCRIPTION	COLOR	SIZE
95217-5202	LEVO FSR COMP 6FATTIE	CNDYRED/HYP	S
95217-5203			M
95217-5204			L
95217-5205			XL
95216-5102	LEVO FSR COMP 6FATTIE	MONGRN/BLK	S
95216-5103			M
95216-5104			L
95216-5105			XL
95216-5002	LEVO FSR COMP 6FATTIE	BLK/CHAR	S
95216-5003			M
95216-5004			L
95216-5005			XL

LEVO FSR					
SIZE	S	M	L	XL	
Seat Tube Length, Center to Top (mm)	396	435	468	520	
Top Tube Length, Horizontal (mm)	555	585	615	650	
Bottom Bracket Drop (mm)	21	21	21	21	
Bottom Bracket Height (mm)	342	342	342	342	
Chainstay Length (mm)	459	459	459	459	
Seat Tube Angle, Actual (deg)	69.3	69.3	69.3	69.3	
Seat Tube Angle, Effective (deg)	74.5	74.2	73.9	73.6	
Head Tube Angle (deg)	66.5	66.5	66.5	66.5	
Wheel Base (mm)	1154	1181	1212	1246	
Standover Height (mm)	755	763	773	781	
Head Tube Length (mm)	95	100	130	150	
Stack (mm)	596	600	628	646	
Reach (mm)	389	415	434	460	
Handlebar Width (mm)	750	750	750	750	
Stem Length (mm)	45	60	60	60	
Saddle Width (mm)	143	143	143	143	
Seat Post Length (mm)	390	430	430	430	
Crank Length (mm)	165	170	170	170	

SPECS	All specs are subject to change without notice.
FRAME	Specialized M5 Premium Aluminum, Trail Geometry, integrated down tube battery, enclosed internal cable and Command Post IR routing, 148mm spacing, fully sealed cartridge bearings, 120mm travel
REAR SHOCK	FOX FLOAT Performance, Rx Trail Tune, AUTOSAG, DPS damper, rebound and 3-position compression adjust, 197x47.6mm
FORK	RockShox Yari RC 29/27.5+, Solo Air spring, adjustable compression and rebound, 15x110mm Maxle Ultimate thru-axle, 51mm offset, 140mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width
GRIPS	Specialized Sip Grip, light lock-on, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide R, hydraulic disc, metallic pads, Guide S4 4-piston caliper, 200mm rotor
REAR BRAKE	SRAM Guide R, hydraulic disc, metallic pads, Guide S4 4-piston caliper, 200mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM GX, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PCX1, 11-speed w/PowerLink
CRANKSET	Custom alloy crankarms
CHAINRINGS	32T
RIMS	Roval Traverse 650b, hookless alloy, 38mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 110x15mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless
FRONT TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Command Post IRcc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel
MOTOR	Exclusive custom tune and software, Trail Tune, 250W
USER INTERFACE	Integrated Trail display, 10-LED battery display, Mission Control iOS/Android App
BATTERY	Custom Levo Battery, 460Wh, 40x3.2Ah, ANT+/Bluetooth® connectivity, IP 67
CHARGER	Custom charger, 42V4A w/Rosenberger plug
WIRING HARNESS	Custom harness w/ Rosenberger plug

TURBO LEVO FSR 6FATTIE



BLK/RKTRD

When designing the Turbo Levo FSR 6Fattie, we started by building a trail bike with all the hallmarks that our mountain bikes are known for, while streamlining the design for full integration of our Turbo technology.

- The frame was constructed from our M5 Premium Aluminum, which is equal parts strong, lightweight, and incredibly responsive. The design of the frame itself revolves around our Trail Geometry that includes all of our trail hallmarks, like a low-slung bottom bracket, roomy top tube, and ultra-short chainstays. Cable routing is all internal, including that of the Command Post IR, while the battery and motor is fully integrated in the down tube.
- A RockShox Revelation RC3 fork was developed to deliver 140mm of plush, trail taming travel, while accommodating a 15x110mm Boost Maxle Lite thru-axle for reliable handling and durability over rough, bumpy, or loose terrain.
- SRAM DB5 brakes feature a high-volume reservoir and a custom four-piston design in order to provide you with heaps of stopping power for hard and steep riding.

PART NO.	DESCRIPTION	COLOR	SIZE
95217-7202	LEVO FSR 6FATTIE	BLK/RKTRD	S
95217-7203			M
95217-7204			L
95217-7205			XL

LEVO FSR					
SIZE	S	M	L	XL	
Seat Tube Length, Center to Top (mm)	396	435	468	520	
Top Tube Length, Horizontal (mm)	555	585	615	650	
Bottom Bracket Drop (mm)	21	21	21	21	
Bottom Bracket Height (mm)	342	342	342	342	
Chainstay Length (mm)	459	459	459	459	
Seat Tube Angle, Actual (deg)	69.3	69.3	69.3	69.3	
Seat Tube Angle, Effective (deg)	74.5	74.2	73.9	73.6	
Head Tube Angle (deg)	66.5	66.5	66.5	66.5	
Wheel Base (mm)	1154	1181	1212	1246	
Standover Height (mm)	755	763	773	781	
Head Tube Length (mm)	95	100	130	150	
Stack (mm)	596	600	628	646	
Reach (mm)	389	415	434	460	
Handlebar Width (mm)	750	750	750	750	
Stem Length (mm)	45	60	60	60	
Saddle Width (mm)	143	143	143	143	
Seat Post Length (mm)	350	350	400	400	
Crank Length (mm)	165	170	170	170	

SPECS	All specs are subject to change without notice.
FRAME	Specialized M5 Premium Aluminum, Trail Geometry, integrated down tube battery, enclosed internal cable and Command Post IR routing, 148mm spacing, fully sealed cartridge bearings, 120mm travel
REAR SHOCK	FOX FLOAT Performance, Rx Trail Tune, AUTOSAG, DPS damper, rebound and 3-position compression adjust, 197x47.6mm
FORK	RockShox Revelation RC3 29/27.5+, Solo Air spring, compression and rebound adjust, 15x110mm Maxle Lite thru-axle, 51mm offset, 140mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width
GRIPS	Specialized Sip Grip, light lock-on, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM DB5, hydraulic disc, custom 4-piston caliper, semi-organic pads, 200mm rotor
REAR BRAKE	SRAM DB5, hydraulic disc, 2-piston caliper, semi-organic pads, 200mm rotor
REAR DERAILLEUR	SRAM NX, long cage, 11-speed
SHIFT LEVERS	SRAM NX, 11-speed, trigger
CASSETTE	SRAM PG-1130, 11-speed, 11-42t
CHAIN	SRAM PC1130, 11-speed w/PowerLink
CRANKSET	Custom alloy crankarms
CHAINRINGS	32T
RIMS	Roval Traverse 650b, hookless alloy, 38mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 110x15mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless
FRONT TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Alloy, 2-bolt clamp, 12.5mm offset, 30.9mm, anti-corrosion hardware
MOTOR	Exclusive custom tune and software, Trail Tune, 250W
USER INTERFACE	Integrated Trail display, 10-LED battery display, Mission Control iOS/Android App
BATTERY	Custom LEVO battery, 460Wh, 40x3.2Ah, ANT+/Bluetooth connectivity, IP 67
CHARGER	Custom charger, 42V4A w/Rosenberger plug
WIRING HARNESS	Custom harness w/ Rosenberger plug

TURBO LEVO COMP FAT



CHAR/RKTRED

The Turbo Levo Comp Fat bike was built to go anywhere, ride anything, and to do it all with ease. It provides all of the trail manners that our fat bikes are known for, while seamlessly accommodating our Turbo technology. So it features snappy chainstays, roomy top tubes, and a low bottom bracket that makes the bike feel glued to the trail.

- The frame was constructed from our M5 Premium Aluminum, which is equal parts strong, lightweight, and incredibly responsive. The design of the frame itself revolves around our Fat Hardtail Geometry for Fat tires that includes all of our trail hallmarks, like a low-slung bottom bracket, roomy top tube, and ultra-short chainstays. Cable routing is all internal, including that of the Command Post IR, while the battery and motor is fully integrated in the down tube.
- The RockShox Bluto RL fork is air sprung for smooth, plush travel, while featuring strong and stiff 32mm alloy stanchions and an external rebound adjust for on-the-fly fine-tuning of your suspension performance.
- SRAM Guide R brakes provide powerful, precise, and highly adjustable braking. Their based on a four-piston caliper design that puts out smooth, dependable stopping power, while the Reach Adjust feature allows you to customize the position for easy, one-finger lever pulls. And with SRAM's SwingLink technology, the cam system minimizes deadband without sacrificing modulation.

LEVO FAT				
SIZE	S	L	M	XL
Seat Tube Length, Center to Top (mm)	394	520	470	434
Top Tube Length, Horizontal (mm)	589	650	602	624
Bottom Bracket Drop (mm)	55	55	55	55
Bottom Bracket Height (mm)	324	324	324	324
Chainstay Length (mm)	460	460	460	460
Seat Tube Angle, Effective (deg)	73	73	73	73
Head Tube Angle (deg)	67.5	67.5	67.5	67.5
Wheel Base (mm)	1145	1211	1159	1182
Standover Height (mm)	763	818	791	854
Head Tube Length (mm)	105	130	95	110
Stack (mm)	588	629	611	597
Reach (mm)	410	420	458	437
Fork Length (full) (mm)	491	511	511	511
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	60	60	70	70
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	170	170	170

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Fat HT Geometry, integrated down tube battery, enclosed internal cable and Command Post IR routing, 197mm spacing
FORK	RockShox Bluto RL, Solo Air, 15x150mm Stealth Maxle thru-axle, rebound and lockout adjust, 100mm travel
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise, 31.8mm clamp, 60mm
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width
GRIPS	Specialized Sip Grip, light lock-on, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide R, hydraulic disc, metallic pads, Guide S4 4-piston caliper, 200mm rotor
REAR BRAKE	SRAM Guide R, hydraulic disc, metallic pads, Guide S4 4-piston caliper, 200mm rotor
REAR DERAILLEUR	SRAM GX, Type 2.1, long cage, 10-speed
SHIFT LEVERS	SRAM GX, 10-speed, trigger
CASSETTE	Sunrace, 10-speed, 11-40t
CHAIN	SRAM PC1031, 11-speed w/PowerLink
CRANKSET	Custom alloy crankarms
CHAINRINGS	32T
RIMS	Stout XC, hookless alloy, single wall, 90mm inner width, sleeve joint, 32h
FRONT HUB	Specialized Stout XC, alloy disc, double-sealed cartridge bearings, 15x150mm thru-axle, 32h
REAR HUB	Stout XC, disc alloy, SRAM XD driver body, sealed cartridge bearings, 12x148mm thru-axle, 32h
SPOKES	Stainless, butted, 2.0/1.8/2.0mm, black
FRONT TIRE	Ground Control Fat, Control casing, 26x4.6", 120TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control Fat, Control casing, 26x4.6", 120TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Sport, steel rails, 143mm
SEATPOST	Command Post IRoc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel
MOTOR	Exclusive custom tune and software, Trail Tune, 250W
USER INTERFACE	Integrated Trail display, 10-LED battery display, Mission Control iOS/Android App
BATTERY	Custom LEVO battery, 460Wh, 40x3.2Ah, ANT+/Bluetooth connectivity, IP 67
CHARGER	Custom charger, 42V4A w/Rosenberger plug
WIRING HARNESS	Custom harness w/ Rosenberger plug

PART NO.	DESCRIPTION	COLOR	SIZE
95216-7102	LEVO HT COMP FAT	CHAR/RKTRED	S
95216-7103			M
95216-7104			L
95216-7105			XL

TURBO LEVO HARDTAIL COMP 6FATTIE



BLK/BLK

The Turbo Levo Hardtail Comp 6Fattie has all of the speed and nimble handling that our hardtail trail bikes are known for—only with a sophisticated Turbo boost. Then comes the efficient and powerful Turbo technology, mating the battery and motor into the M5 frame in a new way.

- The frame was constructed from our M5 Premium Aluminum, which is equal parts strong, lightweight, and incredibly responsive. The design of the frame itself revolves around our Trail HT Geometry that includes all of our trail hallmarks, like a low-slung bottom bracket, roomy top tube, and ultra-short chainstays. Cable routing is all internal, including that of the Command Post IR, while the battery and motor is fully integrated in the down tube.
- A RockShox Reba RL fork was developed to deliver up to 120mm of plush, trail taming travel, while accommodating 15x110mm thru-axles for reliable handling and durability over rough, bumpy, or loose terrain.
- SRAM DB5 brakes feature a high-volume reservoir and a custom four-piston design in order to provide you with heaps of stopping power for hard and steep riding.

LEVO HARDTAIL MEN				
SIZE	S	M	L	XL
Seat Tube Length, Center to Top (mm)	394	434	470	505
Top Tube Length, Horizontal (mm)	574	608	633	655
Bottom Bracket Drop (mm)	55	55	55	55
Bottom Bracket Height (mm)	308	308	308	308
Chainstay Length (mm)	450	450	450	450
Seat Tube Angle, Effective (deg)	74	73	73	73
Head Tube Angle (deg)	67	67	67	67
Wheel Base (mm)	1140	1164	1190	1213
Standover Height (mm)	756	786	812	838
Head Tube Length (mm)	110	100	115	130
Stack (mm)	607	616	630	644
Reach (mm)	400	420	440	458
Fork Length (full) (mm)	510	530	530	530
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	370	412	412	412
Crank Length (mm)	165	170	170	170

SPECS	All specs are subject to change without notice.
FRAME	Specialized M5 Premium Aluminum, Trail HT Geometry, integrated down tube battery, enclosed internal cable and Command Post IR routing, 148mm spacing
FORK	RockShox Reba RL 29/27.5+, Fast Black uppers, Solo air, 15x110mm thru-axle, 100/120mm travel (frame size specific)
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width
GRIPS	Specialized Sip Grip, light lock-on, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM DB5, hydraulic disc, custom 4-piston caliper, semi-organic pads, 200mm rotor
REAR BRAKE	SRAM DB5, hydraulic disc, 2-piston caliper, semi-organic pads, 200mm rotor
REAR DERAILLEUR	SRAM GX, Type 2.1, long cage, 10-speed
SHIFT LEVERS	SRAM GX, 10-speed, trigger
CASSETTE	Sunrace, 10-speed, 11-40t
CHAIN	SRAM PC1031, 11-speed w/PowerLink
CRANKSET	Custom alloy crankarms
CHAINRINGS	32T
BOTTOM BRACKET	Integrated in motor
RIMS	Roval Traverse 650b, hookless alloy, 38mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 110x15mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless
FRONT TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Sport, steel rails, 143mm
SEATPOST	TranzX dropper, internal cable routing, remote lever, 30.9mm, S/M: 100mm, L/XL: 120mm travel
MOTOR	Exclusive custom tune and software, Trail Tune, 250W
USER INTERFACE	Integrated Trail display, 10-LED battery display, Mission Control iOS/Android App
BATTERY	Custom LEVO battery, 460Wh, 40x3.2Ah, ANT+/Bluetooth connectivity, IP 67
CHARGER	Custom charger, 42V4A w/Rosenberger plug
WIRING HARNESS	Custom harness w/ Rosenberger plug

PART NO.	DESCRIPTION	COLOR	SIZE
95216-7002	LEVO HT COMP 6FATTIE	BLK/BLK	S
95216-7003			M
95216-7004			L
95216-7005			XL

S-WORKS ERA FSR WORLD CUP



CARB/HYP/TARBLK

Is it moxie? Is it hutzpah? Is it enough raw speed to guarantee motion blur? Actually, the all-new S-Works Era World Cup embodies all these qualities, but with some barely contained "let's do this!" enthusiasm mixed in. Designed and engineered to be the fastest, lightest, and best-fitting women's full-suspension XC machine out there.

- The Era's responsive FACT 11m carbon frame is stiff, ultra-lightweight, and delivers an efficient, nimble-handling ride. Designed with Women's Competitive XC 29 Geometry for great fit and control, cabling is internally routed, while the built-in SWAT™ Tool cradle means you'll always have an EMT multi-tool on hand.
- The custom RockShox SID World Cup 29 fork w/ Brain provides 90 to 100mm of efficient travel depending on the frame size. It also features Brain technology that distinguishes between terrain and rider input in order to maximize your power, while a Brain Fade adjusts the oil flow when not hitting bumps. Lastly, the fork is custom-tuned for women, so you'll always have a performance advantage on the trail.
- The one-by drivetrain is controlled by SRAM's venerable XX1 Eagle components, while braking duties are handled by SRAM's Level Ultimate binders. Combined, the system forms the ultimate in efficiency and intuitive feel, while also having the added benefit of significant weight savings and minimal required maintenance.

ERA FSR			
SIZE	S	M	L
Stack (mm)	588	598	607
Reach (mm)	393	415	438
Head-Tube Length (mm)	90	95	110
Head-Tube Angle (deg)	70.5	70.5	70.5
B-B Height (mm)	320	325	330
B-B Drop (mm)	50	45	40
Trail (mm)	82	82	82
Fork Length (full) (mm)	496	506	506
Fork Rake/Offset (mm)	46	46	46
Front-Center (mm)	634	661	688
Chain-Stay Length (mm)	450	450	450
Wheelbase (mm)	1079	1107	1135
Top-Tube Length (horizontal) (mm)	550	575	600
Bike Stand-Over Height (mm)	719	729	737
Seat-Tube Length (mm)	385	420	445
Seat-Tube Angle (deg)	75	75	75
Handlebar Width (mm)	700	700	700
Stem Length (mm)	(-) 60	75	90
Saddle Width (mm)	155	155	155
Seat Post Length (mm)	350	350	400
Crank Length (mm)	165	170	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 11m, full carbon frame, Women's Competitive XC Geometry, PF30 BB, carbon headset cups, 12x142mm dropouts, internal cable routing, front derailleur mount, PM 160 rear brake, 95mm travel, SWAT™ tool cradle
FORK	Custom RockShox SID World Cup w/ Brain, Position Sensitive damper w/top-mount Brain Fade adjust, Women's Rx Tune, rebound adjust, Solo Air spring, tapered carbon crown/steerer, 15x100mm Maxle Stealth thru-axle, 51mm offset, 90/100mm travel
STEM	Syntace F109, 6-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Mini-rise, FACT carbon, 6-degree upsweep, 8-degree backsweep, 10mm rise, 700mm, 31.8mm
GRIPS	Specialized Sip Grip, lock-on, half-waffle, regular thickness
FRONT BRAKE	SRAM Level Ultimate, hydraulic disc, carbon lever, titanium hardware, organic pads, 180/160mm rotor
REAR BRAKE	SRAM Level Ultimate, hydraulic disc, carbon lever, titanium hardware, organic pads, 160mm rotor
REAR DERAILLEUR	SRAM XX1 Eagle, 12-speed
SHIFT LEVERS	SRAM XX1 Eagle, 12-speed, trigger
CASSETTE	SRAM XG-1295, 12-speed, 10-50t
CHAIN	SRAM XX1 Eagle, black, 12-speed w/PowerLink
CRANKSET	SRAM XX1 Eagle, carbon, 30mm spindle, 49mm chainline
CHAINRINGS	SRAM X-Sync, direct mount, 32T
BOTTOM BRACKET	SRAM PF30, OS press-in bearings
RIMS	Roval Control SL 29, hookless carbon, 22mm inner width, 24/28h, tubeless ready
FRONT HUB	Roval Control SL, sealed cartridge bearings, labyrinth style, 15mm thru-axle, 100mm spacing, 24h
SPOKES	DT Swiss Revolution
FRONT TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Women's Body Geometry Myth Expert Thin, hollow titanium rails, 155mm
SEATPOST	S-Works FACT carbon, 0mm setback, carbon rail clamps, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
94817-0002	SW ERA CARBON WORLDCUP	CARB/HYP/TARBLK	S
94817-0003			M
94817-0004			L

ERA FSR EXPERT CARBON WORLD CUP



REDFLKTNT/NRDCRED/BBYBLU

Going fast is as much about attitude as it is raw power, and the Era Expert Carbon 29er has sass to spare. With high-performance components and wheels, this bike's ready to help convert your raw power into your best time ever—and maybe a podium spot to boot.

- By pairing a FACT 9m carbon fiber frame w/ an M5 alloy rear end with our Women's World Cup XC 29 Geometry, this Era FSR places a focus on tight tube angles and light overall weight for explosive speed and nimble handling on the race circuit.
- The custom RockShox SID Brain 29 fork provides 90 to 100mm of efficient travel depending on the frame size. It also features Brain technology that distinguishes between terrain and rider input in order to maximize your power, while a Brain Fade adjusts the oil flow when not hitting bumps. Lastly, the fork is custom-tuned for women, so you'll always have a performance advantage on the trail.
- A SRAM X1 rear derailleur controls a wide range of gears with reliable precision.

ERA FSR			
SIZE	S	M	L
Stack (mm)	588	598	607
Reach (mm)	393	415	438
Head-Tube Length (mm)	90	95	110
Head-Tube Angle (deg)	70.5	70.5	70.5
B-B Height (mm)	320	325	330
B-B Drop (mm)	50	45	40
Trail (mm)	82	82	82
Fork Length (full) (mm)	496	506	506
Fork Rake/Offset (mm)	46	46	46
Front-Center (mm)	634	661	688
Chain-Stay Length (mm)	450	450	450
Wheelbase (mm)	1079	1107	1135
Top-Tube Length (horizontal) (mm)	550	575	600
Bike Stand-Over Height (mm)	719	729	737
Seat-Tube Length (mm)	385	420	445
Seat-Tube Angle (deg)	75	75	75
Handlebar Width (mm)	700	700	700
Stem Length (mm)	(-) 60	70	90
Saddle Width (mm)	155	155	155
Seat Post Length (mm)	350	350	400
Crank Length (mm)	165	170	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 9m, carbon front triangle, M5 alloy rear end, Women's Competitive XC Geometry, PF30 BB, carbon headset cups, 12x142mm dropouts, internal cable routing, front derailleurmount, PM 160 rear brake, SWAT™ tool cradle
REAR SHOCK	FOX/Specialized remote w/ Mini Brain, Women's Rx tune, AUTOSAG, Spike Valve, BRAIN Fade adjust I-Valve, 200x48mm
FORK	Custom RockShox SID w/ Brain, Women's Rx tune, Position Sensitive damper, bottom-mount Brain Fade adjust, rebound adjust, Solo Air spring, tapered alloy crown/steerer, 100x15mm Maxle Stealth thru-axle, 90/100mm travel, 51mm offset
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 7050 alloy, 8-backsweep, 6-upsweep, 10mm rise, 700mm width, 31.8mm clamp
GRIPS	Specialized Sip Grip, lock-on, half-waffle, regular thickness
FRONT BRAKE	Shimano Deore SLX M7000, hydraulic disc, metallic pad, 180/160mm rotor
REAR BRAKE	Shimano Deore SLX M7000, hydraulic disc, metallic pad, 160mm rotor
REAR DERAILLEUR	SRAM X1 Type 2.1, 11-speed
SHIFT LEVERS	SRAM X1, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PC-1130, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 49mm chainline
CHAINRINGS	RaceFace, direct mount, 30T
BOTTOM BRACKET	PF30
RIMS	Roval Control 29, hookless alloy, 21mm inner width, 32h, tubeless ready
FRONT HUB	Roval Control, sealed cartridge bearings, 15mm thru-axle, 100mm spacing, 32h
REAR HUB	Roval Control, DT Swiss internals, 36T engagement, XD driver body, 12x142mm, 32h
SPOKES	DT Swiss Revolution
FRONT TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Specialized, alloy, single bolt, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
93017-3002	ERA EXPERT CARBON WORLDCUP	REDFLKTNT/NRDCRED/BBYBLU	S
93017-3003			M
93017-3004			L

ERA FSR COMP CARBON



NRDCRED/LTTUR/TARBLK

XC racing is hard enough, so when there's an opportunity to have a significant performance advantage, why wouldn't you take it? Don't worry, because our Era Comp Carbon has your back. It's designed for women from the ground up, and it's loaded with game-changing technology that's sure to take your results to the next level.

- By pairing a FACT 9m carbon fiber frame w/ an M5 alloy rear end with our Women's World Cup XC 29 Geometry, this Epic places a focus on tight tube angles and light overall weight for explosive speed and nimble handling on the race circuit.
- A custom RockShox Reba RL 29 fork offers 90 to 100mm of smooth travel, while an easily accessible compression and rebound adjust permit you to customize the feel according to the terrain at hand. Even better, it's custom-tuned for women, so your performance advantage will be that much greater.
- Shimano Deore XT 11-speed rear derailleur is tough, reliable, and incredibly precise.

ERA FSR			
SIZE	S	M	L
Stack (mm)	588	598	607
Reach (mm)	393	415	438
Head-Tube Length (mm)	90	95	110
Head-Tube Angle (deg)	70.5	70.5	70.5
B-B Height (mm)	320	325	330
B-B Drop (mm)	50	45	40
Trail (mm)	82	82	82
Fork Length (full) (mm)	496	506	506
Fork Rake/Offset (mm)	46	46	46
Front-Center (mm)	634	661	688
Chain-Stay Length (mm)	450	450	450
Wheelbase (mm)	1079	1107	1135
Top-Tube Length (horizontal) (mm)	550	575	600
Bike Stand-Over Height (mm)	719	729	737
Seat-Tube Length (mm)	385	420	445
Seat-Tube Angle (deg)	75	75	75
Handlebar Width (mm)	700	700	700
Stem Length (mm)	(-) 60	70	90
Saddle Width (mm)	155	155	155
Seat Post Length (mm)	350	350	400
Crank Length (mm)	165	170	175

SPECS All specs are subject to change without notice.

FRAME	FACT 9m, carbon front triangle, M5 alloy rear end, Women's Competitive XC Geometry, PF30 BB, carbon headset cups, 12x142mm dropouts, internal cable routing, front derailleurmount, PM 160 rear brake, SWAT™ tool cradle
REAR SHOCK	FOX/Specialized remote Mini Brain, Women's Tune, AUTOSAG, Spike Valve, Brain Fade adjust I-Valve, 200x48mm
FORK	Custom RockShox Reba RL, Solo Air, Women's Rx Tune, rebound adjust, tapered alloy crown/steerer, 15x100mm Maxle Stealth thru-axle, 51mm offset, 90/100mm travel
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 6000 alloy, 8-backsweep, 6-upsweep, 10mm rise, 700mm width, 31.8mm clamp
GRIPS	Specialized Sip Grip, lock-on, half-waffle, regular thickness
FRONT BRAKE	Shimano M506, hydraulic disc, resin pad, 180/160mm rotor
REAR BRAKE	Shimano M506, hydraulic disc, resin pad, 160mm rotor
FRONT DERAILLEUR	Shimano SLX 7025, direct-mount, down-swing
REAR DERAILLEUR	Shimano Deore XT M8000, Shadow Plus, SGS cage, 11-speed
SHIFT LEVERS	Shimano SLX, 11-speed
CASSETTE	Shimano SLX M7000, 11-speed, 11-42t
CHAIN	KMC X11EL, 11-speed w/reusable MissingLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 49mm chainline
CHAINRINGS	RaceFace, 34/24T, 104/64mm BCD
BOTTOM BRACKET	PF30
RIMS	Roval Control, hookless alloy, 21mm inner width, 32h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x100mm thru-axle, 32h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x142mm thru-axle, 32h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Specialized, alloy, single bolt, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
93017-5002	ERA COMP CARBON	NRDCRED/LTTUR/TARBLK	S
93017-5003			M
93017-5004			L

WOMEN'S EPIC HT COMP CARBON



NRDCRED/TARBLK/LTTUR

Lighter, faster, better handling—the Women's Epic Hardtail Comp Carbon is changing XC hardtails in a major way. Even better, it plays host to tons of women's-specific components and a custom fork tune that's ideal for lighter riders.

- By pairing a FACT 10m carbon fiber frame with our XC 29 Geometry, this Epic HT places a focus on tight tube angles and extremely light overall weight for explosive speed and nimble handling on the race circuit. For good measure, we also gave it 148mm rear spacing and all-new triangulated post-mount brake mounts.
- A custom RockShox Reba RL 29 fork offers up 100mm of smooth travel, while an easily accessible compression and rebound adjusts permit you to customize the feel according to the terrain at hand. Lastly, this fork has received our custom Women's Rx Tune for even better performance.
- Shimano Deore XT Shadow Plus 11-speed rear derailleur is tough, reliable, and incredibly precise.

EPIC HT WMN CARBON				
SIZE	XS	S	M	L
Stack (mm)	589	599	608	622
Reach (mm)	380	395	418	441
Head-Tube Length (mm)	95	95	95	110
Head-Tube Angle (deg)	69.8	69.8	69.8	69.8
B-B Height (mm)	309	309	309	309
B-B Drop (mm)	61	61	61	61
Trail (mm)	81.8	81.8	81.8	81.8
Fork Length (full) (mm)	486	496	506	506
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	631	650	676	704
Chain-Stay Length (mm)	430	430	430	430
Wheelbase (mm)	1054	1073	1099	1127
Top-Tube Length (horizontal) (mm)	549	568	595	623
Bike Stand-Over Height (mm)	731	760	790	814
Seat-Tube Length (mm)	370	400	430	470
Seat-Tube Angle (deg)	74	73.9	73.8	73.7
Handlebar Width (mm)	700	700	700	700
Stem Length (mm)	(-) 60	70	90	90
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	350	350	400	400
Crank Length (mm)	165	170	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 10m, full carbon, XC Geometry, internal split-housing cable routing, PF30 BB, 12x148mm rear end, triangulated post-mount 160mm brake
FORK	Custom RockShox Reba RL, Women's Rx Tune, rebound adjust, Solo Air spring, tapered alloy crown/steerer, 15x110mm Maxle Stealth thru-axle, 51mm offset, 80/90/100mm travel
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 6000 alloy, 8-backsweep, 6-upsweep, 10mm rise, 700mm width, 31.8mm clamp
GRIPS	Specialized Sip Grip, lock-on, half-waffle, regular thickness
FRONT BRAKE	Shimano M506, hydraulic disc, resin pad, 180/160mm rotor
REAR BRAKE	Shimano M506, hydraulic disc, resin pad, 160mm rotor
FRONT DERAILLEUR	Shimano SLX 7025, direct-mount, down-swing
REAR DERAILLEUR	Shimano Deore XT M8000, Shadow Plus, SGS cage, 11-speed
SHIFT LEVERS	Shimano SLX M7000, 11-speed
CASSETTE	SRAM PG-1130, 11-speed, 11-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 52mm chainline
BOTTOM BRACKET	PF30
RIMS	Roval Control, hookless alloy rim, 21mm inner width, 32h
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x110mm thru-axle, 32h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h
SPOKES	DT Swiss Comp
FRONT TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Specialized, alloy, 2-bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
93117-7003	EPIC HT WMN COMP CARBON 29	NRDCRED/TARBLK/LTTUR	M

JETT PRO 29



TARBLK/HYP/PDRGRN

Whether you're just getting your feet wet in the world of cross country mountain biking or you have heaps of experience and just need a bike that matches your skills, the Jett Pro 29 will deliver all of the performance you need in an XC rig.

- The A1 SL Aluminum frame is lightweight, incredibly sturdy, and reliable for all your Cross Country exploits. It's also designed with our Women's XC 29er Geometry, so you'll get an ultra-low standover, an incredible fit, and more confidence and control while riding.
- A RockShox 30 Gold suspension fork offers 80mm of plush, high-performance travel that'll smooth out the bumps and ruts on your trail rides. It features proprietary technology from RockShox, like its Solo Air™ spring, that maintains an ideal equilibrium, as well as being one of the lightest air springs on the market.
- The Shimano Deore XT rear derailleur is one of the most sought after components in mountain biking. It's remarkably reliable, precise and crisp in its shifting, and is nothing if not durable.

JETT A1 SL			
SIZE	S	M	L
Stack (mm)	589	601	615
Reach (mm)	377	396	412
Head-Tube Length (mm)	90	100	115
Head-Tube Angle (deg)	70.5	71	71
B-B Height (mm)	305	305	305
B-B Drop (mm)	63.5	63.5	63.5
Trail (mm)	82	82	82
Fork Length (full) (mm)	480	480	480
Fork Rake/Offset (mm)	46	46	46
Front-Center (mm)	615	633	654
Chain-Stay Length (mm)	442	442	442
Wheelbase (mm)	1049	1067	1088
Top-Tube Length (horizontal) (mm)	552	574	594
Bike Stand-Over Height (mm)	711	746	768
Seat-Tube Length (mm)	381	432	483
Seat-Tube Angle (deg)	73.5	73.5	73.5
Handlebar Width (mm)	700	700	700
Stem Length (mm)	60	70	70
Saddle Width (mm)	155	155	155
Seat Post Length (mm)	350	350	400
Crank Length (mm)	165	170	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 SL Aluminum, Women's XC 29 Geometry, women's fully-butted tube sets, tapered head tube, forged post-mount 160mm dropouts, replaceable derailleur hanger
FORK	RockShox 30 Gold 29, Solo Air spring, remote lockout, rebound adjust, 9mm QR, 80mm travel
STEM	Specialized Stout, 3D-forged alloy, 4-bolt, 6-degree rise, anti-corrosion hardware
HANDLEBARS	Stout, alloy, 8-degree backsweep, 6-degree upsweep, 10mm rise, 700mm width, 31.8mm
GRIPS	Lock-on grips, 130.4mm length
FRONT BRAKE	Shimano BR-M506, hydraulic disc, resin pads, 160mm rotor
REAR BRAKE	Shimano BR-M506, hydraulic disc, resin pads, 160mm
FRONT DERAILLEUR	SRAM X5, high-clamp 34.9mm, 2x10
REAR DERAILLEUR	Shimano Deore XT, Shadow Plus, SGS cage, 10-speed
SHIFT LEVERS	Shimano Deore, RapidFire, 1-spec, 10-speed
CASSETTE	SRAM PG-1020, 10-speed, 11-36t
CHAIN	SRAM PC-1031, 10-speed w/PowerLink
CRANKSET	Specialized Stout XC, 2-piece 2x10, 24mm spindle, anti-corrosion hardware
CHAINRINGS	Stout 36/22T chainrings
BOTTOM BRACKET	BSA threaded, external bearing, 73mm width
RIMS	Stout XC SL 29, alloy disc, double-wall, sleeve joint, 21mm inner width, 28h
FRONT HUB	Shimano HB-RM35, Center Lock disc, 9x100mm, 28h
REAR HUB	Shimano FH-RM35, Center Lock disc, 10x135mm, 28h
SPOKES	Stainless, 14g, black
FRONT TIRE	Ground Control Sport, 29x2.1", 60TPI, wire bead, Flak Jacket protection
REAR TIRE	Ground Control Sport, 29x2.1", 60TPI, wire bead, Flak Jacket protection
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
91817-1002	JETT PRO 29	TARBLK/HYP/PDRGRN	S
91817-1003			M
91817-1004			L

JETT COMP 29



DPNDGO/NRDCCRED/FLKSIL



TUR/PDRGRN/TARBLK

We designed the Jett Comp 29 to help you get out there and ride all the cross country terrain you can get your hands on. To make sure of it, it features a high-performance, super-lightweight aluminum frame, plus an efficient component package.

- The A1 SL Aluminum frame is lightweight, incredibly sturdy, and reliable for all your Cross Country exploits. It's also designed with our Women's XC 29er Geometry, so you'll get an ultra-low standover, an incredible fit, and more confidence and control while riding.
- SR Suntour XCR-Air fork puts out 80/100mm (size-specific) of plush and reactive travel, provided by air-sprung suspension that's custom-tuned for lighter riders.
- Shimano Deore rear derailleur provides crisp, reliable shifting that you can count on when the going gets rough. With it, you'll be able to precisely move through the wide, 11-36t gear range to make cruising the flats almost as easy climbing those hills.

JETT A1 SL

SIZE	S	M	L
Stack (mm)	589	601	615
Reach (mm)	377	396	412
Head-Tube Length (mm)	90	100	115
Head-Tube Angle (deg)	70.5	71	71
B-B Height (mm)	305	305	305
B-B Drop (mm)	63.5	63.5	63.5
Trail (mm)	82	82	82
Fork Length (full) (mm)	480	480	480
Fork Rake/Offset (mm)	46	46	46
Front-Center (mm)	615	633	654
Chain-Stay Length (mm)	442	442	442
Wheelbase (mm)	1049	1067	1088
Top-Tube Length (horizontal) (mm)	552	574	594
Bike Stand-Over Height (mm)	711	746	768
Seat-Tube Length (mm)	381	432	483
Seat-Tube Angle (deg)	73.5	73.5	73.5
Handlebar Width (mm)	680	680	680
Stem Length (mm)	60	70	70
Saddle Width (mm)	155	155	155
Seat Post Length (mm)	350	350	400
Crank Length (mm)	165	170	175

SPECS

All specs are subject to change without notice.

FRAME	Specialized A1 SL Aluminum, Women's XC 29 Geometry, women's fully-butted tube sets, tapered head tube, forged post-mount 160mm dropouts, replaceable derailleur hanger
FORK	SR Suntour XCR-Air, rebound adjustment w/remote lockout, 80/100mm of travel (size specific)
STEM	Stout, 3D-forged alloy, 31.8mm clamp, 6-degree rise
HANDLEBARS	Stout, alloy, 8-degree backsweep, 6-degree upsweep, 10mm rise, 680mm width, 31.8mm
GRIPS	Specialized MTB lock-on
FRONT BRAKE	Shimano BL-M315, hydraulic disc, resin pads, 160mm rotor
REAR BRAKE	Shimano BR-M315, hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	SRAM X5, high-clamp 34.9mm, 2x10
REAR DERAILLEUR	Shimano Deore, Shadow design, SGS cage, 9-speed
SHIFT LEVERS	Shimano Acera, RapidFire Plus, 9-speed
CASSETTE	Sunrace, 9-speed, 11-36t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	Stout, forged alloy construction, 2x9, anti-corrosion hardware
CHAINRINGS	36/22T steel chainrings
BOTTOM BRACKET	Square taper, 73mm, internal bearings
RIMS	Stout XC 29, alloy disc, double-wall, pinned joint, 21mm inner width, 28/32h
FRONT HUB	Shimano HB-RM35, Center Lock disc, 9x100mm, 28h
REAR HUB	Shimano FH-RM35, Center Lock disc, 10x135mm, 32h
SPOKES	Stainless, 14g, black
FRONT TIRE	Ground Control Sport, 29x2.1", 60TPI, wire bead, Flak Jacket protection
REAR TIRE	Fast Trak Sport, 29x2.0", 30TPI, wire bead, Flak Jacket protection
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
81817-5002	JETT COMP 29	DPNDGO/NRDCCRED/FLKSIL	S
81817-5003			M
81817-5004			L
81817-5102	JETT COMP 29	TUR/PDRGRN/TARBLK	S
81817-5103			M
81817-5104			L

JETT SPORT 29



NRDCRED/TARBLK/LTTUR



TARBLK/LTTUR/METWHTSIL

The Jett Sport 29 features a lightweight aluminum frame and a durable component package that ensures you can get out there and ride all the cross country terrain in your area with a newfound confidence.

- The rugged A1 Premium Aluminum frame is sturdy and reliable for all your Cross Country exploits. It's also designed with our Women's XC 29er Geometry, so you'll get an ultra-low standover, an incredible fit, and more confidence and control while riding.
- The SR Suntour XCM fork puts out 80/100mm (size-specific) of plush and reactive travel, provided by air-sprung air-sprung suspension that's custom-tuned for lighter riders.
- A Shimano Alivio rear derailleur controls the rear shifting with durable aplomb. It shifts along a wide gear range, 11-34t, so you can ride confidently knowing that you'll always have the right gear for the hill at hand.

JETT A1			
SIZE	S	M	L
Stack (mm)	612	623	633
Reach (mm)	378	392	414
Head-Tube Length (mm)	100	110	120
Head-Tube Angle (deg)	70	70.5	70.5
B-B Height (mm)	308	308	308
B-B Drop (mm)	64.5	64.5	64.5
Trail (mm)	86	83	83
Fork Length (full) (mm)	495	495	495
Fork Rake/Offset (mm)	46	46	46
Front-Center (mm)	629	642	667
Chain-Stay Length (mm)	450	450	450
Wheelbase (mm)	1071	1084	1109
Top-Tube Length (horizontal) (mm)	559	577	601
Bike Stand-Over Height (mm)	684	725	754
Seat-Tube Length (mm)	361	417	468
Seat-Tube Angle (deg)	73.5	73.5	73.5
Handlebar Width (mm)	680	680	680
Stem Length (mm)	60	70	70
Saddle Width (mm)	155	155	155
Seat Post Length (mm)	350	350	400
Crank Length (mm)	165	170	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Women's XC 29 Geometry, forged post-mount 160mm dropouts, replaceable derailleur hanger, kickstand mount
FORK	SR Suntour XCM, coil spring, hydraulic lock-out w/Multi-Circuit Damping, 80/100mm of travel (size specific)
STEM	Stout, 3D-forged alloy, 31.8mm clamp, 6-degree rise
HANDLEBARS	Stout, alloy, 8-degree backsweep, 6-degree upsweep, 10mm rise, 680mm width, 31.8mm
GRIPS	Specialized MTB lock-on
FRONT BRAKE	Shimano BL-M315, hydraulic disc, resin pads, 160mm rotor
REAR BRAKE	Shimano BR-M315, hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	Shimano Altus, 34.9mm clamp, down-swing, 7/8-speed
REAR DERAILLEUR	Shimano Alivio, Shadow design, SGS cage, 9-speed
SHIFT LEVERS	Shimano Altus, 8-speed
CASSETTE	Sunrace, 8-speed, 11-34t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Stout, forged alloy construction, 8-speed
CHAINRINGS	44/32/22T
BOTTOM BRACKET	Square taper, 73mm, internal bearings
RIMS	Stout 29, alloy disc, double-wall, pinned joint, 20mm inner width, 32h
FRONT HUB	Shimano Center Lock, disc, 9x100mm QR, 32h
REAR HUB	Shimano Center Lock, disc, 10x135mm QR, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Ground Control Sport, 29x2.1", 60TPI, wire bead, Flak Jacket protection
REAR TIRE	Fast Trak Sport, 29x2.0", 30TPI, wire bead, Flak Jacket protection
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
81817-6002	JETT SPORT 29	NRDCRED/TARBLK/LTTUR	S
81817-6003			M
81817-6004			L
81817-6102	JETT SPORT 29	TARBLK/LTTUR/METWHTSIL	S
81817-6103			M
81817-6104			L

RHYME PRO CARBON 6FATTIE



TARBLK/HYP/CLGRY

After one ride on the Rhyme Pro Carbon 6Fattie, you'll never be riding trail again. It's a bold statement to make, but the increase in traction, control, and floatation that our 6Fattie Wheel System provides is nothing short of revolutionary.

- FACT 11m carbon fiber Trail Chassis with a Rhyme FSR rear end that blends stiffness with light weight to form the pinnacle of efficiency, while fully enclosed cable routing and an integrated SWAT™ Door create exceptional handling and zero-hassle storage.
- RockShox Pike RC fork features a 15x110mm Maxle Ultimate thru-axle and 150mm of plush travel to take on big hits and bumpy terrain with supreme speed and efficiency.
- SRAM Guide RS brakes offer the most adjustability and power in their class. They feature a four-piston design and the latest SwingLink™ lever cam, which leads to a respectable overall weight, top-of-the-line heat management, and smooth, consistent modulation.

RHYME 6FATTIE CARBON				
SIZE	XS	S	M	L
Stack (mm)	616	618	618	646
Reach (mm)	371	386	413	431
Head-Tube Length (mm)	95	95	95	125
Head-Tube Angle (deg)	67	67	67	67
B-B Height (29x2.3") (mm)	338	338	338	338
B-B Height (650x3") (mm)	331	331	331	331
B-B Height (650x2.8") (mm)	325	325	325	325
B-B Drop (mm)	33	33	33	33
Trail (mm)	97	97	97	96.5
Fork Length (full) (mm)	560	560	560	560
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	673	687	714	744
Chain-Stay Length (mm)	437	437	437	437
Wheelbase (mm)	1106	1122	1149	1179
Top-Tube Length (horizontal) (mm)	538	563	590	616
Bike Stand-Over Height (mm)	732	754	761	770
Seat-Tube Length (mm)	386	396	430	468
Seat-Tube Angle (deg)	75	74	74	74
Handlebar Width (mm)	720	720	720	720
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	310	390	390	430
Crank Length (mm)	165	170	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 11m, full carbon chassis and rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 135mm of travel
REAR SHOCK	Custom Öhlins STX, Single Tube design, Women's Rx Trail Tune, 3rd Chamber air spring technology, AUTOSAG, adjustable compression & rebound damping, 197x48mm
FORK	RockShox Pike RC 29/27.5+, Solo Air, compression and rebound adjust, tapered steerer, 15x110mm Maxle Stealth thru-axle, 51mm offset, 150mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Mini-rise, 7050 alloy, 8-backsweep, 6-upsweep, 10mm rise, 720mm width, 31.8mm clamp
GRIPS	Specialized Sip Grip, lock-on, half-waffle, regular thickness
FRONT BRAKE	SRAM Guide RS carbon, hydraulic disc, organic pads, carbon lever, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide RS, hydraulic disc, organic pads, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM X01 Eagle, 12-speed
SHIFT LEVERS	SRAM X01 Eagle, 12-speed, trigger
CASSETTE	SRAM XG-1295, 12-speed, 10-50t
CHAIN	SRAM X01 Eagle, silver, 12-speed w/PowerLink
CRANKSET	Custom SRAM XX1 Eagle, alloy, 30mm spindle, 52mm chainline
CHAINRINGS	Custom X1, direct mount, 30T
BOTTOM BRACKET	SRAM PF30, OS press-in bearings
RIMS	Roval Traverse 650, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Roval Traverse, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
REAR HUB	Roval Traverse, DT Swiss internals, sealed cartridge bearings, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
SPOKES	DT Swiss Revolution
FRONT TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Women's Body Geometry Myth Expert Thin, hollow titanium rails, 155mm
SEATPOST	Command Post IRcc, 10-12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, XS: 75mm, S/M: 100mm, L: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
96317-1001	RHYME PRO CARBON 6FATTIE	TARBLK/HYP/CLGRY	XS
96317-1002			S
96317-1003			M

RHYME COMP CARBON 6FATTIE



CLGRY/TUR/DPNDGO

If you can't benefit from more control when you're hammering on the trail, we'll have what you're drinking, because control is the name of the game for serious trail riding. For the rest of mere mortals, though, there's our Rhyme FSR Comp Carbon 6Fattie.

- FACT 9m carbon fiber Trail Chassis with a Rhyme FSR M5 alloy rear end blends stiffness with light weight to form the pinnacle of efficiency, while 135mm of travel, fully enclosed cable routing, and integrated SWAT™ Door create exceptional handling and zero-hassle storage.
- RockShox Yari 27.5+ fork features a 15x110mm Maxle Ultimate thru-axle, a Solo Air™ spring, and 150mm of plush travel to take on big hits and bumpy terrain with supreme speed and efficiency.
- SRAM Guide brakes w/ S4 calipers provide powerful, precise, and highly adjustable braking. Their based on a four-piston caliper design that puts out smooth, dependable stopping power, while the Reach Adjust feature allows you to customize the position for easy, one-finger lever pulls.

RHYME 6FATTIE CARBON				
SIZE	XS	S	M	L
Stack (mm)	616	618	618	646
Reach (mm)	371	386	413	431
Head-Tube Length (mm)	95	95	95	125
Head-Tube Angle (deg)	67	67	67	67
B-B Height (29x2.3") (mm)	338	338	338	338
B-B Height (650x3") (mm)	331	331	331	331
B-B Height (650x2.8") (mm)	325	325	325	325
B-B Drop (mm)	33	33	33	33
Trail (mm)	97	97	97	96.5
Fork Length (full) (mm)	560	560	560	560
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	673	687	714	744
Chain-Stay Length (mm)	437	437	437	437
Wheelbase (mm)	1106	1122	1149	1179
Top-Tube Length (horizontal) (mm)	538	563	590	616
Bike Stand-Over Height (mm)	732	754	761	770
Seat-Tube Length (mm)	386	396	430	468
Seat-Tube Angle (deg)	75	74	74	74
Handlebar Width (mm)	720	720	720	720
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	310	390	390	430
Crank Length (mm)	165	170	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 9m, carbon front chassis, M5 alloy rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 135mm of travel
REAR SHOCK	RockShox Monarch RT, Women's Rx Tune, AUTOSAG, rebound and 2-position compression adjust, 197x48mm
FORK	RockShox Yari 29/27.5+, Solo Air, rebound & compression adjust, 15x110mm Maxle Ultimate thru-axle, 150mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Flat Top, alloy, 8-degree backsweep, 6-degree upsweep, 10mm rise, 720mm width, 31.8mm
GRIPS	Specialized Sip Grip, lock-on, half-waffle, regular thickness
FRONT BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM GX, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 52mm chainline
BOTTOM BRACKET	Race Face, PF30
RIMS	Roval Traverse 650b, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x110mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Command Post IRoc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote adjust SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
96317-5301	RHYME COMP CARBON 6FATTIE	CLGRY/TUR/DPNDGO	XS
96317-5302			S
96317-5303			M

RHYME COMP 6FATTIE



LTTUR/NRDCRED/TARBLK

We all know a value when we see it, but sadly, value and performance rarely come together. Our RhyME FSR Comp 6Fattie, however, is guaranteed to take your trail riding to the next level—all without breaking the bank.

- M5 alloy Trail Chassis with a RhyME FSR rear end blends durability, stiffness, and light weight, while 150mm of travel Trail Geometry provide more than capable handling.
- A custom RockShox Revelation RL fork was developed to deliver 150mm of plush, trail-taming travel, while accommodating a 15x110mm Maxle Lite thru-axle for reliable handling and durability over rough, bumpy, or loose terrain.
- SRAM Guide brakes w/ S4 calipers provide powerful, precise, and highly adjustable braking. Their based on a four-piston caliper design that puts out smooth, dependable stopping power, while the Reach Adjust feature allows you to customize the position for easy, one-finger lever pulls.
- Roval 650b rims have an ultra-wide 29mm internal width and an alloy construction for increased durability, stability, and speed down the trail.

RHYME 6FATTIE ALLOY				
SIZE	XS	S	M	L
Stack (mm)	616	618	618	645
Reach (mm)	371	386	413	435
Head-Tube Length (mm)	95	95	95	125
Head-Tube Angle (deg)	67	67	67	67.5
B-B Height (29x2.3") (mm)	338	338	338	338
B-B Height (650x3") (mm)	331	331	331	331
B-B Height (650x2.8") (mm)	325	325	325	325
B-B Drop (mm)	33	33	33	36
Trail (mm)	97	97	97	104
Fork Length (full) (mm)	560	560	560	551
Fork Rake/Offset (mm)	51	51	51	46
Front-Center (mm)	673	687	714	738
Chain-Stay Length (mm)	437	437	437	437
Wheelbase (mm)	1106	1122	1149	1172
Top-Tube Length (horizontal) (mm)	538	563	590	611
Bike Stand-Over Height (mm)	732	754	761	766
Seat-Tube Length (mm)	386	396	430	468
Seat-Tube Angle (deg)	74.5	74	74	75
Handlebar Width (mm)	720	720	720	720
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	310	390	390	430
Crank Length (mm)	165	170	175	175

SPECS	All specs are subject to change without notice.
FRAME	M5 alloy, Trail Geometry, PF30 BB, internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 135mm of travel
REAR SHOCK	RockShox Monarch RT, Women's RxL Tune, AUTOSAG, rebound and 2-position compression adjust, 197x48mm
FORK	RockShox Revelation RL 29/27.5+, Solo Air spring, lockout and rebound adjust, 15x110mm Maxle Lite thru-axle, 51mm offset, 150mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Flat Top, alloy, 8-degree backsweep, 6-degree upsweep, 10mm rise, 720mm width, 31.8mm
GRIPS	Specialized Sip Grip, lock-on, half-waffle, regular thickness
FRONT BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM GX, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 52mm chainline
RIMS	Roval Traverse 650b, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x110mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Command Post IRcc, 10-12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, XS: 75mm, S/M: 100mm, L: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
96317-5101	RHYME COMP 6FATTIE	LTTUR/NRDCRED/TARBLK	XS
96317-5102			S
96317-5103			M

RHYME COMP CARBON 650B



NRDCRED/LTTUR/TARBLK

The mission of the Rhyme FSR Comp Carbon 650b is pretty simple: Give women the best performing trail bike out there. It features our proprietary trail shock tune for women, Women's Rx Tune, that's tailored to give women the best suspension performance possible.

- The FACT 9m carbon fiber Trail Chassis with a Rhyme FSR M5 alloy rear end blends stiffness with light weight to reach the pinnacle of efficiency, while fully enclosed cable routing and an integrated SWAT™ Door create exceptional handling and zero-hassle storage. The frame also features our Trail 650b Geometry that adds to confidence, fit, and performance.
- RockShox Yari fork features a 15x110mm Maxle Ultimate thru-axle, a Solo Air™ spring, and 150mm of plush travel to take on big hits and bumpy terrain with supreme speed and efficiency.
- SRAM Guide brakes w/ S4 calipers provide powerful, precise, and highly adjustable braking. Their based on a four-piston caliper design that puts out smooth, dependable stopping power, while the Reach Adjust feature allows you to customize the position for easy, one-finger lever pulls.

RHYME 650 CARBON				
SIZE	XS	S	M	L
Stack (mm)	587	590	599	608
Reach (mm)	369	388	414	442
Head-Tube Length (mm)	95	95	105	115
Head-Tube Angle (deg)	66.5	67	67	67
B-B Height (650x2.3") (mm)	335	335	335	335
B-B Height (650x2.6") (mm)	340	340	340	340
B-B Drop (mm)	18	18	18	18
Trail (mm)	108	104	104	104
Fork Length (full) (mm)	542	542	542	542
Fork Rake/Offset (mm)	42	42	42	46
Front-Center (mm)	663	677	706	738
Chain-Stay Length (mm)	420	420	420	420
Wheelbase (mm)	1082	1096	1126	1158
Top-Tube Length (horizontal) (mm)	539	558	587	618
Bike Stand-Over Height (mm)	724	742	748	757
Seat-Tube Length (mm)	386	396	430	468
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	720	720	720	720
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	310	390	390	430
Crank Length (mm)	165	170	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 9m, carbon front chassis, M5 alloy rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 150mm of travel
REAR SHOCK	RockShox Monarch RT, Women's Rx Tune, AUTOSAG, rebound and 2-position compression adjust, 197x48mm
FORK	RockShox Yari RC 27.5, Solo Air, rebound & compression adjust, 15x110mm Maxle Ultimate thru-axle, 150mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Flat Top, alloy, 8-degree backsweep, 6-degree upsweep, 10mm rise, 720mm width, 31.8mm
GRIPS	Specialized Sip Grip, lock-on, half-waffle, regular thickness
FRONT BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM GX, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 52mm chainline
CHAINRINGS	Race Face CINCH, 28T
BOTTOM BRACKET	Race Face, PF30
RIMS	Roval Traverse 650b, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x110mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Butcher, GRID casing, 650x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Slaughter, GRID casing, 650x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Command Post IRcc, 10-12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, XS: 75mm, S/M: 100mm, L: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
96317-5201	RHYME COMP CARBON 650B	NRDCRED/LTTUR/TARBLK	XS
96317-5202			S
96317-5203			M

RHYME COMP 650B



GRPH/TARBLK/PDRGRN

Just because you ride hard on the trail doesn't mean that you want to take out a second mortgage just to get a capable trail bike. We get it, and that's why our Rhyme FSR Comp 650b gives you revolutionary tech and performance in a package with an obvious value.

- The M5 alloy Trail Chassis with a Rhyme FSR 650b rear end with 148mm spacing blends durability, stiffness, and light weight, while 150mm of travel and Trail 650b Geometry provide more than capable handling.
- A custom RockShox Revelation RL fork was developed to deliver 150mm of plush, trail-taming travel, while accommodating a 15x110mm Maxle Lite thru-axle for reliable handling and durability over rough, bumpy, or loose terrain.
- SRAM Guide brakes w/ S4 calipers provide powerful, precise, and highly adjustable braking. Their based on a four-piston caliper design that puts out smooth, dependable stopping power, while the Reach Adjust feature allows you to customize the position for easy, one-finger lever pulls.

RHYME 650 ALLOY

SIZE	XS	S	M	L
Stack (mm)	587	590	599	608
Reach (mm)	369	388	414	442
Head-Tube Length (mm)	95	95	105	115
Head-Tube Angle (deg)	66.5	67	67	67
B-B Height (650x2.3") (mm)	335	335	335	335
B-B Height (650x2.6") (mm)	340	340	340	340
B-B Drop (mm)	18	18	18	18
Trail (mm)	108	104	104	104
Fork Length (full) (mm)	542	542	542	542
Fork Rake/Offset (mm)	42	42	42	46
Front-Center (mm)	663	677	706	738
Chain-Stay Length (mm)	420	420	420	420
Wheelbase (mm)	1082	1096	1126	1158
Top-Tube Length (horizontal) (mm)	532	553	585	618
Bike Stand-Over Height (mm)	724	742	748	757
Seat-Tube Length (mm)	386	396	430	468
Seat-Tube Angle (deg)	74.5	74	74	74
Handlebar Width (mm)	720	720	720	720
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	310	390	390	430
Crank Length (mm)	165	170	175	175

SPECS

All specs are subject to change without notice.

FRAME	M5 alloy, Trail Geometry, PF30 BB, internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 150mm of travel
REAR SHOCK	RockShox Monarch RT, Women's Rx Tune, AUTOSAG, rebound and 2-position compression adjust, 197x48mm
FORK	RockShox Revelation RL 27.5, Solo Air spring, lockout and rebound adjust, 15x110mm Maxle Lite thru-axle, 46mm offset, 150mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Flat Top, alloy, 8-degree backsweep, 6-degree upsweep, 10mm rise, 720mm width, 31.8mm
GRIPS	Specialized Sip Grip, lock-on, half-waffle, regular thickness
FRONT BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM GX, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 52mm chainline
RIMS	Roval Traverse 650b, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x110mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Butcher, GRID casing, 650x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Slaughter, GRID casing, 650x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Command Post IRoc, 10-12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, XS: 75mm, S/M: 100mm, L: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
96317-5001	RHYME COMP 650B	GRPH/TARBLK/PDRGRN	XS
96317-5002			S
96317-5003			M

WOMEN'S CAMBER COMP CARBON 650B



NBLBLU/NRDCRED/FLKSIL

We've all heard the old euphemism, "you can't have it both ways." But our Women's Camber 650b lets you have your cake and eat it, too. It climbs well, it descends with confidence, it looks amazing—it's the perfect jumping off point into the world of trail riding.

- FACT 9m carbon Trail Chassis w/ Camber FSR M5 Alloy rear end is mated with our Trail 650b Geometry to form a bike that's just as at home on the climbs as it is mowing over rough trail sections. You'll also find internal cable routing for clean lines and minimal maintenance and an integrated SWAT™ Door for zero-hassle storage of your trail essentials.
- A custom RockShox Revelation RL 650b fork was developed to deliver 130mm of plush, trail taming travel, while accommodating a 15x110mm thru-axle for reliable handling and durability over rough, bumpy, or loose terrain. It also features our Women's Rx Trail Tune that specifically tailors the suspension to lighter riders.
- SRAM GX 11-speed rear derailleur grants you access to a wide range of gears, while providing crisp, reliable shifting.

CAMBER WMN 650 CARBON

SIZE	XS	S	M	L
Stack (mm)	578	580	590	599
Reach (mm)	380	399	425	454
Head-Tube Length (mm)	95	95	105	115
Head-Tube Angle (deg)	67.5	68	68	68
B-B Height (650x2.3) (mm)	329	329	329	329
B-B Height (650x2.6) (mm)	334	334	334	334
B-B Drop (mm)	23	23	23	23
Trail (mm)	100	97	97	97
Fork Length (full) (mm)	522	522	522	522
Fork Rake/Offset (mm)	42	42	42	42
Front-Center (mm)	655	670	700	732
Chain-Stay Length (mm)	420	420	420	420
Wheelbase (mm)	1074	1089	1119	1151
Top-Tube Length (horizontal) (mm)	535	554	583	614
Bike Stand-Over Height (mm)	711	725	730	743
Seat-Tube Length (mm)	386	396	430	468
Seat-Tube Angle (deg)	75	75	75	75
Handlebar Width (mm)	720	720	720	720
Stem Length (mm)	60	60	75	90
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	310	390	390	430
Crank Length (mm)	165	170	175	175

SPECS

All specs are subject to change without notice.

FRAME	FACT 9m, carbon front chassis, M5 alloy rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, Concentric Pivot link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 130mm of travel
REAR SHOCK	FOX FLOAT Performance, Women's Rx Tune, AUTOSAG, DPS damper, rebound and 3-position compression adjust, 205x53mm
FORK	RockShox Revelation RL 27.5, Solo Air spring, lockout and rebound adjust, 15x110mm Maxle Lite thru-axle, 46mm offset, 130mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Mini-rise, 7050 alloy, 8-backsweep, 6-upsweep, 10mm rise, 720mm width, 31.8mm clamp
GRIPS	Specialized Sip Grip, lock-on, half-waffle, regular thickness
FRONT BRAKE	Shimano M506, hydraulic disc, resin pad, 200/180mm rotor
REAR BRAKE	Shimano M506, hydraulic disc, resin pad, 180/160mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM NX, 11-speed, trigger
CASSETTE	SRAM PG-1130, 11-speed, 11-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 52mm chainline
CHAINRINGS	RaceFace, 28T
BOTTOM BRACKET	PF30
RIMS	Roval Traverse 650b, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x110mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Purgatory, Control casing, 650bx2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control, Control casing, 650bx2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Command Post IRoc, 10-12 position micro-height adjustable, alien head design, bottom mount cable routing, remote adjust SRL lever, 30.9mm, XS: 75mm, S/M: 100mm, L: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
95317-5201	CAMBER WMN COMP CARBON	NBLBLU/NRDCRED/FLKSIL	XS
95317-5202			S
95317-5203			M

WOMEN'S CAMBER COMP 650B



CLGRY/DPNDGO/PDRGRN



TUR/HYP/TARBLK

No matter the skill level, any woman can benefit from a trail bike that's durable enough to take on rough, technical descents in stride, while also being efficient enough to get up the trail with ease. In other words, any trail rider who appreciates responsive, nimble handling will love our new Women's Camber Comp 650b.

- M5 Alloy Trail Chassis w/ Camber FSR rear end has been paired with our Trail 650b Geometry to form a bike that's playful, energetic, and remarkably efficient. It also features the shortest, most nimble rear end possible, and internal shift cable routing to make clean lines and reliable shifting through any condition.
- A custom RockShox Revelation RL 650b fork was developed to deliver 130mm of plush, trail taming travel, while accommodating a 15x110mm thru-axle for reliable handling and durability over rough, bumpy, or loose terrain. It also features our Women's Rx Trail Tune that specifically tailors the suspension to lighter riders.
- SRAM GX 11-speed rear derailleur grants you access to a wide range of gears, while providing crisp, reliable shifting.

CAMBER WMN 650 ALLOY

SIZE	XS	S	M	L
Stack (mm)	578	580	590	599
Reach (mm)	380	399	425	454
Head-Tube Length (mm)	95	95	105	115
Head-Tube Angle (deg)	67.5	68	68	68
B-B Height (650x2.3) (mm)	329	329	329	329
B-B Height (650x2.6) (mm)	334	334	334	334
B-B Drop (mm)	23	23	23	23
Trail (mm)	100	97	97	97
Fork Length (full) (mm)	522	522	522	522
Fork Rake/Offset (mm)	42	42	42	42
Front-Center (mm)	655	670	700	732
Chain-Stay Length (mm)	420	420	420	420
Wheelbase (mm)	1074	1089	1119	1151
Top-Tube Length (horizontal) (mm)	530	554	583	614
Bike Stand-Over Height (mm)	709	724	728	743
Seat-Tube Length (mm)	386	396	430	468
Seat-Tube Angle (deg)	75.5	75	75	75
Handlebar Width (mm)	720	720	720	720
Stem Length (mm)	60	60	75	90
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	350	350	400	400
Crank Length (mm)	165	170	175	175

SPECS

All specs are subject to change without notice.

FRAME	M5 alloy, Trail Geometry, PF30 BB, internal cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 130mm of travel
REAR SHOCK	FOX FLOAT Performance, Women's Rx Tune, AUTOSAG, DPS damper, rebound and 3-position compression adjust, 205x53mm
FORK	RockShox Revelation RL 27.5, Women's Rx Tune, Solo Air spring, lockout and rebound adjust, 15x110mm Maxle Lite thru-axle, 46mm offset, 130mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Flat Top, alloy, 8-degree backsweep, 6-degree upsweep, 10mm rise, 720mm width, 31.8mm
GRIPS	Specialized Sip Grip, lock-on, half-waffle, regular thickness
FRONT BRAKE	Shimano M506, hydraulic disc, resin pad, 200/180mm rotor
REAR BRAKE	Shimano M506, hydraulic disc, resin pad, 180/160mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM NX, 11-speed, trigger
CASSETTE	SRAM PG-1130, 11-speed, 11-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 52mm chainline
CHAINRINGS	RaceFace, 28T
BOTTOM BRACKET	PF30
RIMS	Roval Traverse 650b, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x110mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Purgatory, Control casing, 650bx2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control, Control casing, 650bx2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Specialized, alloy, single bolt, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
95317-5001	CAMBER WMN COMP	CLGRY/DPNDGO/PDRGRN	XS
95317-5002			S
95317-5003			M
95317-5101	CAMBER WMN COMP	TUR/HYP/TARBLK	XS
95317-5102			S
95317-5103			M

WOMEN'S CAMBER 650B



NRDCRED/LTTUR/TARBLK



BLK/TARBLK

We've all heard the old euphemism, "you can't have it both ways." But our Women's Camber 650b, however, lets you have your cake and eat it, too. It climbs well, it descends with confidence, it looks amazing—it's the perfect jumping off point into the world of trail riding.

- M5 Alloy Trail Chassis w/ Camber FSR rear end has been paired with our Trail 650b Geometry to form a bike that's playful, energetic, and remarkably efficient. It also features the shortest, most nimble rear end possible, and internal shift cable routing to make clean lines and reliable shifting through any condition.
- The RockShox Sector Silver RL 650b features 130mm of plush, predictable travel, plus stiff 32mm stanchions and a 15x110mm Maxle Lite thru-axle.
- Tektro Gemini Comp hydraulic disc brakes provide powerful braking over rough terrain, while also remaining durable, reliable, and easy to maintain.
- A Shimano Deore rear derailleur will win your heart with reliable shift after reliable shift. It's built with durability in mind, so it's tougher than your average rear mech.

CAMBER WMN 650 ALLOY

SIZE	XS	S	M	L
Stack (mm)	578	580	590	599
Reach (mm)	380	399	425	454
Head-Tube Length (mm)	95	95	105	115
Head-Tube Angle (deg)	67.5	68	68	68
B-B Height (650x2.3) (mm)	329	329	329	329
B-B Height (650x2.6) (mm)	334	334	334	334
B-B Drop (mm)	23	23	23	23
Trail (mm)	100	97	97	97
Fork Length (full) (mm)	522	522	522	522
Fork Rake/Offset (mm)	42	42	42	42
Front-Center (mm)	655	670	700	732
Chain-Stay Length (mm)	420	420	420	420
Wheelbase (mm)	1074	1089	1119	1151
Top-Tube Length (horizontal) (mm)	530	554	583	614
Bike Stand-Over Height (mm)	709	724	728	743
Seat-Tube Length (mm)	386	396	430	468
Seat-Tube Angle (deg)	75.5	75	75	75
Handlebar Width (mm)	720	720	720	720
Stem Length (mm)	60	60	70	90
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	350	350	400	400
Crank Length (mm)	165	170	175	175

SPECS

All specs are subject to change without notice.

FRAME	M5 alloy, Trail Geometry, threaded BB, internal cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 130mm of travel
REAR SHOCK	Custom X-Fusion 02 Pro RL, Women's Rx Tune, air sleeve, rebound adjust, lockout, 205x53mm
FORK	RockShox Sector Silver RL 27.5, Solo Air, lockout and rebound adjust, 15x110mm Maxle Lite thru-axle, 46mm offset, 130mm travel
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Flat Top, alloy, 8-degree backsweep, 6-degree upsweep, 10mm rise, 720mm width, 31.8mm
GRIPS	Specialized Sip Grip, lock-on, half-waffle, regular thickness
FRONT BRAKE	Tektro Gemini Comp, hydraulic disc, resin pad, 180/200mm rotor
REAR BRAKE	Tektro Gemini Comp, hydraulic disc, resin pad, 180/160mm rotor
FRONT DERAILLEUR	SRAM GX, bottom pull
REAR DERAILLEUR	SRAM GX, Type 2.1, long cage, 10-speed
SHIFT LEVERS	SRAM GX, 10-speed, trigger
CASSETTE	Sunrace, 10-speed, 11-42t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	SRAM NX, alloy, 24mm spindle, 52mm chainline, direct mount chainring
BOTTOM BRACKET	Truvativ Powerspline, 73x113mm
RIMS	Specialized 650b, alloy, 27mm inner width, 32h
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x110mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	Stainless, 14g
FRONT TIRE	Purgatory, Control casing, 650bx2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control, Control casing, 650bx2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Alloy, 2-bolt clamp, 12.5mm offset, 30.9mm, anti-corrosion hardware

PART NO.	DESCRIPTION	COLOR	SIZE
95317-7101	CAMBER WMN BASE	NRDCRED/LTTUR/TARBLK	XS
95317-7102			S
95317-7103			M
95317-7001	CAMBER WMN BASE	BLK/TARBLK	XS
95317-7002			S
95317-7003			M

RUZE EXPERT



WRMCHAR/TARBLK/LTTUR

You don't need all the trail fixings to benefit from more traction, increased control, and elevated confidence. Nope. You just need what you know will work, day-in and day-out, from the trail head to the ride home. And of course, you'll be in need of the Ruze Expert with our all-new 6Fattie Wheel System.

- When it came to construction, M4 Premium Aluminum proved to be the right material for the job, allowing a lightweight, durable frame with our Women's Trail Geometry that's equal parts snappy and efficient on climbs and descents, while maintaining an ultra-low standover. It also allowed us to accommodate the 6Fattie Wheel System without compromising on our hallmark short chainstays that provide unrivaled handling and climbing prowess.
- A Rock Shox Reba RL fork pairs 100/120mm (size-specific) of smooth travel with adjustable rebound for maximum absorbency over harsh terrain and easy, on-the-fly adjustments to the damping to hit the perfect tune.
- SRAM GX 11-speed rear derailleur grants you access to a wide range of gears, while providing crisp, reliable shifting.

RUZE			
SIZE	S	M	L
Stack (mm)	592	607	625
Reach (mm)	375	405	430
Head-Tube Length (mm)	95	110	130
Head-Tube Angle (deg)	67	67	67
B-B Height (mm)	310	310	310
B-B Drop (mm)	53	53	53
Trail (mm)	104	104	104
Fork Length (full) (mm)	512	512	512
Fork Rake/Offset (mm)	51	51	51
Front-Center (mm)	662	697	730
Chain-Stay Length (mm)	430	430	430
Wheelbase (mm)	1086	1122	1155
Top-Tube Length (horizontal) (mm)	556	590	621
Bike Stand-Over Height (mm)	676	700	707
Seat-Tube Length (mm)	396	430	450
Seat-Tube Angle (deg)	73	73	73
Handlebar Width (mm)	720	720	720
Stem Length (mm)	45	45	60
Saddle Width (mm)	155	155	155
Seat Post Length (mm)	328	328	370
Crank Length (mm)	165	170	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized M4 Aluminum, Women's trail geometry, fully-butted w/ smooth welds, tapered head tube, tapered seat tube, forged 160mm disc mounts, 148mm thru-axle dropouts, replaceable alloy derailleur hanger
FORK	RockShox Reba RL, Fast Black uppers, solo air, 15x100mm thru-axle, 100/120mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Stout XC Flat Top, alloy, 8-degree backsweep, 6-degree upsweep, 10mm rise, 720mm width, 31.8mm
GRIPS	Specialized Sip Grip, lock-on, half-waffle, regular thickness
FRONT BRAKE	SRAM DB3, hydraulic disc, custom 4-piston caliper, semi-metallic pads, 200/180mm rotor
REAR BRAKE	SRAM DB3, hydraulic disc, custom 4-piston caliper, semi-metallic pads, 180/160mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM GX, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PC-1130, 11-speed w/PowerLink
CRANKSET	Specialized Stout XC Pro, forged alloy, 30mm alloy spindle, 52mm chainline, 76mm BCD spider, 28T chainring
CHAINRINGS	28T, 76mm BCD
BOTTOM BRACKET	BB30, sealed cartridge bearings
RIMS	Stout XC SL 38 650b, 2Bliss Ready, 19mm depth, 38mm internal width, 24/28h
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 110x15mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	Stainless, butted, 2.0/1.8/2.0mm, black
FRONT TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	TranzX alloy dropper, 30.9mm, internal cable routing, Size S/M: 328mm length, 80mm travel, Size L: 370mm length, 100mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
99717-3003	RUZE EXPERT 6FATTIE	WRMCHAR/TARBLK/LTTUR	M



NRDCRED/LTTUR/TUR



GRPH/TARBLK/RFPNK

More traction gives you more confidence, and with the Women's Ruze, you get just that. It's specifically designed from the ground up to give women of all skill levels an advantage on the trail, earning it the nickname of "the ultimate trail hardtail."

- When it came to construction, M4 Premium Aluminum proved to be the right material for the job, allowing a lightweight, durable frame with our Women's Trail Geometry that's equal parts snappy and efficient on climbs and descents, while maintaining an ultra-low standover. It also allowed us to accommodate the 6Fattie Wheel System without compromising on our hallmark short chainstays that provide unrivaled handling and climbing prowess.
- SR Suntour XCM 650b+ fork's 80mm of travel soaks up trail bumps, while our Women's Custom Tune better accommodates lighter riders.
- SRAM X7 rear derailleur is precise and strong, so it can face down rock gardens and rough trails while still providing accurate, reliable shifting.

RUZE A1				
SIZE	XS	S	M	L
Stack (mm)	603	603	612	622
Reach (mm)	362	382	405	425
Head-Tube Length (mm)	100	100	110	120
Head-Tube Angle (deg)	68.5	68.5	68.5	68.5
B-B Height (mm)	305	310	310	310
B-B Drop (mm)	52	52	52	52
Trail (mm)	93	93	93	93
Fork Length (full) (mm)	500	500	500	500
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	631	651	677	701
Chain-Stay Length (mm)	435	435	435	435
Wheelbase (mm)	1060	1080	1107	1131
Top-Tube Length (horizontal) (mm)	546	566	592	615
Bike Stand-Over Height (mm)	652	674	697	722
Seat-Tube Length (mm)	330	371	417	463
Seat-Tube Angle (deg)	73	73	73	73
Handlebar Width (mm)	700	720	720	720
Stem Length (mm)	50	50	60	60
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	300	350	400	400
Crank Length (mm)	165	170	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized M4 Aluminum, Women's trail geometry, fully-buttressed w/ smooth welds, tapered head tube, tapered seat tube, forged 160mm disc mounts, 148mm thru-axle dropouts, replaceable alloy derailleur hanger
FORK	SR Suntour XCM Plus 650b+
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Stout XC Flat Top, alloy, 8-degree backsweep, 6-degree upsweep, 10mm rise, 720mm width, 31.8mm
GRIPS	Specialized MTB Grip, lock-on
FRONT BRAKE	Tektro Auriga, hydraulic disc, organic pads, 180mm rotor
REAR BRAKE	Tektro Auriga, hydraulic disc, organic pads, 160mm rotor
REAR DERAILLEUR	SRAM X7 Type 2.1, long cage, 10-speed
SHIFT LEVERS	SRAM X5, 10-speed, trigger
CASSETTE	Sunrace, 10-speed, 11-42t
CHAIN	SRAM PC-1031, 10-speed w/PowerLink
CRANKSET	Specialized Stout, forged alloy, PF30, Cr-Mo spindle, 28T, 76mm BCD spider
BOTTOM BRACKET	Square taper, 73mm, internal bearings
RIMS	Stout XC 38 650b, 19mm depth, 38mm internal width, 24/28h
FRONT HUB	Stout XC, alloy, sealed cartridge bearings, 15x110mm thru-axle
REAR HUB	Stout XC, alloy, freehub, sealed cartridge bearings, 10x141mm QR spacing
SPOKES	Stainless, 14g, black
REAR TIRE	Fast Trak, GRID casing, 650bx2.8", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
99717-7101	RUZE 6FATTIE	NRDCRED/LTTUR/TUR	XS
99717-7102			S
99717-7103			M
99717-7104			L
99717-7001	RUZE 6FATTIE	GRPH/TARBLK/RFPNK	XS
99717-7002			S
99717-7003			M
99717-7004			L

JYNX COMP 650B



FTHYWHT/NRDCRED/TUR



TARBLK/BLK

Over the course of your rides, you've surely felt the call of a trail or two along the way. And as long as you're on an ill-equipped bike for the occasion, this call goes unanswered. That is until now. With the Jynx Comp 650b, you'll find a bike that features an even temperament for whatever kind of terrain you're up for riding.

- The frame was constructed from A1 Premium Aluminum, while our Women's Sport Trail 650b Geometry is on display in order to provide a confident, comfortable platform for riding over mixed terrain.
- Custom SR Suntour 650b fork features our Multi-Circuit Damping technology to eliminate any "pogo" effect, while delivering 80mm of hydraulic damped, coil-sprung suspension and preload adjust to smooth out rough terrain.
- Shimano Deore rear derailleur provides crisp, reliable shifting that you can count on when the going gets rough. With it, you'll be able to precisely move through the wide, 11-34t gear range to make cruising the flats almost as easy climbing those hills.

JYNX				
SIZE	XS	S	M	L
Stack (mm)	576	576	587	597
Reach (mm)	362	382	390	407
Head-Tube Length (mm)	100	100	110	120
Head-Tube Angle (deg)	69.5	69.5	70	70
B-B Height (mm)	305	305	305	305
B-B Drop (mm)	48	48	48	48
Trail (mm)	87	87	84	84
Fork Length (full) (mm)	475	475	475	475
Fork Rake/Offset (mm)	42	42	42	42
Front-Center (mm)	606	626	633	653
Chain-Stay Length (mm)	426	426	426	426
Wheelbase (mm)	1027	1047	1054	1075
Top-Tube Length (horizontal) (mm)	527	547	569	589
Bike Stand-Over Height (mm)	668	686	715	745
Seat-Tube Length (mm)	330	371	417	463
Seat-Tube Angle (deg)	74	74	73	73
Handlebar Width (mm)	640	640	680	680
Stem Length (mm)	60	60	80	80
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	300	350	350	400
Crank Length (mm)	165	170	170	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Women's Sport Trail 650b Geometry, forged dropouts, replaceable derailleur hanger, kickstand mount
FORK	SR Suntour XCR 32 650b, coil spring, custom Multi-Circuit Damping, 80mm of travel
STEM	Ahead 3D-forged alloy, 31.8mm, 6-degree rise
HANDLEBARS	Alloy bar, 15mm rise, 9-degree backsweep, 5-degree upsweep, 640/680mm width, 31.8mm
GRIPS	Specialized MTB Grip, lock-on
FRONT BRAKE	Shimano BL-M315, hydraulic disc, resin pads
REAR BRAKE	Shimano BL-M315, hydraulic disc, resin pads
FRONT DERAILLEUR	Shimano Altus, 34.9mm clamp, down-swing
REAR DERAILLEUR	Shimano Deore, Shadow design, SGS cage
SHIFT LEVERS	Shimano Altus, 9-speed
CASSETTE	Sunrace, 9-speed, 11-34t
CHAIN	KMC X9, 9-speed w/reusable MissingLink
CRANKSET	Stout, forged alloy construction
CHAINRINGS	44/32/22T
BOTTOM BRACKET	Square taper, 73mm, internal bearings
RIMS	650b, disc, alloy, double-wall, pin joint, 25mm inner width, 32h
FRONT HUB	Shimano Center Lock, disc, 9x100mm QR, 32h
REAR HUB	Shimano Center Lock, disc, 10x135mm QR, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Fast Trak Sport, 650bx2.0", 60TPI, wire bead, Flak Jacket protection
REAR TIRE	Fast Trak Sport, 650bx2.0", 60TPI, wire bead, Flak Jacket protection
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
85617-5001	JYNX COMP 650B	FTHYWHT/NRDCRED/TUR	XS
85617-5002			S
85617-5003			M
85617-5004			L
85617-5101	JYNX COMP 650B	TARBLK/BLK	XS
85617-5102			S
85617-5103			M
85617-5104			L

JYNX SPORT 650B



CRL/TARBLK/LTTUR



GRPH/TARBLK/RFPNK

It's been said that variety is the spice of life, and the same could be said for riding. After all, life's too short to spend all of your time out on the bike path. It's time to grab your ride by the horns, take it out of the city, and let it roam free. It's time to get on a Jynx Sport 650b.

- The frame was constructed from A1 Premium Aluminum, while our Women's Sport Trail 650b Geometry is on display in order to provide a confident, comfortable platform for riding over mixed terrain.
- Custom SR Suntour 650b suspension fork utilizes our Multi-Circuit Damping technology to eliminate any "pogo" effect by delivering 80mm of hydraulic damped, coil-sprung suspension to smooth out rough terrain.
- A Shimano Alivio rear derailleur controls the rear shifting with durable aplomb. It shifts along a wide gear range, 11-34t, so you can ride confidently knowing that you'll always have the right gear for the hill at hand.

JYNX				
SIZE	XS	S	M	L
Stack (mm)	576	576	587	597
Reach (mm)	362	382	390	407
Head-Tube Length (mm)	100	100	110	120
Head-Tube Angle (deg)	69.5	69.5	70	70
B-B Height (mm)	305	305	305	305
B-B Drop (mm)	48	48	48	48
Trail (mm)	87	87	84	84
Fork Length (full) (mm)	475	475	475	475
Fork Rake/Offset (mm)	42	42	42	42
Front-Center (mm)	606	626	633	653
Chain-Stay Length (mm)	426	426	426	426
Wheelbase (mm)	1027	1047	1054	1075
Top-Tube Length (horizontal) (mm)	527	547	569	589
Bike Stand-Over Height (mm)	668	686	715	745
Seat-Tube Length (mm)	330	371	417	463
Seat-Tube Angle (deg)	74	74	73	73
Handlebar Width (mm)	640	640	680	680
Stem Length (mm)	60	60	80	80
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	300	350	350	400
Crank Length (mm)	165	170	170	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Women's Sport Trail 650b Geometry, forged dropouts, replaceable derailleur hanger, kickstand mount
FORK	SR Suntour XCM 650b, coil spring, custom Multi-Circuit Damping, 80mm of travel
STEM	Ahead 3D-forged alloy, 31.8mm, 6-degree rise
HANDLEBARS	Alloy bar, 15mm rise, 9-degree backsweep, 5-degree upsweep, 640/680mm width, 31.8mm
GRIPS	Specialized MTB Grip, lock-on
FRONT BRAKE	Shimano BR-M315, hydraulic disc, resin pads
REAR BRAKE	Shimano BR-M315, hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	Shimano Altus, 34.9mm clamp, down-swing
REAR DERAILLEUR	Shimano Alivio, Shadow design, SGS cage
SHIFT LEVERS	Shimano Altus, 8-speed
CASSETTE	Sunrace, 8-speed, 11-34t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Stout, forged alloy construction
CHAINRINGS	44/32/22T
BOTTOM BRACKET	Square taper, 73mm, internal bearings
RIMS	650b, disc, alloy, double-wall, pin joint, 25mm inner width, 32h
FRONT HUB	Shimano Center Lock, disc, 9x100mm QR, 32h
REAR HUB	Shimano Center Lock, disc, 10x135mm QR, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Fast Trak Sport, 650bx2.0", 60TPI, wire bead, Flak Jacket protection
REAR TIRE	Fast Trak Sport, 650bx2.0", 60TPI, wire bead, Flak Jacket protection
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
85617-6001	JYNX SPORT 650B	CRL/TARBLK/LTTUR	XS
85617-6002			S
85617-6003			M
85617-6004			L
85617-6101	JYNX SPORT 650B	GRPH/TARBLK/RFPNK	XS
85617-6102			S
85617-6103			M
85617-6104			L

JYNX 650B



FLKSIL/DPNDGO/CRL



TARBLK/HYP/TUR



LTTUR/TARBLK/TUR

We've all felt the compulsion to break free from our day-to-day routine, especially when it comes to riding. Sure, laps around town are fun, but compared to the freedom of getting out in the woods or on country roads, life on the pavement starts to look pretty mundane. Lucky for you, our Jynx 650b unlocks the potential of your ride.

- The frame was constructed from A1 Premium Aluminum, while our Women's Sport Trail 650b Geometry is on display in order to provide a confident, comfortable platform for riding over mixed terrain.
- SR Suntour 650b fork features 80mm of hydraulic damped suspension travel to smooth out rough terrain.
- A Shimano Acera rear derailleur is built to with durability in mind, so you can rest assured that you'll have a reliable shifting partner for the long trails ahead.

JYNX				
SIZE	XS	S	M	L
Stack (mm)	576	576	587	597
Reach (mm)	362	382	390	407
Head-Tube Length (mm)	100	100	110	120
Head-Tube Angle (deg)	69.5	69.5	70	70
B-B Height (mm)	305	305	305	305
B-B Drop (mm)	48	48	48	48
Trail (mm)	87	87	84	84
Fork Length (full) (mm)	475	475	475	475
Fork Rake/Offset (mm)	42	42	42	42
Front-Center (mm)	606	626	633	653
Chain-Stay Length (mm)	426	426	426	426
Wheelbase (mm)	1027	1047	1054	1075
Top-Tube Length (horizontal) (mm)	527	547	569	589
Bike Stand-Over Height (mm)	668	686	715	745
Seat-Tube Length (mm)	330	371	417	463
Seat-Tube Angle (deg)	74	74	73	73
Handlebar Width (mm)	640	640	680	680
Stem Length (mm)	60	60	80	80
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	300	350	350	400
Crank Length (mm)	165	170	170	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Women's Sport Trail 650b Geometry, forged dropouts, replaceable derailleur hanger, kickstand mount
FORK	SR Suntour XCT 650b, coil spring, custom Multi-Circuit Damping, 80mm travel
STEM	Ahead 3D-forged alloy, 31.8mm, 6-degree rise
HANDLEBARS	Alloy bar, 15mm rise, 9-degree backsweep, 5-degree upsweep, 640/680 bar width, 31.8mm
GRIPS	Specialized MTB Grip, lock-on
FRONT BRAKE	Shimano BR-M375, mechanical disc, resin pads, 180/160mm rotor
REAR BRAKE	Shimano BR-M375, mechanical disc, resin pads, 160mm rotor
FRONT DERAILLEUR	Shimano Altus, 34.9mm clamp, down-swing, 7/8-speed
REAR DERAILLEUR	Shimano Acera, SGS cage, 8-speed
SHIFT LEVERS	Shimano EF510, EZ Fire Plus, 8-speed
CASSETTE	Sunrace, 8-speed, 11-34t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Forged alloy, square taper spindle w/chainguard
CHAINRINGS	44/32/22T
BOTTOM BRACKET	Square taper, 73mm, internal bearings
RIMS	650b, disc, alloy, double-wall, pin joint, 25mm inner width, 32h
FRONT HUB	Shimano Center Lock, disc, 9x100mm QR, 32h
REAR HUB	Shimano Center Lock, disc, 10x135mm QR, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Fast Trak Sport, 650bx2.0", 60TPI, wire bead, Flak Jacket protection
REAR TIRE	Fast Trak Sport, 650bx2.0", 60TPI, wire bead, Flak Jacket protection
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
85617-7001	JYNX 650B	FLKSIL/DPNDGO/CRL	XS
85617-7002			S
85617-7003			M
85617-7004			L
85617-7201	JYNX 650B	TARBLK/HYP/TUR	XS
85617-7202			S
85617-7203			M
85617-7204			L
85617-7101	JYNX 650B	LTTUR/TARBLK/TUR	XS
85617-7102			S
85617-7103			M
85617-7104			L

MYKA DISC 650B



NRDCRED/TUR/LTTUR



DPNDGO/CLGRY/PDRGRN

Whether you're just starting to get your wheels dirty, or you already revel in mixing it up on every ride, the Myka Disc 650b checks all of your required boxes for a fun, capable mountain bike. Not only is the ride dedicated to rolling over rough sections, but every facet of the bike is also specifically tailored to women.

- A1 Premium Aluminum frame construction ensures that the bike is lightweight and durable, while the Women's Sport Trail 650b Geometry and 650b wheels make for an extremely low standover and heightened sense of control to accommodate more women's body types and experience levels without sacrificing trail performance or handling.
- SR Suntour 650b fork features 75mm of smooth suspension travel to effectively smooth out bumpy terrain. And to make sure of it, the fork carries our Women's Custom Tune that was developed specifically for women, so it's guaranteed to perform the task at hand on every ride.
- Shimano Tourney 7-speed rear derailleur has a wide gear range to make climbing hills a breeze.

MYKA DISC				
SIZE	XS	S	M	L
Stack (mm)	581	581	592	602
Reach (mm)	362	382	390	407
Head-Tube Length (mm)	100	100	110	120
Head-Tube Angle (deg)	69.5	69.5	70	70
B-B Height (mm)	308.5	308.5	308.5	308.5
B-B Drop (mm)	48	48	48	48
Trail (mm)	88	88	85	85
Fork Length (full) (mm)	480	480	480	480
Fork Rake/Offset (mm)	42	42	42	42
Front-Center (mm)	608	628	635	655
Chain-Stay Length (mm)	426	426	426	426
Wheelbase (mm)	1029	1049	1056	1076
Top-Tube Length (horizontal) (mm)	529	549	571	591
Bike Stand-Over Height (mm)	649.7	688.1	720.3	740.4
Seat-Tube Length (mm)	310	371	417	463
Seat-Tube Angle (deg)	74	74	73	73
Handlebar Width (mm)	640	640	680	680
Stem Length (mm)	60	60	80	80
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	300	350	350	400
Crank Length (mm)	165	170	170	175

SPECS	All specs are subject to change without notice.
FRAME	A1 Premium Aluminum, forged 3D dropouts, reinforced disc mount, alloy replaceable derailleur hanger
FORK	SR Suntour M3030 650b, 1-1/8" steel steerer, 75mm of travel, 9mm axle, coil spring w/preload adjust
STEM	3D-forged alloy, 31.8mm clamp, 6-degree rise
HANDLEBARS	Flat bar, double-buttressed 6061 alloy, 640/680mm width, 10-degree upsweep, 4-degree upsweep, 31.8mm
GRIPS	Specialized MTB Grip, lock-on
FRONT BRAKE	Tektro MD-M280, mechanical disc, 160mm rotor
REAR BRAKE	Tektro MD-M280, mechanical disc, 160mm rotor
FRONT DERAILLEUR	Shimano Tourney, top-swing, 34.9mm clamp
REAR DERAILLEUR	Shimano Tourney, 7-speed
SHIFT LEVERS	Shimano EF500, EZ Fire Plus, 7-speed
CASSETTE	Sunrace, 7-speed, 11-34t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Samox, forged alloy
CHAINRINGS	42/34/24T
BOTTOM BRACKET	Square taper, 73mm, internal bearings
RIMS	650b, disc, alloy, double-wall, pin joint, 25mm inner width, 32h
FRONT HUB	Specialized disc, double-sealed, loose ball bearings, 9mm QR
REAR HUB	Specialized disc, loose ball bearings, QR, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Fast Trak Sport, 650bx2.0", 60TPI, wire bead, Flak Jacket protection
REAR TIRE	Fast Trak Sport, 650bx2.0", 60TPI, wire bead, Flak Jacket protection
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
81517-7301	MYKA DISC 650B	NRDCRED/TUR/LTTUR	XS
81517-7302			S
81517-7303			M
81517-7304			L
81517-7201	MYKA DISC 650B	DPNDGO/CLGRY/PDRGRN	XS
81517-7202			S
81517-7203			M
81517-7204			L

MYKA 650B



GRPH/TARBLK/RFPNK



PDRGRN/TUR/TARBLK

If you've felt that the dirt is calling your name, it's about time that you answered. With the Myka 650b, you get a ride that's ready to start getting you off of the road. And to ensure that you hit the trail full of confidence, it features a capable geometry, wheel size, and components that are thoughtfully selected and tuned for women.

- A1 Premium Aluminum frame construction ensures that the bike is lightweight and durable, while the Women's Sport Trail 650b Geometry and 650b wheels make for an extremely low standover and heightened sense of control to accommodate more women's body types and experience levels without sacrificing trail performance or handling.
- An SR Suntour 650b suspension fork serves up 75mm of coil-sprung travel, providing you with a plush ride that's ready to soak up the bumps and ask for more.
- Linear pull V-brakes offer confident stopping power, a classic look, and hassle-free maintenance.

MYKA DISC

SIZE	XS	S	M	L
Stack (mm)	581	581	592	602
Reach (mm)	362	382	390	407
Head-Tube Length (mm)	100	100	110	120
Head-Tube Angle (deg)	69.5	69.5	70	70
B-B Height (mm)	308.5	308.5	308.5	308.5
B-B Drop (mm)	48	48	48	48
Trail (mm)	88	88	85	85
Fork Length (full) (mm)	480	480	480	480
Fork Rake/Offset (mm)	42	42	42	42
Front-Center (mm)	608	628	635	655
Chain-Stay Length (mm)	426	426	426	426
Wheelbase (mm)	1029	1049	1056	1076
Top-Tube Length (horizontal) (mm)	529	549	571	591
Bike Stand-Over Height (mm)	649.7	688.1	720.3	740.4
Seat-Tube Length (mm)	310	371	417	463
Seat-Tube Angle (deg)	74	74	73	73
Handlebar Width (mm)	640	640	680	680
Stem Length (mm)	60	60	80	80
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	300	350	350	400
Crank Length (mm)	165	170	170	175

SPECS

All specs are subject to change without notice.

FRAME	A1 Premium Aluminum, forged 3D dropouts, alloy replaceable derailleur hanger
FORK	SR Suntour M3030 650b, 1-1/8" steel steerer, 75mm of travel, 9mm axle, coil spring w/preload adjust
STEM	3D-forged alloy, 31.8mm clamp, 6-degree rise
HANDLEBARS	Flat bar, double-buttressed 6061 alloy, 640/680mm width, 10-degree upsweep, 4-degree upsweep, 31.8mm
GRIPS	Specialized MTB Grip, lock-on
FRONT BRAKE	V-brake, linear pull
REAR BRAKE	V-brake, linear pull
FRONT DERAILLEUR	Shimano Tourney, top-swing, 34.9mm clamp
REAR DERAILLEUR	Shimano Tourney
SHIFT LEVERS	Shimano EF500, EZ Fire Plus, 7-speed
CASSETTE	Shimano Tourney freewheel, 7-speed, 14-34t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Samox, forged alloy
CHAINRINGS	42/34/24T
BOTTOM BRACKET	Square taper, 73mm, internal bearings
RIMS	650b, V-brake, alloy, double-wall, CNC sidewalls, pin joint, 25mm wide, 32h
FRONT HUB	Specialized V-brake, alloy, loose ball bearings, 9mm, QR
REAR HUB	Specialized V-brake, loose ball bearings, QR, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Fast Trak Sport, 650bx2.0", 60TPI, wire bead, Flak Jacket protection
REAR TIRE	Fast Trak Sport, 650bx2.0", 60TPI, wire bead, Flak Jacket protection
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
81517-7001	MYKA 650B	GRPH/TARBLK/RFPNK	XS
81517-7002			S
81517-7003			M
81517-7004			L
81517-7101	MYKA 650B	PDRGRN/TUR/TARBLK	XS
81517-7102			S
81517-7103			M
81517-7104			L

HELLGA EXPERT



686 NVY HZ/BRTTL



NVY/HYP/BRTPNK

Don't hold back. The Hellga Expert is ready to give you the ultimate in super-fun-happy-times by providing superb traction, floatation, and control on all kinds of terrain. It's a recipe for having a blast, really.

- Hellga's M4 Aluminum frame with ultra-low standover is lightweight, durable, and provides a confident and maneuverable ride, both up and down the trail.
- The lightweight FACT carbon fork delivers superb handling and control while absorbing trail chatter.
- Tackle dirt, sand, and snow with equal confidence, thanks to the Hellga's 26x4.6" Ground Control Fat tires, featuring a custom tread pattern for great traction, acceleration and control.

HELLGA			
SIZE	S	M	L
Stack (mm)	580	590	604
Reach (mm)	380	400	415
Head-Tube Length (mm)	100	110	125
Head-Tube Angle (deg)	70.5	70.5	70.5
B-B Height (mm)	316	316	316
B-B Drop (mm)	60	60	60
Trail (mm)	83	83	83
Fork Length (full) (mm)	467	467	467
Fork Rake/Offset (mm)	47	47	47
Front-Center (mm)	617	640	660
Chain-Stay Length (mm)	455	455	455
Wheelbase (mm)	1065	1088	1108
Top-Tube Length (horizontal) (mm)	552	575	594
Bike Stand-Over Height (mm)	676	702	728
Seat-Tube Length (mm)	381	430	470
Seat-Tube Angle (deg)	73.5	73.5	73.5

SPECS	All specs are subject to change without notice.
FRAME	Specialized M4 Aluminum, smooth welds, tapered head tube, forged post-mount disc dropouts, 190mm rear hub spacing, replaceable alloy derailleur hanger
FORK	Specialized FACT carbon, full monocone, tapered steerer, 135mm hub spacing, open QR dropouts
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Mini-rise, 7050 alloy, 8-backsweep, 6-upsweep, 10mm rise, 700mm width, 31.8mm clamp
GRIPS	Specialized Sip Grip, lock-on, half-waffle, regular thickness
FRONT BRAKE	Shimano XT, hydraulic disc, metallic pads w/fins, 200mm rotor
REAR BRAKE	Shimano Deore XT, hydraulic disc, metallic pads w/fins, 160mm Ice-Tech rotor
REAR DERAILLEUR	SRAM X01 Type 2.1, 11-speed
SHIFT LEVERS	SRAM X1, 11-speed, trigger
CASSETTE	SRAM X1, 11-speed, 10-42t
CHAIN	KMC X11L, 11-speed w/reusable MissingLink
CRANKSET	e.13, 11-speed, PF30, 100mm spindle
CHAINRINGS	36T/22T
BOTTOM BRACKET	PF30 Included with crankset
RIMS	Stout XC, hookless alloy, single wall, 90mm inner width, sleeve joint, 32h
FRONT HUB	Specialized Stout XC 135, disc, sealed cartridge bearings, QR, 32h
REAR HUB	Specialized Stout XC 190, Hi Hi disc, alloy, sealed cartridge bearings, QR, 32h
SPOKES	Stainless, butted, 2.0/1.8/2.0mm, black
FRONT TIRE	Ground Control Fat, Control casing, 26x4.6", 120TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control Fat, Control casing, 26x4.6", 120TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Alloy, 2-bolt clamp, 12.5mm offset, 30.9mm, anti-corrosion hardware

PART NO.	DESCRIPTION	COLOR	SIZE
95816-3102	HELLGA EXPERT	686 NVY HZ/BRTTL	S
95816-3103			M
95816-3104			L
95816-3002	HELLGA EXPERT	NVY/HYP/BRTPNK	S
95816-3003			M
95816-3004			L

HELLGA COMP



PRLTUR/LTTUR/DPFUS



BLK/MULTI

Fat bikes are for more than just the snow—they're for anyone that wants the confidence that comes from the superb traction, floatation, and control of the Hellga Comp. Consider it a recipe for having a blast out on the trail.

- Hellga's M4 Aluminum frame with ultra-low standover is lightweight, durable, and provides a confident and maneuverable ride, both up and down the trail.
- The lightweight FACT carbon fork delivers superb handling and control while absorbing trail chatter.
- Tackle dirt, sand, and snow with equal confidence, thanks to the Hellga's 26x4.6" Ground Control Fat tires, featuring a custom tread pattern for great traction, acceleration and control.

SPECS	All specs are subject to change without notice.
FRAME	Specialized M4 Aluminum, smooth welds, tapered head tube, forged post-mount disc dropouts, 190mm rear hub spacing, replaceable alloy derailleur hanger
FORK	Specialized FACT carbon, full mono-coque, tapered steerer, 135mm hub spacing, open QR dropouts
STEM	Specialized Stout, 3D-forged alloy, 4-bolt, 6-degree rise, anti-corrosion hardware
HANDLEBARS	Specialized Stout, double-butt 6061 alloy, 9-degree backsweep, 5-degree upsweep, 15mm rise, 740mm width, 31.8mm
GRIPS	Specialized Sip Grip, lock-on, half-waffle, regular thickness
FRONT BRAKE	Tektro Gemini, hydraulic disc, resin pads
REAR BRAKE	Tektro Gemini, hydraulic disc, resin pads, 1-spec compatible
FRONT DERAILLEUR	SRAM X5, bottom pull, 2x10
REAR DERAILLEUR	SRAM X7 Type 2.1, long cage, 10-speed
SHIFT LEVERS	SRAM X7, 10-speed, trigger
CASSETTE	Sunrace, 10-speed, 11-36t
CHAIN	KMC X10L, 10-speed w/reusable MissingLink
CRANKSET	Custom Samox, forged alloy, 2x10, 104mm BCD spider
CHAINRINGS	36/22T
BOTTOM BRACKET	BB30, sealed cartridge bearings
RIMS	Stout XC, hookless alloy, single wall, 90mm inner width, sleeve joint, 32h
FRONT HUB	Specialized Stout XC 135, disc, sealed cartridge bearings, QR, 32h
REAR HUB	Specialized Stout XC 190, Hi Hi disc, alloy, sealed cartridge bearings, QR, 32h
SPOKES	Stainless, 14g, black
FRONT TIRE	Ground Control Fat, Control casing, 26x4.6", 120TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control Fat, Control casing, 26x4.6", 120TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Alloy, 2-bolt clamp, 12.5mm offset, 30.9mm, anti-corrosion hardware

HELLGA			
SIZE	S	M	L
Stack (mm)	580	590	604
Reach (mm)	380	400	415
Head-Tube Length (mm)	100	110	125
Head-Tube Angle (deg)	70.5	70.5	70.5
B-B Height (mm)	316	316	316
B-B Drop (mm)	60	60	60
Trail (mm)	83	83	83
Fork Length (full) (mm)	467	467	467
Fork Rake/Offset (mm)	47	47	47
Front-Center (mm)	617	640	660
Chain-Stay Length (mm)	455	455	455
Wheelbase (mm)	1065	1088	1108
Top-Tube Length (horizontal) (mm)	552	575	594
Bike Stand-Over Height (mm)	676	702	728
Seat-Tube Length (mm)	381	430	470
Seat-Tube Angle (deg)	73.5	73.5	73.5

PART NO.	DESCRIPTION	COLOR	SIZE
95816-5102	HELLGA COMP	PRLTUR/LTTUR/DPFUS	S
95816-5103			M
95816-5104			L
95816-5002	HELLGA COMP	BLK/MULTI	S
95816-5003			M
95816-5004			L

HELLGA



CRL/DPFUS/LTTUR



FTHYWHT/MULTI



CARBGRY/CRL/LTTUR

What happens when you mix a durable M4 Aluminum frame with a build kit that's handpicked to stand up to the trail? Awesomeness, that's what. The Hellga is designed to be your go-to steed for all things mountain, regardless of the weather or terrain type.

- Hellga's M4 Aluminum frame with ultra-low standover is lightweight, durable, and provides a confident and maneuverable ride, both up and down the trail.
- The alloy fork with air-formed legs is lightweight and strong for great handling and control.
- Tackle dirt, sand, and snow with equal confidence, thanks to the Hellga's 26x4.6" Ground Control Fat tires, featuring a custom tread pattern for great traction, acceleration and control.

SPECS	All specs are subject to change without notice.
FRAME	Specialized M4 Aluminum, smooth welds, tapered head tube, forged post-mount disc dropouts, 190mm rear hub spacing, replaceable alloy derailleur hanger
FORK	Specialized, alloy, air-formed legs, tapered alloy steerer, 135mm hub spacing, open QR dropouts
STEM	3D-forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Stout, double-buttet 6061 alloy, 9-degree backsweep, 5-degree upsweep, 15mm rise, 740mm width, 31.8mm
GRIPS	Specialized Sip Grip, lock-on, half-waffle, regular thickness
FRONT BRAKE	Tektro Aries, mechanical disc, organic pads, 160mm rotor
REAR BRAKE	Tektro Aries, mechanical disc, organic pads, 160mm rotor
FRONT DERAILLEUR	SRAM X5, bottom pull, 2x10
REAR DERAILLEUR	SRAM X5, long cage, 10-speed
SHIFT LEVERS	SRAM X5, 10-speed, trigger
CASSETTE	Sunrace, 10-speed, 11-36t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	Custom Samox, forged alloy, 2x10, Cr-Mo spindle, 104mm BCD spider
CHAINRINGS	36/22T
BOTTOM BRACKET	BB30, sealed cartridge bearings
RIMS	Stout XC, hookless alloy, single wall, 90mm inner width, sleeve joint, 32h
FRONT HUB	Specialized Stout XC 135, disc alloy, loose ball bearings, bolt-on axle, 32h
REAR HUB	Specialized Stout XC 190, Hi Hi disc, alloy, sealed cartridge bearings, QR, 32h
SPOKES	Stainless, 14g, black
FRONT TIRE	Ground Control Fat, 26x4.6", 60TPI, wire bead
REAR TIRE	Ground Control Fat, 24x4.6", 60TPI, wire bead
SADDLE	Women's Body Geometry Myth Sport, steel rails, 155mm
SEATPOST	Alloy, 2-bolt, micro-adjust, 12.5mm offset, 27.2mm

HELLGA			
SIZE	S	M	L
Stack (mm)	580	590	604
Reach (mm)	380	400	415
Head-Tube Length (mm)	100	110	125
Head-Tube Angle (deg)	70.5	70.5	70.5
B-B Height (mm)	316	316	316
B-B Drop (mm)	60	60	60
Trail (mm)	83	83	83
Fork Length (full) (mm)	467	467	467
Fork Rake/Offset (mm)	47	47	47
Front-Center (mm)	617	640	660
Chain-Stay Length (mm)	455	455	455
Wheelbase (mm)	1065	1088	1108
Top-Tube Length (horizontal) (mm)	552	575	594
Bike Stand-Over Height (mm)	676	702	728
Seat-Tube Length (mm)	381	430	470
Seat-Tube Angle (deg)	73.5	73.5	73.5

PART NO.	DESCRIPTION	COLOR	SIZE
95816-7102	HELLGA	CRL/DPFUS/LTTUR	S
95816-7103			M
95816-7104			L
95816-7202	HELLGA	FTHYWHT/MULTI	S
95816-7203			M
95816-7204			L
95816-7002	HELLGA	CARBGRY/CRL/LTTUR	S
95816-7003			M
95816-7004			L

S-WORKS AMIRA ETAP



TARBLK/NRDCRED/KLSIL

It's simple: when someone attacks on a climb, you want to respond quickly and with confident assurance. And when it's you who's breaking away, you'll want to accelerate with snappy intensity and leave everyone in your wake. The S-Works Amira eTap is born to race to any strategy.

- The Amira's S-Works FACT 11r carbon frame represents the utmost of our design abilities. It's our lightest, highest quality carbon, which provides a stiff and nimble ride that's propelled more riders to World Tour podiums than we care to count.
- Enjoy true handling precision, even on the most technical of descents, with the full-monocoque S-Works FACT carbon fiber fork.
- SRAM eTap, 11-speed shifters glimpse into the future of shifting. They communicate wirelessly with the front and rear derailleurs for a ground-breaking level of performance, while offering new, intuitive shift capabilities.

AMIRA					
SIZE	44	48	51	54	56
Stack (mm)	504	516	529	548	565
Reach (mm)	365	371	378	378	380
Head-Tube Length (mm)	105	115	125	145	165
Head-Tube Angle (deg)	70.5	71.25	72	72	72
B-B Height (mm)	269	269	269	269	270
B-B Drop (mm)	73	73	73	73	72
Trail (mm)	67	62	59	59	59
Fork Length (full) (mm)	369	369	369	369	369
Fork Rake/Offset (mm)	51	51	49	49	49
Front-Center (mm)	576	580	582	588	596
Chain-Stay Length (mm)	405	405	405	405	408
Wheelbase (mm)	970	974	976	982	994
Top-Tube Length (horizontal) (mm)	491	502	515	535	547
Bike Stand-Over Height (mm)	692	718	735	758	777
Seat-Tube Length (mm)	390	420	460	490	510
Seat-Tube Angle (deg)	76	76	76	74	74
Handlebar Width (mm)	360	380	400	400	420
Stem Length (mm)	75	75	90	100	100
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	350	350	400	400	400
Crank Length (mm)	165	167.5	170	170	172.5

SPECS	All specs are subject to change without notice.
FRAME	FACT 11r carbon, women's carbon layup & competitive geometry, tapered head tube, OSBB, internal routing, 130mm spacing
FORK	S-Works FACT carbon, full monocoque
STEM	S-Works SL, alloy, titanium bolts, 6-degree rise
HANDLEBARS	Specialized Women's SL carbon Shallow Drop, 125mm drop, 75mm reach
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	SRAM Red 22
REAR BRAKE	SRAM Red 22
FRONT DERAILLEUR	SRAM eTap, braze-on
REAR DERAILLEUR	SRAM eTap, 11-speed
SHIFT LEVERS	SRAM eTap
CASSETTE	SRAM Red 22, 11-28t
CHAIN	SRAM Red 22, 11-speed
CRANKSET	SRAM Red 22
CHAINRINGS	52/36T
BOTTOM BRACKET	SRAM BB30, 83mm
FRONT WHEEL	Roval CLX 40, carbon 40mm depth rim, carbon hub shell, CeramicSpeed bearings, 18h
REAR WHEEL	Roval CLX 40, carbon 40mm depth rim, DT Swiss 240 internals, Ceramic Speed bearings, 24h
FRONT TIRE	Turbo Cotton, 700x24mm
REAR TIRE	Turbo Cotton, 700x24mm
SADDLE	Body Geometry Oura Pro, carbon rails, 155mm
SEATPOST	S-Works FACT carbon, 20mm offset

PART NO.	DESCRIPTION	COLOR	SIZE
99217-0044	SW AMIRA ETAP	TARBLK/NRDCRED/KLSIL	44
99217-0048			48
99217-0051			51
99217-0054			54
99217-0056			56



BOELS DOLMANS

If any bike was born to race and take you to the next level of riding, it's the Amira Expert UDI2 in the replica colors of the Boels-Dolmans Cycling Team. Sprinting, climbing, tempo training rides with the group—it's the dream bike for women with competitive hearts and bodies.

- The FACT 10r carbon frame combines the lightweight performance and compliance of our top-end carbon production methods with our Women's Competitive Geometry. This creates a no-compromise, balanced ride quality for women that's equally suited to performing on the most demanding of climbs, descents, and punishing of flatland efforts.
- Enjoy true handling precision, even on the most technical of descents, with the full-monocoque FACT carbon fiber fork.
- Shimano Ultegra Di2 shifting offers 11 speeds of electronic wonderment. Shifts are as precise as it gets and the trim adjust up front ensures that chain rub is a thing of the past—no matter how extreme your cross-chaining gets.

AMIRA					
SIZE	44	48	51	54	56
Stack (mm)	504	516	529	548	565
Reach (mm)	365	371	378	378	380
Head-Tube Length (mm)	105	115	125	145	165
Head-Tube Angle (deg)	70.5	71.25	72	72	72
B-B Height (mm)	269	269	269	269	270
B-B Drop (mm)	73	73	73	73	72
Trail (mm)	67	62	59	59	59
Fork Length (full) (mm)	369	369	369	369	369
Fork Rake/Offset (mm)	51	51	49	49	49
Front-Center (mm)	576	580	582	588	596
Chain-Stay Length (mm)	405	405	405	405	408
Wheelbase (mm)	970	974	976	982	994
Top-Tube Length (horizontal) (mm)	491	502	515	535	547
Bike Stand-Over Height (mm)	692	718	735	758	777
Seat-Tube Length (mm)	390	420	460	490	510
Seat-Tube Angle (deg)	76	76	76	74	74
Handlebar Width (mm)	360	380	400	400	420
Stem Length (mm)	75	75	90	100	100
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	350	350	400	400	400
Crank Length (mm)	165	165	170	170	172.5

SPECS	All specs are subject to change without notice.
FRAME	FACT 10r carbon, women's carbon layup & competitive geometry, tapered head tube, OSBB, internal routing, 130mm spacing
FORK	FACT carbon, full monocoque
STEM	Specialized Pro SL, alloy, 4-bolt
HANDLEBARS	Specialized Women's Expert Shallow Drop, alloy, 123mm drop, 75mm reach
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	Shimano Ultegra
REAR BRAKE	Shimano Ultegra
FRONT DERAILLEUR	Shimano Ultegra Di2 6870, 11-speed, braze-on
REAR DERAILLEUR	Shimano Ultegra Di2, 6870, 11-speed
SHIFT LEVERS	Shimano Ultegra Di2, 6870, 11-speed
CASSETTE	Shimano Ultegra 6800, 11-speed, 11-28t
CHAIN	Shimano HG70, 11-speed
CRANKSET	Specialized Pro carbon
CHAINRINGS	52/36T
BOTTOM BRACKET	Enduro BB30
FRONT WHEEL	DT Swiss R460 Pro, QR
REAR WHEEL	DT Swiss R460 Pro, QR
FRONT TIRE	Turbo Pro, 700x23mm, 127TPI, folding bead, BlackBelt protection
REAR TIRE	Turbo Pro, 700x23mm, 127TPI, folding bead, BlackBelt protection
SADDLE	Body Geometry Oura Expert Gel, hollow titanium rails, 155mm
SEATPOST	S-Works FACT carbon, 20mm offset

PART NO.	DESCRIPTION	COLOR	SIZE
97217-3044	AMIRA EXPERT UDI2	BOELS DOLMANS	44
97217-3048			48
97217-3051			51
97217-3054			54
97217-3056			56

AMIRA COMP UDI2



CARB/CHAR



TUR/HYP/BLK

The Amira Comp isn't just a bike that's born to race—it's a bike that proves you don't need to take out a second mortgage to have a luxurious ride.

- The FACT 9r carbon fiber construction is well suited to every form of road riding. It's incredibly stiff and lightweight for a responsive and agile ride quality, while our Women's Competitive Geometry makes for the perfect fit and feel over the long haul on the road.
- Enjoy true handling precision, even on the most technical of descents, with the full-monocoque FACT carbon fiber fork.
- Shimano Ultegra Di2 shifting offers 11 speeds of electronic wonderment. Shifts are as precise as it gets and the trim adjust up front ensures that chain rub is a thing of the past—no matter how extreme your cross-chaining gets.

AMIRA					
SIZE	44	48	51	54	56
Stack (mm)	504	516	529	548	565
Reach (mm)	365	371	378	378	380
Head-Tube Length (mm)	105	115	125	145	165
Head-Tube Angle (deg)	70.5	71.25	72	72	72
B-B Height (mm)	269	269	269	269	270
B-B Drop (mm)	73	73	73	73	72
Trail (mm)	67	62	59	59	59
Fork Length (full) (mm)	369	369	369	369	369
Fork Rake/Offset (mm)	51	51	49	49	49
Front-Center (mm)	576	580	582	588	596
Chain-Stay Length (mm)	405	405	405	405	408
Wheelbase (mm)	970	974	976	982	994
Top-Tube Length (horizontal) (mm)	491	502	515	535	547
Bike Stand-Over Height (mm)	692	718	735	758	777
Seat-Tube Length (mm)	390	420	460	490	510
Seat-Tube Angle (deg)	76	76	76	74	74
Handlebar Width (mm)	360	380	400	400	420
Stem Length (mm)	70	80	90	100	100
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	350	350	400	400	400
Crank Length (mm)	165	165	170	170	172.5

SPECS	All specs are subject to change without notice.
FRAME	FACT 9r carbon, women's carbon layup & competitive geometry, tapered head tube, OSBB, internal routing, 130mm spacing
FORK	FACT carbon, full monocoque
STEM	3D-forged alloy, 7-degree rise
HANDLEBARS	Specialized Women's Comp Shallow Drop, alloy, 123mm drop, 75mm reach
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	Shimano Ultegra
REAR BRAKE	Shimano Ultegra
FRONT DERAILLEUR	Shimano Ultegra Di2 6870, 11-speed, braze-on
REAR DERAILLEUR	Shimano Ultegra Di2, 6870, 11-speed
SHIFT LEVERS	Shimano Ultegra Di2, 6870, 11-speed
CASSETTE	Shimano 105 5800 11-speed, 11-28t
CHAIN	KMC X11, 11-speed
CRANKSET	Shimano Ultegra Compact
CHAINRINGS	50/34T
BOTTOM BRACKET	Shimano Ultegra BB
FRONT WHEEL	DT Swiss R460, QR
REAR WHEEL	DT Swiss R460, QR
FRONT TIRE	Turbo Pro, 700x23mm, 127TPI, folding bead, BlackBelt protection
REAR TIRE	Turbo Pro, 700x23mm, 127TPI, folding bead, BlackBelt protection
SADDLE	Body Geometry Oura Comp, hollow Cr-Mo rails, 155mm
SEATPOST	Specialized Comp carbon, single bolt

PART NO.	DESCRIPTION	COLOR	SIZE
97217-5244	AMIRA COMP UDI2	CARB/CHAR	44
97217-5248			48
97217-5251			51
97217-5254			54
97217-5256			56
97217-5344	AMIRA COMP UDI2	TUR/HYP/BLK	44
97217-5348			48
97217-5351			51
97217-5354			54
97217-5356			56

AMIRA COMP



CARB/CHAR



TUR/HYP/BLK

The Amira Comp isn't just a bike that's born to race—it's a bike that proves you don't need to take out a second mortgage to have a luxurious ride.

- The FACT 9r carbon fiber construction is well suited to every form of road riding. It's incredibly stiff and lightweight for a responsive and agile ride quality, while our Women's Competitive Geometry makes for the perfect fit and feel over the long haul on the road.
- Enjoy true handling precision, even on the most technical of descents, with the full-monocoque FACT carbon fiber fork.
- Shave weight off your race rig with the DT Swiss R460 wheelset. It offers a superb, confident ride quality that's well suited to both racing and training.

AMIRA					
SIZE	44	48	51	54	56
Stack (mm)	504	516	529	548	565
Reach (mm)	365	371	378	378	380
Head-Tube Length (mm)	105	115	125	145	165
Head-Tube Angle (deg)	70.5	71.25	72	72	72
B-B Height (mm)	269	269	269	269	270
B-B Drop (mm)	73	73	73	73	72
Trail (mm)	67	62	59	59	59
Fork Length (full) (mm)	369	369	369	369	369
Fork Rake/Offset (mm)	51	51	49	49	49
Front-Center (mm)	576	580	582	588	596
Chain-Stay Length (mm)	405	405	405	405	408
Wheelbase (mm)	970	974	976	982	994
Top-Tube Length (horizontal) (mm)	491	502	515	535	547
Bike Stand-Over Height (mm)	692	718	735	758	777
Seat-Tube Length (mm)	390	420	460	490	510
Seat-Tube Angle (deg)	76	76	76	74	74
Handlebar Width (mm)	360	380	400	400	420
Stem Length (mm)	70	80	90	100	100
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	350	350	400	400	400
Crank Length (mm)	165	165	170	170	172.5

SPECS	All specs are subject to change without notice.
FRAME	FACT 9r carbon, women's carbon layup & competitive geometry, tapered head tube, OSBB, internal routing, 130mm spacing
FORK	FACT carbon, full monocoque
STEM	3D-forged alloy, 7-degree rise
HANDLEBARS	Specialized Women's Comp Shallow Drop, alloy, 123mm drop, 75mm reach
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	Shimano Ultegra
REAR BRAKE	Shimano Ultegra
FRONT DERAILLEUR	Shimano Ultegra 6800, 11-speed, braze-on
REAR DERAILLEUR	Shimano Ultegra 6800, 11-speed, braze-on
SHIFT LEVERS	Shimano Ultegra 6800, 11-speed
CASSETTE	Shimano 105 5800, 11-speed, 11/28t
CHAIN	KMC X11, 11-speed
CRANKSET	Shimano Ultegra Compact
CHAINRINGS	50/34T
BOTTOM BRACKET	Shimano Ultegra
FRONT WHEEL	DT Swiss R460, QR
REAR WHEEL	DT Swiss R460, QR
FRONT TIRE	Turbo Pro, 700x23mm, 127TPI, folding bead, BlackBelt protection
REAR TIRE	Turbo Pro, 700x23mm, 127TPI, folding bead, BlackBelt protection
SADDLE	Body Geometry Oura Comp, hollow Cr-Mo rails, 155mm
SEATPOST	Specialized Comp carbon, single bolt

PART NO.	DESCRIPTION	COLOR	SIZE
97217-5044	AMIRA COMP	CARB/CHAR	44
97217-5048			48
97217-5051			51
97217-5054			54
97217-5056			56
97217-5144	AMIRA COMP	TUR/HYP/BLK	44
97217-5148			48
97217-5151			51
97217-5154			54
97217-5156			56

AMIRA SPORT



CARB/RFPNK/MXORG



WHT/TARBLK

We're firm believers that speed is a right, not a privilege. And for this reason, we designed the Amira Sport to be a high-performance road machine at a price that's, well, more palatable than what you'll find under the Boels-Dolmans squad.

- The FACT 9r carbon fiber construction is well suited to every form of road riding. It's incredibly stiff and lightweight for a responsive and agile ride quality, while our Women's Competitive Geometry makes for the perfect fit and feel over the long haul on the road.
- Enjoy true handling precision, even on the most technical of descents, with the full-monocoque FACT carbon fiber fork.
- Significantly lighter than comparable wheelsets in its class, these tough Axis Elite wheels offer tremendous value in one smooth-rolling package.

AMIRA					
SIZE	44	48	51	54	56
Stack (mm)	504	516	529	548	565
Reach (mm)	365	371	378	378	380
Head-Tube Length (mm)	105	115	125	145	165
Head-Tube Angle (deg)	70.5	71.25	72	72	72
B-B Height (mm)	269	269	269	269	270
B-B Drop (mm)	73	73	73	73	72
Trail (mm)	67	62	59	59	59
Fork Length (full) (mm)	369	369	369	369	369
Fork Rake/Offset (mm)	51	51	49	49	49
Front-Center (mm)	576	580	582	588	596
Chain-Stay Length (mm)	405	405	405	405	408
Wheelbase (mm)	970	974	976	982	994
Top-Tube Length (horizontal) (mm)	491	502	515	535	547
Bike Stand-Over Height (mm)	692	718	735	758	777
Seat-Tube Length (mm)	390	420	460	490	510
Seat-Tube Angle (deg)	76	76	76	74	74
Handlebar Width (mm)	360	380	400	400	420
Stem Length (mm)	70	80	90	100	100
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	350	350	400	400	400
Crank Length (mm)	165	165	170	170	172.5

SPECS	All specs are subject to change without notice.
FRAME	FACT 9r carbon, women's carbon layup & competitive geometry, tapered head tube, OSBB, internal routing, 130mm spacing
FORK	FACT carbon, full monocoque
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Women's Comp Shallow Drop, alloy, 123mm drop, 75mm reach
TAPE	Specialized S-Wrap
FRONT BRAKE	Shimano Tiagra
REAR BRAKE	Shimano Tiagra
FRONT DERAILLEUR	Shimano 105 5800, 11-speed, braze-on
REAR DERAILLEUR	Shimano 105 5800, 11-speed
SHIFT LEVERS	Shimano 105 5800, 11-speed
CASSETTE	Shimano 105 5800, 11-speed, 11/28t
CHAIN	KMC X11, 11-speed
CRANKSET	Praxis Alba
CHAINRINGS	50/34T
BOTTOM BRACKET	Praxis BB
FRONT WHEEL	Axis Elite, QR
REAR WHEEL	Axis Elite, QR
FRONT HUB	Specialized ESPOIR ELITE, 700x23C, 60TPI
REAR HUB	Specialized ESPOIR ELITE, 700x23C, 60TPI
FRONT TIRE	Specialized Espoir Elite, 700x23mm, 60TPI
REAR TIRE	Specialized Espoir Elite, 700x23mm, 60TPI
SADDLE	Oura Sport, steel rails, 155mm
SEATPOST	Specialized Comp carbon, single bolt

PART NO.	DESCRIPTION	COLOR	SIZE
97217-6044	AMIRA SPORT	CARB/RFPNK/MXORG	44
97217-6048			48
97217-6051			51
97217-6054			54
97217-6056			56
97217-6144	AMIRA SPORT	WHT/TARBLK	44
97217-6148			48
97217-6151			51
97217-6154			54
97217-6156			56

S-WORKS AMIRA FRAMESET



NBLBLU/KLSIL/NRDCCRED



BOELS DOLMANS

It's simple: when someone attacks on a climb, you want to respond quickly and with confident assurance. And when it's you who's breaking away, you'll want to accelerate with snappy intensity and leave everyone in your wake. The S-Works Amira frameset is born to race to any strategy.

- The Amira's S-Works FACT 11r carbon frame represents the utmost of our design abilities. It's our lightest, highest quality carbon, which provides a stiff and nimble ride that's propelled more riders to World Tour podiums than we care to count.
- Enjoy true handling precision, even on the most technical of descents, with the full-monocoque S-Works FACT carbon fiber fork.
- With its high-modulus construction, the S-Works FACT full carbon seatpost provides impeccable power transfer, while still allowing for ample compliance for long days in the saddle.

SPECS **All specs are subject to change without notice.**

FRAME	FACT 11r carbon, women's carbon layup & competitive geometry, tapered head tube, OSBB, internal routing, 130mm spacing
FORK	S-Works FACT carbon, full monocoque
BOTTOM BRACKET	OSBB, CeramicSpeed bearings
SEATPOST	S-Works FACT carbon, 20mm offset

PART NO.	DESCRIPTION	COLOR	SIZE
79217-0144	SW AMIRA FRMSET	NBLBLU/KLSIL/NRDCCRED	44
79217-0148			48
79217-0151			51
79217-0154			54
79217-0156			56
79217-0044	SW AMIRA FRMSET	BOELS DOLMANS	44
79217-0048			48
79217-0051			51
79217-0054			54
79217-0056			56

AMIRA					
SIZE	44	48	51	54	56
Stack (mm)	504	516	529	548	565
Reach (mm)	365	371	378	378	380
Head-Tube Length (mm)	105	115	125	145	165
Head-Tube Angle (deg)	70.5	71.25	72	72	72
B-B Height (mm)	269	269	269	269	270
B-B Drop (mm)	73	73	73	73	72
Trail (mm)	67	62	59	59	59
Fork Length (full) (mm)	369	369	369	369	369
Fork Rake/Offset (mm)	51	51	49	49	49
Front-Center (mm)	576	580	582	588	596
Chain-Stay Length (mm)	405	405	405	405	408
Wheelbase (mm)	970	974	976	982	994
Top-Tube Length (horizontal) (mm)	491	502	515	535	547
Bike Stand-Over Height (mm)	692	718	735	758	777
Seat-Tube Length (mm)	390	420	460	490	510
Seat-Tube Angle (deg)	76	76	76	74	74
Seat Post Length (mm)	350	350	400	400	400

RUBY SL4 COMP ULTEGRA DI2 - RIM BRAKE



DPNDGO/HYP/CLGRY

The Ruby SL4 Comp UDi2 is what you might call an "upgrade," as this endurance-bred bike is head and shoulders above its competition. After all, we designed it to be more than just a step-up from an entry-level road bike.

- Enjoy a comfortable and responsive ride with the lightweight Specialized FACT 9r carbon frame. Featuring Zertz to help reduce road chatter, it provides a responsive yet smooth ride with no compromise on performance.
- The agile and responsive Specialized FACT carbon, full-monocoque fork features Zertz inserts to absorb road roughness and give you a smoother ride.
- Shimano Ultegra Di2 shifting offers 11 speeds of electronic wonderment. Shifts are as precise as it gets, dropping chains becomes a rarity, and the trim adjust up front ensures that chain rub is a thing of the past—no matter how extreme your cross-chaining gets.

RUBY SL4					
SIZE	44	48	51	54	57
Stack (mm)	516	529	544	566	588
Reach (mm)	358	370	370	374	390
Head-Tube Length (mm)	120	130	145	165	190
Head-Tube Angle (deg)	70.25	71.25	71.5	72	72
B-B Height (mm)	269.5	269.5	269.5	269.5	271
B-B Drop (mm)	73	73	73	73	71.5
Trail (mm)	69	62	61	60	60
Fork Length (full) (mm)	368	368	368	368	368
Fork Rake/Offset (mm)	51	51	51	49	49
Front-Center (mm)	576	583	586	590	614
Chain-Stay Length (mm)	412	415	415	415	417
Wheelbase (mm)	977	987	990	994	1020
Top-Tube Length (horizontal) (mm)	501	517	526	536	564
Bike Stand-Over Height (mm)	702	721	740	768	792
Seat-Tube Length (mm)	363	391.5	421.5	456.5	486.5
Seat-Tube Angle (deg)	74.5	74.5	74	74	73.5
Handlebar Width (mm)	360	380	400	400	400
Stem Length (mm)	70	80	90	90	100
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	350	350	350	400	400
Crank Length (mm)	165	165	170	170	172.5

SPECS	All specs are subject to change without notice.
FRAME	Specialized FACT 9r carbon rim, FACT construction, Women's Endurance Geometry, Women's Layup, Zertz, threaded
FORK	Specialized Ruby FACT carbon, full monocoque, Zertz inserts
STEM	3D-forged alloy, 7-degree rise
HANDLEBARS	Specialized Women's Comp Shallow Drop, alloy, 123mm drop, 75mm reach
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	Shimano 105
REAR BRAKE	Shimano 105
FRONT DERAILLEUR	Shimano Ultegra Di2 6870, 11-speed, braze-on
REAR DERAILLEUR	Shimano Ultegra Di2, 11-speed
SHIFT LEVERS	Shimano Ultegra Di2, 11-speed
CASSETTE	Shimano 105, 11-speed, 11-32t
CHAIN	KMC X11, 11-speed
CRANKSET	Praxis Zayante, threaded
CHAINRINGS	50/34T
FRONT WHEEL	Axis Elite, QR
REAR WHEEL	Axis Elite, QR
FRONT TIRE	Turbo Pro, 700x26mm, 60TPI, folding bead, BlackBelt protection
REAR TIRE	Turbo Pro, 700x26mm, 60TPI, folding bead, BlackBelt protection
SADDLE	Lithia Comp Gel, hollow Cr-Mo rails, 155mm
SEATPOST	Specialized CG-R, FACT carbon, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90217-5344	RUBY SL4 COMP UDI2 RIM	DPNDGO/HYP/CLGRY	44
90217-5348			48
90217-5351			51
90217-5354			54
90217-5357			57

RUBY SL4 SPORT - RIM BRAKE



CARB/WHT/NRDCRED



WHT/TARBLK

Hitting a sweet spot between performance and value, the Ruby SL4 Sport was designed to thrive on long rides where the roads are, well, less than ideal.

- Enjoy a comfortable and responsive ride with the lightweight Specialized FACT 9r carbon frame. Featuring Zertz to help reduce road chatter, it provides a responsive yet smooth ride with no compromise on performance.
- The agile and responsive Specialized FACT carbon, full-monocone fork features Zertz inserts to absorb road roughness and give you a smoother ride.
- Power to the pedals is provided by the exceptional Praxis Alba alloy crankset. It's stiff and efficient, and the ramping of the chainrings ensures beautiful shifts between rings.

RUBY SL4					
SIZE	44	48	51	54	57
Stack (mm)	516	529	544	566	588
Reach (mm)	358	370	370	374	390
Head-Tube Length (mm)	120	130	145	165	190
Head-Tube Angle (deg)	70.25	71.25	71.5	72	72
B-B Height (mm)	269.5	269.5	269.5	269.5	271
B-B Drop (mm)	73	73	73	73	71.5
Trail (mm)	69	62	61	60	60
Fork Length (full) (mm)	368	368	368	368	368
Fork Rake/Offset (mm)	51	51	51	49	49
Front-Center (mm)	576	583	586	590	614
Chain-Stay Length (mm)	412	415	415	415	417
Wheelbase (mm)	977	987	990	994	1020
Top-Tube Length (horizontal) (mm)	501	517	526	536	564
Bike Stand-Over Height (mm)	702	721	740	768	792
Seat-Tube Length (mm)	363	391.5	421.5	456.5	486.5
Seat-Tube Angle (deg)	74.5	74.5	74	74	73.5
Handlebar Width (mm)	360	380	400	400	400
Stem Length (mm)	70	80	90	90	100
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	350	350	350	400	400
Crank Length (mm)	165	165	170	170	172.5

SPECS	All specs are subject to change without notice.
FRAME	Specialized FACT 9r carbon rim, FACT construction, Women's Endurance Geometry, Women's Layup, Zertz, threaded
FORK	Specialized Ruby FACT carbon, full monocone, Zertz inserts
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Women's Comp Shallow Drop, alloy, 123mm drop, 75mm reach
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	AXIS 1.0
REAR BRAKE	AXIS 1.0
FRONT DERAILLEUR	Shimano 105, braze-on
REAR DERAILLEUR	Shimano 105, GS cage, 11-speed
SHIFT LEVERS	Shimano 105 STI, 11-speed
CASSETTE	Shimano 105, 11-speed, 11-32t
CHAIN	KMC X11, 11-speed
CRANKSET	Praxis Alba
CHAINRINGS	50/34T
FRONT WHEEL	Axis Elite, QR
REAR WHEEL	Axis Elite, QR
FRONT TIRE	Turbo Pro, 700x26mm, 60TPI, folding bead, BlackBelt protection
REAR TIRE	Turbo Pro, 700x26mm, 60TPI, folding bead, BlackBelt protection
SADDLE	Lithia Comp Gel, hollow Cr-Mo rails, 155mm
SEATPOST	Specialized CG-R, FACT carbon, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90217-6044	RUBY SL4 SPORT RIM	CARB/WHT/NRDCRED	44
90217-6048			48
90217-6051			51
90217-6054			54
90217-6057			57
90217-6144	RUBY SL4 SPORT RIM	WHT/TARBLK	44
90217-6148			48
90217-6151			51
90217-6154			54
90217-6157			57

RUBY SL4 - RIM BRAKE



CLGRY/HYP/BLK



TARBLK/RFPNK/WRMCHAR

The Ruby SL4 makes sure that you have what you need to explore the road less traveled, while keeping room in your wallet for a mid-ride cappuccino.

- Enjoy a comfortable and responsive ride with the lightweight Specialized FACT 9r carbon frame. Featuring Zertz to help reduce road chatter, it provides a responsive yet smooth ride with no compromise on performance.
- The agile and responsive Specialized FACT carbon, full-monocone fork features Zertz inserts to absorb road roughness and give you a smoother ride.
- Power to the pedals is provided by the exceptional Praxis Alba alloy crankset. It's stiff and efficient, and the ramping of the chainrings ensures beautiful shifts between rings.

RUBY SL4					
SIZE	44	48	51	54	57
Stack (mm)	516	529	544	566	588
Reach (mm)	358	370	370	374	390
Head-Tube Length (mm)	120	130	145	165	190
Head-Tube Angle (deg)	70.25	71.25	71.5	72	72
B-B Height (mm)	269.5	269.5	269.5	269.5	271
B-B Drop (mm)	73	73	73	73	71.5
Trail (mm)	69	62	61	60	60
Fork Length (full) (mm)	368	368	368	368	368
Fork Rake/Offset (mm)	51	51	51	49	49
Front-Center (mm)	576	583	586	590	614
Chain-Stay Length (mm)	412	415	415	415	417
Wheelbase (mm)	977	987	990	994	1020
Top-Tube Length (horizontal) (mm)	501	517	526	536	564
Bike Stand-Over Height (mm)	702	721	740	768	792
Seat-Tube Length (mm)	363	391.5	421.5	456.5	486.5
Seat-Tube Angle (deg)	74.5	74.5	74	74	73.5
Handlebar Width (mm)	360	380	400	400	400
Stem Length (mm)	70	80	90	90	100
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	350	350	350	400	400
Crank Length (mm)	165	165	170	170	172.5

SPECS	All specs are subject to change without notice.
FRAME	Specialized FACT 9r carbon rim, FACT construction, Women's Endurance Geometry, Women's Layout, Zertz, threaded
FORK	Specialized Ruby FACT carbon, full monocone, Zertz inserts
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Women's Comp Shallow Drop, alloy, 123mm drop, 75mm reach
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	AXIS 1.0
REAR BRAKE	AXIS 1.0
FRONT DERAILLEUR	Shimano Tiagra, braze-on
REAR DERAILLEUR	Shimano Tiagra, long cage, 10-speed
SHIFT LEVERS	Shimano Tiagra STI, 10-speed
CASSETTE	Shimano Tiagra, 10-speed, 11-34t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	Praxis Alba
CHAINRINGS	50/34T
FRONT WHEEL	Axis Elite, QR
REAR WHEEL	Axis Elite, QR
FRONT TIRE	Espoir Elite, 700x25mm
REAR TIRE	Espoir Elite, 700x25mm
SADDLE	Body Geometry Women's Riva Comp Plus, hollow Cr-Mo rails
SEATPOST	Specialized CG-R, FACT carbon, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90217-7044	RUBY SL4 RIM	CLGRY/HYP/BLK	44
90217-7048			48
90217-7051			51
90217-7054			54
90217-7057			57
90217-7144	RUBY SL4 RIM	TARBLK/RFPNK/WRMCHAR	44
90217-7148			48
90217-7151			51
90217-7154			54
90217-7157			57

DOLCE COMP EVO



METBLK/RKTRED/REFLSIL

Are you one of those people who can't help but wonder, "where does that road go?" The Dolce Comp EVO is a bike that'll help you find out. Built to tackle any gravel or dirt road adventure with comfortable confidence.

- The D'Aluisio Smartweld technology in the E5 Premium Aluminum frame provides a lightweight and precise-handling ride, while the Women's Endurance Geometry of the frame delivers improved stability for confident control when climbing and descending. This geo also puts you in a less aggressive and more natural ride position for hours of comfortable riding.
- The lightweight, smooth-shifting Shimano 105 drivetrain with a Praxis Alba 48/32T crankset is perfect for tackling steep grades.
- Veer off and onto dirt and fireroads with confidence with the high-traction, wide, 30/32mm Roubaix Pro tires that feature our long-lasting BlackBelt puncture protection.

DOLCE DISC

SIZE	44	48	51	54	57
Stack (mm)	519	532	548	567	589
Reach (mm)	360	370	370	374	390
Head-Tube Length (mm)	90	100	115	135	160
Head-Tube Angle (deg)	70.5	71.5	72	72	72
B-B Height (mm)	268.5	268.5	268.5	268.5	270
B-B Drop (mm)	73	73	73	73	71.5
Trail (mm)	69	63	60	60	60
Fork Length (full) (mm)	400	400	400	400	400
Fork Rake/Offset (mm)	49	49	49	49	49
Front-Center (mm)	575	580	581	591	614
Chain-Stay Length (mm)	412	415	415	415	417
Wheelbase (mm)	976	984	985	995	1021
Top-Tube Length (horizontal) (mm)	511	522	530	539	566
Bike Stand-Over Height (mm)	692	718	735	758	777
Seat-Tube Length (mm)	390	420	460	490	510
Seat-Tube Angle (deg)	76	75.75	75.5	74	73.5
Handlebar Width (mm)	360	380	400	400	400
Stem Length (mm)	70	80	90	90	100
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	350	350	350	400	400
Crank Length (mm)	165	165	170	170	172.5

SPECS

All specs are subject to change without notice.

FRAME	Specialized E5 Premium Aluminum w/D'Aluisio Smartweld Technology, Women's Endurance Geometry, women's fully-manipulated tube sets w/smooth welds, Zertz, 1-1/8" lower bearing, disc mount
FORK	FACT carbon fiber, alloy steerer/crown, Zertz inserts, post disc mount, Plug + Play fender mount
STEM	Alloy, 7-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 65mm short-reach
TAPE	Specialized S-Wrap w/gel
FRONT BRAKE	Shimano BR-785, hydraulic disc, Ice-Tech resin pads w/fins
REAR BRAKE	Shimano BR-785, hydraulic disc, Ice-Tech resin pads w/fins
FRONT DERAILLEUR	Shimano 105, braze-on
REAR DERAILLEUR	Shimano 105, GS cage, 11-speed
SHIFT LEVERS	Shimano ST-RS505, 11-speed
CASSETTE	Shimano 105, 11-speed, 11-32t
CHAIN	Shimano 105, 11-speed
CRANKSET	Praxis Alba
CHAINRINGS	Subcompact, 48/32T
FRONT WHEEL	Axis Elite Disc, quick-release
REAR WHEEL	Axis Elite Disc, QR
FRONT TIRE	Roubaix Pro 2Bliss Ready, 700x30/32mm, 120TPI, folding bead, BlackBelt protection, Endurant casing
REAR TIRE	Roubaix Pro, 700x30/32mm, 120TPI, folding bead, BlackBelt protection, Endurant casing
SADDLE	Women's Body Geometry Myth Comp Thin, hollow Cr-Mo rails, 155mm
SEATPOST	Specialized CG-R, FACT carbon, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90817-5044	DOLCE COMP EVO	METBLK/RKTRED/REFLSIL	44
90817-5048			48
90817-5051			51
90817-5054			54
90817-5057			57



KLSIL/CRL/BLK

If you're like us, you get a little tired of riding the same old roads weekend after weekend. And if you've ever shied from a beckoning dirt road for lack of confidence, we have the bike for you—the Dolce EVO.

- The D'Aluisio Smartweld technology in the E5 Premium Aluminum frame provides a lightweight and precise-handling ride, while the Women's Endurance Geometry of the frame delivers improved stability for confident control when climbing and descending. This geo also puts you in a less aggressive and more natural ride position for hours of comfortable riding.
- This Praxis Alba 48/32T crankset is perfect for tackling steep grades and rough roads.
- Veer off and onto dirt and fireroads with confidence with the high-traction, wide, 30/32mm Roubaix Pro tires that feature our long-lasting BlackBelt puncture protection.

DOLCE DISC					
SIZE	44	48	51	54	57
Stack (mm)	519	532	548	567	589
Reach (mm)	360	370	370	374	390
Head-Tube Length (mm)	90	100	115	135	160
Head-Tube Angle (deg)	70.5	71.5	72	72	72
B-B Height (mm)	268.5	268.5	268.5	268.5	270
B-B Drop (mm)	73	73	73	73	71.5
Trail (mm)	69	63	60	60	60
Fork Length (full) (mm)	400	400	400	400	400
Fork Rake/Offset (mm)	49	49	49	49	49
Front-Center (mm)	575	580	581	591	614
Chain-Stay Length (mm)	412	415	415	415	417
Wheelbase (mm)	976	984	985	995	1021
Top-Tube Length (horizontal) (mm)	511	522	530	539	566
Bike Stand-Over Height (mm)	692	718	735	758	777
Seat-Tube Length (mm)	390	420	460	490	510
Seat-Tube Angle (deg)	76	75.75	75.5	74	73.5
Handlebar Width (mm)	360	380	400	400	400
Stem Length (mm)	70	80	90	90	100
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	350	350	350	400	400
Crank Length (mm)	165	165	170	170	172.5

SPECS	All specs are subject to change without notice.
FRAME	Specialized E5 Premium Aluminum w/D'Aluisio Smartweld Technology, Women's Endurance Geometry, women's fully-manipulated tube sets w/smooth welds, Zertz, 1-1/8" lower bearing, disc mount
FORK	FACT carbon fiber, alloy steerer/crown, Zertz inserts, post disc mount, Plug + Play fender mount
STEM	Alloy, 7-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 65mm short-reach
TAPE	Specialized S-Wrap w/gel
FRONT BRAKE	TRP HY/RD, cable-actuated hydraulic disc
REAR BRAKE	TRP HY/RD, cable-actuated hydraulic disc
FRONT DERAILLEUR	Shimano Tiagra, braze-on
REAR DERAILLEUR	Shimano Tiagra, long cage, 10-speed
SHIFT LEVERS	Shimano Tiagra STI, 10-speed
CASSETTE	Shimano Tiagra, 10-speed, 11-32t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	FSA Gossamer Pro crankset, Direct mount ABS, 9-/10-speed
FRONT WHEEL	Axis Sport Disc, QR
REAR WHEEL	Axis Sport Disc, QR
FRONT TIRE	Roubaix Pro, 700x30/32mm, 120TPI, folding bead, BlackBelt protection, Endurant casing
REAR TIRE	Roubaix Pro, 700x30/32mm, 120TPI, folding bead, BlackBelt protection, Endurant casing
SADDLE	Women's Body Geometry Myth Sport Thin, steel rails, 155mm
SEATPOST	Specialized Comp carbon, single bolt

PART NO.	DESCRIPTION	COLOR	SIZE
90817-7344	DOLCE EVO	KLSIL/CRL/BLK	44
90817-7348			48
90817-7351			51
90817-7354			54
90817-7357			57

DOLCE ELITE E5



TARBLK/BLK

The Dolce Elite E5 is purpose-built to take you places—both physically and geographically—and make sure you're enjoying the best ride along the way. It's the perfect bike to introduce you to the sport, taking you to new levels of confidence on your cycling journey.

- The Dolce's sturdy and reliable E5 Premium Aluminum frame w/ D'Aluisio Smartweld technology is built with our Women's Endurance Geometry and delivers two important benefits. This geo improves stability and handling for confident control when climbing and descending, while also putting you in a less aggressive and more natural ride position. Result? Hours of comfortable riding.
- The agile and responsive FACT carbon fork features Zertz inserts to absorb road roughness and give you a smoother ride.
- Shimano Sora 9-speed shifting is nothing short of legendary. It's built to last over the long haul, and it's well-equipped to deliver precise shifts across a wide range of gears.

DOLCE RIM

SIZE	44	48	51	54	57
Stack (mm)	519	532	548	567	589
Reach (mm)	360	370	370	374	390
Head-Tube Length (mm)	120	130	145	165	190
Head-Tube Angle (deg)	70.5	71.5	72	72	72
B-B Height (mm)	269.5	269.5	269.5	269.5	271
B-B Drop (mm)	73	73	73	73	72
Trail (mm)	69	63	60	60	60
Fork Length (full) (mm)	369	369	369	369	369
Fork Rake/Offset (mm)	49	49	49	49	49
Front-Center (mm)	574	580	580	590	614
Chain-Stay Length (mm)	412	415	415	415	417
Wheelbase (mm)	975	984	984	994	1020
Top-Tube Length (horizontal) (mm)	504	517	527	536	564
Bike Stand-Over Height (mm)	679.5	699.8	720.8	750.6	778.5
Seat-Tube Length (mm)	363	392	422	457	487
Seat-Tube Angle (deg)	74.5	74.5	74	74	73.5
Handlebar Width (mm)	360	380	400	400	400
Stem Length (mm)	70	80	90	90	100
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	350	350	350	400	400
Crank Length (mm)	165	165	170	170	172.5

SPECS

All specs are subject to change without notice.

FRAME	Specialized E5 Premium Aluminum w/D'Aluisio Smartweld Technology, Women's Endurance Geometry, women's fully-manipulated tube sets w/smooth welds, Zertz, 1-1/8" lower bearing
FORK	Ruby, full carbon monocoque w/Zertz
STEM	Alloy, 7-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized S-Wrap
FRONT BRAKE	AXIS 1.0
REAR BRAKE	AXIS 1.0
FRONT DERAILLEUR	Shimano Tiagra, braze-on
REAR DERAILLEUR	Shimano Tiagra, long cage, 10-speed
SHIFT LEVERS	Shimano Tiagra STI, 10-speed
CASSETTE	Shimano Tiagra, 10-speed, 11-32t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	Praxis Alba
CHAINRINGS	Subcompact, 48/32T
FRONT WHEEL	Axis Sport
REAR WHEEL	Axis Sport
FRONT TIRE	Espoir Sport, 700x25mm, 60TPI, wire bead, double BlackBelt protection
REAR TIRE	Espoir Sport, 700x25mm, 60TPI, wire bead, double BlackBelt protection
SADDLE	Body Geometry Women's Riva Sport Plus, steel rails, 155mm
SEATPOST	Specialized Sport, alloy, 2-bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90817-4044	DOLCE ELITE E5	TARBLK/BLK	44
90817-4048			48
90817-4051			51
90817-4054			54
90817-4057			57



TARBLK/RFPNK/WRMCHAR



TUR/HYP/TARBLK

We're adamant that if you feel like riding somewhere, your bike should be able to take you there with the utmost in confidence. That's why we designed the Dolce Sport to give you all of the performance that you need for the road, with a little extra boost to make riding over rougher terrain a breeze.

- The Dolce Sport's sturdy and reliable A1 Premium Aluminum frame is built with our Women's Endurance Geometry and delivers two important benefits. This geo improves stability and handling for confident control when climbing and descending, while also putting you in a less aggressive and more natural ride position. Result? Hours of comfortable riding.
- The agile and responsive FACT carbon fork features Zertz inserts to absorb road roughness and give you a smoother ride.
- Shimano Sora 9-speed shifting is nothing short of legendary. It's built to last over the long haul, and it's well-equipped to deliver precise shifts across a wide range of gears.

DOLCE RIM					
SIZE	44	48	51	54	57
Stack (mm)	519	532	548	567	589
Reach (mm)	360	370	370	374	390
Head-Tube Length (mm)	120	130	145	165	190
Head-Tube Angle (deg)	70.5	71.5	72	72	72
B-B Height (mm)	269.5	269.5	269.5	269.5	271
B-B Drop (mm)	73	73	73	73	72
Trail (mm)	69	63	60	60	60
Fork Length (full) (mm)	369	369	369	369	369
Fork Rake/Offset (mm)	49	49	49	49	49
Front-Center (mm)	574	580	580	590	614
Chain-Stay Length (mm)	412	415	415	415	417
Wheelbase (mm)	975	984	984	994	1020
Top-Tube Length (horizontal) (mm)	504	517	527	536	564
Bike Stand-Over Height (mm)	679.5	699.8	720.8	750.6	778.5
Seat-Tube Length (mm)	363	392	422	457	487
Seat-Tube Angle (deg)	74.5	74.5	74	74	73.5
Handlebar Width (mm)	360	380	400	400	400
Stem Length (mm)	70	80	90	90	100
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	350	350	350	400	400
Crank Length (mm)	165	165	170	170	172.5

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Women's Endurance Geometry, women's fully-manipulated tube sets, 1-1/8" lower bearing
FORK	FACT carbon fiber, alloy steerer/crown, Zertz inserts
STEM	Alloy, 7-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized S-Wrap
FRONT BRAKE	AXIS 1.0
REAR BRAKE	AXIS 1.0
FRONT DERAILLEUR	Shimano Sora, braze-on
REAR DERAILLEUR	Shimano Sora, 9-speed
SHIFT LEVERS	Shimano Sora STI
CASSETTE	Sunrace, 9-speed, 11-32t
CHAIN	KMC X9, 9-speed w/reusable MissingLink
CRANKSET	Praxis Alba
CHAINRINGS	Subcompact, 48/32T
FRONT WHEEL	Axis Sport
REAR WHEEL	Axis Sport
FRONT TIRE	Espoir Sport, 700x25mm, 60TPI, wire bead, double BlackBelt protection
REAR TIRE	Espoir Sport, 700x25mm, 60TPI, wire bead, double BlackBelt protection
SADDLE	Body Geometry Women's Riva Sport Plus, steel rails, 155mm
SEATPOST	Specialized Sport, alloy, 2-bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90817-6044	DOLCE SPORT	TARBLK/RFPNK/WRMCHAR	44
90817-6048			48
90817-6051			51
90817-6054			54
90817-6057			57
90817-6144	DOLCE SPORT	TUR/HYP/TARBLK	44
90817-6148			48
90817-6151			51
90817-6154			54
90817-6157			57



WHT/FLKSIL



CLGRY/HYP/TARBLK

Whether you're new to riding or just looking for a bike that can do it all with confidence you'll feel right at home with the Dolce. It's been designed specifically for women, so you can expect an incredible geometry, women's-specific components, and a ride quality that's sure to deliver a smile to your face.

- The Dolce Sport's sturdy and reliable A1 Premium Aluminum frame is built with our Women's Endurance Geometry and delivers two important benefits. This geo improves stability and handling for confident control when climbing and descending, while also putting you in a less aggressive and more natural ride position. Result? Hours of comfortable riding.
- Shimano Claris 2400 9-speed shifting is built to last over the long haul, and it's well-equipped to deliver precise shifts across a wide range of gears.
- Subcompact, 48/32T chainrings give you ample gearing to get up the steepest of climbs without sacrificing your ability to go hard on the flats.

DOLCE RIM					
SIZE	44	48	51	54	57
Stack (mm)	519	532	548	567	589
Reach (mm)	360	370	370	374	390
Head-Tube Length (mm)	120	130	145	165	190
Head-Tube Angle (deg)	70.5	71.5	72	72	72
B-B Height (mm)	269.5	269.5	269.5	269.5	271
B-B Drop (mm)	73	73	73	73	72
Trail (mm)	69	63	60	60	60
Fork Length (full) (mm)	369	369	369	369	369
Fork Rake/Offset (mm)	49	49	49	49	49
Front-Center (mm)	574	580	580	590	614
Chain-Stay Length (mm)	412	415	415	415	417
Wheelbase (mm)	975	984	984	994	1020
Top-Tube Length (horizontal) (mm)	504	517	527	536	564
Bike Stand-Over Height (mm)	679.5	699.8	720.8	750.6	778.5
Seat-Tube Length (mm)	363	392	422	457	487
Seat-Tube Angle (deg)	74.5	74.5	74	74	73.5
Handlebar Width (mm)	360	380	400	400	400
Stem Length (mm)	70	80	90	90	100
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	350	350	350	400	400
Crank Length (mm)	165	165	170	170	172.5

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Women's Endurance Geometry, women's fully-manipulated tube sets, 1-1/8" lower bearing
FORK	FACT carbon fiber, alloy steerer/crown, Zertz inserts
STEM	Alloy, 7-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized S-Wrap
FRONT BRAKE	Tektro, caliper, dual pivot, long reach
REAR BRAKE	Tektro, caliper, long reach, dual pivot
FRONT DERAILLEUR	Shimano Claris 2400, braze-on
REAR DERAILLEUR	Shimano Claris 2400, 8-speed
SHIFT LEVERS	Shimano Claris 2400 ST1
CASSETTE	Sunrace, 8-speed, 11-32t
CHAIN	KMC Z7, 8-speed w/reusable MissingLink
CRANKSET	FSA Gossamer Pro crankset, Direct mount ABS, 9-/10-speed
CHAINRINGS	Subcompact, 48/32T
FRONT WHEEL	Axis Sport
REAR WHEEL	Axis Sport
FRONT TIRE	Espoir Sport, 700x25mm, 60TPI, wire bead, double BlackBelt protection
REAR TIRE	Espoir Sport, 700x25mm, 60TPI, wire bead, double BlackBelt protection
SADDLE	Body Geometry Women's Riva Sport Plus, steel rails, 155mm
SEATPOST	Specialized Sport, alloy, 2-bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90817-7244	DOLCE	WHT/FLKSIL	44
90817-7248			48
90817-7251			51
90817-7254			54
90817-7257			57
90817-7044	DOLCE	CLGRY/HYP/TARBLK	44
90817-7048			48
90817-7051			51
90817-7054			54
90817-7057			57

VITA EXPERT CARBON



PLAT/MCRPRLWHT/PNK

Workout buddies can be all the motivation you need to get out there, and the Vita Expert Carbon is the epitome of a pure performance partner.

- The lightweight FACT 9r carbon frame features Zertz inserts to smooth out your ride, plus mounts for racks and fenders. The frame is also engineered and designed with our Women's Fitness Geometry, helping you ride more efficiently in a position that will see you riding comfortably, mile-after-mile.
- The agile and responsive FACT carbon, full-monocoque fork features our proprietary Zertz inserts to help absorb road roughness, giving you a smoother ride.
- Shimano Deore hydraulic disc brakes provide incredible stopping power in all conditions, while also reducing hand fatigue during braking.

VITA CARBON					
SIZE	XS	S	M	L	XL
Stack (mm)	536	550	572	587	606
Reach (mm)	374	379	383	384	393
Head-Tube Length (mm)	120	130	150	165	185
Head-Tube Angle (deg)	69	70	71	71	71
B-B Height (mm)	275	275	275	275	275
B-B Drop (mm)	70	70	70	70	70
Trail (mm)	78	71	65	65	65
Fork Length (full) (mm)	398	398	398	398	398
Fork Rake/Offset (mm)	51	51	51	51	51
Front-Center (mm)	612	612	614	620	635
Chain-Stay Length (mm)	435	435	435	435	435
Wheelbase (mm)	1037	1037	1039	1045	1061
Top-Tube Length (horizontal) (mm)	518	531	547	563	578
Bike Stand-Over Height (mm)	687.7	719.8	752.3	776.7	812.3
Seat-Tube Length (mm)	360	395	440	475	510
Seat-Tube Angle (deg)	75	74.5	74	73	73
Handlebar Width (mm)	580	580	600	600	620
Stem Length (mm)	75	90	90	105	105
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	300	300	350	350	350
Crank Length (mm)	165	165	170	170	172.5

SPECS	All specs are subject to change without notice.
FRAME	FACT 9r carbon fiber, Women's Fitness Geometry, Zertz inserts, internal cable routing, disc mount, Plug + Play fender mount, rack mount
FORK	Specialized FACT carbon, full monocoque, Zertz, post mount disc, Plug + Play fender mounts
STEM	Specialized Flow Set, integrated, 3D forged alloy, 4-bolt, XS/S/M: 12-degree rise, L/XL: 20 degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-buttressed alloy, 9-degree backsweep, 31.8mm
TAPE	Specialized Body Geometry Targa Women's, lock-on, integrated bar ends
FRONT BRAKE	Shimano Deore, hydraulic disc, resin pads, 160mm rotor
REAR BRAKE	Shimano Deore, hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	Shimano 105, braze-on, road double
REAR DERAILLEUR	Shimano 105, GS cage, 11-speed
SHIFT LEVERS	microSHIFT flatbar road, 11-speed
CASSETTE	Shimano 105, 11-speed, 11-32t
CHAIN	KMC X11-1, 11-speed w/reusable MissingLink
CRANKSET	FSA Gossamer Pro, forged aluminum, sub compact
CHAINRINGS	48/32T w/chainguard
BOTTOM BRACKET	BB386 EVO
FRONT WHEEL	Axis Expert Deep
REAR WHEEL	Axis Expert Deep
FRONT TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
REAR TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
SADDLE	Body Geometry Women's Riva Comp, hollow Cr-Mo rails, 155mm
SEATPOST	Specialized CG-R, FACT carbon, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
92916-3001	VITA EXPERT CARBON	PLAT/MCRPRLWHT/PNK	XS
92916-3002			S
92916-3003			M
92916-3004			L
92916-3005			XL

VITA COMP CARBON



BLUTNT/NDGO/LTTUR



RFBLKTNT/METWHTSIL/FLKSIL

Meet your new, high-performance workout partner—she's always up for a challenge and ready to help you reach, exceed, and create new goals. The Vita Comp Carbon is lightweight and agile, and it features the reliable stopping power of disc brakes, plus an efficient and durable component package.

- The lightweight FACT 9r carbon frame features Zertz inserts to smooth out your ride, plus mounts for racks and fenders. The frame is also engineered and designed with our Women's Fitness Geometry, helping you ride more efficiently in a position that will see you riding comfortably, mile-after-mile.
- The agile and responsive FACT carbon, full-monocoque fork features our proprietary Zertz inserts to help absorb road roughness, giving you a smoother ride.
- Shimano Alivio hydraulic disc brakes provide reliable stopping power in all conditions, while also reducing hand fatigue while you're braking.

VITA CARBON					
SIZE	XS	S	M	L	XL
Stack (mm)	536	550	572	587	606
Reach (mm)	374	379	383	384	393
Head-Tube Length (mm)	120	130	150	165	185
Head-Tube Angle (deg)	69	70	71	71	71
B-B Height (mm)	275	275	275	275	275
B-B Drop (mm)	70	70	70	70	70
Trail (mm)	78	71	65	65	65
Fork Length (full) (mm)	398	398	398	398	398
Fork Rake/Offset (mm)	51	51	51	51	51
Front-Center (mm)	612	612	614	620	635
Chain-Stay Length (mm)	435	435	435	435	435
Wheelbase (mm)	1037	1037	1039	1045	1061
Top-Tube Length (horizontal) (mm)	518	531	547	563	578
Bike Stand-Over Height (mm)	687.7	719.8	752.3	776.7	812.3
Seat-Tube Length (mm)	360	395	440	475	510
Seat-Tube Angle (deg)	75	74.5	74	73	73
Handlebar Width (mm)	580	580	600	600	620
Stem Length (mm)	75	90	90	105	105
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	300	300	350	350	350
Crank Length (mm)	165	165	170	170	172.5

SPECS	All specs are subject to change without notice.
FRAME	FACT 9r carbon fiber, Women's Fitness Geometry, Zertz inserts, internal cable routing, disc mount, Plug + Play fender mount, rack mount
FORK	Specialized FACT carbon, full monocoque, Zertz, post mount disc, Plug + Play fender mounts
STEM	Specialized Flow Set, integrated, 3D forged alloy, 4-bolt, XS/S/M: 12-degree rise, L/XL: 20 degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-buttressed alloy, 9-degree backsweep, 31.8mm
TAPE	Specialized Body Geometry Targa Women's, lock-on, integrated bar ends
FRONT BRAKE	Shimano Alivio hydraulic disc, resin pads, 160mm rotor
REAR BRAKE	Shimano Alivio hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	Shimano Tiagra 4700, 10-speed, braze-on
REAR DERAILLEUR	Shimano Tiagra, 10-speed, GS Cage
SHIFT LEVERS	microSHIFT flatbar road, 10-speed
CASSETTE	Shimano, 10-speed, 11-34t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	FSA Gossamer Pro, forged aluminum, MegaExo, sub compact
CHAINRINGS	48/32T w/chainguard
BOTTOM BRACKET	FSA MegaExo
FRONT WHEEL	Axis Elite Deep
REAR WHEEL	Axis Elite Deep
FRONT TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
REAR TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
SADDLE	Body Geometry Women's Riva Sport Plus, steel rails, 155mm
SEATPOST	Specialized Pro Pave, FACT carbon, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
92917-5001	VITA COMP CARBON	BLUTNT/NDGO/LTTUR	XS
92917-5002			S
92917-5003			M
92917-5004			L
92917-5005			XL
92917-5101	VITA COMP CARBON	RFBLKTNT/METWHTSIL/FLKSIL	XS
92917-5102			S
92917-5103			M
92917-5104			L
92917-5105			XL

VITA SPORT CARBON



BLKBRYTNT/WRMCHAR/CLGRY



CLGRY/CRL/LTTUR

When you're on a mission to get fit and healthy, you need a hard-working bike that's up to the task. The lightweight carbon fiber frame of the Vita Sport Carbon is fast and handles incredibly, delivering a smooth ride quality in a package teeming with value.

- The lightweight FACT 9r carbon frame features Zertz inserts to smooth out your ride, plus mounts for racks and fenders. The frame is also engineered and designed with our Women's Fitness Geometry, helping you ride more efficiently in a position that will see you riding comfortably, mile-after-mile.
- The agile and responsive FACT carbon, full-monocone fork features our proprietary Zertz inserts to help absorb road roughness, giving you a smoother ride.
- Shimano M315 hydraulic disc brakes give you stopping power that you can believe in, while also reducing hand fatigue while you're braking.

VITA CARBON					
SIZE	XS	S	M	L	XL
Stack (mm)	536	550	572	587	606
Reach (mm)	374	379	383	384	393
Head-Tube Length (mm)	120	130	150	165	185
Head-Tube Angle (deg)	69	70	71	71	71
B-B Height (mm)	275	275	275	275	275
B-B Drop (mm)	70	70	70	70	70
Trail (mm)	78	71	65	65	65
Fork Length (full) (mm)	398	398	398	398	398
Fork Rake/Offset (mm)	51	51	51	51	51
Front-Center (mm)	612	612	614	620	635
Chain-Stay Length (mm)	435	435	435	435	435
Wheelbase (mm)	1037	1037	1039	1045	1061
Top-Tube Length (horizontal) (mm)	518	531	547	563	578
Bike Stand-Over Height (mm)	687.7	719.8	752.3	776.7	812.3
Seat-Tube Length (mm)	360	395	440	475	510
Seat-Tube Angle (deg)	75	74.5	74	73	73
Handlebar Width (mm)	580	580	600	600	620
Stem Length (mm)	75	90	90	105	105
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	300	300	350	350	350
Crank Length (mm)	165	165	170	170	172.5

SPECS	All specs are subject to change without notice.
FRAME	FACT 9r carbon fiber, Women's Fitness Geometry, Zertz inserts, internal cable routing, disc mount, Plug + Play fender mount, rack mount
FORK	Specialized FACT carbon, full monocone, Zertz, post mount disc, Plug + Play fender mounts
STEM	Specialized Flow Set, integrated, 3D forged alloy, 4-bolt, XS/S/M: 12-degree rise, L/XL: 20 degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-buttressed alloy, 9-degree backsweep, 31.8mm
TAPE	Specialized Body Geometry Targa Women's, lock-on, integrated bar ends
FRONT BRAKE	Shimano M315 hydraulic disc, resin pads, 160mm rotor
REAR BRAKE	Shimano M315 hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	microSHIFT R9, braze-on 9-speed, road double
REAR DERAILLEUR	Shimano Alivio, 9-speed
SHIFT LEVERS	microSHIFT flatbar road, 9-speed
CASSETTE	Shimano, 9-speed, 11-34t
CHAIN	SRAM PC-971 w/PowerLink
CRANKSET	FSA Vero, alloy, sub compact, 110mm BCD spider
CHAINRINGS	48/32T w/chainguard
BOTTOM BRACKET	FSA MegaExo
RIMS	Disc, 6061 aluminum double-wall
FRONT HUB	Specialized Center Lock, loose ball bearings, 32h, 9mm QR
REAR HUB	Shimano Center Lock, disc, 10x135mm QR, 32h
SPOKES	Stainless, 14g w/self-locking threads
FRONT TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
REAR TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
SADDLE	Body Geometry Women's Riva Sport Plus, steel rails, 155mm
SEATPOST	Alloy, 2-bolt, micro-adjust, 25mm offset, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
92917-6201	VITA SPORT CARBON	BLKBRYTNT/WRMCHAR/CLGRY	XS
92917-6202			S
92917-6203			M
92917-6204			L
92917-6205			XL
92917-6301	VITA SPORT CARBON	CLGRY/CRL/LTTUR	XS
92917-6302			S
92917-6303			M
92917-6304			L
92917-6305			XL



TARBLK/TARBLK



TUR/LTTUR/NRDCCRED

If you're looking to find a partner along your path to fitness, we'd like to introduce you to the Vita Elite Disc. It's constructed from our E5 Premium Aluminum, so it's guaranteed to be tough, strong, and responsive.

- Discover what an incredible ride feels like with the Vita's E5 Premium Aluminum frame. It's light and durable, while also being equipped with rack and fender mounts for easy portage and wet weather riding. You'll also find that it's engineered with our Women's Fitness Geometry, which is designed to ensure that you ride more efficiently and comfortably as you chase down your fitness goals.
- An agile and responsive FACT carbon fiber fork features our Zertz inserts in order to absorb and alleviate the fatigue associated with rough terrain. Additionally, this fork was designed to be compatible with our Plug + Play fenders, which is a nice add-on for anyone that foresees wet commutes and riding in their future.
- Shimano M315 hydraulic disc brakes give you stopping power that you can believe in, while also reducing hand fatigue while you're braking.

VITA E5					
SIZE	XS	S	M	L	XL
Stack (mm)	536	550	572	587	606
Reach (mm)	376	383	386	386	395
Head-Tube Length (mm)	120	130	150	165	185
Head-Tube Angle (deg)	69	70	71	71	71
B-B Height (mm)	275	275	275	275	275
B-B Drop (mm)	70	70	70	70	70
Trail (mm)	78	71	65	65	65
Fork Length (full) (mm)	398	398	398	398	398
Fork Rake/Offset (mm)	51	51	51	51	51
Front-Center (mm)	614	615	617	621	637
Chain-Stay Length (mm)	439	439	439	439	439
Wheelbase (mm)	1043	1045	1046	1051	1067
Top-Tube Length (horizontal) (mm)	520	535	550	565	580
Bike Stand-Over Height (mm)	680.5	704.5	739.5	765	793.5
Seat-Tube Length (mm)	360	395	440	475	510
Seat-Tube Angle (deg)	75	74.5	74	73	73
Handlebar Width (mm)	580	580	600	600	620
Stem Length (mm)	75	90	90	105	105
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	300	300	350	350	350
Crank Length (mm)	165	165	170	170	172.5

SPECS	All specs are subject to change without notice.
FRAME	Specialized E5 Premium Aluminum, Women's Fitness Geometry, women's double-butted tube sets, integrated headset, internal cable routing, disc mount, Plug + Play fender mount, rack mount
FORK	FACT carbon fiber, alloy steerer/crown, Zertz inserts, post disc mount, Plug + Play fender mount
STEM	Specialized Flow Set, integrated, 3D forged alloy, 4-bolt, XS/S/M: 12-degree rise, L/XL: 20 degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-butted alloy, 9-degree backsweep, 31.8mm
TAPE	Specialized Body Geometry Targa Women's, lock-on, integrated bar ends
FRONT BRAKE	Shimano M315 hydraulic disc, resin pads, 160mm rotor
REAR BRAKE	Shimano M315 hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	Shimano Sora, 9-speed
REAR DERAILLEUR	Shimano Sora, GS cage, 9-speed
SHIFT LEVERS	microSHIFT flatbar road, 9-speed
CASSETTE	Shimano, 9-speed, 11-34t
CHAIN	SRAM PC-971 w/PowerLink
CRANKSET	FSA Gossamer Pro, forged aluminum, MegaExo, sub compact
CHAINRINGS	48/32T w/chainguard
BOTTOM BRACKET	FSA MegaExo
FRONT WHEEL	Axis Sport Deep
REAR WHEEL	Axis Sport Deep
FRONT TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
REAR TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
SADDLE	Body Geometry Women's Riva Sport Plus, steel rails, 155mm
SEATPOST	Alloy, 2-bolt, micro-adjust, 25mm offset, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
92917-4001	VITA ELITE	TARBLK/TARBLK	XS
92917-4002			S
92917-4003			M
92917-4004			L
92917-4005			XL
92917-4101	VITA ELITE	TUR/LTTUR/NRDCCRED	XS
92917-4102			S
92917-4103			M
92917-4104			L
92917-4105			XL



BLUFLKTNT/TUR/HYP



LTTUR/NRDCRED/TARBLK

When you're on a mission to get fit and healthy, you need a hard-working bike that's up to the task at hand. In other words, you need a bike like the Vita Sport Disc to be your partner in fitness.

- The hard-working & sturdy A1 Premium Aluminum frame is light and durable, and it also features rack and fender mounts features for easy portage and dry riding in wet conditions. You'll also find that it's engineered with our Women's Fitness Geometry, meaning that you'll go fast with maximum efficiency, but without the discomfort of an aggressive ride position. After all, the more comfortable you are, the longer you'll ride.
- Precision steering and handling is delivered via a lightweight and incredibly strong A1 Premium Aluminum fork that also features rack & fender mounts for getting around town.
- Shimano M315 hydraulic disc brakes give you stopping power that you can believe in, while also reducing hand fatigue while you're braking.

VITA A1					
SIZE	XS	S	M	L	XL
Stack (mm)	547	561	584	598	617
Reach (mm)	373	379	383	382	391
Head-Tube Length (mm)	120	130	150	165	185
Head-Tube Angle (deg)	69	70	71	71	71
B-B Height (mm)	281	281	281	281	281
B-B Drop (mm)	70	70	70	70	70
Trail (mm)	80	73	67	67	67
Fork Length (full) (mm)	410	410	410	410	410
Fork Rake/Offset (mm)	51	51	51	51	51
Front-Center (mm)	615	616	617	622	638
Chain-Stay Length (mm)	445	445	445	445	445
Wheelbase (mm)	1051	1052	1053	1057	1073
Top-Tube Length (horizontal) (mm)	520	535	550	565	580
Bike Stand-Over Height (mm)	691	717	752	776	802
Seat-Tube Length (mm)	360	395	440	475	510
Seat-Tube Angle (deg)	75	74.5	74	73	73
Handlebar Width (mm)	580	580	600	600	620
Stem Length (mm)	70	80	90	100	100
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	300	300	350	350	350
Crank Length (mm)	165	165	170	170	172.5

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Women's Fitness Geometry, women's tube sets w/hourglass seatstays, integrated lower bearing, disc mount, fender/rack mounts
FORK	FACT carbon fiber, alloy steerer/crown, Zertz inserts, post disc mount, Plug + Play fender mount
STEM	Alloy, 4-bolt, 31.8mm clamp
HANDLEBARS	Specialized, double-buttressed alloy, 9-degree backsweep, 31.8mm
TAPE	Specialized Body Geometry Contour Women's, lock-on
FRONT BRAKE	Shimano M315 hydraulic disc, resin pads, 160mm rotor
REAR BRAKE	Shimano M315 hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	microSHIFT R9, 31.8mm clamp, 9-speed, road double
REAR DERAILLEUR	Shimano Alivio, 9-speed
SHIFT LEVERS	microSHIFT flatbar road, 9-speed
CASSETTE	Shimano, 9-speed, 11-34t
CHAIN	KMC X9, 9-speed w/reusable MissingLink
CRANKSET	FSA Vero, forged alloy, sub compact, 110mm BCD spider
CHAINRINGS	48/32T w/chainguard
BOTTOM BRACKET	FSA MegaExo
RIMS	Disc, 6061 aluminum double-wall
FRONT HUB	Specialized Center Lock, loose ball bearings, 32h, 9mm QR
REAR HUB	Shimano Center Lock, disc, 10x135mm QR, 32h
SPOKES	Stainless, 14g w/self-locking threads
FRONT TIRE	Nimbus Reflect, 700x32mm, 26TPI, Flak Jacket protection
REAR TIRE	Nimbus Reflect, 700x32mm, 26TPI, Flak Jacket protection
SADDLE	Body Geometry Women's Riva Sport Plus, steel rails, 155mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
82917-6001	VITA SPORT	BLUFLKTNT/TUR/HYP	XS
82917-6002			S
82917-6003			M
82917-6004			L
82917-6005			XL
82917-6101	VITA SPORT	LTTUR/NRDCRED/TARBLK	XS
82917-6102			S
82917-6103			M
82917-6104			L
82917-6105			XL

VITA SPORT STEP THROUGH



BLUFLKTNT/TUR/HYP

When you're on a mission to get fit and healthy, you need a hard-working bike that's up to the task at hand. In other words, you need a bike like the Vita Sport Disc Step Through to be your partner in fitness. This version has a step through design that makes getting on and off the bike as well as putting a foot down, a total breeze.

- The hard-working & sturdy A1 Premium Aluminum frame is light and durable, and it also features rack and fender mounts features for easy portage and dry riding in wet conditions. You'll also find that it's engineered with our Women's Fitness Geometry, meaning that you'll go fast with maximum efficiency, but without the discomfort of an aggressive ride position. After all, the more comfortable you are, the longer you'll ride.
- Precision steering and handling is delivered via a lightweight and incredibly strong A1 Premium Aluminum fork that also features rack & fender mounts for getting around town.
- Shimano M315 hydraulic disc brakes give you stopping power that you can believe in, while also reducing hand fatigue while you're braking.

VITA A1 ST			
SIZE	S	M	L
Stack (mm)	561	584	598
Reach (mm)	379	383	382
Head-Tube Length (mm)	130	150	165
Head-Tube Angle (deg)	70	71	71
B-B Height (mm)	277	277	277
B-B Drop (mm)	70	70	70
Trail (mm)	72	66	66
Fork Length (full) (mm)	410	410	410
Fork Rake/Offset (mm)	51	51	51
Front-Center (mm)	616	618	622
Chain-Stay Length (mm)	445	445	445
Wheelbase (mm)	1052	1053	1057
Top-Tube Length (horizontal) (mm)	535	550	565
Bike Stand-Over Height (mm)	615.9	624.5	624.8
Seat-Tube Length (mm)	395	440	475
Seat-Tube Angle (deg)	74.5	74	73
Handlebar Width (mm)	580	600	600
Stem Length (mm)	80	90	100
Saddle Width (mm)	155	155	155
Seat Post Length (mm)	300	350	350
Crank Length (mm)	165	170	170

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, step through, Women's Fitness Geometry, women's tube sets w/hourglass seatstays, disc mount, fender/rack mounts
FORK	FACT carbon fiber, alloy steerer/crown, Zertz inserts, post disc mount, Plug + Play fender mount
STEM	Alloy, 4 bolt, 31.8mm clamp
HANDLEBARS	Specialized, double-buttressed alloy, 9-degree backsweep, 31.8mm
TAPE	Specialized Body Geometry Contour Women's, lock-on
FRONT BRAKE	Shimano M315 hydraulic disc, resin pads, 160mm rotor
REAR BRAKE	Shimano M315 hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	microSHIFT R9, 31.8mm clamp, 9-speed, road double
REAR DERAILLEUR	Shimano Alivio, 9-speed
SHIFT LEVERS	microSHIFT flatbar road, 9-speed
CASSETTE	Shimano, 9-speed, 11-34t
CHAIN	KMC X9, 9-speed w/reusable MissingLink
CRANKSET	FSA Vero, forged alloy, sub compact, 110mm BCD spider
CHAINRINGS	48/32T w/chainguard
BOTTOM BRACKET	FSA MegaExo
RIMS	Disc, 6061 aluminum double-wall
FRONT HUB	Specialized Center Lock, loose ball bearings, 32h, 9mm QR
REAR HUB	Shimano Center Lock, disc, 10x135mm QR, 32h
SPOKES	Stainless, 14g w/self-locking threads
FRONT TIRE	Nimbus Reflect, 700x32mm, 26TPI, Flak Jacket protection
REAR TIRE	Nimbus Reflect, 700x32mm, 26TPI, Flak Jacket protection
SADDLE	Body Geometry Women's Riva Sport Plus, steel rails, 155mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
82917-6402	VITA SPORT STEP THROUGH	BLUFLKTNT/TUR/HYP	S
82917-6403			M
82917-6404			L



METBLK/DRMSIL/EMDGRN



PDRGRN/TUR/CRL

What sounds like more fun? Being locked in a steamy room staring at someone in front of you for an hour or cruising the open road along a path to total freedom and fitness? Yeah, we'd choose the latter, too, which is why we designed the Vita Disc.

- The hard-working & sturdy A1 Premium Aluminum frame is light and durable, and it also features rack and fender mounts features for easy portage and dry riding in wet conditions. You'll also find that it's engineered with our Women's Fitness Geometry, meaning that you'll go fast with maximum efficiency, but without the discomfort of an aggressive ride position. After all, the more comfortable you are, the longer you'll ride.
- Precision steering and handling is delivered via a lightweight and incredibly strong A1 Premium Aluminum fork that also features rack & fender mounts for getting around town.
- Mechanical disc brakes provide improved stopping power with hassle-free maintenance that's free of brake bleeds.

VITA A1					
SIZE	XS	S	M	L	XL
Stack (mm)	547	561	584	598	617
Reach (mm)	373	379	383	382	391
Head-Tube Length (mm)	120	130	150	165	185
Head-Tube Angle (deg)	69	70	71	71	71
B-B Height (mm)	281	281	281	281	281
B-B Drop (mm)	70	70	70	70	70
Trail (mm)	80	73	67	67	67
Fork Length (full) (mm)	410	410	410	410	410
Fork Rake/Offset (mm)	51	51	51	51	51
Front-Center (mm)	615	616	617	622	638
Chain-Stay Length (mm)	445	445	445	445	445
Wheelbase (mm)	1051	1052	1053	1057	1073
Top-Tube Length (horizontal) (mm)	520	535	550	565	580
Bike Stand-Over Height (mm)	691	717	752	776	802
Seat-Tube Length (mm)	360	395	440	475	510
Seat-Tube Angle (deg)	75	74.5	74	73	73
Handlebar Width (mm)	580	580	600	600	620
Stem Length (mm)	70	80	80	100	100
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	300	300	350	350	350
Crank Length (mm)	165	165	170	170	172.5

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Women's Fitness Geometry, women's tube sets w/hourglass seatstays, integrated lower bearing, disc mount, fender/rack mounts
FORK	Steel, straight blades, IS disc mount, fender/rack mounts
STEM	Alloy, 4 bolt, 20-degree rise, 25.4mm clamp
HANDLEBARS	Specialized, alloy, 9-degree backsweep, 25.4mm
TAPE	Specialized Body Geometry Contour Women's, lock-on
FRONT BRAKE	Mechanical disc, resin pads, 160mm
REAR BRAKE	Mechanical disc, resin pads, 160mm
FRONT DERAILLEUR	Shimano Tourney, top swing, dual pull, 31.8mm band clamp
REAR DERAILLEUR	Shimano Altus, 8-speed
SHIFT LEVERS	Shimano EF500, EZ Fire Plus, 8-speed
CASSETTE	Shimano, 8-speed, 11-32t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Stout, forged alloy
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	Disc, 6061 aluminum double-wall
FRONT HUB	Specialized disc, double-sealed, loose ball bearings, 9mm QR
REAR HUB	Specialized disc, loose ball bearings, for Shimano 8-/9-speed cassettes, QR
SPOKES	Stainless, 14g
FRONT TIRE	Nimbus Reflect, 700x32mm, 26TPI, Flak Jacket protection
REAR TIRE	Nimbus Reflect, 700x32mm, 26TPI, Flak Jacket protection
SADDLE	Body Geometry Women's Riva Sport Plus, steel rails, 155mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
82916-7201	VITA DISC	METBLK/DRMSIL/EMDGRN	XS
82916-7202			S
82916-7203			M
82916-7204			L
82916-7205			XL
82917-7101	VITA DISC	PDRGRN/TUR/CRL	XS
82917-7102			S
82917-7103			M
82917-7104			L
82917-7105			XL

VITA DISC STEP THROUGH



METBLK/DRMSIL/EMDGRN

What sounds like more fun? Being locked in a steamy room staring at someone in front of you for an hour or cruising along the open on a path to fitness? Yeah, we'd choose the latter, too, which is why we designed the Vita Disc Step Through with a design that makes getting on and off the bike, as well as putting a foot down, a total breeze.

- The hard-working & sturdy A1 Premium Aluminum frame is light and durable, and it also features rack and fender mounts for easy portage and dry riding in wet conditions. You'll also find that it's engineered with our Women's Fitness Geometry, meaning that you'll go fast with maximum efficiency, but without the discomfort of an aggressive ride position. After all, the more comfortable you are, the longer you'll ride.
- Precision steering and handling is delivered via a lightweight and incredibly strong A1 Premium Aluminum fork that also features rack & fender mounts for getting around town.
- Mechanical disc brakes provide improved stopping power with hassle-free maintenance that's free of brake bleeds.

VITA A1 ST			
SIZE	S	M	L
Stack (mm)	561	584	598
Reach (mm)	379	383	382
Head-Tube Length (mm)	130	150	165
Head-Tube Angle (deg)	70	71	71
B-B Height (mm)	277	277	277
B-B Drop (mm)	70	70	70
Trail (mm)	72	66	66
Fork Length (full) (mm)	410	410	410
Fork Rake/Offset (mm)	51	51	51
Front-Center (mm)	616	618	622
Chain-Stay Length (mm)	445	445	445
Wheelbase (mm)	1052	1053	1057
Top-Tube Length (horizontal) (mm)	535	550	565
Bike Stand-Over Height (mm)	615.9	624.5	624.8
Seat-Tube Length (mm)	395	440	475
Seat-Tube Angle (deg)	74.5	74	73
Handlebar Width (mm)	580	600	600
Stem Length (mm)	80	80	80
Saddle Width (mm)	155	155	155
Seat Post Length (mm)	300	350	350
Crank Length (mm)	165	170	170

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, step through, Women's Fitness Geometry, women's tube sets w/hourglass seatstays, disc mount, fender/rack mounts
FORK	Steel, straight blades, IS disc mount, fender/rack mounts
STEM	Alloy, 4 bolt, 20-degree rise, 25.4mm clamp
HANDLEBARS	Specialized, alloy, 9-degree backsweep, 25.4mm
TAPE	Specialized Body Geometry Contour Women's, lock-on
FRONT BRAKE	Mechanical disc, resin pads, 160mm
REAR BRAKE	Mechanical disc, resin pads, 160mm
FRONT DERAILLEUR	Shimano Tourney, top swing, dual pull, 31.8mm band clamp
REAR DERAILLEUR	Shimano Altus, 8-speed
SHIFT LEVERS	Shimano EF500, EZ Fire Plus, 8-speed
CASSETTE	Shimano, 8-speed, 11-32t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Stout, forged alloy
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	Disc, 6061 aluminum double-wall
FRONT HUB	Specialized disc, double-sealed, loose ball bearings, 9mm QR
REAR HUB	Specialized disc, loose ball bearings, for Shimano 8-/9-speed cassettes, QR
SPOKES	Stainless, 14g
FRONT TIRE	Nimbus Reflect, 700x32mm, 26TPI, Flak Jacket protection
REAR TIRE	Nimbus Reflect, 700x32mm, 26TPI, Flak Jacket protection
SADDLE	Body Geometry Women's Riva Sport Plus, steel rails, 155mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
82917-7302	VITA DISC STEP THROUGH	METBLK/DRMSIL/EMDGRN	S
82917-7303			M
82917-7304			L



WHT/SIL/CHAR



NRDCRED/LTTUR/METWHTSIL



INDIGO/CHAR/WHT

Getting fit is hard enough without emptying every last cent in your wallet for the tools to do it with. Never fear, though, because our Vita was designed to be your partner in all things fitness at a price that won't leave you broke and hungry.

- The hard-working & sturdy A1 Premium Aluminum frame is light and durable, and it also features rack and fender mounts features for easy portage and dry riding in wet conditions. You'll also find that it's engineered with our Women's Fitness Geometry, meaning that you'll go fast with maximum efficiency, but without the discomfort of an aggressive ride position. After all, the more comfortable you are, the longer you'll ride.
- Precision steering and handling is delivered via a lightweight and incredibly strong A1 Premium Aluminum fork that also features rack & fender mounts for getting around town.
- V-brakes provide excellent stopping power and allow for larger tire sizes to be run.

SPECS All specs are subject to change without notice.

FRAME	Specialized A1 Premium Aluminum, Women's Fitness Geometry, women's tube sets w/hourglass seatstays, fender/rack mounts
FORK	Steel, straight blades, fender/rack mounts
STEM	Alloy, 4-bolt, 20-degree rise, 25.4mm clamp
HANDLEBARS	Specialized, alloy, 9-degree backsweep, 25.4mm
TAPE	Specialized Body Geometry Contour Women's, lock-on
FRONT BRAKE	V-brake, linear pull
REAR BRAKE	V-brake, linear pull
FRONT DERAILLEUR	Shimano Tourney, top swing, dual pull, 31.8mm band clamp
REAR DERAILLEUR	Shimano Altus, 8-speed
SHIFT LEVERS	Shimano EF500, EZ Fire Plus, 8-speed
CASSETTE	Shimano, 8-speed, 11-32t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Stout, forged alloy
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	700c, 6061 aluminum double-wall
FRONT HUB	Specialized V-brake, alloy, loose ball bearings, 9mm, QR
REAR HUB	Specialized, 8-/9-speed cassette body, QR
SPOKES	Stainless, 14g
FRONT TIRE	Nimbus Reflect, 700x32mm, 26TPI, Flak Jacket protection
REAR TIRE	Nimbus Reflect, 700x32mm, 26TPI, Flak Jacket protection
SADDLE	Body Geometry Women's Riva Sport Plus, steel rails, 155mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

VITA A1					
SIZE	XS	S	M	L	XL
Stack (mm)	547	561	584	598	617
Reach (mm)	373	379	383	382	391
Head-Tube Length (mm)	120	130	150	165	185
Head-Tube Angle (deg)	69	70	71	71	71
B-B Height (mm)	281	281	281	281	281
B-B Drop (mm)	70	70	70	70	70
Trail (mm)	80	73	67	67	67
Fork Length (full) (mm)	410	410	410	410	410
Fork Rake/Offset (mm)	51	51	51	51	51
Front-Center (mm)	615	616	617	622	638
Chain-Stay Length (mm)	445	445	445	445	445
Wheelbase (mm)	1051	1052	1053	1057	1073
Top-Tube Length (horizontal) (mm)	520	535	550	565	580
Bike Stand-Over Height (mm)	691	717	752	776	802
Seat-Tube Length (mm)	360	395	440	475	510
Seat-Tube Angle (deg)	75	74.5	74	73	73
Handlebar Width (mm)	580	580	600	600	620
Stem Length (mm)	70	80	80	100	100
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	300	300	350	350	350
Crank Length (mm)	165	165	170	170	170

PART NO.	DESCRIPTION	COLOR	SIZE
82915-7001	VITA	WHT/SIL/CHAR	XS
82915-7002			S
82915-7003			M
82915-7004			L
82915-7005			XL
82917-7001	VITA	NRDCRED/LTTUR/METWHTSIL	XS
82917-7002			S
82917-7003			M
82917-7004			L
82917-7005			XL
82915-7101	VITA	INDIGO/CHAR/WHT	XS
82915-7102			S
82915-7103			M
82915-7104			L
82915-7105			XL

ARIEL ELITE CARBON



LTSILTNT/TARBLK/LTTUR

The most important part of fitness is that you're following a path, not what kind of terrain lies beneath your tires. So to make sure that you can mix things up between the road and dirt, our Ariel Elite Carbon comes equipped with everything you need to hit your goals, like women's-specific components and a custom suspension fork.

- Working with our Body Geometry team, we designed a frame that strikes the optimal balance between comfort and efficiency. The FACT 9r carbon fiber keeps the bike ultra-light and efficient, while the rack, fender, and disc mounts give you an incredibly versatile package.
- An SR Suntour NCX fork w/ Fitness Brain technology features 60mm of coil-sprung travel that takes the sting out of bumpy terrain, while an integrated remote lockout is coupled with our Fitness Brain technology to promote more climbing and pedaling efficiency.
- Braking duties are handled by Tektro Flow Set Control hydraulic Disc Brakes to ensure effective, consistent, and reliable power through any kind of terrain or condition.

ARIEL CARBON				
SIZE	XS	S	M	L
Seat-Tube Length, B-B Center to Top (mm)	330	372	422	472
Top-Tube Length, Horizontal (mm)	555	571	586	604
B-B Drop (mm)	65	65	65	65
Chain-Stay Length (mm)	445	445	445	445
Seat-Tube Angle (deg)	73	73	73	73
Head-Tube Angle (deg)	70	70	70.5	70.5
Fork Rake (mm)	43	43	43	43
Trail (mm)	78	78	75	75
Front-Center (mm)	614	631	641	660
Wheelbase (mm)	1051	1068	1078	1097
Stand-Over Height (mm)	698	732	769	806
Head-Tube Length (mm)	95	110	125	145
Reach (mm)	378	390	400	412
Stack (mm)	578	592	608	627
Handlebar Width (mm)	640	640	660	660
Stem Length (mm)	60	75	75	90
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	350	350	350	350
Crank Length (mm)	165	165	170	170

SPECS	All specs are subject to change without notice.
FRAME	FACT 11m, full carbon, XC Geometry, internal split-housing cable routing, PF30 BB, 12x148mm rear end, triangulated post-mount 160mm brake mount
FORK	SR Suntour NCX w/Specialized Fitness Brain technology, 60mm of travel, 1-1/8" steerer, 12mm thru-axle
STEM	Specialized Flowset, integrated, 3D forged alloy, 4-bolt, 12-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-buttressed alloy, 9-degree backsweep, 31.8mm
GRIPS	Body Geometry Flow Set Control Grips, lock-on
FRONT BRAKE	Tektro Flow Set Control, hydraulic disc, metal pads, post mount, 160mm rotor
REAR BRAKE	Tektro Flow Set Control, hydraulic disc, metal pads, flat mount, 140mm rotor
FRONT DERAILLEUR	microSHIFT XCD, 31.8mm clamp, 10-/11-speed, MTB double
REAR DERAILLEUR	Shimano SLX, Shadow Plus design, SGS cage, 10-speed
SHIFT LEVERS	Flow Set Control, 10-speed
CASSETTE	Sunrace, 11-40t, 10-speed
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	FSA V-Drive, MegaEXO BB, 10-/11-speed, hollow forged 7075 aluminum, 170mm Q-factor, direct-mount
CHAINRINGS	44/32T w/chainguard
BOTTOM BRACKET	FSA MegaEXO
RIMS	700c Disc 6061 double wall pin joint
FRONT HUB	Axis Sport Disc
REAR HUB	Shimano, loose ball bearings, 11-speed, 135mm axle, 28h
SPOKES	Stainless, 14g w/self-locking threads
FRONT TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
REAR TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
SADDLE	Aldia Comp, hollow Cr-Mo rails, 155mm
SEATPOST	Alloy, 2-bolt, micro-adjust, 25mm offset, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
92217-4201	ARIEL ELITE CARBON	LTSILTNT/TARBLK/LTTUR	XS
92217-4202			S
92217-4203			M
92217-4204			L

ARIEL ELITE



FLKSIL/HYP/DPNDGO

You take your fitness journey seriously, and the last thing that you need is to feel restrained by the tools that get you there. That's why our Ariel Elite comes equipped with a suspension fork with our Fitness Brain technology for fast, efficient, and intuitive use over any surface.

- Designed for women who want to mix adventure with fitness, the hard-working, sturdy A1 SL Premium Aluminum frame features our Women's Fitness Geometry—meaning that you'll go faster with maximum efficiency, only without the discomfort of an aggressive ride position. The more comfortable you are, the longer you'll ride.
- An SR Suntour NCX fork w/ Fitness Brain technology features 60mm of coil-sprung travel that takes the sting out of bumpy terrain, while an integrated remote lockout is coupled with our Fitness Brain technology to promote more climbing and pedaling efficiency.
- Braking duties are handled by Tektro Flow Set Control hydraulic Disc Brakes to ensure effective, consistent, and reliable power through any kind of terrain or condition.

ARIEL A1 SL				
SIZE	XS	S	M	L
Seat-Tube Length, B-B Center to Top (mm)	355	375	425	475
Top-Tube Length, Horizontal (mm)	555	572	587	604
B-B Drop (mm)	65	65	65	65
Chain-Stay Length (mm)	445	445	445	445
Seat-Tube Angle (deg)	73	73	73	73
Head-Tube Angle (deg)	70	70	70	70
Fork Rake (mm)	42	42	42	42
Trail (mm)	87	87	87	87
Front-Center (mm)	613	630	641	659
Wheelbase (mm)	1051	1067	1078	1096
Stand-Over Height (mm)	697	725	758	790
Head-Tube Length (mm)	95	110	125	145
Reach (mm)	378	390	400	412
Stack (mm)	580	594	611	630
Handlebar Width (mm)	640	640	660	660
Stem Length (mm)	60	75	75	90
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	350	350	350	350
Crank Length (mm)	165	165	170	170

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 SL Premium Aluminum, Fitness Geometry, fully-manipulated butted tubing, internal cable routing, flat mount disc, rack & Plug + Play mounts
HANDLEBARS	Specialized, double-butted alloy, 9-degree backsweep, 31.8mm
GRIPS	Body Geometry Flow Set Control Grips, lock-on
FRONT BRAKE	Tektro Flow Set Control, hydraulic disc, metal pads, post mount, 160mm rotor
REAR BRAKE	Tektro Flow Set Control, hydraulic disc, metal pads, post mount, 160mm rotor
FRONT DERAILLEUR	microSHIFT XCD, 31.8mm clamp, 10-/11-speed, MTB double
REAR DERAILLEUR	Shimano SLX, Shadow Plus design, SGS cage, 10-speed
SHIFT LEVERS	Flow Set Control, 10-speed
CASSETTE	Sunrace, 11-40t, 10-speed
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	FSA V-Drive, MegaEXO BB, 10-/11-speed, hollow forged 7075 aluminum, 170mm Q-factor, direct-mount
CHAINRINGS	44/32T w/chainguard
BOTTOM BRACKET	FSA MegaEvo Road, 68mm, Di2 wiring compatible
RIMS	700c Disc 6061 double wall pin joint
FRONT HUB	Axis Sport Disc
REAR HUB	Shimano, loose ball bearings, 11-speed, 135mm axle, 28h
SPOKES	Stainless, 14g w/self-locking threads, 700c
FRONT TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
REAR TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
SADDLE	Aldia Sport, steel rails, 155mm

PART NO.	DESCRIPTION	COLOR	SIZE
82217-4001	ARIEL ELITE	FLKSIL/HYP/DPNDGO	XS
82217-4002			S
82217-4003			M
82217-4004			L

ARIEL SPORT



LTTUR/TUR/TARBLK



OAKGRN/SPR/PDRGRN

The Ariel Sport will see you tackling workouts on either paved or dirt surfaces with equal confidence, and you'll look good while doing it. Its hard-working component package is paired with the ever-reliable A1 SL Premium aluminum frame and powerful, no-nonsense hydraulic disc brakes.

- Designed for women who want to mix adventure with fitness, the hard-working, sturdy A1 SL Premium Aluminum frame features our Women's Fitness Geometry—meaning that you'll go faster with maximum efficiency, only without the discomfort of an aggressive ride position. The more comfortable you are, the longer you'll ride.
- An SR Suntour NEX fork w/ Fitness Brain technology features 55mm of coil-sprung travel that takes the sting out of bumpy terrain, while our Fitness Brain technology promotes more climbing and pedaling efficiency.
- Braking duties are handled by Tektro Flow Set Control hydraulic disc brakes to ensure effective, consistent, and reliable power through any kind of terrain or condition.

ARIEL A1 SL				
SIZE	XS	S	M	L
Seat-Tube Length, B-B Center to Top (mm)	355	375	425	475
Top-Tube Length, Horizontal (mm)	555	572	587	604
B-B Drop (mm)	65	65	65	65
Chain-Stay Length (mm)	445	445	445	445
Seat-Tube Angle (deg)	73	73	73	73
Head-Tube Angle (deg)	70	70	70	70
Fork Rake (mm)	42	42	42	42
Trail (mm)	87	87	87	87
Front-Center (mm)	613	630	641	659
Wheelbase (mm)	1051	1067	1078	1096
Stand-Over Height (mm)	697	725	758	790
Head-Tube Length (mm)	95	110	125	145
Reach (mm)	378	390	400	412
Stack (mm)	580	594	611	630
Handlebar Width (mm)	640	640	660	660
Stem Length (mm)	60	70	80	90
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	350	350	350	350
Crank Length (mm)	165	165	170	170

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 SL Premium Aluminum, Fitness Geometry, fully-manipulated butted tubing, internal cable routing, flat mount disc, rack & Plug + Play mounts
STEM	3D forged aluminum, 7-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-buttressed alloy, 9-degree backsweep, 31.8mm
GRIPS	Body Geometry Flow Set Control Grips, lock-on
FRONT BRAKE	Tektro Flow Set Control, hydraulic disc, metal pads, post mount, 160mm rotor
REAR BRAKE	Tektro Flow Set Control, hydraulic disc, metal pads, post mount, 160mm rotor
FRONT DERAILLEUR	microSHIFT, 31.8mm clamp, 9-speed, MTB double
REAR DERAILLEUR	Shimano Alivio, Shadow design, SGS cage, 9-speed
SHIFT LEVERS	microSHIFT MTB, 9-speed
CASSETTE	Sunrace, 9-speed, 11-36t
CRANKSET	FSA Alpha Drive, forged 6061 aluminum
CHAINRINGS	44/32T w/chainguard
BOTTOM BRACKET	FSA BB-7420ST
RIMS	700c disc, 6061 aluminum double-wall
FRONT HUB	Specialized Center Lock, loose ball bearings, 32h, 9mm QR
REAR HUB	Shimano Center Lock disc, 8-/9-/10-speed freehub, 135mm axle, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
REAR TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
SADDLE	Aldia Sport, steel rails, 155mm

PART NO.	DESCRIPTION	COLOR	SIZE
82217-6001	ARIEL SPORT	LTTUR/TUR/TARBLK	XS
82217-6002			S
82217-6003			M
82217-6004			L
82217-6101	ARIEL SPORT	OAKGRN/SPR/PDRGRN	XS
82217-6102			S
82217-6103			M
82217-6104			L

ARIEL SPORT STEP THROUGH



LTTUR/TUR/TARBLK

The Ariel Sport Step Through will see you tackling workouts on either paved or dirt surfaces with equal confidence. Its hard-working component package is paired with the ever-reliable A1 SL Premium aluminum frame that makes putting a foot down a breeze.

- Designed for women who want to mix adventure with fitness, the hard-working, sturdy A1 SL Premium Aluminum frame features our Women's Fitness Geometry—meaning that you'll go faster with maximum efficiency, only without the discomfort of an aggressive ride position. The more comfortable you are, the longer you'll ride.
- An SR Suntour NEX fork w/ Fitness Brain technology features 55mm of coil-sprung travel that takes the sting out of bumpy terrain, while our Fitness Brain technology promotes more climbing and pedaling efficiency.
- Braking duties are handled by Tektro Flow Set Control hydraulic disc brakes to ensure effective, consistent, and reliable power through any kind of terrain or condition.

ARIEL A1 SL STEP THROUGH

SIZE	S	M	L
Seat-Tube Length, B-B Center to Top (mm)	400	450	500
Top-Tube Length, Horizontal (mm)	572	587	604
B-B Drop (mm)	65	65	65
Chain-Stay Length (mm)	445	445	445
Seat-Tube Angle (deg)	73	73	73
Head-Tube Angle (deg)	70	70.5	70.5
Fork Rake (mm)	42	42	42
Trail (mm)	91	88	88
Front-Center (mm)	630	641	659
Wheelbase (mm)	1067	1078	1096
Stand-Over Height (mm)	645	655	665
Head-Tube Length (mm)	110	125	145
Reach (mm)	390	400	412
Stack (mm)	594	611	630
Handlebar Width (mm)	640	660	660
Stem Length (mm)	60	70	80
Saddle Width (mm)	155	155	155
Seat Post Length (mm)	350	350	350
Crank Length (mm)	165	170	170

SPECS

All specs are subject to change without notice.

FRAME	Specialized A1 SL Premium Aluminum, Fitness Geometry, fully-manipulated butted tubing, internal cable routing, flat mount disc, rack & Plug + Play mounts
FORK	SR Suntour NEX w/Specialized Fitness Brain technology, 55mm of travel, 1-1/8" steerer, 9mm QR
STEM	3D forged aluminum, 7-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-butt alloy, 9-degree backsweep, 31.8mm
GRIPS	Body Geometry Flow Set Control Grips, lock-on
FRONT BRAKE	Tektro Flow Set Control, hydraulic disc, metal pads, post mount, 160mm rotor
REAR BRAKE	Tektro Flow Set Control, hydraulic disc, metal pads, post mount, 160mm rotor
FRONT DERAILLEUR	microSHIFT, 31.8mm clamp, 9-speed, MTB double
REAR DERAILLEUR	Shimano Alivio, Shadow design, SGS cage, 9-speed
SHIFT LEVERS	microSHIFT MTB, 9-speed
CASSETTE	Sunrace, 9-speed, 11-36t
CHAIN	KMC X9, 9-speed w/reusable MissingLink
CRANKSET	FSA Alpha Drive, forged 6061 aluminum
CHAINRINGS	44/32T w/chainguard
BOTTOM BRACKET	FSA BB-7420ST
RIMS	700c disc, 6061 aluminum double-wall
FRONT HUB	Specialized Center Lock, loose ball bearings, 32h, 9mm QR
REAR HUB	Shimano Center Lock disc, 8-/9-/10-speed freehub, 135mm axle, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
REAR TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
SADDLE	Aldia Sport, steel rails, 155mm
SEATPOST	Alloy, 2-bolt, 12.5mm offset, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
82217-6202	ARIEL SPORT STEP THROUGH	LTTUR/TUR/TARBLK	S
82217-6203			M
82217-6204			L



DPNDGO/NRBLK/HYP



METWHTSIL/FLKSIL/TUR

Safety and control—two things that can be top-of-mind when heading out to get your heart rate up. The Ariel Disc takes care of safety with powerful disc brakes, while control is provided through a women's-specific geometry and a custom suspension fork that'll have you tackling workouts on paved or dirt surfaces with equal confidence.

- Designed for women who want to mix adventure with fitness, the hard-working, sturdy A1 SL Premium Aluminum frame features our Women's Fitness Geometry—meaning that you'll go faster with maximum efficiency, only without the discomfort of an aggressive ride position. The more comfortable you are, the longer you'll ride.
- Enjoy greater control over varying terrain with a custom, easy-adjust, Multi-Circuit Damping fork with 60mm of travel that's tuned for the trail.
- Braking duties are handled by Tektro Flow Set Control hydraulic disc brakes to ensure effective, consistent, and reliable power through any kind of terrain or condition.

ARIEL A1 SL				
SIZE	XS	S	M	L
Seat-Tube Length, B-B Center to Top (mm)	355	375	425	475
Top-Tube Length, Horizontal (mm)	555	572	587	604
B-B Drop (mm)	65	65	65	65
Chain-Stay Length (mm)	445	445	445	445
Seat-Tube Angle (deg)	73	73	73	73
Head-Tube Angle (deg)	70	70	70	70
Fork Rake (mm)	42	42	42	42
Trail (mm)	87	87	87	87
Front-Center (mm)	613	630	641	659
Wheelbase (mm)	1051	1067	1078	1096
Stand-Over Height (mm)	697	725	758	790
Head-Tube Length (mm)	95	110	125	145
Reach (mm)	378	390	400	412
Stack (mm)	580	594	611	630
Handlebar Width (mm)	640	640	660	660
Stem Length (mm)	60	70	80	90
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	350	350	350	350
Crank Length (mm)	165	165	170	170

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 SL Premium Aluminum, Fitness Geometry, fully-manipulated butted tubing, internal cable routing, flat mount disc, rack & Plug + Play mounts
STEM	3D forged aluminum, 7-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-buttressed alloy, 9-degree backsweep, 31.8mm
GRIPS	Body Geometry Flow Set Control Grips, lock-on
FRONT BRAKE	Tektro Flow Set Control, hydraulic disc, metal pads, post mount, 160mm rotor
REAR BRAKE	Tektro Flow Set Control, hydraulic disc, metal pads, post mount, 160mm rotor
FRONT DERAILLEUR	Shimano Tourney, top swing, for 7-/8-speed 31.8mm clamp
REAR DERAILLEUR	Shimano Altus, 8-speed
SHIFT LEVERS	Shimano Altus, 8-speed
CASSETTE	Sunrace, 8-speed, 11-34t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Stout, forged alloy
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	700c disc, 6061 aluminum double-wall
FRONT HUB	Specialized disc, double-sealed, loose ball bearings, 9mm QR
REAR HUB	Specialized disc, loose ball bearings, for Shimano 8-/9-speed cassettes, 9mm QR
SPOKES	Stainless, 14g
FRONT TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
REAR TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
SADDLE	Aldia Sport, steel rails, 155mm

PART NO.	DESCRIPTION	COLOR	SIZE
82217-7001	ARIEL DISC	DPNDGO/NRBLK/HYP	XS
82217-7002			S
82217-7003			M
82217-7004			L
82217-7101	ARIEL DISC	METWHTSIL/FLKSIL/TUR	XS
82217-7102			S
82217-7103			M
82217-7104			L



PDRGRN/TARBLK/TUR



TARBLK/NRBLK/RFPNK

Take your fitness to new and adventurous levels with the Ariel, a bike that'll see you tackling workouts on paved or dirt paths with equal confidence and control. It features a light and tough A1 SL Premium aluminum frame that's been designed with our Women's Fitness Geometry with an ultra-low standover.

- Designed for women who want to mix adventure with fitness, the hard-working, sturdy A1 SL Premium Aluminum frame features our Women's Fitness Geometry—meaning that you'll go faster with maximum efficiency, only without the discomfort of an aggressive ride position. The more comfortable you are, the longer you'll ride.
- Enjoy greater control over varying terrain with a custom, easy-adjust, Multi-Circuit Damping fork with 60mm of travel that's tuned for the trail.
- V-brakes provide reliable stopping power and hassle-free maintenance, so you'll be able to spend more time riding and less time bleeding those brakes.

ARIEL A1				
SIZE	XS	S	M	L
Seat-Tube Length, B-B Center to Top (mm)	355	375	425	475
Top-Tube Length, Horizontal (mm)	555	572	587	604
B-B Drop (mm)	65	65	65	65
Chain-Stay Length (mm)	445	445	445	445
Seat-Tube Angle (deg)	73	73	73	73
Head-Tube Angle (deg)	70	70	70	70
Fork Rake (mm)	42	42	42	42
Trail (mm)	87	87	87	87
Front-Center (mm)	613	630	641	659
Wheelbase (mm)	1051	1067	1078	1096
Stand-Over Height (mm)	697	725	758	790
Head-Tube Length (mm)	95	110	125	145
Reach (mm)	378	390	400	412
Stack (mm)	580	594	611	630
Handlebar Width (mm)	640	640	660	660
Stem Length (mm)	60	70	80	90
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	350	350	350	350
Crank Length (mm)	165	165	170	170

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 SL Premium Aluminum, Fitness Geometry, rack & Plug + Play mounts
REAR SHOCK	3D forged aluminum, 7-degree rise, 31.8mm clamp
STEM	3D forged aluminum, 7-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-butt alloy, 9-degree backsweep, 31.8mm
GRIPS	Body Geometry Flow Set Control Grips, lock-on
FRONT DERAILLEUR	Shimano Tourney, top swing, for 7-/8-speed 31.8mm clamp
REAR DERAILLEUR	Shimano Altus, 8-speed
SHIFT LEVERS	Shimano EF500, EZ Fire Plus, 8-speed
CASSETTE	Sunrace, 8-speed, 11-34t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Stout, forged alloy
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	700c, 6061 aluminum double-wall
FRONT HUB	Specialized, loose ball bearings, 32h, 9mm QR
REAR HUB	Specialized, loose ball bearings, 8-/9-speed cassette body, 32h, 9mm QR
SPOKES	Stainless, 14g
FRONT TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
REAR TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
SADDLE	Alidia Sport, steel rails, 155mm

PART NO.	DESCRIPTION	COLOR	SIZE
82217-7201	ARIEL	PDRGRN/TARBLK/TUR	XS
82217-7202			S
82217-7203			M
82217-7204			L
82217-7301	ARIEL	TARBLK/NRBLK/RFPNK	XS
82217-7302			S
82217-7303			M
82217-7304			L

ARIEL STEP THROUGH



PDRGRN/TARBLK/TUR

Take your fitness to new and adventurous levels with the Ariel Step Through, a bike that'll see you tackling workouts on paved or dirt paths with equal confidence and control. It features a light & tough frame that starts with our Women's Fitness Geometry and ends with a step through design that makes getting a foot down as easy as can be.

- Designed for women who want to mix adventure with fitness, the hard-working, sturdy A1 SL Premium Aluminum frame features our Women's Fitness Geometry—meaning that you'll go faster with maximum efficiency, only without the discomfort of an aggressive ride position. The more comfortable you are, the longer you'll ride.
- Enjoy greater control over varying terrain with a custom, easy-adjust, Multi-Circuit Damping fork with 60mm of travel that's tuned for the trail.
- V-brakes provide reliable stopping power and hassle-free maintenance, so you'll be able to spend more time riding and less time bleeding those brakes.

ARIEL A1 STEP THROUGH

SIZE	S	M	L
Seat-Tube Length, B-B Center to Top (mm)	400	450	500
Top-Tube Length, Horizontal (mm)	572	587	604
B-B Drop (mm)	65	65	65
Chain-Stay Length (mm)	445	445	445
Seat-Tube Angle (deg)	73	73	73
Head-Tube Angle (deg)	70	70.5	70.5
Fork Rake (mm)	42	42	42
Trail (mm)	91	88	88
Front-Center (mm)	630	641	659
Wheelbase (mm)	1067	1078	1096
Stand-Over Height (mm)	645	655	665
Head-Tube Length (mm)	110	125	145
Reach (mm)	390	400	412
Stack (mm)	594	611	630
Handlebar Width (mm)	640	660	660
Stem Length (mm)	60	70	80
Saddle Width (mm)	155	155	155
Seat Post Length (mm)	350	350	350
Crank Length (mm)	165	170	170

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 SL Premium Aluminum, Fitness Geometry, rack & Plug + Play mounts
FORK	SR Suntour NEX, aluminum V-brake lower, coil spring, hydraulic lock-out w/Multi-Circuit Damping, 60mm of travel
STEM	3D forged aluminum, 7-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-buttressed alloy, 9-degree backsweep, 31.8mm
GRIPS	Body Geometry Flow Set Control Grips, lock-on
FRONT BRAKE	V-brake, alloy, linear pull
REAR BRAKE	V-brake, alloy, linear pull
FRONT DERAILLEUR	Shimano Tourney, top swing, for 7-/8-speed 31.8mm clamp
REAR DERAILLEUR	Shimano Altus, 8-speed
SHIFT LEVERS	Shimano EF500, EZ Fire Plus, 8-speed
CASSETTE	Sunrace, 8-speed, 11-34t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Stout, forged alloy
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	700c, 6061 aluminum double-wall
FRONT HUB	Specialized, loose ball bearings, 32h, 9mm QR
REAR HUB	Specialized, loose ball bearings, 8-/9-speed cassette body, 32h, 9mm QR
SPOKES	Stainless, 14g
FRONT TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
REAR TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
SADDLE	Aldia Sport, steel rails, 155mm
SEATPOST	Alloy, 2-bolt, 12.5mm offset, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
82217-7402	ARIEL STEP THROUGH	PDRGRN/TARBLK/TUR	S
82217-7403			M
82217-7404			L

S-WORKS EPIC FSR Di2



CARB/RKTRED/WHT

The S-Works Epic FSR Di2 is the finest XC race bike that money can buy. It rides like a rocket ship, engineered for speed and packed with technology. Featuring XTR Di2, the world's most advanced XC frame, tuned and efficient suspension with proprietary Brain technology, it's truly a winning combination.

- S-Works FACT 11m carbon fiber frame provides the ideal blend of stiffness, strength, and light weight, resulting in the pinnacle of efficiency and speed. Meanwhile, our XC 29 Geometry, 100mm of travel, internal cable routing, and a SWAT™ Tool Cradle create exceptional handling and zero-hassle maintenance.
- RockShox RS-1 Brain fork is arguably the most sought-after fork in XC racing. Compared to a traditional fork, its inverted design creates a carbon fiber upper that provides superior stiffness, while behaving with more sensitivity to small bumps and more control over larger hits. And with Brain technology, these characteristics are amplified and even more efficient. It also includes our Spike Valve technology that minimizes yaw in cornering, while providing maximum travel in high velocity impacts.
- Drivetrain duties are handled by the revolutionary Shimano XTR Di2 11-speed groupset, with 36/26T gearing up front and 11-40t at the rear. The first ever electronic mountain groupset, it provides unparalleled shift precision, reliability, and accuracy, making it the secret weapon in any racer's arsenal.

EPIC 29 CARBON				
SIZE	S	M	L	XL
Stack (mm)	587	601	615	634
Reach (mm)	393	418	441	462
Head-Tube Length (mm)	90	105	120	140
Head-Tube Angle (deg)	70.5	70.5	70.5	70.5
B-B Height (mm)	332	332	332	332
B-B Drop (mm)	40	40	40	40
Trail (mm)	84	84	84	84
Fork Length (full) (mm)	506	506	506	506
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	634	664	692	720
Chain-Stay Length (mm)	448	448	448	448
Wheelbase (mm)	1082	1112	1140	1168
Top-Tube Length (horizontal) (mm)	564	593	620	647
Bike Stand-Over Height (mm)	770	774	780	793
Seat-Tube Length (mm)	400	434	470	520
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	720	720	720	720
Stem Length (mm)	75	90	100	110
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	350	400	400	400
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	S-Works FACT 11m, full carbon frame w/unique S-Works lay-up, XC Geometry, PF30 BB, carbon headset cups, 12x142mm rear spacing, internal cable routing, front derailleur mount, 100mm of travel, SWAT™ tool cradle
REAR SHOCK	FOX/Specialized remote Mini Brain, AUTOSAG, Spike Valve, Brain Fade adjust I-Valve, 205x53mm, Kashima Coating
FORK	RockShox RS-1 Brain, Solo Air spring, Spike Valve, top-mount Brain Fade adjust, rebound adjust, inverted design, tapered carbon crown/steerer, 15mm Maxle Stealth thru-axle, 51mm offset, 100mm of travel
STEM	Syntace F109, 6-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Mini-rise, FACT carbon, 6-degree upsweep, 8-degree backsweep, 10mm rise, 720mm, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Shimano XTR M9000, hydraulic disc, post mount, metallic pads, 180/160mm rotors
REAR BRAKE	Shimano XTR M9000, hydraulic disc, post mount, metallic pads, 160mm rotors
FRONT DERAILLEUR	Shimano XTR M9070 Di2, down-swing, 2x11
REAR DERAILLEUR	Shimano XTR M9050 Di2, Shadow Plus design, 11-speed
SHIFT LEVERS	Shimano XTR M9050 Di2, electric 11-speed
CASSETTE	Shimano XTR M9001, 11-speed, 11-40t
CHAIN	Shimano HG901, 11-speed
CRANKSET	RaceFace Next SL, hollow carbon, 11-speed, 30mm spindle, 49mm chainline
RIMS	Roval Control SL 29, hookless carbon, 22mm inner width, 24/28h, tubeless ready
FRONT HUB	Roval Control SL, Torque Tube
SPOKES	DT Swiss Revolution
FRONT TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry S-Works Phenom, carbon rails, 143mm
SEATPOST	S-Works FACT carbon, 0mm setback, carbon rail clamps

PART NO.	DESCRIPTION	COLOR	SIZE
93417-0002	SW EPIC FSR CARBON Di2	CARB/RKTRED/WHT	S
93417-0003			M
93417-0004			L
93417-0005			XL

S-WORKS EPIC FSR WORLD CUP



CARB/HYP/WHT

The S-Works Epic World Cup is inspired by the same obsessive design philosophy of its longer wheelbase cousin, only it's tuned for the tight handling of the World Cup circuit. This tighter geo creates faster handling, while still maintaining space for two bottles and a SWAT™ tool cradle.

- S-Works FACT 11m carbon fiber frame provides the ideal blend of stiffness, strength, and light weight, resulting in the pinnacle of efficiency and speed. Meanwhile, our World Cup XC 29 Geometry, 95mm of travel, internal cable routing, and a SWAT™ Tool Cradle create exceptional handling and zero-hassle maintenance.
- The RockShox SID World Cup 29 w/ Brain fork provides 100mm of efficient travel. It features Brain technology that distinguishes between terrain and rider input in order to maximize your power, while a Brain Fade adjusts the oil flow when not hitting bumps.
- The one-by drivetrain is controlled by SRAM's venerable XX1 Eagle components, while braking duties are handled by a SRAM Level Ultimate carbon lever. Combined, the system forms the ultimate in efficiency and intuitive feel, while also having the added benefit of significant weight savings and minimal required maintenance.

EPIC 29 CARBON WC				
SIZE	S	M	L	XL
Stack (mm)	583	597	611	630
Reach (mm)	398	423	446	465
Head-Tube Length (mm)	90	105	120	140
Head-Tube Angle (deg)	70.75	70.75	70.75	70.75
B-B Height (mm)	332	332	332	332
B-B Drop (mm)	40	40	40	40
Trail (mm)	77	77	77	77
Fork Length (full) (mm)	504	504	504	504
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	633	661	691	717
Chain-Stay Length (mm)	439	439	439	439
Wheelbase (mm)	1073	1103	1131	1157
Top-Tube Length (horizontal) (mm)	562	592	618	643
Bike Stand-Over Height (mm)	770	774	780	793
Seat-Tube Length (mm)	400	434	470	520
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	720	720	720	720
Stem Length (mm)	75	90	100	110
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	350	400	400	400
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	S-Works FACT 11m, full carbon frame w/unique S-Works lay-up, XC Geometry, MFS chainstay, PF30 BB, carbon headset cups, 12x142mm rear spacing, internal cable routing, 95mm of travel, SWAT™ tool cradle
REAR SHOCK	FOX/Specialized remote Mini Brain, AUTOSAG, Spike Valve, Brain Fade adjust I-Valve, 200x48mm, Kashima Coating
FORK	RockShox SID Brain World Cup, Position Sensitive damper, top-mount Brain Fade and rebound adjust, Solo Air, tapered carbon crown/steerer, 15x100mm Maxle Stealth thru-axle, 51mm offset, 100mm travel
STEM	Syntace F109, 6-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Mini-rise, FACT carbon, 6-degree upsweep, 8-degree backsweep, 10mm rise, 720mm, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Level Ultimate, hydraulic disc, carbon lever, titanium hardware, organic pads, 180/160mm rotor
REAR BRAKE	SRAM Level Ultimate, hydraulic disc, carbon lever, titanium hardware, organic pads, 160mm rotor
REAR DERAILLEUR	SRAM XX1 Eagle, 12-speed
SHIFT LEVERS	SRAM XX1 Eagle, 12-speed, trigger
CASSETTE	SRAM XG-1295, 12-speed, 10-50t
CHAIN	SRAM XX1 Eagle, black, 12-speed w/PowerLink
CRANKSET	SRAM XX1 Eagle, carbon, 30mm spindle, 49mm chainline
BOTTOM BRACKET	SRAM PF30, OS press-in bearings
RIMS	Roval Control SL 29, hookless carbon, 22mm inner width, 24/28h, tubeless ready
FRONT HUB	Roval Control SL, sealed cartridge bearings, labyrinth style, 15mm thru-axle, 100mm spacing, 24h
SPOKES	DT Swiss Revolution
FRONT TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry S-Works Phenom, carbon rails, 143mm
SEATPOST	S-Works FACT carbon, 0mm setback, carbon rail clamps

PART NO.	DESCRIPTION	COLOR	SIZE
93417-0202	SW EPIC FSR CARBON WC	CARB/HYP/WHT	S
93417-0203			M
93417-0204			L
93417-0205			XL

EPIC FSR PRO CARBON WORLD CUP



CARB/CHAR

Drawing inspiration from the rigors of pro racing, the Epic FSR Pro Carbon World Cup delivers the fast handling, rigidity, and responsiveness required to compete at the top levels. But for training, it also features SWAT™ storage and space for two bottles to keep you stocked on long weekend loops.

- FACT 10m carbon fiber frame provides the ideal blend of stiffness, strength, and light weight, resulting in the pinnacle of efficiency and speed. Meanwhile, our World Cup XC 29 Geometry, 95mm of travel, internal cable routing, and a SWAT™ Tool Cradle create exceptional handling and zero-hassle maintenance.
- The Custom RockShox SID 29 w/ Brain fork provides 100mm of efficient travel. It features Brain technology that distinguishes between terrain and rider input in order to maximize your power, while a Brain Fade adjusts the oil flow when not hitting bumps.
- SRAM's 12-speed X01 Eagle groupset features a wide gear range that delivers climbing and descending efficiency in spades. On top of this, the one-by setup is notorious for being next to impossible to drop a chain with, plus it provides a significant weight savings in comparison to a standard 2x setup.

EPIC 29 CARBON WC				
SIZE	S	M	L	XL
Stack (mm)	583	597	611	630
Reach (mm)	398	423	446	465
Head-Tube Length (mm)	90	105	120	140
Head-Tube Angle (deg)	70.75	70.75	70.75	70.75
B-B Height (mm)	332	332	332	332
B-B Drop (mm)	40	40	40	40
Trail (mm)	77	77	77	77
Fork Length (full) (mm)	504	504	504	504
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	633	661	691	717
Chain-Stay Length (mm)	439	439	439	439
Wheelbase (mm)	1073	1103	1131	1157
Top-Tube Length (horizontal) (mm)	562	592	618	643
Bike Stand-Over Height (mm)	770	774	780	793
Seat-Tube Length (mm)	400	434	470	520
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	720	720	720	720
Stem Length (mm)	70	90	100	110
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	350	400	400	400
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 10m, full carbon frame, XC Geometry, MFS chainstay, PF30 BB, carbon headset cups, 12x142mm rear spacing, internal cable routing, 95mm of travel, SWAT™ tool cradle
REAR SHOCK	FOX/Specialized remote Mini Brain, AUTOSAG, Spike Valve, Brain Fade adjust I-Valve, 200x48mm, Kashima Coating
FORK	Custom RockShox SID w/Brain, Position Sensitive damper, top-mount Brain Fade adjust, rebound adjust, Solo Air spring, tapered alloy crown/steerer, 15x100mm Maxle Stealth thru-axle, 100mm of travel, 46mm offset
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Mini-rise, 7050 alloy, 8-backsweep, 6-upsweep, 10mm rise, 720mm width, 31.8mm clamp
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Shimano XT M8000, hydraulic disc, post mount, metallic pads, 180/160mm rotors
REAR BRAKE	Shimano XT M8000, hydraulic disc, post mount, metallic pads, 160mm rotors
REAR DERAILLEUR	SRAM X01 Eagle, 12-speed
SHIFT LEVERS	SRAM X01 Eagle, 12-speed, trigger
CASSETTE	SRAM XG-1295, 12-speed, 10-50t
CHAIN	SRAM X01 Eagle, silver, 12-speed w/PowerLink
CRANKSET	Custom SRAM X1 Eagle, alloy, 30mm spindle, 49mm chainline
CHAINRINGS	SRAM X-Sync, direct mount, 34T
RIMS	Roval Control Carbon 29, hookless carbon, 22mm inner width, 32h, tubeless ready
FRONT HUB	Roval Control, sealed bearings, 15x100mm thru-axle, 32h
REAR HUB	Roval Control, DT Swiss internals, 36T engagement, XD driver body, 12x142mm, 32h
SPOKES	DT Swiss Revolution
FRONT TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Phenom Expert, Adaptive Edge design, hollow titanium rails, 143mm
SEATPOST	Specialized, alloy, single bolt, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
90317-1002	EPIC FSR PRO CARBON WC	CARB/CHAR	S
90317-1003			M
90317-1004			L
90317-1005			XL

EPIC FSR EXPERT CARBON WORLD CUP



CARB/NRDCRED/KLSIL

The Epic FSR Expert Carbon World Cup is the first and last word in XC bikes, built with the tuned shocks and quick handling required of the World Cup circuit. Yet it also boasts an immaculate carbon construction, tight, race-proven geometry, and a SRAM one-by groupset that's all business come race day.

- By pairing a FACT 9m carbon fiber frame w/ an M5 alloy rear end with our World Cup XC 29 Geometry, this Epic places a focus on tight tube angles and light overall weight for explosive speed and nimble handling on the race circuit.
- The RockShox SID Brain 29 fork provides 100mm of efficient travel. It features Brain technology that distinguishes between terrain and rider input in order to maximize your power, while a Brain Fade adjusts the oil flow when not hitting bumps.
- A SRAM X1 rear derailleur controls a wide range of gears with reliable precision.

EPIC 29 CARBON WC				
SIZE	S	M	L	XL
Stack (mm)	583	597	611	630
Reach (mm)	398	423	446	465
Head-Tube Length (mm)	90	105	120	140
Head-Tube Angle (deg)	70.75	70.75	70.75	70.75
B-B Height (mm)	332	332	332	332
B-B Drop (mm)	40	40	40	40
Trail (mm)	77	77	77	77
Fork Length (full) (mm)	504	504	504	504
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	633	661	691	717
Chain-Stay Length (mm)	439	439	439	439
Wheelbase (mm)	1073	1103	1131	1157
Top-Tube Length (horizontal) (mm)	562	592	618	643
Bike Stand-Over Height (mm)	770	774	780	793
Seat-Tube Length (mm)	400	434	470	520
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	720	720	720	720
Stem Length (mm)	70	90	100	110
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	350	400	400	400
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 9m, carbon front triangle, M5 alloy rear end, XC Geometry, MFS chainstay, PF30 BB, carbon headset cups, 12x142mm rear spacing, internal cable routing, 95mm of travel, SWAT™ tool cradle
REAR SHOCK	FOX/Specialized remote Mini Brain, AUTOSAG, Spike Valve, Brain Fade adjust I-Valve, 200x48mm, Kashima Coating
FORK	Custom RockShox SID w/Brain, Position Sensitive damper, top-mount Brain Fade adjust, rebound adjust, Solo Air spring, tapered alloy crown/steerer, 15x100mm Maxle Stealth thru-axle, 100mm of travel, 46mm offset
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Mini-rise, 7050 alloy, 8-backsweep, 6-upsweep, 10mm rise, 720mm width, 31.8mm clamp
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Shimano Deore SLX M7000, hydraulic disc, metallic pad, 180/160mm rotor
REAR BRAKE	Shimano Deore SLX M7000, hydraulic disc, metallic pad, 160mm rotor
REAR DERAILLEUR	SRAM X1 Type 2.1, 11-speed
SHIFT LEVERS	SRAM X1, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PC-1130, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 49mm chainline
CHAINRINGS	RaceFace, direct mount, 32T
BOTTOM BRACKET	PF30
RIMS	Roval Control, hookless alloy, 21mm inner width, 32h, tubeless ready
FRONT HUB	Roval Control, sealed bearings, 15x100mm thru-axle, 32h
REAR HUB	Roval Control, DT Swiss internals, 36T engagement, XD driver body, 12x142mm, 32h
SPOKES	DT Swiss Revolution
FRONT TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized, alloy, single bolt, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
90317-3002	EPIC FSR EXPERT CARBON WC	CARB/NRDCRED/KLSIL	S
90317-3003			M
90317-3004			L
90317-3005			XL

EPIC FSR COMP CARBON WORLD CUP



CARB/HYP

A bike that's calling out to be someone's introduction to the world of XC riding and racing, the Epic FSR Comp Carbon World Cup is set up with tech that makes the Epic a race winner—nimble World Cup geometry, Brain technology suspension, and a reliable one-by components package from SRAM and Shimano.

- By pairing a FACT 9m carbon fiber frame w/ an M5 alloy rear end with our World Cup XC 29 Geometry, this Epic places a focus on tight tube angles and light overall weight for explosive speed and nimble handling on the race circuit.
- A custom RockShox Reba RL 29 fork offers up 100mm of smooth travel, while an easily accessible compression and rebound adjusts permit you to customize the feel according to the terrain at hand.
- Shimano Deore XT 11-speed rear derailleur is tough, reliable, and incredibly precise.

EPIC 29 CARBON WC				
SIZE	S	M	L	XL
Stack (mm)	583	597	611	630
Reach (mm)	398	423	446	465
Head-Tube Length (mm)	90	105	120	140
Head-Tube Angle (deg)	70.75	70.75	70.75	70.75
B-B Height (mm)	332	332	332	332
B-B Drop (mm)	40	40	40	40
Trail (mm)	77	77	77	77
Fork Length (full) (mm)	504	504	504	504
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	633	661	691	717
Chain-Stay Length (mm)	439	439	439	439
Wheelbase (mm)	1073	1103	1131	1157
Top-Tube Length (horizontal) (mm)	562	592	618	643
Bike Stand-Over Height (mm)	770	774	780	793
Seat-Tube Length (mm)	400	434	470	520
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	720	720	720	720
Stem Length (mm)	70	90	100	110
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	350	400	400	400
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 9m, carbon front triangle, M5 alloy rear end, XC Geometry, MFS chainstay, PF30 BB, carbon headset cups, 12x142mm rear spacing, internal cable routing, 95mm of travel, SWAT™ tool cradle
REAR SHOCK	FOX/Specialized remote Mini Brain, AUTOSAG, Spike Valve, Brain Fade adjust I-Valve, 200x48mm, Kashima Coating
FORK	Custom RockShox Reba RL, rebound adjust, Solo Air spring, tapered alloy crown/steerer, 15x100mm Maxle Stealth thru-axle, 100mm of travel, 51mm offset
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Mini-rise, 6000 alloy, 8-backsweep, 6-upsweep, 10mm rise, 720mm width, 31.8mm clamp
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Shimano M506, hydraulic disc, resin pad, 180/160mm rotor
REAR BRAKE	Shimano M506, hydraulic disc, resin pad, 160mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM NX, 11-speed, trigger
CASSETTE	SRAM PG-1130, 11-speed, 11-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 49mm chainline
CHAINRINGS	RaceFace, direct mount, 32T
BOTTOM BRACKET	PF30
RIMS	Roval Control, hookless alloy, 21mm inner width, 32h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x100mm thru-axle, 32h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x142mm thru-axle, 32h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized, alloy, single bolt, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
90317-5502	EPIC FSR COMP CARBON WC	CARB/HYP	S
90317-5503			M
90317-5504			L
90317-5505			XL

EPIC FSR COMP



BLK/WHT/FLORED



MONGRN/BLK

The Epic FSR Comp makes the most of alloy's undeniable appeal—the perfect blend of performance and strength. It offers the same incredible handling and climbing prowess as its expensive stable mates, while it's built with Shimano Deore stopping power, a 2x10 drivetrain, and Roval rolling stock.

- Given its lightweight and ultra-stiff characteristics, M5 aluminum was the natural choice for the frame's construction. And when complemented with our speed-focused XC 29 Geometry and internal cable routing, you get a bike that compromises nothing in delivering explosive speed and hassle-free maintenance.
- A custom RockShox Reba RL 29 fork offers up 100mm of smooth travel, while an easily accessible compression and rebound adjusts permit you to customize the feel according to the terrain at hand.
- Shimano Deore XT 11-speed rear derailleur is tough, reliable, and incredibly precise.

EPIC 29 ALLOY				
SIZE	S	M	L	XL
Stack (mm)	587	601	615	634
Reach (mm)	393	418	441	462
Head-Tube Length (mm)	100	110	125	145
Head-Tube Angle (deg)	70.5	70.5	70.5	70.5
B-B Height (mm)	332	332	332	332
B-B Drop (mm)	40	40	40	40
Trail (mm)	84	84	84	84
Fork Length (full) (mm)	506	506	506	506
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	634	664	692	720
Chain-Stay Length (mm)	448	448	448	448
Wheelbase (mm)	1082	1112	1140	1168
Top-Tube Length (horizontal) (mm)	568	593	620	647
Bike Stand-Over Height (mm)	776	781	791	793
Seat-Tube Length (mm)	400	434	470	520
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	720	720	720	720
Stem Length (mm)	70	90	100	110
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	350	400	400	400
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	M5 alloy, fully butted, PF30 BB, front derailleur mount, 12x142mm rear spacing, 100mm of travel, internal cable routing
REAR SHOCK	FOX/Specialized remote Mini Brain, AUTOSAG, Spike Valve, Brain Fade adjust I-Valve, 200x48mm
FORK	Custom RockShox Reba RL, rebound adjust, Solo Air spring, tapered alloy crown/steerer, 15x100mm Maxle Stealth thru-axle, 100mm of travel, 51mm offset
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Mini-rise, 6000 alloy, 8-backsweep, 6-upsweep, 10mm rise, 720mm width, 31.8mm clamp
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Shimano M506, hydraulic disc, resin pad, 180/160mm rotor
REAR BRAKE	Shimano M506, hydraulic disc, resin pad, 160mm rotor
FRONT DERAILLEUR	Shimano SLX 7025, direct-mount, down-swing
REAR DERAILLEUR	Shimano Deore XT M8000, Shadow Plus, SGS cage, 11-speed
SHIFT LEVERS	Shimano SLX M7000, 11-speed
CASSETTE	Shimano SLX M7000, 11-speed, 11-42t
CHAIN	KMC X11EL, 11-speed w/reusable MissingLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 49mm chainline
CHAINRINGS	RaceFace, 34/24T, 104/64mm BCD
BOTTOM BRACKET	PF30
RIMS	Roval Control, hookless alloy, 21mm inner width, 32h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x100mm thru-axle, 32h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x142mm thru-axle, 32h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized, alloy, single bolt, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
90317-5002	EPIC FSR COMP	BLK/WHT/FLORED	S
90317-5003			M
90317-5004			L
90317-5005			XL
90317-5102	EPIC FSR COMP	MONGRN/BLK	S
90317-5103			M
90317-5104			L
90317-5105			XL

S-WORKS EPIC FSR FRAME



CARB/CNDYRED/HYP



CARB

The backbone for an XC dream build, the S-Works Epic frameset has the handling, explosive accelerations, and climbing prowess that top racers demand. It's found here with our Brain technology suspension, an S-Works seatpost, and an 11m carbon layup.

- S-Works FACT 11m carbon fiber frame provides the ideal blend of stiffness, strength, and light weight, resulting in the pinnacle of efficiency and speed. Meanwhile, our XC 29 Geometry, 100mm of travel, internal cable routing, and a SWAT™ Tool Cradle create exceptional handling and zero-hassle maintenance.
- With its high-modulus construction, the S-Works FACT full carbon seatpost provides impeccable power transfer while still allowing for ample compliance for long days in the saddle.

SPECS

All specs are subject to change without notice.

FRAME	S-Works FACT 11m, full carbon frame w/unique S-Works lay-up, XC Geometry, PF30 BB, carbon headset cups, 12x142mm rear spacing, internal cable routing, front derailleur mount, 100mm of travel, SWAT™ tool cradle
REAR SHOCK	FOX/Specialized remote Mini Brain, AUTOSAG, Spike Valve, Brain Fade adjust I-Valve, 205x53mm, Kashima Coating
SEATPOST	FACT carbon, 0mm offset, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
73417-0102	SW EPIC FSR CARBON FRM	CARB/CNDYRED/HYP	S
73417-0103			M
73417-0104			L
73417-0105			XL
73417-0002	SW EPIC FSR CARBON FRM	CARB	S
73417-0003			M
73417-0004			L
73417-0005			XL

EPIC 29 CARBON

SIZE	S	M	L	XL
Stack (mm)	587	601	615	634
Reach (mm)	393	418	441	462
Head-Tube Length (mm)	90	105	120	140
Head-Tube Angle (deg)	70.5	70.5	70.5	70.5
B-B Height (mm)	332	332	332	332
B-B Drop (mm)	40	40	40	40
Trail (mm)	84	84	84	84
Fork Length (full) (mm)	506	506	506	506
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	634	664	692	720
Chain-Stay Length (mm)	448	448	448	448
Wheelbase (mm)	1082	1112	1140	1168
Top-Tube Length (horizontal) (mm)	564	593	620	647
Bike Stand-Over Height (mm)	770	774	780	793
Seat-Tube Length (mm)	400	434	470	520
Seat-Tube Angle (deg)	74	74	74	74
Seat Post Length (mm)	350	400	400	400

S-WORKS EPIC FSR WORLD CUP FRAME



TL/RKTRED/BLK



CARB/HYP/WHT

Ready for your XC dream build, the S-Works Epic FSR World Cup frameset has a tighter geometry than its standard cousin, making it ideal for the explosive speeds required of World Cup racing. There's also our Brain suspension and an S-Works seatpost.

- S-Works FACT 11m carbon fiber frame provides the ideal blend of stiffness, strength, and light weight, resulting in the pinnacle of efficiency and speed. Meanwhile, our World Cup XC 29 Geometry, 95mm of travel, internal cable routing, and a SWAT Tool Cradle create exceptional handling and zero-hassle maintenance.
- With its high-modulus construction, the S-Works FACT full carbon seatpost provides impeccable power transfer while still allowing for ample compliance for long days in the saddle.

SPECS	All specs are subject to change without notice.
FRAME	S-Works FACT 11m, full carbon frame w/unique S-Works lay-up, XC Geometry, MFS chainstay, PF30 BB, carbon headset cups, 12x142mm rear spacing, internal cable routing, 95mm of travel, SWAT™ tool cradle
REAR SHOCK	FOX/Specialized remote Mini Brain, AUTOSAG, Spike Valve, Brain Fade adjust I-Valve, 200x48mm, Kashima Coating
SEATPOST	S-Works FACT carbon, 0mm offset, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
73417-0302	SW EPIC FSR CARBON WC FRM	TL/RKTRED/BLK	S
73417-0303			M
73417-0304			L
73417-0305			XL
73417-0202	SW EPIC FSR CARBON WC FRM	CARB/HYP/WHT	S
73417-0203			M
73417-0204			L
73417-0205			XL

EPIC 29 CARBON WC				
SIZE	S	M	L	XL
Stack (mm)	583	597	611	630
Reach (mm)	398	423	446	465
Head-Tube Length (mm)	90	105	120	140
Head-Tube Angle (deg)	70.75	70.75	70.75	70.75
B-B Height (mm)	332	332	332	332
B-B Drop (mm)	40	40	40	40
Trail (mm)	77	77	77	77
Fork Length (full) (mm)	504	504	504	504
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	633	661	691	717
Chain-Stay Length (mm)	439	439	439	439
Wheelbase (mm)	1073	1103	1131	1157
Top-Tube Length (horizontal) (mm)	562	592	618	643
Bike Stand-Over Height (mm)	770	774	780	793
Seat-Tube Length (mm)	400	434	470	520
Seat-Tube Angle (deg)	74	74	74	74
Seat Post Length (mm)	350	400	400	400

EPIC HARDTAIL PRO CARBON WORLD CUP



GLDORG/BLK



CARB/CHAR

If you ask us, it had been too long since hardtails got their world shaken up. Well, our all-new Epic Hardtail Pro Carbon World Cup does just that. New geometry, crazy low frame weight, and a build from the racing gods—this bike is ready to shatter the mold.

- By pairing a FACT 10m carbon fiber frame with our XC 29 Geometry, this Epic places a focus on tight tube angles and light overall weight for explosive speed and nimble handling on the race circuit.
- The Custom RockShox SID 29 w/ Brain fork provides 90/100mm of efficient travel. It features Brain technology that distinguishes between terrain and rider input in order to maximize your power, while a Brain Fade adjusts the oil flow when not hitting bumps.
- SRAM's 12-speed X01 Eagle groupset features a wide gear range that delivers climbing and descending efficiency in spades. On top of this, the one-by setup is notorious for being next to impossible to drop a chain with, plus it provides a significant weight savings in comparison to a standard 2x setup.

EPIC HT CARBON				
SIZE	S	M	L	XL
Stack (mm)	599	608	622	637
Reach (mm)	395	418	441	462
Head-Tube Length (mm)	95	95	110	125
Head-Tube Angle (deg)	69.8	69.8	69.8	69.8
B-B Height (mm)	309	309	309	309
B-B Drop (mm)	61	61	61	61
Trail (mm)	82	82	82	82
Fork Length (full) (mm)	496	506	506	506
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	650	676	705	731
Chain-Stay Length (mm)	430	430	430	430
Wheelbase (mm)	1073	1099	1128	1154
Top-Tube Length (horizontal) (mm)	568	595	623	649
Bike Stand-Over Height (mm)	760	790	814	845
Seat-Tube Length (mm)	400	430	470	520
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	720	720	720	720
Stem Length (mm)	70	90	100	110
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	350	400	400	400
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 10m, full carbon, XC Geometry, internal split-housing cable routing, PF30 BB, 12x148mm rear end, triangulated post-mount 160mm brake
FORK	Custom RockShox SID w/Brain, Position Sensitive damper, bottom-mount Brain Fade adjust, rebound adjust, Solo Air spring, tapered alloy crown/steerer, 110x15mm Maxle Stealth thru-axle, 90/100mm travel, 51mm offset
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Mini-rise, 7050 alloy, 8-backsweep, 6-upsweep, 10mm rise, 720mm width, 31.8mm clamp
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Shimano Deore XT M8000, hydraulic disc, metallic pad, 180/160mm rotor
REAR BRAKE	Shimano Deore XT M8000, hydraulic disc, metallic pad, 160mm rotor
REAR DERAILLEUR	SRAM X01 Eagle, 12-speed
SHIFT LEVERS	SRAM X01 Eagle, 12-speed, trigger
CASSETTE	SRAM XG-1295, 12-speed, 10-50t
CHAIN	SRAM X01 Eagle, silver, 12-speed w/PowerLink
CHAINRINGS	SRAM X-Sync, direct mount, 34T
BOTTOM BRACKET	SRAM PF30, OS press-in bearings
RIMS	Roval Control Carbon 29, hookless carbon, 22mm inner width, 32h, tubeless ready
FRONT HUB	Roval Control, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 32h
REAR HUB	Roval Control, DT Swiss internals, 36T engagement, XD driver body, 12x142mm, 32h
SPOKES	DT Swiss Revolution
FRONT TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Phenom Expert, Adaptive Edge design, hollow titanium rails, 143mm
SEATPOST	Specialized, alloy, 2-bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
91317-1103	EPIC HT PRO CARBON WC 29	GLDORG/BLK	M
91317-1104			L
91317-1003	EPIC HT PRO CARBON WC 29	CARB/CHAR	M
91317-1004			L

EPIC HARDTAIL EXPERT CARBON WORLD CUP



CARB/NRDCRED/KLSIL



RKTRED/BLK/WHT

With all of the growth in full-suspension XC bikes, hardtails were starting to become a little same old, same old. So we thought to ourselves, what better time than now to shake things up with a modern, revolutionary design? Say hello to the Epic Hardtail Expert Carbon World Cup.

- By pairing a FACT 10m carbon fiber frame with our XC 29 Geometry, this Epic places a focus on tight tube angles and extremely light overall weight for explosive speed and nimble handling on the race circuit. For good measure, we also gave it 148mm rear spacing and all-new triangulated post-mount brake mounts.
- The Custom RockShox SID 29 w/ Brain fork provides 90/100mm of efficient travel. It features Brain technology that distinguishes between terrain and rider input in order to maximize your power, while a Brain Fade adjusts the oil flow when not hitting bumps.
- A SRAM X1 rear derailleur controls a wide range of gears with reliable precision.

EPIC HT CARBON				
SIZE	S	M	L	XL
Stack (mm)	599	608	622	637
Reach (mm)	395	418	441	462
Head-Tube Length (mm)	95	95	110	125
Head-Tube Angle (deg)	69.8	69.8	69.8	69.8
B-B Height (mm)	309	309	309	309
B-B Drop (mm)	61	61	61	61
Trail (mm)	82	82	82	82
Fork Length (full) (mm)	496	506	506	506
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	650	676	705	731
Chain-Stay Length (mm)	430	430	430	430
Wheelbase (mm)	1073	1099	1128	1154
Top-Tube Length (horizontal) (mm)	568	595	623	649
Bike Stand-Over Height (mm)	760	790	814	845
Seat-Tube Length (mm)	400	430	470	520
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	720	720	720	720
Stem Length (mm)	70	90	100	110
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	350	400	400	400
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 10m, full carbon, XC Geometry, internal split-housing cable routing, PF30 BB, 12x148mm rear end, triangulated post-mount 160mm brake
FORK	Custom RockShox SID w/Brain, Position Sensitive damper, bottom-mount Brain Fade adjust, rebound adjust, Solo Air spring, tapered alloy crown/steerer, 110x15mm Maxle Stealth thru-axle, 90/100mm travel, 51mm offset
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Mini-rise, 7050 alloy, 8-backsweep, 6-upsweep, 10mm rise, 720mm width, 31.8mm clamp
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Shimano Deore SLX M7000, hydraulic disc, metallic pad, 180/160mm rotor
REAR BRAKE	Shimano Deore SLX M7000, hydraulic disc, metallic pad, 160mm rotor
REAR DERAILLEUR	SRAM X1 Type 2.1, 11-speed
SHIFT LEVERS	SRAM X1, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PC-1130, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 52mm chainline
CHAINRINGS	32T
BOTTOM BRACKET	PF30
RIMS	Roval Control, hookless alloy, 21mm inner width, 32h, tubeless ready
FRONT HUB	Roval Control, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 32h
REAR HUB	Roval Control, DT Swiss internals, 36T engagement, XD driver body, 12x148mm, 32h
SPOKES	DT Swiss Revolution
FRONT TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized, alloy, 2-bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
91317-3003	EPIC HT EXPERT CARBON WC 29	CARB/NRDCRED/KLSIL	M
91317-3004			L
91317-3103	EPIC HT EXPERT CARBON WC 29	RKTRED/BLK/WHT	M
91317-3104			L

EPIC HARDTAIL COMP CARBON WORLD CUP



BBYBLU/NENBLU/NRDCRED



CARB/HYP

For the Epic Hardtail Comp Carbon World Cup, we took a revolutionary new frame design and spec'd it specifically for the rigors of racing at the highest level.

- By pairing a FACT 10m carbon fiber frame with our XC 29 Geometry, this Epic places a focus on tight tube angles and extremely light overall weight for explosive speed and nimble handling on the race circuit. For good measure, we also gave it 148mm rear spacing and all-new triangulated post-mount brake mounts.
- A custom RockShox Reba RL 29 fork offers up 90/100mm of smooth travel, while an easily accessible compression and rebound adjusts permit you to customize the feel according to the terrain at hand.
- 1x, 11-speed shifting is provided by a durable mix of SRAM GX and NX components.

EPIC HT CARBON				
SIZE	S	M	L	XL
Stack (mm)	599	608	622	637
Reach (mm)	395	418	441	462
Head-Tube Length (mm)	95	95	110	125
Head-Tube Angle (deg)	69.8	69.8	69.8	69.8
B-B Height (mm)	309	309	309	309
B-B Drop (mm)	61	61	61	61
Trail (mm)	82	82	82	82
Fork Length (full) (mm)	496	506	506	506
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	650	676	705	731
Chain-Stay Length (mm)	430	430	430	430
Wheelbase (mm)	1073	1099	1128	1154
Top-Tube Length (horizontal) (mm)	568	595	623	649
Bike Stand-Over Height (mm)	760	790	814	845
Seat-Tube Length (mm)	400	430	470	520
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	720	720	720	720
Stem Length (mm)	70	90	100	110
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	350	400	400	400
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 10m, full carbon, XC Geometry, internal split-housing cable routing, PF30 BB, 12x148mm rear end, triangulated post-mount 160mm brake
FORK	Custom RockShox Reba RL, rebound adjust, Solo Air spring, tapered alloy crown/steerer, 15x110mm Maxle Stealth thru-axle, 90/100mm of travel, 51mm offset
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Mini-rise, 6000 alloy, 8-backsweep, 6-upsweep, 10mm rise, 720mm width, 31.8mm clamp
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Shimano M506, hydraulic disc, resin pad, 180/160mm rotor
REAR BRAKE	Shimano M506, hydraulic disc, resin pad, 160mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM NX, 11-speed, trigger
CASSETTE	SRAM PG-1130, 11-speed, 11-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 52mm chainline
CHAINRINGS	RaceFace, direct mount, 32T
BOTTOM BRACKET	PF30
RIMS	Roval Control, hookless alloy, 21mm inner width, 32h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 100x15mm thru-axle, 32h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized, alloy, 2-bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
91317-5003	EPIC HT COMP CARBON WC 29	BBYBLU/NENBLU/NRDCRED	M
91317-5004			L
91317-5103	EPIC HT COMP CARBON WC 29	CARB/HYP	M
91317-5104			L

EPIC HARDTAIL



BLK/DPBLU



MONGRN/BLK



NRDCRED/TUR

Our Epic Hardtail singlehandedly takes hardtail alloy XC bikes into the modern age, with the most capable geometry out there and a build kit that's all business.

- Given its lightweight and ultra-stiff characteristics, M5 aluminum was the natural choice for the frame's construction. And when complemented with our speed-focused XC 29 Geometry and internal cable routing, you get a bike that compromises nothing in delivering explosive speed, confident handling, and hassle-free maintenance.
- A custom RockShox Reba RL 29 fork offers up 80/95mm of smooth travel, while an easily accessible compression and rebound adjusts permit you to customize the feel according to the terrain at hand.
- Shimano controls the 11-speed shifting with SLX shifters and an ultra-crisp and reliable Deore XT M8000 rear derailleur.

EPIC HT ALLOY				
SIZE	S	M	L	XL
Stack (mm)	592	610	625	639
Reach (mm)	390	414	437	458
Head-Tube Length (mm)	90	100	115	130
Head-Tube Angle (deg)	71	71	71	71
B-B Height (mm)	310	310	310	310
B-B Drop (mm)	61	61	61	61
Trail (mm)	79	79	79	79
Fork Length (full) (mm)	486	496	496	496
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	624	655	682	708
Chain-Stay Length (mm)	430	430	430	430
Wheelbase (mm)	1047	1078	1105	1131
Top-Tube Length (horizontal) (mm)	565	593	620	643
Bike Stand-Over Height (mm)	760	799	826	849
Seat-Tube Length (mm)	394	434	470	505
Seat-Tube Angle (deg)	73.5	73.5	73.5	73.5
Handlebar Width (mm)	720	720	720	720
Stem Length (mm)	70	90	100	110
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	350	400	400	400
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	M5 alloy, XC 29 Geometry, tapered head tube, internal cable routing, 12x142mm dropouts, PM 160 rear brake, replaceable alloy rear derailleur hanger
FORK	Custom RockShox Reba RL, rebound adjust, Solo Air spring, tapered alloy crown/steerer, 15x100mm Maxle Stealth thru-axle, 80/95mm of travel, 51mm offset
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Flat Top, alloy, 8-degree backsweep, 6-degree upsweep, 10mm rise, 720mm width, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Shimano M506, hydraulic disc, resin pad, 180/160mm rotor
REAR BRAKE	Shimano M506, hydraulic disc, resin pad, 160mm rotor
FRONT DERAILLEUR	Shimano SLX 7025, direct-mount, down-swing
REAR DERAILLEUR	Shimano Deore XT M8000, Shadow Plus, SGS cage, 11-speed
SHIFT LEVERS	Shimano SLX M7000, 11-speed
CASSETTE	Shimano SLX M7000, 11-speed, 11-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 49mm chainline
RIMS	Specialized Stout, alloy hookless bead, 32h
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x100mm thru-axle, 32h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x142mm thru-axle, 32h
SPOKES	Stainless, 14g, black
FRONT TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Fast Trak, Control casing, 29x2.2", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized, alloy, 2-bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
91317-7002	EPIC HT BASE 29	BLK/DPBLU	S
91317-7003			M
91317-7004			L
91317-7005			XL
91317-7202	EPIC HT BASE 29	MONGRN/BLK	S
91317-7203			M
91317-7204			L
91317-7205			XL
91317-7302	EPIC HT BASE 29	NRDCRED/TUR	S
91317-7303			M
91317-7304			L
91317-7305			XL

S-WORKS CAMBER 29



CARB/BLK/HYP

The S-Works Camber 29 represents a new way of thinking about trail bikes, giving the handling and cushion required for challenging trails without compromising on near XC climbing ability. Think of it as a "do-everything" trail bike that's fully equipped with SWAT™ storage and a superlative build kit.

- A FACT 11m carbon fiber Trail Chassis w/ Camber FSR rear end is stiff, responsive, and remarkably efficient, making the Camber well suited to climbing and descending over technical terrain. You'll also find internal cable routing for clean lines and minimal maintenance, plus an integrated SWAT™ Door at the down tube for zero-hassle storage of your trail essentials.
- Connected with our FSR Concentric Linkage, a FOX FLOAT Factory DPS rear shock features AUTOSAG for easy set up, 120mm of fine-tunable suspension, and our custom Rx Trail Tune for the ultimate in performance and feel.
- FOX 34 Factory 29 fork features 34mm aluminum stanchions that are equal parts strong and stiff, 120mm of plush, trail taming travel, and three-position lever adjust that lets you customize the suspension on-the-fly for any trail condition.

CAMBER 29 CARBON

SIZE	S	M	L	XL
Stack (mm)	609	609	627	655
Reach (mm)	399	427	445	471
Head-Tube Length (mm)	95	95	115	145
Head-Tube Angle (deg)	68.5	68.5	68.5	68.5
B-B Height (mm)	330	330	330	330
B-B Drop (mm)	42	42	42	42
Trail (mm)	97	97	97	97
Fork Length (full) (mm)	531	531	531	531
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	673	701	726	763
Chain-Stay Length (mm)	437	437	437	437
Wheelbase (mm)	1107	1135	1160	1197
Top-Tube Length (horizontal) (mm)	562	590	613	647
Bike Stand-Over Height (mm)	732	735	752	766
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	75	75	75	75
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	60	60	75	90
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS

All specs are subject to change without notice.

FRAME	FACT 11m, full carbon chassis and rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, Concentric Pivot link, 12x142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 120mm of travel
REAR SHOCK	FOX FLOAT Factory, Rx Trail Tune, AUTOSAG, DPS damper, Kashima coating, rebound and 3-position compression and Open adjust, 205x53mm
FORK	FOX 34 Factory 29, Kashima coating, 3-position adjust, compression and rebound adjust, 51mm offset, 15x100mm thru-axle, 120mm travel
STEM	Syntaxe F109, 6-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Trail, FACT carbon, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Shimano XTR M9000, hydraulic disc, post mount, metallic pads, 200/180mm rotors
REAR BRAKE	Shimano XTR M9000, hydraulic disc, post mount, metallic pads, 160/180mm rotors
REAR DERAILLEUR	SRAM XX1 Eagle, 12-speed
SHIFT LEVERS	SRAM XX1 Eagle, 12-speed, trigger
CASSETTE	SRAM XG-1295, 12-speed, 10-50t
CHAIN	SRAM XX1 Eagle, black, 12-speed w/PowerLink
CRANKSET	SRAM XX1 Eagle, carbon, 30mm spindle, 49mm chainline
BOTTOM BRACKET	SRAM PF30, OS press-in bearings
RIMS	Roval Traverse SL 29, hookless carbon, 30mm inner width, 24/28h
FRONT HUB	Roval Traverse, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
REAR HUB	Roval Traverse SL, DT Swiss Star Ratchet, 54t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
SPOKES	DT Swiss Revolution
FRONT TIRE	Purgatory, Control casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control, Control casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Expert, hollow titanium rails, 143mm
SEATPOST	Command Post IRcc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
94717-0002	SW CAMBER FSR CARBON 29	CARB/BLK/HYP	S
94717-0003			M
94717-0004			L
94717-0005			XL

S-WORKS CAMBER 650B



CARB/BLK/HYP

The S-Works Camber 650b embodies why 650b wheels have been such a hit in recent years—it's a short-wheelbase bike with undeniably playful handling and the ability to roll over anything. This versatile personality is matched by XC-inspired climbing prowess, SWAT™ storage, and a jaw-dropping build kit.

- A FACT 11m carbon fiber Trail Chassis w/ Camber FSR rear end is stiff, responsive, and remarkably efficient, making the Camber well suited to climbing and descending over technical terrain. You'll also find internal cable routing for clean lines and minimal maintenance, plus an integrated SWAT™ Door at the down tube for zero-hassle storage of your trail essentials.
- FOX 34 Factory 650b fork features 34mm aluminum stanchions that are equal parts strong and stiff, 130mm of plush, trail taming travel, and three-position lever adjust that lets you customize the suspension on-the-fly for any trail condition.

CAMBER 650 CARBON				
SIZE	S	M	L	XL
Stack (mm)	580	590	599	608
Reach (mm)	399	425	454	475
Head-Tube Length (mm)	95	105	115	125
Head-Tube Angle (deg)	68	68	68	68
B-B Height (650x2.3) (mm)	329	329	329	329
B-B Height (650x2.6) (mm)	334	334	334	334
B-B Drop (mm)	23	23	23	23
Trail (mm)	97	97	97	97
Fork Length (full) (mm)	522	522	522	522
Fork Rake/Offset (mm)	42	42	42	42
Front-Center (mm)	670	700	732	757
Chain-Stay Length (mm)	420	420	420	420
Wheelbase (mm)	1089	1119	1151	1176
Top-Tube Length (horizontal) (mm)	554	583	614	638
Bike Stand-Over Height (mm)	725	730	743	752
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	75	75	75	75
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	60	60	75	90
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 10m, carbon chassis and chainstay, M5 alloy seatstay, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, Concentric Pivot link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 130mm of travel
REAR SHOCK	FOX FLOAT Factory, Rx Trail Tune, AUTOSAG, DPS damper, Kashima coating, rebound and 3-position compression and Open adjust, 205x53mm
FORK	FOX 34 Factory 27.5, Kashima coating, 3-position adjust, compression and rebound adjust, 44mm offset, 15x100mm thru-axle, 130mm travel
STEM	Syntaxe F109, 6-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Trail, FACT carbon, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Shimano XTR M9000, hydraulic disc, post mount, metallic pads, 200/180mm rotors
REAR BRAKE	Shimano XTR M9000, hydraulic disc, post mount, metallic pads, 160/180mm rotors
REAR DERAILLEUR	SRAM XX1 Eagle, 12-speed
SHIFT LEVERS	SRAM XX1 Eagle, 12-speed, trigger
CASSETTE	SRAM XG-1295, 12-speed, 10-50t
CHAIN	SRAM XX1 Eagle, black, 12-speed w/PowerLink
CRANKSET	SRAM XX1 Eagle, carbon, 24mm spindle, 52mm chainline
BOTTOM BRACKET	SRAM PF30, OS press-in bearings
RIMS	Roval Traverse SL 650b, hookless carbon, 30mm inner width, 24/28h
FRONT HUB	Roval Traverse, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
REAR HUB	Roval Traverse SL, DT Swiss Star Ratchet, 54t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
SPOKES	DT Swiss Revolution
FRONT TIRE	Purgatory, Control casing, 650bx2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control, Control casing, 650bx2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Expert, hollow titanium rails, 143mm
SEATPOST	Command Post IRcc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
94717-0102	SW CAMBER FSR CARBON 650B	CARB/BLK/HYP	S
94717-0103			M
94717-0104			L
94717-0105			XL

CAMBER PRO CARBON 29



WHTTNT/GLDORG

When sheer speed and trail prowess are the names of the game, look no further than our Camber Pro Carbon 29. It blends all of the trail bike characteristics that you want with the XC climbing ability that you need.

- A FACT 11m carbon fiber Trail Chassis w/ Camber FSR rear end is stiff, responsive, and remarkably efficient, making the Camber well suited to climbing and descending over technical terrain. You'll also find internal cable routing for clean lines and minimal maintenance, plus an integrated SWAT™ Door at the down tube for zero-hassle storage of your trail essentials.
- FOX 34 Performance Elite 29 fork features 34mm aluminum stanchions that are equal parts strong and stiff, 120mm of plush, trail-taming travel, and three-position lever adjust that lets you customize the suspension on-the-fly for any trail condition.
- A SRAM X01 Eagle 12-speed rear derailleur provides the latest in world-class shifting.

CAMBER 29 CARBON				
SIZE	S	M	L	XL
Stack (mm)	609	609	627	655
Reach (mm)	399	427	445	471
Head-Tube Length (mm)	95	95	115	145
Head-Tube Angle (deg)	68.5	68.5	68.5	68.5
B-B Height (mm)	330	330	330	330
B-B Drop (mm)	42	42	42	42
Trail (mm)	97	97	97	97
Fork Length (full) (mm)	531	531	531	531
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	673	701	726	763
Chain-Stay Length (mm)	437	437	437	437
Wheelbase (mm)	1107	1135	1160	1197
Top-Tube Length (horizontal) (mm)	562	590	613	647
Bike Stand-Over Height (mm)	732	735	752	766
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	75	75	75	75
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	60	60	75	90
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 11m, full carbon chassis and rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, Concentric Pivot link, 12x142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 120mm of travel
REAR SHOCK	FOX FLOAT Factory, Rx Trail Tune, AUTOSAG, DPS damper, Kashima coating, rebound and 3-position compression and Open adjust, 205x53mm
FORK	FOX 34 Performance Elite 29, Kashima coating, 3-position adjust, compression and rebound adjust, 51mm offset, 15x100mm thru-axle, 120mm travel
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 25mm rise, 750mm width, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Shimano XT M8000, hydraulic disc, post mount, metallic pads, 180/200mm rotors
REAR BRAKE	Shimano XT M8000, hydraulic disc, post mount, metallic pads, 160/180mm rotors
REAR DERAILLEUR	SRAM X01 Eagle, 12-speed
SHIFT LEVERS	SRAM X01 Eagle, 12-speed, trigger
CASSETTE	SRAM XG-1295, 12-speed, 10-50t
CHAIN	SRAM X01 Eagle, silver, 12-speed w/PowerLink
CRANKSET	Custom SRAM XX1 Eagle, alloy, 30mm spindle, 49mm chainline
CHAINRINGS	SRAM X-Sync, direct mount, 30T
BOTTOM BRACKET	SRAM PF30, OS press-in bearings
RIMS	Roval Traverse 29, hookless alloy, 29mm inner width, 24/28h
FRONT HUB	Roval Traverse, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
REAR HUB	Roval Traverse, DT Swiss internals, sealed cartridge bearings, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
SPOKES	DT Swiss Revolution
FRONT TIRE	Purgatory, Control casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control, Control casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Expert, hollow titanium rails, 143mm
SEATPOST	Command Post IRcc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
93217-1002	CAMBER FSR PRO CARBON 29	WHTTNT/GLDORG	S
93217-1003			M
93217-1004			L
93217-1005			XL

CAMBER PRO CARBON 650B



WHTTNT/GLDORG

Playful handling and loads of climbing prowess—these aren't the hallmarks of just any trail bike, they're the hallmarks of the Camber Pro Carbon 650b. It blends all of the trail bike characteristics that you want with the XC climbing ability that you need.

- A FACT 9m carbon fiber Trail Chassis w/ Camber FSR rear end is stiff, responsive, and remarkably efficient, making the Camber well suited to climbing and descending over technical terrain. You'll also find internal cable routing for clean lines and minimal maintenance, plus an integrated SWAT™ Door at the down tube for zero-hassle storage of your trail essentials.
- FOX 34 Performance Elite 29 fork features 34mm aluminum stanchions that are equal parts strong and stiff, 130mm of plush, trail-taming travel, and three-position lever adjust that lets you customize the suspension on-the-fly for any trail condition.
- A SRAM X01 Eagle 12-speed rear derailleur provides the latest in world-class shifting.

CAMBER 650 CARBON				
SIZE	S	M	L	XL
Stack (mm)	580	590	599	608
Reach (mm)	399	425	454	475
Head-Tube Length (mm)	95	105	115	125
Head-Tube Angle (deg)	68	68	68	68
B-B Height (650x2.3) (mm)	329	329	329	329
B-B Height (650x2.6) (mm)	334	334	334	334
B-B Drop (mm)	23	23	23	23
Trail (mm)	97	97	97	97
Fork Length (full) (mm)	522	522	522	522
Fork Rake/Offset (mm)	42	42	42	42
Front-Center (mm)	670	700	732	757
Chain-Stay Length (mm)	420	420	420	420
Wheelbase (mm)	1089	1119	1151	1176
Top-Tube Length (horizontal) (mm)	554	583	614	638
Bike Stand-Over Height (mm)	725	730	743	752
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	75	75	75	75
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	(-)60	60	75	90
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 9m, carbon chassis and chainstay, M5 alloy seatstay, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, Concentric Pivot link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 130mm of travel
REAR SHOCK	FOX FLOAT Factory, Rx Trail Tune, AUTOSAG, DPS damper, Kashima coating, rebound and 3-position compression and Open adjust, 205x53mm
FORK	FOX 34 Performance Elite 27.5, Kashima coating, 3-position adjust, compression and rebound adjust, 44mm offset, 15x100mm thru-axle, 130mm travel
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 25mm rise, 750mm width, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Shimano XT M8000, hydraulic disc, post mount, metallic pads, 180/200mm rotors
REAR BRAKE	Shimano XT M8000, hydraulic disc, post mount, metallic pads, 160/180mm rotors
REAR DERAILLEUR	SRAM X01 Eagle, 12-speed
SHIFT LEVERS	SRAM X01 Eagle, 12-speed, trigger
CASSETTE	SRAM XG-1295, 12-speed, 10-50t
CHAIN	SRAM X01 Eagle, silver, 12-speed w/PowerLink
CRANKSET	Custom SRAM XX1 Eagle, alloy, 30mm spindle, 52mm chainline
BOTTOM BRACKET	SRAM PF30, OS press-in bearings
RIMS	Roval Traverse 650, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Roval Traverse, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
REAR HUB	Roval Traverse, DT Swiss internals, sealed cartridge bearings, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
SPOKES	DT Swiss Revolution
FRONT TIRE	Purgatory, Control casing, 650bx2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control, Control casing, 650bx2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Expert, hollow titanium rails, 143mm
SEATPOST	Command Post IRcc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
93217-1102	CAMBER FSR PRO CARBON 650B	WHTTNT/GLDORG	S
93217-1103			M
93217-1104			L
93217-1105			XL

CAMBER EXPERT CARBON 29



NBLBLU/NRDCRED/METWHT



CARB/CHAR

Full-blown, big suspension trail bikes are cool, but they get uncool pretty fast when it's time to ride them up the trail. With the large rolling stock found on the Camber Expert Carbon 29, however, you'll be moving with maximum efficiency uphill with enough travel leftover to tear the descent.

- FACT 9m carbon Trail Chassis w/ Camber FSR M5 alloy rear end is mated with our Trail 29 Geometry to form a bike that's just as at home on the climbs as it is mowing over rough trail sections. You'll also find internal cable routing for clean lines and minimal maintenance and an integrated SWAT™ Door for zero-hassle storage of your trail essentials.
- FOX 34 Performance Elite 29 fork features 34mm aluminum stanchions that are equal parts strong and stiff, 120mm of plush, trail-taming travel, and three-position lever adjust that lets you customize the suspension on-the-fly for any trail condition.
- A SRAM X1 rear derailleur controls a wide range of gears with reliable precision.

CAMBER 29 CARBON

SIZE	S	M	L	XL
Stack (mm)	609	609	627	655
Reach (mm)	399	427	445	471
Head-Tube Length (mm)	95	95	115	145
Head-Tube Angle (deg)	68.5	68.5	68.5	68.5
B-B Height (mm)	330	330	330	330
B-B Drop (mm)	42	42	42	42
Trail (mm)	97	97	97	97
Fork Length (full) (mm)	531	531	531	531
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	673	701	726	763
Chain-Stay Length (mm)	437	437	437	437
Wheelbase (mm)	1107	1135	1160	1197
Top-Tube Length (horizontal) (mm)	562	590	613	647
Bike Stand-Over Height (mm)	732	735	752	766
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	75	75	75	75
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	60	60	75	90
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS

All specs are subject to change without notice.

FRAME	FACT 9m, carbon front chassis, M5 alloy rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, Concentric Pivot link, 12x142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 120mm of travel
REAR SHOCK	FOX FLOAT Performance, Rx Trail Tune, AUTOSAG, DPS damper, rebound and 3-position compression adjust, 205x53mm
FORK	FOX 34 Performance 29, air spring, 3-position lever adjust, tapered steerer, 15x110mm thru-axle, 44mm offset, 120mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 25mm rise, 750mm width, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Shimano Deore SLX M7000, hydraulic disc, metallic pad, 200/180mm rotor
REAR BRAKE	Shimano Deore SLX M7000, hydraulic disc, metallic pad, 180/160mm rotor
REAR DERAILLEUR	SRAM X1 Type 2.1, 11-speed
SHIFT LEVERS	SRAM GX, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 49mm chainline
CHAINRINGS	Race Face, direct mount, 28T
RIMS	Roval Traverse 29, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Roval Traverse, sealed cartridge bearings, 15mm thru-axle, 100mm spacing, 24h
REAR HUB	Roval Traverse, DT Swiss internals, sealed cartridge bearings, SRAM XD driver body, 12mm thru-axle, 142mm spacing, 28h
SPOKES	DT Swiss Revolution
FRONT TIRE	Purgatory, Control casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control, Control casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Command Post IRoc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
93217-3102	CAMBER FSR EXPERT CARBON 29	NBLBLU/NRDCRED/METWHT	S
93217-3103			M
93217-3104			L
93217-3105			XL
93217-3002	CAMBER FSR EXPERT CARBON 29	CARB/CHAR	S
93217-3003			M
93217-3004			L
93217-3005			XL

CAMBER COMP CARBON 29



MONGRN/NRDCCRED



CARB/NENBLU

Our Camber Comp Carbon 29 is a "no-sacrifices" trail bike with fast-rolling 29er wheels, rigidly efficient climbing capability, and 120mm of travel to look after you on the way down the trail. And this is all amplified by dependable build kit that includes a lauded SRAM one-by drivetrain.

- FACT 9m carbon Trail Chassis w/ Camber FSR M5 alloy rear end is mated with our Trail 29 Geometry to form a bike that's just as at home on the climbs as it is mowing over rough trail sections. You'll also find internal cable routing for clean lines and minimal maintenance and an integrated SWAT™ Door for zero-hassle storage of your trail essentials.
- A custom RockShox Revelation RL 29 fork was developed to deliver 120mm of plush, trail taming travel, while accommodating a 15x100mm thru-axle for reliable handling and durability over rough, bumpy, or loose terrain. It also features our Rx Trail Tune for the ultimate in performance and feel.
- SRAM GX 11-speed rear derailleur grants you access to a wide range of gears, while providing crisp, reliable shifting.

CAMBER 29 CARBON

SIZE	S	M	L	XL
Stack (mm)	609	609	627	655
Reach (mm)	399	427	445	471
Head-Tube Length (mm)	95	95	115	145
Head-Tube Angle (deg)	68.5	68.5	68.5	68.5
B-B Height (mm)	330	330	330	330
B-B Drop (mm)	42	42	42	42
Trail (mm)	97	97	97	97
Fork Length (full) (mm)	531	531	531	531
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	673	701	726	763
Chain-Stay Length (mm)	437	437	437	437
Wheelbase (mm)	1107	1135	1160	1197
Top-Tube Length (horizontal) (mm)	562	590	613	647
Bike Stand-Over Height (mm)	732	735	752	766
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	75	75	75	75
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	60	60	75	90
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS

All specs are subject to change without notice.

FRAME	FACT 9m, carbon front chassis, M5 alloy rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, Concentric Pivot link, 12x142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 120mm of travel
REAR SHOCK	FOX FLOAT Performance, Rx Trail Tune, AUTOSAG, DPS damper, rebound and 3-position compression adjust, 205x53mm
FORK	RockShox Revelation RL 29, Solo Air spring, lockout and rebound adjust, 15x100mm Maxle Lite thru-axle, 51mm offset, 120mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Shimano M506, hydraulic disc, resin pad, 200/180mm rotor
REAR BRAKE	Shimano M506, hydraulic disc, resin pad, 180/160mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM NX, 11-speed, trigger
CASSETTE	SRAM PG-1130, 11-speed, 11-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 49mm chainline
CHAINRINGS	RaceFace, 28T
BOTTOM BRACKET	PF30
RIMS	Roval Traverse 29, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x100mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x142mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Purgatory, Control casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control, Control casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Command Post IRoc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
93217-5502	CAMBER FSR COMP CARBON 29	MONGRN/NRDCCRED	S
93217-5503			M
93217-5504			L
93217-5505			XL
93217-5402	CAMBER FSR COMP CARBON 29	CARB/NENBLU	S
93217-5403			M
93217-5404			L
93217-5405			XL

CAMBER COMP CARBON 650B



MONGRN/NRDCCRED



CARB/NENBLU

A "no-sacrifices" trail bike, the Camber Comp Carbon 650b's lively handling and 130mm of travel make it ready for descents, while its FSR Concentric Linkage and stiff rear end make climbing a breeze. And this is all amplified with a dependable build kit and a lauded SRAM one-by drivetrain.

- FACT 9m carbon Trail Chassis w/ Camber FSR M5 alloy rear end is mated with our Trail 650b Geometry to form a bike that's just as at home on the climbs as it is mowing over rough trail sections. You'll also find internal cable routing for clean lines and minimal maintenance and an integrated SWAT™ Door for zero-hassle storage of your trail essentials.
- A custom RockShox Revelation RL 29 fork was developed to deliver 130mm of plush, trail taming travel, while accommodating a 15x110mm thru-axle for reliable handling and durability over rough, bumpy, or loose terrain. It also features our Rx Trail Tune for the ultimate in performance and feel.
- SRAM GX 11-speed rear derailleur grants you access to a wide range of gears, while providing crisp, reliable shifting.

CAMBER 650 CARBON

SIZE	S	M	L	XL
Stack (mm)	580	590	599	608
Reach (mm)	399	425	454	475
Head-Tube Length (mm)	95	105	115	125
Head-Tube Angle (deg)	68	68	68	68
B-B Height (650x2.3) (mm)	329	329	329	329
B-B Height (650x2.6) (mm)	334	334	334	334
B-B Drop (mm)	23	23	23	23
Trail (mm)	97	97	97	97
Fork Length (full) (mm)	522	522	522	522
Fork Rake/Offset (mm)	42	42	42	42
Front-Center (mm)	670	700	732	757
Chain-Stay Length (mm)	420	420	420	420
Wheelbase (mm)	1089	1119	1151	1176
Top-Tube Length (horizontal) (mm)	554	583	614	638
Bike Stand-Over Height (mm)	725	730	743	752
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	75	75	75	75
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	60	60	75	90
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS

All specs are subject to change without notice.

FRAME	FACT 9m, carbon front chassis, M5 alloy rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, Concentric Pivot link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 130mm of travel
REAR SHOCK	FOX FLOAT Performance, Rx Trail Tune, AUTOSAG, DPS damper, rebound and 3-position compression adjust, 205x53mm
FORK	RockShox Revelation RL 27.5, Solo Air spring, lockout and rebound adjust, 15x110mm Maxle Lite thru-axle, 46mm offset, 130mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Shimano M506, hydraulic disc, resin pad, 200/180mm rotor
REAR BRAKE	Shimano M506, hydraulic disc, resin pad, 180/160mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM NX, 11-speed, trigger
CASSETTE	SRAM PG-1130, 11-speed, 11-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 52mm chainline
CHAINRINGS	Race Face, 30T
BOTTOM BRACKET	PF30
RIMS	Roval Traverse 650b, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x110mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Purgatory, Control casing, 650bx2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control, Control casing, 650bx2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Command Post IRoc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
93217-5902	CAMBER FSR COMP CARBON 650B	MONGRN/NRDCCRED	S
93217-5903			M
93217-5904			L
93217-5905			XL
93217-5802	CAMBER FSR COMP CARBON 650B	CARB/NENBLU	S
93217-5803			M
93217-5804			L
93217-5805			XL

CAMBER COMP 29



FLORED/HYP/MONGRN



GRPH/BLK

Think of the Camber Comp 29 as a multi-tool, packed with what you'll need in any situation. At the top of the trail, it's fast handling and fun. And on the way back up, it climbs without wasteful suspension sag. Plus, it's built with rugged, hardwearing SRAM components and powerful Shimano brakes.

- An M5 alloy Trail Chassis w/ Camber FSR rear end has been paired with our Trail 29 Geometry to create a bike that's fast, durable, and just at home on the climbs as it is mowing over rock gardens. It also features the shortest, most nimble rear end possible, and internal cable routing to make clean lines and reliable shifting through any condition.
- A custom RockShox Revelation RL 29 fork was developed to deliver 120mm of plush, trail taming travel, while accommodating a 15x100mm thru-axle for reliable handling and durability over rough, bumpy, or loose terrain. It also features our Rx Trail Tune for the ultimate in performance and feel.
- SRAM GX 11-speed rear derailleur grants you access to a wide range of gears, while providing crisp, reliable shifting.

CAMBER 29 ALLOY					
SIZE	S	M	L	XL	XXL
Stack (mm)	609	609	627	655	678
Reach (mm)	399	427	445	471	487
Head-Tube Length (mm)	95	95	115	145	170
Head-Tube Angle (deg)	68.5	68.5	68.5	68.5	68.5
B-B Height (mm)	330	330	330	330	330
B-B Drop (mm)	42	42	42	42	42
Trail (mm)	97	97	97	97	97
Fork Length (full) (mm)	531	531	531	531	531
Fork Rake/Offset (mm)	46	46	46	46	46
Front-Center (mm)	673	701	726	763	788
Chain-Stay Length (mm)	437	437	437	437	437
Wheelbase (mm)	1107	1135	1160	1197	1222
Top-Tube Length (horizontal) (mm)	562	590	613	647	669
Bike Stand-Over Height (mm)	734	739	752	764	778
Seat-Tube Length (mm)	396	430	468	523	523
Seat-Tube Angle (deg)	75	75	75	75	75
Handlebar Width (mm)	750	750	750	750	750
Stem Length (mm)	60	60	75	90	90
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	350	400	400	400	400
Crank Length (mm)	170	175	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	M5 alloy, Trail Geometry, PF30 BB, internal cable routing, 12x142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 120mm of travel
REAR SHOCK	FOX FLOAT Performance, Rx Trail Tune, AUTOSAG, DPS damper, rebound and 3-position compression adjust, 205x53mm
FORK	RockShox Revelation RL 29, Solo Air spring, lockout and rebound adjust, 15x100mm Maxle Lite thru-axle, 51mm offset, 120mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Shimano M506, hydraulic disc, resin pad, 200/180mm rotor
REAR BRAKE	Shimano M506, hydraulic disc, resin pad, 180/160mm rotor
FRONT DERAILLEUR	SRAM GX, mid direct-mount, 2x11
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM NX, 11-speed, trigger
CASSETTE	SRAM PG-1130, 11-speed, 11-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 49mm chainline
CHAINRINGS	Race Face, 28T
BOTTOM BRACKET	PF30
RIMS	Roval Traverse 29, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x100mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x142mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Purgatory, Control casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control, Control casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized, alloy, single bolt, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
93217-5002	CAMBER FSR COMP 29 FLORED/HYP/MONGRN		S
93217-5003			M
93217-5004			L
93217-5005			XL
93217-5006			XXL
93217-5102	CAMBER FSR COMP 29 GRPH/BLK		S
93217-5103			M
93217-5104			L
93217-5105			XL
93217-5106			XXL

CAMBER COMP 650B



FLORED/HYP/MONGRN



GRPH/BLK

Think of the Camber Comp 650b like a multi-tool, but with the added fun and agility of 650b wheels. At the top of the trail, it's lively and fast. And on the way back up, it climbs without any wasteful suspension sag. Plus, it's built with rugged, hardwearing SRAM components and Shimano brakes.

- An M5 alloy Trail Chassis w/ Camber FSR rear end has been paired with our Trail 650b Geometry to create a bike that's fast, durable, and just at home on the climbs as it is mowing over rock gardens. It also features the shortest, most nimble rear end possible, and internal cable routing to make clean lines and reliable shifting through any condition.
- A custom RockShox Revelation RL 650b fork was developed to deliver 130mm of plush, trail taming travel, while accommodating a 15x110mm thru-axle for reliable handling and durability over rough, bumpy, or loose terrain. It also features our Rx Trail Tune for the ultimate in performance and feel.
- SRAM GX 11-speed rear derailleur grants you access to a wide range of gears, while providing crisp, reliable shifting.

CAMBER 650 ALLOY

SIZE	S	M	L	XL
Stack (mm)	580	590	599	608
Reach (mm)	399	425	454	475
Head-Tube Length (mm)	95	105	115	125
Head-Tube Angle (deg)	68	68	68	68
B-B Height (650x2.3) (mm)	329	329	329	329
B-B Height (650x2.6) (mm)	334	334	334	334
B-B Drop (mm)	23	23	23	23
Trail (mm)	97	97	97	97
Fork Length (full) (mm)	522	522	522	522
Fork Rake/Offset (mm)	42	42	42	42
Front-Center (mm)	670	700	732	757
Chain-Stay Length (mm)	420	420	420	420
Wheelbase (mm)	1089	1119	1151	1176
Top-Tube Length (horizontal) (mm)	554	583	614	638
Bike Stand-Over Height (mm)	724	728	743	767
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	75	75	75	75
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	60	60	75	90
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	350	400	400	400
Crank Length (mm)	170	175	175	175

SPECS

All specs are subject to change without notice.

FRAME	M5 alloy, Trail Geometry, PF30 BB, internal cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 130mm of travel
REAR SHOCK	FOX FLOAT Performance, Rx Trail Tune, AUTOSAG, DPS damper, rebound and 3-position compression adjust, 205x53mm
FORK	RockShox Revelation RL 27.5, Solo Air spring, lockout and rebound adjust, 15x110mm Maxle Lite thru-axle, 46mm offset, 130mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Shimano M506, hydraulic disc, resin pad, 200/180mm rotor
REAR BRAKE	Shimano M506, hydraulic disc, resin pad, 180/160mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM NX, 11-speed, trigger
CASSETTE	SRAM PG-1130, 11-speed, 11-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 52mm chainline
CHAINRINGS	Race Face, 30T
BOTTOM BRACKET	PF30
RIMS	Roval Traverse 650b, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x110mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Purgatory, Control casing, 650bx2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control, Control casing, 650bx2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized, alloy, single bolt, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
93217-5202	CAMBER FSR COMP 650B	FLORED/HYP/MONGRN	S
93217-5203			M
93217-5204			L
93217-5205			XL
93217-5302	CAMBER FSR COMP 650B	GRPH/BLK	S
93217-5303			M
93217-5304			L
93217-5305			XL

CAMBER 29



HYP/BLK



CLGRY/FLKSIL

The Camber 29 is just begging to become someone's first trail tool. It's versatile, durable, and ready to be thrown up and down the trails over and over again. Fast handling is matched by its climbing efficiency, while the hardwearing and reliable components package won't let you down, either.

- An M5 alloy Trail Chassis w/ Camber FSR rear end has been paired with our Trail 29 Geometry to create a bike that's fast, durable, and just at home on the climbs as it is mowing over rock gardens. It also features the shortest, most nimble rear end possible, and internal cable routing to make clean lines and reliable shifting through any condition.
- The RockShox Sector Silver RL 29 features 120mm of plush, predictable travel, plus stiff 32mm stanchions and a 15x100mm Maxle Lite thru-axle.
- A Shimano Deore rear derailleur will win your heart with reliable shift after reliable shift. It's built with durability in mind, so it's tougher than your average rear mech.

CAMBER 29 ALLOY					
SIZE	S	M	L	XL	XXL
Stack (mm)	609	609	627	655	678
Reach (mm)	399	427	445	471	487
Head-Tube Length (mm)	95	95	115	145	170
Head-Tube Angle (deg)	68.5	68.5	68.5	68.5	68.5
B-B Height (mm)	330	330	330	330	330
B-B Drop (mm)	42	42	42	42	42
Trail (mm)	97	97	97	97	97
Fork Length (full) (mm)	531	531	531	531	531
Fork Rake/Offset (mm)	46	46	46	46	46
Front-Center (mm)	673	701	726	763	788
Chain-Stay Length (mm)	437	437	437	437	437
Wheelbase (mm)	1107	1135	1160	1197	1222
Top-Tube Length (horizontal) (mm)	562	590	613	647	669
Bike Stand-Over Height (mm)	734	739	752	764	778
Seat-Tube Length (mm)	396	430	468	523	523
Seat-Tube Angle (deg)	75	75	75	75	75
Handlebar Width (mm)	750	750	750	750	750
Stem Length (mm)	60	60	70	90	100
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	350	400	400	400	400
Crank Length (mm)	170	175	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	M5 alloy, Trail Geometry, threaded BB, internal cable routing, 12x142mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 120mm of travel
REAR SHOCK	Custom X-Fusion 02 Pro RL, air sleeve, rebound adjust, lockout, 205x53mm
FORK	RockShox Sector Silver RL 29, Solo Air, lockout and rebound adjust, 15x100mm Maxle Lite thru-axle, 51mm offset, 120mm travel
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width
GRIPS	Specialized Sip Grip, light lock-on, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Tektro Gemini Comp, hydraulic disc, resin pad, 180/200mm rotor
REAR BRAKE	Tektro Gemini Comp, hydraulic disc, resin pad, 180/160mm rotor
FRONT DERAILLEUR	SRAM GX, bottom pull
REAR DERAILLEUR	Shimano Deore, Shadow design, SGS cage, 9-speed
SHIFT LEVERS	Shimano Alivio, 9-speed
CASSETTE	SRAM PG-920, 9-speed, 11-34t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	SRAM 2x, alloy, 10-speed
BOTTOM BRACKET	SRAM GXP XR, 73mm
RIMS	Specialized 29, alloy, 24mm inner width, 32h
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x100mm thru-axle, 32h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x142mm thru-axle, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Purgatory, Control casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control, Control casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Sport, steel rails, 143mm
SEATPOST	Alloy, 2-bolt clamp, 12.5mm offset, 30.9mm, anti-corrosion hardware

PART NO.	DESCRIPTION	COLOR	SIZE
93217-7202	CAMBER FSR 29	HYP/BLK	S
93217-7203			M
93217-7204			L
93217-7205			XL
93217-7206			XXL
93217-7102	CAMBER FSR 29	CLGRY/FLKSIL	S
93217-7103			M
93217-7104			L
93217-7105			XL
93217-7106			XXL

CAMBER 650B



HYP/BLK



CLGRY/FLKSIL

The Camber 650b is just begging to become someone's first trail tool, especially if they want the rapid and playful handling of 650b wheels. The handling is matched by its natural climbing efficiency, while the hardwearing and reliable components package refuses to let you down.

- An M5 alloy Trail Chassis w/ Camber FSR rear end has been paired with our Trail 650b Geometry to create a bike that's fast, durable, and just at home on the climbs as it is mowing over rock gardens. It also features the shortest, most nimble rear end possible, and internal cable routing to make clean lines and reliable shifting through any condition.
- The RockShox Recon Silver RL 650b features 130mm of plush, predictable travel, plus stiff 32mm stanchions and a 15x100mm Maxle Lite thru-axle.
- A Shimano Deore rear derailleur will win your heart with reliable shift after reliable shift. It's built with durability in mind, so it's tougher than your average rear mech.

CAMBER 650 ALLOY

SIZE	S	M	L	XL
Stack (mm)	580	590	599	608
Reach (mm)	399	425	454	475
Head-Tube Length (mm)	95	105	115	125
Head-Tube Angle (deg)	68	68	68	68
B-B Height (650x2.3) (mm)	329	329	329	329
B-B Height (650x2.6) (mm)	334	334	334	334
B-B Drop (mm)	23	23	23	23
Trail (mm)	97	97	97	97
Fork Length (full) (mm)	522	522	522	522
Fork Rake/Offset (mm)	42	42	42	42
Front-Center (mm)	670	700	732	757
Chain-Stay Length (mm)	420	420	420	420
Wheelbase (mm)	1089	1119	1151	1176
Top-Tube Length (horizontal) (mm)	554	583	614	638
Bike Stand-Over Height (mm)	724	728	743	767
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	75	75	75	75
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	60	60	70	90
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	350	400	400	400
Crank Length (mm)	170	175	175	175

SPECS

All specs are subject to change without notice.

FRAME	M5 alloy, Trail Geometry, threaded BB, internal cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 130mm of travel
REAR SHOCK	Custom X-Fusion 02 Pro RL, air sleeve, rebound adjust, lockout, 205x53mm
FORK	RockShox Sector Silver RL 27.5, Solo Air, lockout and rebound adjust, 15x110mm Maxle Lite thru-axle, 46mm offset, 130mm travel
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width
GRIPS	Specialized Sip Grip, light lock-on, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Tektro Gemini Comp, hydraulic disc, resin pad, 180/200mm rotor
REAR BRAKE	Tektro Gemini Comp, hydraulic disc, resin pad, 180/160mm rotor
FRONT DERAILLEUR	SRAM GX, bottom pull
REAR DERAILLEUR	SRAM GX, Type 2.1, long cage, 10-speed
SHIFT LEVERS	SRAM GX, 10-speed, trigger
CASSETTE	Sunrace, 10-speed, 11-42t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	SRAM NX, alloy, 24mm spindle, 52mm chainline, direct mount chainring
BOTTOM BRACKET	Truvativ Powerspline, 73x113mm
RIMS	Specialized 650b, alloy, 27mm inner width, 32h
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x110mm thru-axle, 32h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Purgatory, Control casing, 650bx2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control, Control casing, 650bx2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Sport, steel rails, 143mm
SEATPOST	Alloy, 2-bolt clamp, 12.5mm offset, 30.9mm, anti-corrosion hardware

PART NO.	DESCRIPTION	COLOR	SIZE
93217-7402	CAMBER FSR 650B	HYP/BLK	S
93217-7403			M
93217-7404			L
93217-7405			XL
93217-7302	CAMBER FSR 650B	CLGRY/FLKSIL	S
93217-7303			M
93217-7304			L
93217-7305			XL

S-WORKS STUMPJUMPER FSR 29



SILTNT/RKTRED

When only the best will do, you need the ultimate trail bike. You need the S-Works Stumpjumper FSR 29. It's the pinnacle of trail performance, featuring our top end FACT 11m carbon, SWAT™ Door storage, an aggressive geometry, our own Rx Trail shock tune, and a build spec that spares no expense.

- FACT 11m carbon fiber Trail Chassis with Stumpjumper FSR full carbon rear end blends stiffness with light weight to form the pinnacle of efficiency, while fully enclosed cable routing and an integrated SWAT™ Door create exceptional handling and zero-hassle storage.
- The Öhlins RXF 36 fork was designed to be the gold standard in frontend suspension. It operates off of a three-chamber air spring design (two positive and one negative), and it utilizes proprietary TTX damping technology. Combined, this allows both parallel and separated oil flow that controls the overall pressure levels.
- Roval Traverse SL 29 carbon wheels are the ultimate in lightweight rolling stock for the trail. They're built to take a hit, and they feature a wide rim width that boosts handling and stability over any kind of terrain.

SJ FSR 29/6FATTIE CARBON				
SIZE	S	M	L	XL
Stack (mm)	618	618	646	664
Reach (mm)	386	413	431	457
Head-Tube Length (mm)	95	95	125	145
Head-Tube Angle (deg)	67	67	67	67
B-B Height (29x2.3") (mm)	338	338	338	338
B-B Height (650x3") (mm)	331	331	331	331
B-B Height (650x2.8") (mm)	325	325	325	325
B-B Drop (mm)	33	33	33	33
Trail (mm)	96.5	96.5	96.5	96.5
Fork Length (full) (mm)	560	560	560	560
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	687	714	744	777
Chain-Stay Length (mm)	437	437	437	437
Wheelbase (mm)	1122	1149	1179	1212
Top-Tube Length (horizontal) (mm)	563	590	616	648
Bike Stand-Over Height (mm)	754	761	770	777
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	50	60	60	60
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 11m, full carbon chassis and rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 135mm of travel
REAR SHOCK	Custom Öhlins STX, Single Tube design, Rx Trail Tune, 3rd Chamber air spring technology, AUTOSAG, adjustable compression & rebound damping, 197x48mm
FORK	Öhlins RXF36, 29/27.5+, Twin-Tube design, air spring w/ adjustable 3rd chamber, adjustable high and low speed compression, adjustable rebound, 15x110mm thru-axle, 51mm offset, 150mm travel
STEM	Syntace F109, 6-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Trail, FACT carbon, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide RS carbon, hydraulic disc, organic pads, carbon lever, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide RS carbon, hydraulic disc, organic pads, carbon lever, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM XX1 Eagle, 12-speed
SHIFT LEVERS	SRAM XX1 Eagle, 12-speed, trigger
CASSETTE	SRAM XG-1295, 12-speed, 10-50t
CHAIN	SRAM XX1 Eagle, black, 12-speed w/PowerLink
CRANKSET	SRAM XX1 Eagle, carbon, 30mm spindle, 52mm chainline
BOTTOM BRACKET	SRAM PF30, OS press-in bearings
RIMS	Roval Traverse SL 29, hookless carbon, 30mm inner width, 24/28h, tubeless ready
FRONT HUB	Roval Traverse, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
REAR HUB	Roval Traverse SL, DT Swiss Star Ratchet, 54t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
SPOKES	DT Swiss Revolution
FRONT TIRE	Butcher, GRID casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Slaughter, GRID casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Expert, hollow titanium rails, 143mm
SEATPOST	Command Post IRoc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
97517-0002	SW SJ FSR CARBON 29	SILTNT/RKTRED	S
97517-0003			M
97517-0004			L
97517-0005			XL

S-WORKS STUMPJUMPER FSR 6FATTIE



SILTNT/RKTRED

The S-Works Stumpjumper FSR 6Fattie is a revolution in trail bikes. It starts with our immaculate FACT 11m carbon construction and finishes with the crazy traction of our 6Fattie wheel system. And in between, you'll find a custom shock tune and a slack geometry that devours trail.

- FACT 11m carbon fiber Trail Chassis with Stumpjumper FSR full carbon rear end blends stiffness with light weight to form the pinnacle of efficiency, while fully enclosed cable routing and an integrated SWAT™ Door create exceptional handling and zero-hassle storage.
- The Öhlins RXF 36 fork was designed to be the gold standard in frontend suspension. It operates off of a three-chamber air spring design (two positive and one negative), and it utilizes proprietary TTX damping technology. Combined, this allows both parallel and separated oil flow that controls the overall pressure levels.
- Roval Traverse SL 6Fattie carbon wheels work in tandem with the ultra-wide tires to give you loads of extra traction, floatation, and control.

SJ FSR 29/6FATTIE CARBON				
SIZE	S	M	L	XL
Stack (mm)	618	618	646	664
Reach (mm)	386	413	431	457
Head-Tube Length (mm)	95	95	125	145
Head-Tube Angle (deg)	67	67	67	67
B-B Height (29x2.3") (mm)	338	338	338	338
B-B Height (650x3") (mm)	331	331	331	331
B-B Height (650x2.8") (mm)	325	325	325	325
B-B Drop (mm)	33	33	33	33
Trail (mm)	96.5	96.5	96.5	96.5
Fork Length (full) (mm)	560	560	560	560
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	687	714	744	777
Chain-Stay Length (mm)	437	437	437	437
Wheelbase (mm)	1122	1149	1179	1212
Top-Tube Length (horizontal) (mm)	563	590	616	648
Bike Stand-Over Height (mm)	754	761	770	777
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	50	60	60	60
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 11m, full carbon chassis and rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 135mm of travel
REAR SHOCK	Custom Öhlins STX, Single Tube design, Rx Trail Tune, 3rd Chamber air spring technology, AUTOSAG, adjustable compression & rebound damping, 197x48mm
FORK	Öhlins RXF36, 29/27.5+, Twin-Tube design, air spring w/ adjustable 3rd chamber, adjustable high and low speed compression, adjustable rebound, 15x110mm thru-axle, 51mm offset, 150mm travel
STEM	Syntace F109, 6-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Trail, FACT carbon, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide RS carbon, hydraulic disc, organic pads, carbon lever, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide RS carbon, hydraulic disc, organic pads, carbon lever, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM XX1 Eagle, 12-speed
SHIFT LEVERS	SRAM XX1 Eagle, 12-speed, trigger
CASSETTE	SRAM XG-1295, 12-speed, 10-50t
CHAIN	SRAM XX1 Eagle, black, 12-speed w/PowerLink
CRANKSET	SRAM XX1 Eagle, carbon, 30mm spindle, 52mm chainline
BOTTOM BRACKET	SRAM PF30, OS press-in bearings
RIMS	Roval Traverse SL 650, hookless carbon, 30mm inner width, 24/28h, tubeless ready
FRONT HUB	Roval Traverse, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
REAR HUB	Roval Traverse SL, DT Swiss Star Ratchet, 54t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
SPOKES	DT Swiss Revolution
FRONT TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Expert, hollow titanium rails, 143mm
SEATPOST	Command Post I/Rc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
97517-0202	SW SJ FSR CARBON 6FATTIE	SILTNT/RKTRED	S
97517-0203			M
97517-0204			L
97517-0205			XL

S-WORKS STUMPJUMPER FSR 650B



SILTNT/RKTRED

For many, the ultimate trail bike needs to have the agility of a 650b. We agree, so we made the S-Works Stumpjumper FSR 650b. It's the pinnacle of trail performance, featuring our FACT 11m carbon, SWAT™ Door storage, a nimble geometry, our Rx Trail shock tune, and a build spec that spares no expense.

- FACT 11m carbon fiber Trail Chassis with Stumpjumper FSR full carbon rear end blends stiffness with light weight to form the pinnacle of efficiency, while fully enclosed cable routing and an integrated SWAT™ Door create exceptional handling and zero-hassle storage.
- RockShox Pike RCT3 650b fork features a 15mm Maxle Stealth thru-axle and 150mm of plush travel.
- Roval Traverse SL 650b carbon wheels work in tandem with the ultra-wide tires to give you loads of extra traction, floatation, and control.

SJ FSR 650 CARBON				
SIZE	S	M	L	XL
Stack (mm)	590	599	608	617
Reach (mm)	388	414	442	464
Head-Tube Length (mm)	95	105	115	125
Head-Tube Angle (deg)	67	67	67	67
B-B Height (650x2.3") (mm)	335	335	335	335
B-B Height (650x2.6") (mm)	340	340	340	340
B-B Drop (mm)	18	18	18	18
Trail (mm)	104	104	104	104
Fork Length (full) (mm)	542	542	542	542
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	677	706	738	764
Chain-Stay Length (mm)	420	420	420	420
Wheelbase (mm)	1096	1126	1158	1184
Top-Tube Length (horizontal) (mm)	558	587	618	646
Bike Stand-Over Height (mm)	742	748	762	764
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	50	60	60	60
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 11m, full carbon chassis and rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 150mm of travel
REAR SHOCK	Custom Öhlins STX, Single Tube design, Rx Trail Tune, 3rd Chamber air spring technology, AUTOSAG, adjustable compression & rebound damping, 197x48mm
FORK	RockShox Pike RCT3 27.5+, Solo Air, compression and rebound and threshold adjust, tapered steerer, 15x110mm Maxle Stealth thru-axle, 46mm offset, 150mm travel
STEM	Syntace F109, 6-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Trail, FACT carbon, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide RS carbon, hydraulic disc, organic pads, carbon lever, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide RS carbon, hydraulic disc, organic pads, carbon lever, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM XX1 Eagle, 12-speed
SHIFT LEVERS	SRAM XX1 Eagle, 12-speed, trigger
CASSETTE	SRAM XG-1295, 12-speed, 10-50t
CHAIN	SRAM XX1 Eagle, black, 12-speed w/PowerLink
CRANKSET	SRAM XX1 Eagle, carbon, 30mm spindle, 52mm chainline
BOTTOM BRACKET	SRAM PF30, OS press-in bearings
RIMS	Roval Traverse SL 650, hookless carbon, 30mm inner width, 24/28h, tubeless ready
FRONT HUB	Roval Traverse, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
REAR HUB	Roval Traverse SL, DT Swiss Star Ratchet, 54t engagement, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
SPOKES	DT Swiss Revolution
FRONT TIRE	Butcher, GRID casing, 650x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Slaughter, GRID casing, 650x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Expert, hollow titanium rails, 143mm
SEATPOST	Command Post IRoc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
97517-0102	SW SJ FSR CARBON 650B	SILTNT/RKTRED	S
97517-0103			M
97517-0104			L
97517-0105			XL

STUMPJUMPER FSR PRO CARBON 29



CARB/CARB

Why should S-Works have all the fun? With our Stumpjumper FSR Pro Carbon 29, you get most of the same performance features, like a custom Öhlins rear shock, so you can climb and descend with the best of them at break-neck speed.

- FACT 11m carbon fiber Trail Chassis with Stumpjumper FSR full carbon rear end blends stiffness with light weight to form the pinnacle of efficiency, while fully enclosed cable routing and an integrated SWAT™ Door create exceptional handling and zero-hassle storage.
- RockShox Pike RC fork features a 15mm Maxle Stealth thru-axle and 150mm of plush travel.
- The custom Öhlins STX single tube air shock at the rear features high- and low-speed compression, as well as low-speed rebound. You'll also find an extra-volume reservoir that allows for more oil, which results in more control and an ultra-plush ride quality.

SJ FSR 29/6FATTIE CARBON				
SIZE	S	M	L	XL
Stack (mm)	618	618	646	664
Reach (mm)	386	413	431	457
Head-Tube Length (mm)	95	95	125	145
Head-Tube Angle (deg)	67	67	67	67
B-B Height (29x2.3") (mm)	338	338	338	338
B-B Height (650x3 ") (mm)	331	331	331	331
B-B Height (650x2.8") (mm)	325	325	325	325
B-B Drop (mm)	33	33	33	33
Trail (mm)	96.5	96.5	96.5	96.5
Fork Length (full) (mm)	560	560	560	560
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	687	714	744	777
Chain-Stay Length (mm)	437	437	437	437
Wheelbase (mm)	1122	1149	1179	1212
Top-Tube Length (horizontal) (mm)	563	590	616	648
Bike Stand-Over Height (mm)	754	761	770	777
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 11m, full carbon chassis and rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 135mm of travel
REAR SHOCK	Custom Öhlins STX, Single Tube design, Rx Trail Tune, 3rd Chamber air spring technology, AUTOSAG, adjustable compression & rebound damping, 197x48mm
FORK	RockShox Pike RC 29/27.5+, Solo Air, compression and rebound adjust, tapered steerer, 15x110mm Maxle Stealth thru-axle, 51mm offset, 150mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 25mm rise, 750mm width, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide RS carbon, hydraulic disc, organic pads, carbon lever, Guide S4 4-piston caliper, 200mm rotor
REAR BRAKE	SRAM Guide RS, hydraulic disc, organic pads, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM X01 Eagle, 12-speed
SHIFT LEVERS	SRAM X01 Eagle, 12-speed, trigger
CASSETTE	SRAM XG-1295, 12-speed, 10-50t
CHAIN	SRAM X01 Eagle, silver, 12-speed w/PowerLink
CRANKSET	Custom SRAM X1 Eagle, alloy, 30mm spindle, 52mm chainline
BOTTOM BRACKET	SRAM PF30, OS press-in bearings
RIMS	Roval Traverse 29, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Roval Traverse, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
REAR HUB	Roval Traverse, DT Swiss internals, sealed cartridge bearings, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
SPOKES	DT Swiss Revolution
FRONT TIRE	Butcher, GRID casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Slaughter, GRID casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Expert, hollow titanium rails, 143mm
SEATPOST	Command Post IRoc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
93317-1102	SJ FSR PRO CARBON 29	CARB/CARB	S
93317-1103			M
93317-1104			L
93317-1105			XL

STUMPJUMPER FSR PRO CARBON 6FATTIE



CARB/CARB

Why should S-Works have all the fun? With our Stumpjumper FSR Pro Carbon 6Fattie, you get most of the same performance features, like a custom Öhlins rear shock, plus loads of extra traction, floatation, and control.

- FACT 11m carbon fiber Trail Chassis with Stumpjumper FSR full carbon rear end blends stiffness with light weight to form the pinnacle of efficiency, while fully enclosed cable routing and an integrated SWAT™ Door create exceptional handling and zero-hassle storage.
- RockShox Pike RC fork features a 15mm Maxle Stealth thru-axle and 150mm of plush travel.
- The custom Öhlins STX single tube air shock at the rear features high- and low-speed compression, as well as low-speed rebound. You'll also find an extra-volume reservoir that allows for more oil, which results in more control and an ultra-plush ride quality.

SJ FSR 29/6FATTIE CARBON				
SIZE	S	M	L	XL
Stack (mm)	618	618	646	664
Reach (mm)	386	413	431	457
Head-Tube Length (mm)	95	95	125	145
Head-Tube Angle (deg)	67	67	67	67
B-B Height (29x2.3") (mm)	338	338	338	338
B-B Height (650x3") (mm)	331	331	331	331
B-B Height (650x2.8") (mm)	325	325	325	325
B-B Drop (mm)	33	33	33	33
Trail (mm)	96.5	96.5	96.5	96.5
Fork Length (full) (mm)	560	560	560	560
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	687	714	744	777
Chain-Stay Length (mm)	437	437	437	437
Wheelbase (mm)	1122	1149	1179	1212
Top-Tube Length (horizontal) (mm)	563	590	616	648
Bike Stand-Over Height (mm)	754	761	770	777
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 11m, full carbon chassis and rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 135mm of travel
REAR SHOCK	Custom Öhlins STX, Single Tube design, Rx Trail Tune, 3rd Chamber air spring technology, AUTOSAG, adjustable compression & rebound damping, 197x48mm
FORK	RockShox Pike RC 29/27.5+, Solo Air, compression and rebound adjust, tapered steerer, 15x110mm Maxle Stealth thru-axle, 51mm offset, 150mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 25mm rise, 750mm width, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide RS carbon, hydraulic disc, organic pads, carbon lever, Guide S4 4-piston caliper, 200mm rotor
REAR BRAKE	SRAM Guide RS, hydraulic disc, organic pads, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM X01 Eagle, 12-speed
SHIFT LEVERS	SRAM X01 Eagle, 12-speed, trigger
CASSETTE	SRAM XG-1295, 12-speed, 10-50t
CHAIN	SRAM X01 Eagle, silver, 12-speed w/PowerLink
CRANKSET	Custom SRAM XX1 Eagle, alloy, 30mm spindle, 52mm chainline
BOTTOM BRACKET	SRAM PF30, OS press-in bearings
RIMS	Roval Traverse 650, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Roval Traverse, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
REAR HUB	Roval Traverse, DT Swiss internals, sealed cartridge bearings, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
SPOKES	DT Swiss Revolution
FRONT TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Expert, hollow titanium rails, 143mm
SEATPOST	Command Post I/Rc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
93317-1302	SJ FSR PRO CARBON 6FATTIE	CARB/CARB	S
93317-1303			M
93317-1304			L
93317-1305			XL

STUMPJUMPER FSR EXPERT CARBON 29



RKTRED/BLK



WHT/CARB/HYP

If you know the history of the Stumpy, you know that it doesn't believe in compromising, and neither does the Stumpjumper FSR Expert Carbon 29. It features a workhorse one-by groupset, FACT 9m carbon fiber, all-new SWAT™ Door utility, and geometry that's second to none. Never compromise.

- FACT 9m carbon fiber Trail Chassis with Stumpjumper FSR M5 alloy rear end blends stiffness with light weight to form the pinnacle of efficiency, while fully enclosed cable routing and an integrated SWAT™ Door create exceptional handling and zero-hassle storage.
- RockShox Pike RC 29 fork features a 15mm Maxle Stealth thru-axle and 150mm of plush travel to take on big hits and bumpy terrain with supreme confidence and efficiency.
- Roval Traverse 29 2Bliss Ready wheels provide a strong, stable platform that's built to deliver heaps of responsiveness, speed, and supreme handling.

SJ FSR 29/6FATTIE CARBON				
SIZE	S	M	L	XL
Stack (mm)	618	618	646	664
Reach (mm)	386	413	431	457
Head-Tube Length (mm)	95	95	125	145
Head-Tube Angle (deg)	67	67	67	67
B-B Height (29x2.3") (mm)	338	338	338	338
B-B Height (650x3") (mm)	331	331	331	331
B-B Height (650x2.8") (mm)	325	325	325	325
B-B Drop (mm)	33	33	33	33
Trail (mm)	96.5	96.5	96.5	96.5
Fork Length (full) (mm)	560	560	560	560
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	687	714	744	777
Chain-Stay Length (mm)	437	437	437	437
Wheelbase (mm)	1122	1149	1179	1212
Top-Tube Length (horizontal) (mm)	563	590	616	648
Bike Stand-Over Height (mm)	754	761	770	777
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 9m, carbon front chassis, M5 alloy rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 135mm of travel
REAR SHOCK	RockShox Monarch RT3, Rx Trail Tune, AUTOSAG, rebound and 3-position compression adjust, 197x48mm
FORK	RockShox Pike RC 29/27.5+, Solo Air, compression and rebound adjust, tapered steerer, 15x110mm Maxle Stealth thru-axle, 51mm offset, 150mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 25mm rise, 750mm width, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM X1 Type 2.1, 11-speed
SHIFT LEVERS	SRAM GX, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 52mm chainline
RIMS	Roval Traverse 29, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Roval Traverse, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
REAR HUB	Roval Traverse, DT Swiss internals, sealed cartridge bearings, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
SPOKES	DT Swiss Revolution
FRONT TIRE	Butcher, GRID casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Slaughter, GRID casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Command Post IRcc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
93317-3002	SJ FSR EXPERT CARBON 29	RKTRED/BLK	S
93317-3003			M
93317-3004			L
93317-3005			XL
93317-3102	SJ FSR EXPERT CARBON 29	WHT/CARB/HYP	S
93317-3103			M
93317-3104			L
93317-3105			XL

STUMPJUMPER FSR EXPERT CARBON 6FATTIE



RKTRED/BLK



WHT/CARB/HYP

After one ride on the all-new Stumpjumper FSR Expert Carbon 6Fattie, you'll never be riding trail again. It's a bold statement to make, but the increase in traction, control, and floatation that our 6Fattie Wheel System provides is nothing short of revolutionary.

- FACT 9m carbon fiber Trail Chassis with Stumpjumper 6Fattie M5 alloy rear end with 148mm spacing blends stiffness with light weight to form the pinnacle of efficiency, while 135mm of travel, fully enclosed cable routing, and integrated SWAT™ Door create exceptional handling and zero-hassle storage.
- RockShox Pike RC 29 fork features a 15mm Maxle Stealth thru-axle and 150mm of plush travel to take on big hits and bumpy terrain with supreme confidence and efficiency.
- Roval Traverse 2Bliss Ready wheels provide a strong, stable platform that's built to deliver heaps of responsiveness, speed, and supreme handling.

SJ FSR 29/6FATTIE CARBON

SIZE	S	M	L	XL
Stack (mm)	618	618	646	664
Reach (mm)	386	413	431	457
Head-Tube Length (mm)	95	95	125	145
Head-Tube Angle (deg)	67	67	67	67
B-B Height (29x2.3") (mm)	338	338	338	338
B-B Height (650x3") (mm)	331	331	331	331
B-B Height (650x2.8") (mm)	325	325	325	325
B-B Drop (mm)	33	33	33	33
Trail (mm)	96.5	96.5	96.5	96.5
Fork Length (full) (mm)	560	560	560	560
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	687	714	744	777
Chain-Stay Length (mm)	437	437	437	437
Wheelbase (mm)	1122	1149	1179	1212
Top-Tube Length (horizontal) (mm)	563	590	616	648
Bike Stand-Over Height (mm)	754	761	770	777
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS

All specs are subject to change without notice.

FRAME	FACT 9m, carbon front chassis, M5 alloy rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 135mm of travel
REAR SHOCK	RockShox Monarch RT3, Rx Trail Tune, AUTOSAG, rebound and 3-position compression adjust, 197x48mm
FORK	RockShox Pike RC 29/27.5+, Solo Air, compression and rebound adjust, tapered steerer, 15x110mm Maxle Stealth thru-axle, 51mm offset, 150mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 25mm rise, 750mm width, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM X1 Type 2.1, 11-speed
SHIFT LEVERS	SRAM GX, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 52mm chainline
RIMS	Roval Traverse 650, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Roval Traverse, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
REAR HUB	Roval Traverse, DT Swiss internals, sealed cartridge bearings, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
SPOKES	DT Swiss Revolution
FRONT TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Command Post IRoc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
93317-3402	SJ FSR EXPERT CARBON 6FATTIE	RKTRED/BLK	S
93317-3403			M
93317-3404			L
93317-3405			XL
93317-3502	SJ FSR EXPERT CARBON 6FATTIE	WHT/CARB/HYP	S
93317-3503			M
93317-3504			L
93317-3505			XL

STUMPJUMPER FSR EXPERT CARBON 650B



RKTRED/BLK



WHT/CARB/HYP

If your trail riding philosophy is "go big or go home," you can't beat the agility of our Stumpjumper FSR Expert Carbon 650b. Built to be the ultimate all-rounder, it's loaded with a one-by groupset, SWAT™ Door utility, a 9m carbon construction, and a low, slack geometry that eats up the trail.

- FACT 9m carbon fiber Trail Chassis with Stumpjumper FSR M5 alloy rear end blends stiffness with light weight to form the pinnacle of efficiency, while 150mm of travel, fully enclosed cable routing, and integrated SWAT™ Door create exceptional handling and zero-hassle storage.
- RockShox Pike RC 650b fork features a 15mm Maxle Stealth thru-axle and 150mm of plush travel to take on big hits and bumpy terrain with supreme confidence and efficiency.
- Roval Traverse 2Bliss Ready wheels provide a strong, stable platform that's built to deliver heaps of responsiveness, speed, and supreme handling.

SJ FSR 650 CARBON

SIZE	S	M	L	XL
Stack (mm)	590	599	608	617
Reach (mm)	388	414	442	464
Head-Tube Length (mm)	95	105	115	125
Head-Tube Angle (deg)	67	67	67	67
B-B Height (650x2.3") (mm)	335	335	335	335
B-B Height (650x2.6") (mm)	340	340	340	340
B-B Drop (mm)	18	18	18	18
Trail (mm)	104	104	104	104
Fork Length (full) (mm)	542	542	542	542
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	677	706	738	764
Chain-Stay Length (mm)	420	420	420	420
Wheelbase (mm)	1096	1126	1158	1184
Top-Tube Length (horizontal) (mm)	558	587	618	646
Bike Stand-Over Height (mm)	742	748	762	764
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS

All specs are subject to change without notice.

FRAME	FACT 9m, carbon front chassis, M5 alloy rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 150mm of travel
REAR SHOCK	RockShox Monarch RT3, Rx Trail Tune, AUTOSAG, rebound and 3-position compression adjust, 197x48mm
FORK	RockShox Pike RC 27.5, Solo Air, compression and rebound adjust, tapered steerer, 15x110mm Maxle Stealth thru-axle, 46mm offset, 150mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 25mm rise, 750mm width, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM X1 Type 2.1, 11-speed
SHIFT LEVERS	SRAM GX, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 52mm chainline
RIMS	Roval Traverse 650, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Roval Traverse, sealed cartridge bearings, 15mm thru-axle, 110mm spacing, 24h
REAR HUB	Roval Traverse, DT Swiss internals, sealed cartridge bearings, SRAM XD driver body, 12mm thru-axle, 148mm spacing, 28h
SPOKES	DT Swiss Revolution
FRONT TIRE	Butcher, GRID casing, 650x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Slaughter, GRID casing, 650x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Command Post IRoc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
93317-3202	SJ FSR EXPERT CARBON 650B	RKTRED/BLK	S
93317-3203			M
93317-3204			L
93317-3205			XL
93317-3302	SJ FSR EXPERT CARBON 650B	WHT/CARB/HYP	S
93317-3303			M
93317-3304			L
93317-3305			XL

STUMPJUMPER FSR COMP CARBON 29



HYP/CNDYRED/BLK



CARB/NENBLU/WHT



TARBLK/LTSIL/MONGRN

Trail riding requires a bike that can do it all with ease, and nothing outperforms our new Stumpjumper FSR Comp Carbon 29. To be sure, we gave it hand-selected SRAM components, plus a FACT 9m carbon construction, a proprietary shock tune, and a slack, aggressive geometry.

- FACT 9m carbon fiber Trail Chassis with Stumpjumper FSR M5 alloy rear end blends stiffness with light weight to form the pinnacle of efficiency, while 135mm of travel, fully enclosed cable routing, and integrated SWAT™ Door create exceptional handling and zero-hassle storage.
- RockShox Yari fork features a 15x110mm Maxle Ultimate thru-axle, a Solo Air™ spring, and 140mm of plush travel to take on big hits and bumpy terrain with supreme speed and efficiency.
- Roval Traverse 2Bliss Ready wheels provide a strong, stable platform that's built to deliver heaps of responsiveness, speed, and supreme handling.

SJ FSR 29/6FATTIE CARBON				
SIZE	S	M	L	XL
Stack (mm)	618	618	646	664
Reach (mm)	386	413	431	457
Head-Tube Length (mm)	95	95	125	145
Head-Tube Angle (deg)	67	67	67	67
B-B Height (29x2.3") (mm)	338	338	338	338
B-B Height (650x3") (mm)	331	331	331	331
B-B Height (650x2.8") (mm)	325	325	325	325
B-B Drop (mm)	33	33	33	33
Trail (mm)	96.5	96.5	96.5	96.5
Fork Length (full) (mm)	560	560	560	560
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	687	714	744	777
Chain-Stay Length (mm)	437	437	437	437
Wheelbase (mm)	1122	1149	1179	1212
Top-Tube Length (horizontal) (mm)	563	590	616	648
Bike Stand-Over Height (mm)	754	761	770	777
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 9m, carbon front chassis, M5 alloy rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 135mm of travel
REAR SHOCK	RockShox Monarch RT, Rx Trail Tune, AUTOSAG, rebound and 2-position compression adjust, 197x48mm
FORK	RockShox Yari 29/27.5+, Solo Air, rebound & compression adjust, 15x110mm Maxle Ultimate thru-axle, 150mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM GX, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 52mm chainline
RIMS	Roval Traverse 29, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x110mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Butcher, GRID casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Slaughter, GRID casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Command Post IRcc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
97517-5102	SJ FSR COMP CARBON 29	HYP/CNDYRED/BLK	S
97517-5103			M
97517-5104			L
97517-5105			XL
97517-5002	SJ FSR COMP CARBON 29	CARB/NENBLU/WHT	S
97517-5003			M
97517-5004			L
97517-5005			XL
97517-5202	SJ FSR COMP CARBON 29	TARBLK/LTSIL/MONGRN	S
97517-5203			M
97517-5204			L
97517-5205			XL

STUMPJUMPER FSR COMP CARBON 6FATTIE



HYP/CNDYRED/BLK



CARB/NENBLU/WHT



TARBLK/LTSIL/MONGRN

When you merge innovative technology and pedigree, you get the future of trail bikes, aka, the Stumpjumper FSR Comp Carbon 6Fattie. It has our 6Fattie Wheel System that offers astounding traction and floatation, plus a beautiful construction, strong spec, and a geometry that's second to none.

- FACT 9m carbon fiber Trail Chassis with Stumpjumper FSR M5 alloy rear end blends stiffness with light weight to form the pinnacle of efficiency, while 135mm of travel, fully enclosed cable routing, and integrated SWAT™ Door create exceptional handling and zero-hassle storage.
- RockShox Yari fork features a 15x110mm Maxle Ultimate thru-axle, a Solo Air™ spring, and 150mm of plush travel to take on big hits and bumpy terrain with supreme speed and efficiency.
- Roval Traverse 2Bliss Ready wheels provide a strong, stable platform that's built to deliver heaps of responsiveness, speed, and supreme handling.

SJ FSR 29/6FATTIE CARBON				
SIZE	S	M	L	XL
Stack (mm)	618	618	646	664
Reach (mm)	386	413	431	457
Head-Tube Length (mm)	95	95	125	145
Head-Tube Angle (deg)	67	67	67	67
B-B Height (29x2.3") (mm)	338	338	338	338
B-B Height (650x3") (mm)	331	331	331	331
B-B Height (650x2.8") (mm)	325	325	325	325
B-B Drop (mm)	33	33	33	33
Trail (mm)	96.5	96.5	96.5	96.5
Fork Length (full) (mm)	560	560	560	560
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	687	714	744	777
Chain-Stay Length (mm)	437	437	437	437
Wheelbase (mm)	1122	1149	1179	1212
Top-Tube Length (horizontal) (mm)	563	590	616	648
Bike Stand-Over Height (mm)	754	761	770	777
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 9m, carbon front chassis, M5 alloy rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 135mm of travel
REAR SHOCK	RockShox Monarch RT, Rx Trail Tune, AUTOSAG, rebound and 2-position compression adjust, 197x48mm
FORK	RockShox Yari 29/27.5+, Solo Air, rebound & compression adjust, 15x110mm Maxle Ultimate thru-axle, 150mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM GX, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 52mm chainline
CHAINRINGS	28T, direct mount
BOTTOM BRACKET	PF30
RIMS	Roval Traverse 650b, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x110mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Command Post IRoc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
97517-5702	SJ FSR COMP CARBON 6FATTIE	HYP/CNDYRED/BLK	S
97517-5703			M
97517-5704			L
97517-5705			XL
97517-5602	SJ FSR COMP CARBON 6FATTIE	CARB/NENBLU/WHT	S
97517-5603			M
97517-5604			L
97517-5605			XL
97517-5802	SJ FSR COMP CARBON 6FATTIE	TARBLK/LTSIL/MONGRN	S
97517-5803			M
97517-5804			L
97517-5805			XL

STUMPJUMPER FSR COMP CARBON 650B



HYP/CNDYRED/BLK



CARB/NENBLU/WHT



TARBLK/LTSIL/MONGRN

When you need all of today's tech and an agile wheel size, you can't beat the Stumpjumper FSR Comp Carbon 650b. It has everything you need for trail riding, like a FACT 9m construction, a slack geometry, tuned suspension, and a durable selection of components from SRAM.

- FACT 9m carbon fiber frame construction w/ M5 alloy rear end blends stiffness with light weight to form the pinnacle of efficiency, while 150mm of travel, fully enclosed cable routing, and integrated SWAT™ Door create exceptional handling and zero-hassle storage
- RockShox Yari RC fork features a 15x110mm Maxle Ultimate thru-axle, a Solo Air™ spring, and 150mm of push travel to take on big hits and bumpy terrain with supreme speed and efficiency.
- Roval Traverse 650b wheels provide a strong, stable platform that's built to deliver heaps of responsiveness, speed, and supreme handling.

SJ FSR 650 CARBON				
SIZE	S	M	L	XL
Stack (mm)	590	599	608	617
Reach (mm)	388	414	442	464
Head-Tube Length (mm)	95	105	115	125
Head-Tube Angle (deg)	67	67	67	67
B-B Height (650x2.3") (mm)	335	335	335	335
B-B Height (650x2.6") (mm)	340	340	340	340
B-B Drop (mm)	18	18	18	18
Trail (mm)	104	104	104	104
Fork Length (full) (mm)	542	542	542	542
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	677	706	738	764
Chain-Stay Length (mm)	420	420	420	420
Wheelbase (mm)	1096	1126	1158	1184
Top-Tube Length (horizontal) (mm)	558	587	618	646
Bike Stand-Over Height (mm)	742	748	762	764
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS

All specs are subject to change without notice.

FRAME	FACT 9m, carbon front chassis, M5 alloy rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 150mm of travel
REAR SHOCK	RockShox Monarch RT, Rx Trail Tune, AUTOSAG, rebound and 2-position compression adjust, 197x48mm
FORK	RockShox Yari RC 27.5, Solo Air, rebound & compression adjust, 15x110mm Maxle Ultimate thru-axle, 150mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM GX, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 52mm chainline
RIMS	Roval Traverse 650b, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x110mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Butcher, GRID casing, 650x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Slaughter, GRID casing, 650x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Command Post IRoc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
97517-5402	SJ FSR COMP CARBON 650B	HYP/CNDYRED/BLK	S
97517-5403			M
97517-5404			L
97517-5405			XL
97517-5302	SJ FSR COMP CARBON 650B	CARB/NENBLU/WHT	S
97517-5303			M
97517-5304			L
97517-5305			XL
97517-5502	SJ FSR COMP CARBON 650B	TARBLK/LTSIL/MONGRN	S
97517-5503			M
97517-5504			L
97517-5505			XL

STUMPJUMPER FSR COMP 29



NRDCRED/BLK



PRP/MONGRN/BLK



BLK/CHAR

Don't get us wrong—carbon is awesome. But when it comes to maintaining peace of mind while you're getting rowdy, nothing compares to the confidence of our alloy Stumpjumper FSR Comp 29. It's light, rugged, and packed with all the spec and travel you need to run it wide open out on the trail.

- M5 alloy Trail Chassis with Stumpjumper FSR rear end blends durability, stiffness, and light weight, while 135mm of travel Trail Geometry provide more than capable handling.
- RockShox Revelation RL 29 fork features a 15mm Maxle Lite thru-axle and 150mm of plush travel to take on hits and bumpy terrain with more control and confidence.
- Roval Traverse 29 wheels provide a strong, stable platform that's built to deliver heaps of responsiveness, speed, and supreme handling.

SJ FSR 29/6FATTIE ALLOY					
SIZE	S	M	L	XL	XXL
Stack (mm)	617	617	645	663	686
Reach (mm)	389	417	435	461	477
Head-Tube Length (mm)	95	95	125	145	170
Head-Tube Angle (deg)	67.5	67.5	67.5	67.5	67.5
B-B Height (29x2.3") (mm)	338	338	338	338	338
B-B Height (650x3") (mm)	331	331	331	331	331
B-B Height (650x2.8") (mm)	325	325	325	325	325
B-B Drop (mm)	36	36	36	36	36
Trail (mm)	104	104	104	104	104
Fork Length (full) (mm)	551	551	551	551	551
Fork Rake/Offset (mm)	46	46	46	46	46
Front-Center (mm)	680	708	738	771	797
Chain-Stay Length (mm)	437	437	437	437	437
Wheelbase (mm)	1115	1143	1172	1206	1232
Top-Tube Length (horizontal) (mm)	551	582	611	647	674
Bike Stand-Over Height (mm)	750	757	766	776	778
Seat-Tube Length (mm)	396	430	468	523	564
Seat-Tube Angle (deg)	75	75	75	74	74
Handlebar Width (mm)	750	750	750	750	750
Stem Length (mm)	45	60	60	60	60
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	390	430	430	430	430
Crank Length (mm)	170	175	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	M5 alloy, Trail Geometry, PF30 BB, internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 135mm of travel
REAR SHOCK	RockShox Monarch RT, Rx Trail Tune, AUTOSAG, rebound and 2-position compression adjust, 197x48mm
FORK	RockShox Revelation RL 29/27.5+, Solo Air spring, lockout and rebound adjust, 15x110mm Maxle Lite thru-axle, 51mm offset, 150mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM GX, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 52mm chainline
RIMS	Roval Traverse 29, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x110mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Butcher, GRID casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Slaughter, GRID casing, 29x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Command Post IRcc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
93317-5102	SJ FSR COMP 29	NRDCRED/BLK	S
93317-5103			M
93317-5104			L
93317-5105			XL
93317-5106			XXL
93317-5202	SJ FSR COMP 29	PRP/MONGRN/BLK	S
93317-5203			M
93317-5204			L
93317-5205			XL
93317-5206			XXL
93317-5002	SJ FSR COMP 29	BLK/CHAR	S
93317-5003			M
93317-5004			L
93317-5005			XL
93317-5006			XXL

STUMPJUMPER FSR COMP 6FATTIE



NRDCRED



PRP/MONGRN/BLK



BLK/CHAR

To squeeze every ounce of fun out of the trail, you need a bike that takes a hit and dishes it right back. You need the Stumpjumper FSR Comp 6Fattie. To be sure, we gave it an M5 alloy construction, insane levels of traction and floatation, and SRAM's most durable components.

- M5 alloy Trail Chassis with Stumpjumper FSR rear end blends durability, stiffness, and light weight, while 135mm of travel Trail Geometry provide more than capable handling.
- RockShox Revelation RL fork features a 15mm Maxle Lite thru-axle and 150mm of plush travel to take on hits and bumpy terrain with more control and confidence.
- Roval Traverse 650b alloy wheels work in tandem with the ultra-wide tires to give you loads of extra traction, floatation, and control.

SJ FSR 29/6FATTIE ALLOY					
SIZE	S	M	L	XL	XXL
Stack (mm)	617	617	645	663	686
Reach (mm)	389	417	435	461	477
Head-Tube Length (mm)	95	95	125	145	170
Head-Tube Angle (deg)	67.5	67.5	67.5	67.5	67.5
B-B Height (29x2.3") (mm)	338	338	338	338	338
B-B Height (650x3") (mm)	331	331	331	331	331
B-B Height (650x2.8") (mm)	325	325	325	325	325
B-B Drop (mm)	36	36	36	36	36
Trail (mm)	104	104	104	104	104
Fork Length (full) (mm)	551	551	551	551	551
Fork Rake/Offset (mm)	46	46	46	46	46
Front-Center (mm)	680	708	738	771	797
Chain-Stay Length (mm)	437	437	437	437	437
Wheelbase (mm)	1115	1143	1172	1206	1232
Top-Tube Length (horizontal) (mm)	551	582	611	647	674
Bike Stand-Over Height (mm)	750	757	766	776	778
Seat-Tube Length (mm)	396	430	468	523	564
Seat-Tube Angle (deg)	75	75	75	74	74
Handlebar Width (mm)	750	750	750	750	750
Stem Length (mm)	45	60	60	60	60
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	390	430	430	430	430
Crank Length (mm)	170	175	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	M5 alloy, Trail Geometry, PF30 BB, internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 135mm of travel
REAR SHOCK	RockShox Monarch RT, Rx Trail Tune, AUTOSAG, rebound and 2-position compression adjust, 197x48mm
FORK	RockShox Revelation RL 29/27.5+, Solo Air spring, lockout and rebound adjust, 15x110mm Maxle Lite thru-axle, 51mm offset, 150mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM GX, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 52mm chainline
RIMS	Roval Traverse 650b, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x110mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Purgatory, GRID casing, 650bx3.0", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Command Post IRcc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
93317-5702	SJ FSR COMP 6FATTIE	NRDCRED	S
93317-5703			M
93317-5704			L
93317-5705			XL
93317-5706			XXL
93317-5802	SJ FSR COMP 6FATTIE	PRP/MONGRN/BLK	S
93317-5803			M
93317-5804			L
93317-5805			XL
93317-5806			XXL
93317-5602	SJ FSR COMP 6FATTIE	BLK/CHAR	S
93317-5603			M
93317-5604			L
93317-5605			XL
93317-5606			XXL

STUMPJUMPER FSR COMP 650B



BLK/CHAR



NRDCRED/BLK



PRP/MONGRN/BLK

When you need to blend ruggedness, efficiency, and down right nimbleness into one trail bike, it's pretty damn hard to beat the alloy Stumpjumper FSR Comp 650b. We made it responsive, nimble, and able to take a hit, so it's perfect for tight and technical trail riding.

- M5 alloy Trail Chassis with Stumpjumper FSR rear end blends durability, stiffness, and light weight, while 135mm of travel Trail Geometry provide more than capable handling.
- RockShox Revelation RL fork features a 15mm Maxle Lite thru-axle and 150mm of plush travel to take on hits and bumpy terrain with more control and confidence.
- Roval Traverse 650b alloy wheels provide a strong, stable platform that's built to deliver heaps of responsiveness, speed, and supreme handling.

SJ FSR 650 ALLOY				
SIZE	S	M	L	XL
Stack (mm)	590	599	608	617
Reach (mm)	388	414	442	464
Head-Tube Length (mm)	95	105	115	125
Head-Tube Angle (deg)	67	67	67	67
B-B Height (650x2.3") (mm)	335	335	335	335
B-B Height (650x2.6") (mm)	340	340	340	340
B-B Drop (mm)	18	18	18	18
Trail (mm)	104	104	104	104
Fork Length (full) (mm)	542	542	542	542
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	677	706	738	764
Chain-Stay Length (mm)	420	420	420	420
Wheelbase (mm)	1096	1126	1158	1184
Top-Tube Length (horizontal) (mm)	553	585	618	646
Bike Stand-Over Height (mm)	742	748	762	774
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	45	60	60	60
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	M5 alloy, Trail Geometry, PF30 BB, internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 135mm of travel
REAR SHOCK	RockShox Monarch RT, Rx Trail Tune, AUTOSAG, rebound and 2-position compression adjust, 197x48mm
FORK	RockShox Revelation RL 27.5, Solo Air spring, lockout and rebound adjust, 15x110mm Maxle Lite thru-axle, 46mm offset, 150mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized, 6061 alloy, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM GX, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	RaceFace Aeffect, 6000-series alloy, 24mm spindle, 52mm chainline
RIMS	Roval Traverse 650b, hookless alloy, 29mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x110mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Butcher, GRID casing, 650x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Slaughter, GRID casing, 650x2.3", 60TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Command Post IRoc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
93317-5302	SJ FSR COMP 650B	BLK/CHAR	S
93317-5303			M
93317-5304			L
93317-5305			XL
93317-5402	SJ FSR COMP 650B	NRDCRED/BLK	S
93317-5403			M
93317-5404			L
93317-5405			XL
93317-5502	SJ FSR COMP 650B	PRP/MONGRN/BLK	S
93317-5503			M
93317-5504			L
93317-5505			XL

S-WORKS STUMPJUMPER FSR 29 FRAME



CARB/BLK



LTBLU/NRDCRED



MONGRN/CARB



PRP/WHT/HTPNK



TUR/PNK/HYP

When only the best will do, you need the ultimate trail bike. In other words, you need the S-Works Stumpjumper FSR 29. It reflects everything that we've learned over the years, like our highest-end FACT 11m carbon, integrated SWAT™ utility, a trail-eating geometry, and a proprietary shock tune.

- FACT 11m carbon fiber Trail Chassis with Stumpjumper FSR full carbon rear end blends stiffness with light weight to form the pinnacle of efficiency, while fully enclosed cable routing and an integrated SWAT™ Door create exceptional handling and zero-hassle storage.
- The custom Öhlins STX single tube air shock at the rear features high- and low-speed compression, as well as low-speed rebound. You'll also find an extra-volume reservoir that allows for more oil, which results in more control and an ultra-plush ride quality.

SPECS

All specs are subject to change without notice.

FRAME	FACT 11m, full carbon chassis and rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 135mm of travel
REAR SHOCK	Custom Öhlins STX, Single Tube design, Rx Trail Tune, 3rd Chamber air spring technology, AUTOSAG, adjustable compression & rebound damping, 197x48mm

PART NO.	DESCRIPTION	COLOR	SIZE
77517-0002	SW SJ FSR CARBON 29/6FATTIE FRM	CARB/BLK	S
77517-0003			M
77517-0004			L
77517-0005			XL
77517-0202	SW SJ FSR CARBON 29/6FATTIE FRM	LTBLU/NRDCRED	S
77517-0203			M
77517-0204			L
77517-0205			XL
77517-0302	SW SJ FSR CARBON 29/6FATTIE FRM	MONGRN/CARB	S
77517-0303			M
77517-0304			L
77517-0305			XL
77517-0402	SW SJ FSR CARBON 29/6FATTIE FRM	PRP/WHT/HTPNK	S
77517-0403			M
77517-0404			L
77517-0405			XL
77517-0502	SW SJ FSR CARBON 29/6FATTIE FRM	TUR/PNK/HYP	S
77517-0503			M
77517-0504			L
77517-0505			XL

SJ FSR 29/6FATTIE CARBON

SIZE	S	M	L	XL
Stack (mm)	618	618	646	664
Reach (mm)	386	413	431	457
Head-Tube Length (mm)	95	95	125	145
Head-Tube Angle (deg)	67	67	67	67
B-B Height (29x2.3") (mm)	338	338	338	338
B-B Height (650x3 ") (mm)	331	331	331	331
B-B Height (650x2.8") (mm)	325	325	325	325
B-B Drop (mm)	33	33	33	33
Trail (mm)	96.5	96.5	96.5	96.5
Fork Length (full) (mm)	560	560	560	560
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	687	714	744	777
Chain-Stay Length (mm)	437	437	437	437
Wheelbase (mm)	1122	1149	1179	1212
Top-Tube Length (horizontal) (mm)	563	590	616	648
Bike Stand-Over Height (mm)	754	761	770	777
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	74	74	74	74
Seat Post Length (mm)	100	125	125	125

S-WORKS STUMPJUMPER FSR 650B FRAME



CARB/BLK



LTBLU/NRDCRED



MONGRN/CARB



PRP/WHT/HTPNK



TUR/PNK/HYP

When only the best, most agile trail bike will do, our S-Works Stumpjumper FSR 650b meets your needs. It reflects everything we've learned over the years, like our highest-end FACT 11m carbon, integrated SWAT™ utility, a nimble, trail-eating geometry, and a proprietary shock tune.

- FACT 11m carbon fiber Trail Chassis with Stumpjumper FSR full carbon rear end blends stiffness with light weight to form the pinnacle of efficiency, while fully enclosed cable routing and an integrated SWAT™ Door create exceptional handling and zero-hassle storage.
- The custom Öhlins STX single tube air shock at the rear features high- and low-speed compression, as well as low-speed rebound. You'll also find an extra-volume reservoir that allows for more oil, which results in more control and an ultra-plush ride quality.

SPECS

All specs are subject to change without notice.

FRAME	FACT 11m, full carbon chassis and rear end, Trail Geometry, SWAT™ Door integration, PF30 BB, fully enclosed internal cable routing, ManFu link, 12x148mm dropouts, sealed cartridge bearing pivots, replaceable derailleur hanger, 150mm of travel
REAR SHOCK	Custom Öhlins STX, Single Tube design, Rx Trail Tune, 3rd Chamber air spring technology, AUTOSAG, adjustable compression & rebound damping, 197x48mm

SJ FSR 650 CARBON				
SIZE	S	M	L	XL
Stack (mm)	590	599	608	617
Reach (mm)	388	414	442	464
Head-Tube Length (mm)	95	105	115	125
Head-Tube Angle (deg)	67	67	67	67
B-B Height (650x2.3") (mm)	335	335	335	335
B-B Height (650x2.6") (mm)	340	340	340	340
B-B Drop (mm)	18	18	18	18
Trail (mm)	104	104	104	104
Fork Length (full) (mm)	542	542	542	542
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	677	706	738	764
Chain-Stay Length (mm)	420	420	420	420
Wheelbase (mm)	1096	1126	1158	1184
Top-Tube Length (horizontal) (mm)	558	587	618	646
Bike Stand-Over Height (mm)	742	748	762	764
Seat-Tube Length (mm)	396	430	468	523
Seat-Tube Angle (deg)	74	74	74	74
Seat Post Length (mm)	100	125	125	125

PART NO.	DESCRIPTION	COLOR	SIZE
73317-0002	SW SJ FSR CARBON 650B FRM	CARB/BLK	S
73317-0003			M
73317-0004			L
73317-0005			XL
73317-0202	SW SJ FSR CARBON 650B FRM	LTBLU/NRDCRED	S
73317-0203			M
73317-0204			L
73317-0205			XL
73317-0302	SW SJ FSR CARBON 650B FRM	MONGRN/CARB	S
73317-0303			M
73317-0304			L
73317-0305			XL
73317-0402	SW SJ FSR CARBON 650B FRM	PRP/WHT/HTPNK	S
73317-0403			M
73317-0404			L
73317-0405			XL
73317-0502	SW SJ FSR CARBON 650B FRM	TUR/PNK/HYP	S
73317-0503			M
73317-0504			L
73317-0505			XL

S-WORKS FUSE 6FATTIE



CARB/CHAR/HYP

The S-Works Fuse 6Fattie is a different kind of trail bike. Sure, it maintains the no-expense spared pedigree that S-Works is known the world over for, but even still, there's more to it than meets the eye. This bike proves that hardtails still have a valuable place in trail riding.

- FACT 10m carbon fiber frame construction blends stiffness with light weight to form the pinnacle of efficiency, while internal routing tubes and an integrated SWAT™ Door create a tidy aesthetic and zero-hassle storage.
- Öhlins RXF36 fork features 120mm of travel and a three-chamber air spring with two positive chambers and one negative. This allows for an offset of spring pressure that perfectly mates stiffness with a plush, responsive ride quality. The shape of the spring curve can also be adjusted to increase sensitivity without bottoming out.
- 650bx3.0" 6Fattie Purgatory and Ground Control tires feature a perfectly sized contact patch for life-changing levels of traction and control while cornering, all without sacrificing climbing efficiency or descending prowess. And with a GRID casing protecting the sidewalls, these tires will stand up to anything the trail can throw at them.

FUSE CARBON				
SIZE	S	M	L	XL
Stack (mm)	610	610	634	652
Reach (mm)	400	420	440	458
Head-Tube Length (mm)	95	95	120	140
Head-Tube Angle (deg)	67.5	67.5	67.5	67.5
B-B Height (29x2.3) (mm)	319	319	319	319
B-B Height (650x3) (mm)	312	312	312	312
B-B Height (650x2.8) (mm)	306	306	306	306
B-B Drop (mm)	51	51	51	51
Trail (mm)	95	95	95	95
Fork Length (full) (mm)	531	531	531	531
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	689	709	738	764
Chain-Stay Length (mm)	430	430	430	430
Wheelbase (mm)	1114	1134	1164	1189
Top-Tube Length (horizontal) (mm)	575	607	634	657
Bike Stand-Over Height (mm)	746	770	796	835
Seat-Tube Length (mm)	394	434	470	523
Seat-Tube Angle (deg)	74	73	73	73
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	40	40	60	60
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 10m carbon fiber, SWAT™ Door down tube storage w/internal routing tubes, tapered head tube, 148x12mm thru-axle rear hub spacing, 160mm post mount disc, threaded bottom bracket
FORK	Öhlins RXF36, 29/27.5+, Twin-Tube design, air spring w/ adjustable 3rd chamber, adjustable high and low speed compression, adjustable rebound, 15x110mm thru-axle, 51mm offset, 120mm travel
STEM	Syntace MegaForce 2, 6-degree, 31.8mm bar clamp
HANDLEBARS	Specialized Trail, FACT carbon, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide RS carbon, hydraulic disc, organic pads, carbon lever, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide RS carbon, hydraulic disc, organic pads, carbon lever, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM XX1 Eagle, 12-speed
SHIFT LEVERS	SL XX1 Eagle, 12-speed, trigger
CASSETTE	SRAM XG-1295, 12-speed, 10-50t
CHAIN	SRAM XX1 Eagle, black, 12-speed w/PowerLink
CRANKSET	SRAM XX1 Eagle, carbon, 24mm spindle, 52mm chainline
CHAINRINGS	SRAM X-Sync, direct mount, 30T
BOTTOM BRACKET	Threaded SRAM GXP, 73mm
RIMS	Roval Traverse SL 650b, hookless carbon, 38mm inner width, 24/28h, tubeless ready
FRONT HUB	Roval Traverse, alloy, sealed bearings, 15x100mm, 24h
REAR HUB	Roval Traverse, alloy, sealed bearings, DT Swiss 240 internals, 36T engagement, XX1 driver body, 28h
SPOKES	DT Swiss SuperComp
SADDLE	Body Geometry Henge Expert, hollow titanium rails, 143mm
SEATPOST	Command Post IRcc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
96017-0002	FUSE S-WORKS CARBON 6FATTIE	CARB/CHAR/HYP	S
96017-0003			M
96017-0004			L
96017-0005			XL

FUSE EXPERT CARBON 6FATTIE



BLK/CHAR/NRDCRED



RKTRED/BLK

Last year, the Fuse proved that more volume means more speed. And this year, we took a proven idea and made it even better with carbon. Say hello to the Fuse Expert Carbon 6Fattie.

- FACT 10m carbon fiber frame construction blends stiffness with light weight to form the pinnacle of efficiency, while internal routing tubes and an integrated SWAT™ Door create a tidy aesthetic and zero-hassle storage.
- FOX Rhythm FLOAT 34 is the latest trail-taming fork from the masterminds at FOX, offering two-position sweep adjust and 120mm of plush travel.
- 650b x 3.0" 6Fattie Purgatory and Ground Control tires feature a perfectly sized contact patch for life-changing levels of traction and control while cornering, all without sacrificing climbing efficiency or descending prowess. And with a GRID casing protecting the sidewalls, these tires will stand up to anything the trail can throw at them.

FUSE CARBON				
SIZE	S	M	L	XL
Stack (mm)	610	610	634	652
Reach (mm)	400	420	440	458
Head-Tube Length (mm)	95	95	120	140
Head-Tube Angle (deg)	67.5	67.5	67.5	67.5
B-B Height (29x2.3) (mm)	319	319	319	319
B-B Height (650x3) (mm)	312	312	312	312
B-B Height (650x2.8) (mm)	306	306	306	306
B-B Drop (mm)	51	51	51	51
Trail (mm)	95	95	95	95
Fork Length (full) (mm)	531	531	531	531
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	689	709	738	764
Chain-Stay Length (mm)	430	430	430	430
Wheelbase (mm)	1114	1134	1164	1189
Top-Tube Length (horizontal) (mm)	575	607	634	657
Bike Stand-Over Height (mm)	746	770	796	835
Seat-Tube Length (mm)	394	434	470	523
Seat-Tube Angle (deg)	74	73	73	73
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	45	45	60	60
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	390	430	430	430
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 10m carbon fiber, SWAT™ Door down tube storage w/internal routing tubes, tapered head tube, 148x12mm thru-axle rear hub spacing, 160mm post mount disc, threaded bottom bracket
FORK	FOX Rhythm FLOAT 34, air spring, 2-position Sweep Adjustment, 15x110mm thru-axle, 120mm travel
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Trail, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 25mm rise, 750mm width, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM X1, Type 2.1, 11-speed
SHIFT LEVERS	SRAM GX, 11-speed, trigger
CASSETTE	SRAM XG-1175, 11-speed, 10-42t
CHAIN	SRAM PC-1130, 11-speed w/PowerLink
CRANKSET	RaceFace Turbine Cinch crankset, alloy, 30mm spindle, direct-mount chainring, 52mm chainline, 11-speed
CHAINRINGS	28T
BOTTOM BRACKET	Threaded SRAM GXP, 73mm
RIMS	Roval Traverse 650b, hookless alloy, 38mm inner width, 24/28h, tubeless ready
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 110x15mm thru-axle, 24h
REAR HUB	Specialized disc, alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
SPOKES	DT Swiss SuperComp
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Command Post IRoc, 12 position micro-height adjustable, alien head design, bottom mount cable routing, remote SRL lever, 30.9mm, S: 100mm, M/L/XL: 125mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
96017-3302	FUSE EXPERT CARBON 6FATTIE	BLK/CHAR/NRDCRED	S
96017-3303			M
96017-3304			L
96017-3305			XL
96017-3402	FUSE EXPERT CARBON 6FATTIE	RKTRED/BLK	S
96017-3403			M
96017-3404			L
96017-3405			XL

FUSE EXPERT 6FATTIE



GRPH/BLK/RKTRED



RYLBLU/BLK/CHAR

We said it once, and we'll say it again—more volume means more speed. It might be a claim that sounds flipped on its head, but one ride on the Fuse Expert 6Fattie will have you shouting this sentiment from the rooftops.

- M4 Premium Aluminum proved to be the right material for the job, allowing a lightweight, durable frame with a low and slack geometry that's equal parts snappy and efficient on climbs and descents. It also allowed us to incorporate our exclusive Diamond Stay chainstay that accommodates the 6Fattie wheel/tire combination without compromising on our hallmark short chainstays that provide unrivaled handling and climbing prowess.
- A Rock Shox Reba RL fork pairs 100/120mm (size-specific) of smooth travel with adjustable rebound for maximum absorbency over harsh terrain and easy, on-the-fly adjustments to the damping to hit the perfect tune.
- 650x3.0" 6Fattie Purgatory and Ground Control tires feature a perfectly sized contact patch for life-changing levels of traction and control while cornering, all without sacrificing climbing efficiency or descending prowess. And with a GRID casing protecting the sidewalls, these tires will stand up to anything the trail can throw at them.

FUSE M4					
SIZE	S	M	L	XL	XXL
Stack (mm)	605	614	629	643	661
Reach (mm)	400	420	440	458	476
Head-Tube Length (mm)	110	100	115	130	150
Head-Tube Angle (deg)	67.5	67.5	67.5	67.5	67.5
B-B Height (29x2.3) (mm)	319	319	319	319	319
B-B Height (650x3) (mm)	312	312	312	312	312
B-B Height (650x2.8) (mm)	306	306	306	306	306
B-B Drop (mm)	51	51	51	51	51
Trail (mm)	95	95	95	95	95
Fork Length (full) (mm)	510	530	530	530	530
Fork Rake/Offset (mm)	51	51	51	51	51
Front-Center (mm)	686	708	735	760	786
Chain-Stay Length (mm)	430	430	430	430	430
Wheelbase (mm)	1112	1136	1161	1185	1211
Top-Tube Length (horizontal) (mm)	575	608	633	656	679
Bike Stand-Over Height (mm)	755	781	806	830	866
Seat-Tube Length (mm)	394	434	470	505	555
Seat-Tube Angle (deg)	74	73	73	73	73
Handlebar Width (mm)	750	750	750	750	750
Stem Length (mm)	45	45	60	60	75
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	370	412	412	412	412
Crank Length (mm)	170	175	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	Fully butted M4 Aluminum w/smooth welding, tapered head tube and seat tube, forged post mount 160mm disc, 148mm thru-axle dropout, alloy replaceable derailleur hanger
FORK	RockShox Reba RL 29/27.5+, Fast Black uppers, Solo air, 15x110mm thru-axle, 100/120mm travel (frame size specific)
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Double-buttressed alloy, 9-degree backsweep, 5-degree upsweep, 15mm rise, 750mm width, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM DB3, hydraulic disc, custom 4-piston caliper, semi-metallic pads, 200/180mm rotor
REAR BRAKE	SRAM DB3, hydraulic disc, custom 4-piston caliper, semi-metallic pads, 180/160mm rotor
REAR DERAILLEUR	SRAM GX, long cage, 11-speed
SHIFT LEVERS	SRAM GX, 11-speed, trigger
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	SRAM PC-1130, 11-speed w/PowerLink
CRANKSET	Specialized Stout XC Pro, forged alloy, 30mm alloy spindle, 52mm chainline, 76mm BCD spider, 28T chainring
CHAINRINGS	28T
BOTTOM BRACKET	PF30, sealed cartridge bearings
RIMS	Stout 650b, alloy, disc only, 38mm inner width, 24/28h
FRONT HUB	Specialized Stout, alloy, sealed cartridge bearings, 15x110mm spacing, 24h
REAR HUB	Specialized Stout, SRAM XD driver, sealed cartridge bearings, 12x148mm spacing, 28h
SPOKES	Stainless, butted, 2.0/1.8/2.0mm, black
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	TranzX dropper, internal cable routing, remote lever, 30.9mm, S/M: 100mm, L/XL: 120mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
96017-3102	FUSE EXPERT 6FATTIE	GRPH/BLK/RKTRED	S
96017-3103			M
96017-3104			L
96017-3105			XL
96017-3106			XXL
96017-3202	FUSE EXPERT 6FATTIE	RYLBLU/BLK/CHAR	S
96017-3203			M
96017-3204			L
96017-3205			XL
96017-3206			XXL

FUSE COMP 6FATTIE



HYP/BLK/CHAR



BLK/CHAR/MXGRN

We said it once, and we'll say it again—more volume means more speed. It might be a claim that sounds flipped on its head, but one ride on the Fuse Comp 6Fattie will have you shouting this sentiment from the rooftops.

- M4 Premium Aluminum proved to be the right material for the job, allowing for a lightweight, durable frame with a low and slack geometry that's equal parts snappy and efficient on climbs and descents. It also allowed us to incorporate our exclusive Diamond Stay chainstay that accommodates the wheel/tire combination without compromising on our hallmark short chainstays that provide unrivaled handling and climbing prowess.
- The Manitou Machete fork's 100/120mm (size-specific) of travel soaks up trail bumps, while its compression and rebound adjust enable you to dial-in the damping to your liking.
- 650bx3.0" 6Fattie Purgatory and Ground Control tires feature a perfectly sized contact patch for life-changing levels of traction and control while cornering, all without sacrificing climbing efficiency or descending prowess. And with a GRID casing protecting the sidewalls, these tires will stand up to anything the trail can throw at them.

FUSE M4					
SIZE	S	M	L	XL	XXL
Stack (mm)	605	614	629	643	661
Reach (mm)	400	420	440	458	476
Head-Tube Length (mm)	110	100	115	130	150
Head-Tube Angle (deg)	67.5	67.5	67.5	67.5	67.5
B-B Height (29x2.3) (mm)	319	319	319	319	319
B-B Height (650x3) (mm)	312	312	312	312	312
B-B Height (650x2.8) (mm)	306	306	306	306	306
B-B Drop (mm)	51	51	51	51	51
Trail (mm)	95	95	95	95	95
Fork Length (full) (mm)	510	530	530	530	530
Fork Rake/Offset (mm)	51	51	51	51	51
Front-Center (mm)	686	708	735	760	786
Chain-Stay Length (mm)	430	430	430	430	430
Wheelbase (mm)	1112	1136	1161	1185	1211
Top-Tube Length (horizontal) (mm)	575	608	633	656	679
Bike Stand-Over Height (mm)	755	781	806	830	866
Seat-Tube Length (mm)	394	434	470	505	555
Seat-Tube Angle (deg)	74	73	73	73	73
Handlebar Width (mm)	750	750	750	750	750
Stem Length (mm)	50	50	60	60	70
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	370	412	412	412	412
Crank Length (mm)	170	175	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	Fully butted M4 Aluminum w/smooth welding, tapered head tube and seat tube, forged post mount 160mm disc, 148mm thru-axle dropout, alloy replaceable derailleur hanger
FORK	Manitou Machete 29/27.5+, Absolute Plus damper, air spring, adjustable rebound and compression/lockout, 110x15mm thru-axle, 100/120mm travel
STEM	Alloy, 7-degree rise, 31.8mm clamp
HANDLEBARS	Double-butt'd alloy, 9-degree backsweep, 5-degree upsweep, 15mm rise, 750mm width, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	TRP Slate X2, hydraulic 4-piston disc, I-spec compatible, metallic pads, 203/180 rotor
REAR BRAKE	TRP Slate X2, hydraulic 2-piston disc, I-spec compatible, metallic pads, 180/160mm rotor
REAR DERAILLEUR	SRAM NX, long cage, 11-speed
SHIFT LEVERS	SRAM NX, 11-speed, trigger
CASSETTE	SRAM PG-1130, 11-speed, 11-42t
CHAIN	SRAM PC-1130, 11-speed w/PowerLink
CRANKSET	Specialized Stout XC, forged alloy, 30mm Cr-Mo spindle, 76mm BCD spider
CHAINRINGS	28T
BOTTOM BRACKET	BB30, sealed cartridge bearings
RIMS	Stout 650b, alloy, disc only, 38mm inner width, 24/28h
FRONT HUB	Specialized Stout, alloy, sealed cartridge bearings, 15x110mm spacing, 24h
REAR HUB	Specialized Stout, SRAM XD driver, 12x148mm spacing, sealed cartridge bearings, 28h
SPOKES	Stainless, 14g, black
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	TranzX dropper, internal cable routing, remote lever, 30.9mm, S/M: 100mm, L/XL: 120mm travel

PART NO.	DESCRIPTION	COLOR	SIZE
96017-5102	FUSE COMP 6FATTIE	HYP/BLK/CHAR	S
96017-5103			M
96017-5104			L
96017-5105			XL
96017-5106			XXL
96017-5002	FUSE COMP 6FATTIE	BLK/CHAR/MXGRN	S
96017-5003			M
96017-5004			L
96017-5005			XL
96017-5006			XXL

FUSE SPORT 6FATTIE



WHT/BLK/NRDCRED



INK/BLK/NRDCRED

All too often, trail riders feel locked between a rock and a hard place. On one hand, you need to climb, and on the other, you need to descend. The reality of this situation is that you're typically forced to sacrifice on one end or the other, and needless to say, we didn't like that. This is where our Fuse Sport 6 Fattie comes in.

- The frame features an A1 Premium Aluminum construction that provides the ideal blend of efficiency and durability. It also allowed us to accommodate the 6Fattie wheels & tires without compromising on our hallmark characteristics, like short chainstays that provide unrivaled handling and climbing prowess.
- A Suntour XCR Air fork features stiff 32mm stanchions and 80/100mm (size specific) of smooth travel.
- 650bx3.0" 6Fattie Ground Control tires feature a perfectly sized contact patch for life-changing levels of traction and control while cornering, all without sacrificing climbing efficiency or descending prowess. And with a GRID casing protecting the sidewalls, these tires will stand up to anything the trail can throw at them.

FUSE A1					
SIZE	XS	S	M	L	XL
Stack (mm)	603	622	622	636	650
Reach (mm)	380	395	415	435	455
Head-Tube Length (mm)	100	100	100	115	130
Head-Tube Angle (deg)	68.5	68.5	68.5	68.5	68.5
B-B Height (29x2.3) (mm)	317	317	317	317	317
B-B Height (650x3) (mm)	310	310	310	310	310
B-B Height (650x2.8) (mm)	304	304	304	304	304
B-B Drop (mm)	520	520	520	520	520
Trail (mm)	93	93	93	93	93
Fork Length (full) (mm)	500	520	520	520	520
Fork Rake/Offset (mm)	46	46	46	46	46
Front-Center (mm)	649	671	691	716	742
Chain-Stay Length (mm)	435	435	435	435	435
Wheelbase (mm)	1078	1101	1121	1146	1172
Top-Tube Length (horizontal) (mm)	553	585	605	629	654
Bike Stand-Over Height (mm)	715	755	785	808	841
Seat-Tube Length (mm)	330	373	432	460	510
Seat-Tube Angle (deg)	74	73	73	73	73
Handlebar Width (mm)	750	750	750	750	750
Stem Length (mm)	50	50	60	60	70
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	350	350	400	400	400
Crank Length (mm)	170	175	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	A1 Premium Aluminum w/smooth welding, Zero Stack 44 head tube, forged post mount 160mm disc, 141mm QR dropout, alloy replaceable derailleur hanger
FORK	Suntour XCR Air, lockout, 15x110mm thru-axle, 80/100mm of travel (frame size-specific)
STEM	Alloy, 7-degree rise, 31.8mm clamp
HANDLEBARS	Double-buttressed alloy, 9-degree backsweep, 5-degree upsweep, 15mm rise, 750mm width, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Tektro Gemini, hydraulic disc, resin pads, i-Spec compatible, 180mm rotor
REAR BRAKE	Tektro Gemini, hydraulic disc, resin pads, i-spec compatible, 160mm rotor
REAR DERAILLEUR	SRAM GX, Type 2.1, long cage, 10-speed
SHIFT LEVERS	SRAM X5, 10-speed, trigger
CASSETTE	Sunrace, 10-speed, 11-42t
CHAIN	SRAM PC-1031, 10-speed w/PowerLink
CRANKSET	SRAM NX, alloy, 24mm spindle, 52mm chainline, direct mount chaining
CHAINRINGS	SRAM X-SYNC, steel 28T
BOTTOM BRACKET	SRAM GXP, 73mm
RIMS	Stout 650b, alloy, disc only, 38mm inner width, 24/28h
FRONT HUB	Specialized Stout, sealed cartridge bearings, 15x110mm spacing, 24h
REAR HUB	Specialized Stout, 10-speed, 10x141mm spacing, sealed cartridge bearings, 28h
SPOKES	Stainless, 14g, black
SADDLE	Body Geometry Henge Sport, steel rails, 143mm
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
96017-6101	FUSE SPORT 6FATTIE	WHT/BLK/NRDCRED	XS
96017-6102			S
96017-6103			M
96017-6104			L
96017-6105			XL
96017-6001	FUSE SPORT 6FATTIE	INK/BLK/NRDCRED	XS
96017-6002			S
96017-6003			M
96017-6004			L
96017-6005			XL

FUSE 6FATTIE



LTBLU/BLK/NRDCRED



BLK/WHT



WRMCHAR/HYP/NRDCRED

If you show us the trail rider that says they couldn't use more traction, we'll show the trail rider that's never ridden our Fuse 6Fattie. We like to call it the ultimate trail hardtail, and with our 6Fattie Wheel System, this becomes more than just talk.

- The frame features an A1 Premium Aluminum construction that provides the ideal blend of efficiency and durability. It also allowed us to accommodate the 6Fattie wheels & tires without compromising on our hallmark characteristics, like short chainstays that provide unrivaled handling and climbing prowess.
- An SR Suntour XCM 27.5+ fork with Multi-Circuit Damping features a stiff 15mm thru-axle and 80/100mm of smooth travel.
- 650x3.0" 6Fattie Ground Control tires feature a perfectly sized contact patch for life-changing levels of traction and control while cornering, all without sacrificing climbing efficiency or descending prowess. And with a GRID casing protecting the sidewalls, these tires will stand up to anything the trail can throw at them.

FUSE A1					
SIZE	XS	S	M	L	XL
Stack (mm)	603	622	622	636	650
Reach (mm)	380	395	415	435	455
Head-Tube Length (mm)	100	100	100	115	130
Head-Tube Angle (deg)	68.5	68.5	68.5	68.5	68.5
B-B Height (29x2.3) (mm)	317	317	317	317	317
B-B Height (650x3) (mm)	310	310	310	310	310
B-B Height (650x2.8) (mm)	304	304	304	304	304
B-B Drop (mm)	520	520	520	520	520
Trail (mm)	93	93	93	93	93
Fork Length (full) (mm)	500	520	520	520	520
Fork Rake/Offset (mm)	46	46	46	46	46
Front-Center (mm)	649	671	691	716	742
Chain-Stay Length (mm)	435	435	435	435	435
Wheelbase (mm)	1078	1101	1121	1146	1172
Top-Tube Length (horizontal) (mm)	553	585	605	629	654
Bike Stand-Over Height (mm)	715	755	785	808	841
Seat-Tube Length (mm)	330	373	432	460	510
Seat-Tube Angle (deg)	74	73	73	73	73
Handlebar Width (mm)	750	750	750	750	750
Stem Length (mm)	50	50	60	60	70
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	350	350	400	400	400
Crank Length (mm)	170	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	A1 Premium Aluminum w/smooth welding, Zero Stack 44 head tube, forged post mount 160mm disc, 141mm QR dropout, alloy replaceable derailleur hanger
FORK	SR Suntour XCM, coil spring, custom Multi-Circuit Damping, lockout, 32mm stanchions, 15x110mm thru-axle, 80/100mm of travel
STEM	Alloy, 7-degree rise, 31.8mm clamp
HANDLEBARS	Double-buttressed alloy, 9-degree backsweep, 5-degree upsweep, 15mm rise, 750mm width, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Tektro Auriga, hydraulic disc, organic pads, 180mm rotor
REAR BRAKE	Tektro Auriga, hydraulic disc, organic pads, 160mm rotor
REAR DERAILLEUR	SRAM X7, Type 2.1, long cage, 10-speed
SHIFT LEVERS	SRAM X5, 10-speed, trigger
CASSETTE	Sunrace, 10-speed, 11-42t
CHAIN	SRAM PC-1031, 10-speed w/PowerLink
CRANKSET	Stout, 76mm BCD spider
CHAINRINGS	28T
BOTTOM BRACKET	Square taper, 73mm, internal bearings
RIMS	Stout 650b, alloy, disc only, 38mm inner width, 24/28h
FRONT HUB	Specialized Stout, sealed cartridge bearings, 15x110mm spacing, 24h
REAR HUB	Specialized Stout, 10-speed, 10x141mm spacing, sealed cartridge bearings, 28h
SPOKES	Stainless, 14g, black
SADDLE	Body Geometry Henge Sport, steel rails, 143mm
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
96017-7101	FUSE 6FATTIE	LTBLU/BLK/NRDCRED	XS
96017-7102			S
96017-7103			M
96017-7104			L
96017-7105			XL
96017-7001	FUSE 6FATTIE	BLK/WHT	XS
96017-7002			S
96017-7003			M
96017-7004			L
96017-7005			XL
96017-7201	FUSE 6FATTIE	WRMCHAR/HYP/NRDCRED	XS
96017-7202			S
96017-7203			M
96017-7204			L
96017-7205			XL

ROCKHOPPER PRO 29



TLTNT/BLK



DRMSIL/BLK/NRDCRED

If you're ready to take your trail riding to the next level, let us introduce you to your new friend, the Rockhopper Pro 29. We built it to be light, durable, and exceedingly capable, but how we did it is far more interesting.

- The frame is constructed from lightweight A1 SL aluminum in order to provide a compliant, durable platform to support our acclaimed Trail 29 Geometry. Combined, you get a bike that's more than efficient on climbs and eager to get down to business on descents.
- A RockShox 30 Gold suspension fork offers 80/100mm (size specific) of plush, high-performance travel that'll smooth out the bumps and ruts on your trail rides. It features proprietary technology from RockShox, like its Solo Air™ spring, that maintains an ideal equilibrium, as well as being one of the lightest air springs on the market.
- The Shimano Deore XT rear derailleur is one of the most sought after components in mountain biking. It's remarkably reliable, precise and crisp in its shifting, and is nothing if not durable.

ROCKHOPPER A1 SL					
SIZE	S	M	L	XL	XXL
Stack (mm)	615	624	639	653	672
Reach (mm)	400	412	430	450	464
Head-Tube Length (mm)	110	100	115	130	150
Head-Tube Angle (deg)	71	71	71	71	71
B-B Height (mm)	310	310	310	310	310
B-B Drop (mm)	64	64	64	64	64
Trail (mm)	80	80	80	80	80
Fork Length (full) (mm)	485	505	505	505	505
Fork Rake/Offset (mm)	46	46	46	46	46
Front-Center (mm)	642	657	680	704	725
Chain-Stay Length (mm)	442	442	442	442	442
Wheelbase (mm)	1076	1091	1114	1139	1159
Top-Tube Length (horizontal) (mm)	588	615	637	662	682
Bike Stand-Over Height (mm)	763.6	810.4	828.7	860	894.1
Seat-Tube Length (mm)	395	445	460	510	560
Seat-Tube Angle (deg)	73	72	72	72	72
Handlebar Width (mm)	720	720	720	720	720
Stem Length (mm)	60	70	70	90	90
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	350	350	400	400	400
Crank Length (mm)	170	175	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 SL Aluminum, Trail 29 geometry, fully-butted tube sets, ORE down tube, tapered head tube, forged dropouts, disc mount, replaceable derailleur hanger
FORK	RockShox 30 Gold 29, Solo Air spring, remote lockout, rebound adjust, 9mm QR, 80mm travel
STEM	Specialized Stout, 3D-forged alloy, 4-bolt, 6-degree rise, anti-corrosion hardware
HANDLEBARS	Stout, alloy, 8-degree backsweep, 6-degree upsweep, 10mm rise, 720mm width, 31.8mm
GRIPS	Lock-on grips, 130.4mm length
FRONT BRAKE	Shimano BR-M506, hydraulic disc, resin pads, 180/160mm rotors
REAR BRAKE	Shimano BR-M506, hydraulic disc, resin pads, 160mm
FRONT DERAILLEUR	SRAM X5, high-clamp 34.9mm, 2x10
REAR DERAILLEUR	Shimano Deore XT, Shadow Plus, SGS cage, 10-speed
SHIFT LEVERS	Shimano Deore, RapidFire, 1-spec, 10-speed
CASSETTE	SRAM PG-1020, 10-speed, 11-36t
CHAIN	SRAM PC-1031, 10-speed w/PowerLink
CRANKSET	Specialized Stout XC, 2-piece 2x10, 24mm spindle, anti-corrosion hardware
CHAINRINGS	36/22T
BOTTOM BRACKET	BSA threaded, external bearing, 73mm width
RIMS	Stout XC SL 29, alloy disc, double-wall, sleeve joint, 21mm inner width, 28h
FRONT HUB	Shimano HB-RM35, Center Lock disc, 9x100mm, 28h
REAR HUB	Shimano FH-RM35, Center Lock disc, 10x135mm, 28h
SPOKES	Stainless, 14g, black
FRONT TIRE	Ground Control Sport, 29x2.1", 60TPI, wire bead, Flak Jacket protection
REAR TIRE	Ground Control Sport, 29x2.1", 60TPI, wire bead, Flak Jacket protection
SADDLE	Body Geometry Henge Sport, steel rails, 143mm
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
91217-1102	ROCKHOPPER PRO 29	TLTNT/BLK	S
91217-1103			M
91217-1104			L
91217-1105			XL
91217-1106			XXL
91217-1002	ROCKHOPPER PRO 29	DRMSIL/BLK/NRDCRED	S
91217-1003			M
91217-1004			L
91217-1005			XL
91217-1006			XXL

ROCKHOPPER EXPERT 29



HYP/BLK



GRPH/NENBLU

If you're the one in your group that's always getting followed on the trail, the Rockhopper Expert 29 is here to make sure that it stays that way. We built it to be light, durable, and exceedingly capable, but how we did it is far more interesting.

- The frame is constructed from lightweight A1 SL aluminum in order to provide a compliant, durable platform to support our acclaimed Trail 29 Geometry. Combined, you get a bike that's more than efficient on climbs and eager to get down to business on descents.
- A Manitou M30 29 fork offers 80/100mm (size-specific) of plush, trail taming travel and stiff 30mm stanchions.
- It's hard to beat the blend of durability, reliability, and performance that the Shimano SLX rear derailleur provides. It's designed to take a hit, and more importantly, its shifting is crisp, precise, and always on the money.

ROCKHOPPER A1 SL					
SIZE	S	M	L	XL	XXL
Stack (mm)	615	624	639	653	672
Reach (mm)	400	412	430	450	464
Head-Tube Length (mm)	110	100	115	130	150
Head-Tube Angle (deg)	71	71	71	71	71
B-B Height (mm)	310	310	310	310	310
B-B Drop (mm)	64	64	64	64	64
Trail (mm)	80	80	80	80	80
Fork Length (full) (mm)	485	505	505	505	505
Fork Rake/Offset (mm)	46	46	46	46	46
Front-Center (mm)	642	657	680	704	725
Chain-Stay Length (mm)	442	442	442	442	442
Wheelbase (mm)	1076	1091	1114	1139	1159
Top-Tube Length (horizontal) (mm)	588	615	637	662	682
Bike Stand-Over Height (mm)	763.6	810.4	828.7	860	894.1
Seat-Tube Length (mm)	395	445	460	510	560
Seat-Tube Angle (deg)	73	72	72	72	72
Handlebar Width (mm)	720	720	720	720	720
Stem Length (mm)	60	70	70	80	90
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	350	350	400	400	400
Crank Length (mm)	170	175	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 SL Aluminum, Trail 29 geometry, fully-butted tube sets, ORE down tube, tapered head tube, forged dropouts, disc mount, replaceable derailleur hanger
FORK	Manitou M30 29, 80/100mm of travel (size specific), 1.125x1.5" tapered steerer, 30mm stanchion, QR, 51mm offset, post mount disc, 160mm rotor
STEM	Stout, 3D-forged alloy, 31.8mm clamp, 6-degree rise
HANDLEBARS	Stout, alloy, 8-degree backsweep, 6-degree upsweep, 10mm rise, 720mm width, 31.8mm
GRIPS	Lock-on grips, 130.4mm length
FRONT BRAKE	Shimano BR-M365, hydraulic disc, resin pads, 180/160mm rotor
REAR BRAKE	Shimano BR-M365, hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	SRAM X5, high-clamp 34.9mm, 2x10
REAR DERAILLEUR	Shimano SLX, Shadow Plus, SGS cage, 10-speed
SHIFT LEVERS	Shimano Deore, 10-speed
CASSETTE	SRAM PG-1020, 10-speed, 11-36t
CHAIN	SRAM PC-1031, 10-speed w/PowerLink
CRANKSET	Specialized Stout XC, 2-piece 2x10, 24mm spindle, anti-corrosion hardware
CHAINRINGS	36/22T, alloy
BOTTOM BRACKET	BSA threaded, external bearing, 73mm width
RIMS	Stout XC 29, alloy disc, double-wall, pinned joint, 21mm inner width, 28/32h
FRONT HUB	Shimano HB-RM35, Center Lock disc, 9x100mm, 28h
REAR HUB	Shimano FH-RM35, Center Lock disc, 10x135mm, 32h
SPOKES	Stainless, 14g, black
FRONT TIRE	Ground Control Sport, 29x2.1", 60TPI, wire bead, Flak Jacket protection
REAR TIRE	Ground Control Sport, 29x2.1", 60TPI, wire bead, Flak Jacket protection
SADDLE	Body Geometry Henge Sport, steel rails, 143mm
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
91217-3102	ROCKHOPPER EXPERT 29	HYP/BLK	S
91217-3103			M
91217-3104			L
91217-3105			XL
91217-3106			XXL
91217-3002	ROCKHOPPER EXPERT 29	GRPH/NENBLU	S
91217-3003			M
91217-3004			L
91217-3005			XL
91217-3006			XXL

ROCKHOPPER COMP 29



NRDCRED/BLK



CHAR/BLK/FTHYWHT

Whether you've been riding trails for decades or you're just starting to cut your teeth, the Rockhopper Comp 29 will take your rides to the next level. We built it with just the right balance between performance and durability, and not to toot our own horn, but we nailed it.

- The frame is constructed from lightweight A1 SL aluminum in order to provide a compliant, durable platform to support our acclaimed Trail 29 Geometry. Combined, you get a bike that's more than efficient on climbs and eager to get down to business on descents.
- SR Suntour XCR-Air fork features 80/100mm (size-specific) of suspension travel that swings well above its weight class.
- Shimano Deore rear derailleur provides crisp, reliable shifting that you can count on when the going gets rough. With it, you'll be able to precisely move through the wide, 11-36t gear range to make cruising the flats almost as easy climbing those hills.

ROCKHOPPER A1 SL					
SIZE	S	M	L	XL	XXL
Stack (mm)	615	624	639	653	672
Reach (mm)	400	412	430	450	464
Head-Tube Length (mm)	110	100	115	130	150
Head-Tube Angle (deg)	71	71	71	71	71
B-B Height (mm)	310	310	310	310	310
B-B Drop (mm)	64	64	64	64	64
Trail (mm)	80	80	80	80	80
Fork Length (full) (mm)	485	505	505	505	505
Fork Rake/Offset (mm)	46	46	46	46	46
Front-Center (mm)	642	657	680	704	725
Chain-Stay Length (mm)	442	442	442	442	442
Wheelbase (mm)	1076	1091	1114	1139	1159
Top-Tube Length (horizontal) (mm)	588	615	637	662	682
Bike Stand-Over Height (mm)	763.6	810.4	828.7	860	894.1
Seat-Tube Length (mm)	395	445	460	510	560
Seat-Tube Angle (deg)	73	72	72	72	72
Handlebar Width (mm)	720	720	720	720	720
Stem Length (mm)	60	70	70	80	90
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	350	350	400	400	400
Crank Length (mm)	170	175	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 SL Aluminum, Trail 29 geometry, fully-butted tube sets, ORE down tube, tapered head tube, forged dropouts, disc mount, replaceable derailleur hanger
FORK	SR Suntour XCR-Air, rebound adjustment w/remote lockout, 80/100mm of travel (size specific)
STEM	Stout, 3D-forged alloy, 31.8mm clamp, 6-degree rise
HANDLEBARS	Stout, alloy, 8-degree backsweep, 6-degree upsweep, 10mm rise, 720mm width, 31.8mm
GRIPS	Specialized MTB lock-on
FRONT BRAKE	Shimano BR-M315, hydraulic disc, resin pads
REAR BRAKE	Shimano BR-M315, hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	SRAM X5, high-clamp 34.9mm, 2x10
REAR DERAILLEUR	Shimano Deore, Shadow design, SGS cage, 9-speed
SHIFT LEVERS	Shimano Acera, RapidFire Plus, 9-speed
CASSETTE	Sunrace, 9-speed, 11-36t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	Stout, forged alloy construction, 2x9, anti-corrosion hardware
CHAINRINGS	36/22T
BOTTOM BRACKET	Square taper, 73mm, internal bearings
RIMS	Stout XC 29, alloy disc, double-wall, pinned joint, 21mm inner width, 28/32h
FRONT HUB	Shimano HB-RM35, Center Lock disc, 9x100mm, 28h
REAR HUB	Shimano FH-RM35, Center Lock disc, 10x135mm, 32h
SPOKES	Stainless, 14g, black
FRONT TIRE	Ground Control Sport, 29x2.1", 60TPI, wire bead, Flak Jacket protection
REAR TIRE	Ground Control Sport, 29x2.1", 60TPI, wire bead, Flak Jacket protection
SADDLE	Body Geometry Henge Sport, steel rails, 143mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
81217-5102	ROCKHOPPER COMP 29	NRDCRED/BLK	S
81217-5103			M
81217-5104			L
81217-5105			XL
81217-5106			XXL
81217-5002	ROCKHOPPER COMP 29	CHAR/BLK/FTHYWHT	S
81217-5003			M
81217-5004			L
81217-5005			XL
81217-5006			XXL

ROCKHOPPER SPORT 29



BLK/RKTRED



NENBLU/GRPH

Maybe you're finding your legs on the singletrack, or perhaps you're just dirt-curious? Either way, the Rockhopper Sport 29 is the only bike you need to live out your trail fantasies. It places a focus on long haul performance, and we're not talking about 100-mile trail rides.

- The frame is constructed from lightweight A1 Premium aluminum in order to provide a compliant, durable platform to support our acclaimed Trail 29 Geometry. Combined, you get a bike that's more than efficient on climbs and eager to get down to business on descents.
- Custom SR Suntour XCM fork features 80/100mm (size-specific) of coil-sprung suspension travel that swings well above its weight class.
- A Shimano Alivio rear derailleur controls the rear shifting with durable aplomb. It shifts along a wide gear range, 11-34t, so you can ride confidently knowing that you'll always have the right gear for the hill at hand.

ROCKHOPPER A1					
SIZE	S	M	L	XL	XXL
Stack (mm)	623	634	648	658	677
Reach (mm)	383	388	404	427	441
Head-Tube Length (mm)	105	95	110	120	140
Head-Tube Angle (deg)	70.5	71	71	71	71
B-B Height (mm)	305	305	305	305	305
B-B Drop (mm)	69	69	69	69	69
Trail (mm)	83	80	80	80	80
Fork Length (full) (mm)	495	515	515	515	515
Fork Rake/Offset (mm)	46	46	46	46	46
Front-Center (mm)	632	635	656	682	702
Chain-Stay Length (mm)	450	450	450	450	450
Wheelbase (mm)	1073	1076	1097	1123	1144
Top-Tube Length (horizontal) (mm)	559	582	602	628	648
Bike Stand-Over Height (mm)	749.6	797.2	827.4	865.8	894.6
Seat-Tube Length (mm)	394	444	483	530	560
Seat-Tube Angle (deg)	74.25	73	73	73	73
Handlebar Width (mm)	720	720	720	720	720
Stem Length (mm)	60	70	70	80	90
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	350	350	400	400	400
Crank Length (mm)	170	175	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Trail 29 Geometry ORE down tube, butted tube sets, externally relieved head tube, forged dropouts, reinforced disc mount, replaceable alloy derailleur hanger
FORK	SR Suntour XCM, coil spring, hydraulic lock-out w/Multi-Circuit Damping, 80/100mm of travel (size specific)
STEM	Stout, 3D-forged alloy, 31.8mm clamp, 6-degree rise
HANDLEBARS	Stout, alloy, 8-degree backsweep, 6-degree upsweep, 10mm rise, 720mm width, 31.8mm
GRIPS	Specialized MTB Grip, lock-on
FRONT BRAKE	Shimano BL-M315, hydraulic disc, resin pads, 180/160mm rotor
REAR BRAKE	Shimano BR-M315, hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	Shimano Altus, 34.9mm clamp, down-swing, 7/8-speed
REAR DERAILLEUR	Shimano Alivio, Shadow design, SGS cage, 9-speed
SHIFT LEVERS	Shimano Altus, 8-speed
CASSETTE	Sunrace, 8-speed, 11-34t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Stout, forged alloy construction, 8-speed
CHAINRINGS	44/32/22T
BOTTOM BRACKET	Square taper, 73mm, internal bearings
RIMS	Stout 29, alloy disc, double-wall, pinned joint, 20mm inner width, 32h
FRONT HUB	Shimano Center Lock, disc, 9x100mm QR, 32h
REAR HUB	Shimano Center Lock, disc, 10x135mm QR, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Ground Control Sport, 29x2.1", 60TPI, wire bead, Flak Jacket protection
REAR TIRE	Ground Control Sport, 29x2.1", 60TPI, wire bead, Flak Jacket protection
SADDLE	Body Geometry Henge Sport, steel rails, 143mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
81217-6002	ROCKHOPPER SPORT 29	BLK/RKTRED	S
81217-6003			M
81217-6004			L
81217-6005			XL
81217-6006			XXL
81217-6202	ROCKHOPPER SPORT 29	NENBLU/GRPH	S
81217-6203			M
81217-6204			L
81217-6205			XL
81217-6206			XXL

ROCKHOPPER 29



CNDYRED/HYP



WRMCHAR/NRDCCRED/TL

We've been there. The trail can be a pretty intimidating place—intimidating, that is, until you hit it on the right bike. The Rockhopper 29 is the bike for you to find your confidence on the trail. It features our Trail 29 Geometry that will keep you feeling planted and comfortable over bumpy terrain.

- The frame is constructed from lightweight A1 Premium aluminum in order to provide a compliant, durable platform to support our acclaimed Trail 29 Geometry. Combined, you get a bike that's more than efficient on climbs and eager to get down to business on descents.
- Custom SR Suntour XCT fork features 80/100mm (size-specific) of coil-sprung suspension travel that swings well above its weight class.
- A Shimano Acera rear derailleur is built to with durability in mind, so you can rest assured that you'll have a reliable shifting partner for the long trails ahead.

ROCKHOPPER A1					
SIZE	S	M	L	XL	XXL
Stack (mm)	623	634	648	658	677
Reach (mm)	383	388	404	427	441
Head-Tube Length (mm)	105	95	110	120	140
Head-Tube Angle (deg)	70.5	71	71	71	71
B-B Height (mm)	305	305	305	305	305
B-B Drop (mm)	69	69	69	69	69
Trail (mm)	83	80	80	80	80
Fork Length (full) (mm)	495	515	515	515	515
Fork Rake/Offset (mm)	46	46	46	46	46
Front-Center (mm)	632	635	656	682	702
Chain-Stay Length (mm)	450	450	450	450	450
Wheelbase (mm)	1073	1076	1097	1123	1144
Top-Tube Length (horizontal) (mm)	559	582	602	628	648
Bike Stand-Over Height (mm)	749.6	797.2	827.4	865.8	894.6
Seat-Tube Length (mm)	394	444	483	530	560
Seat-Tube Angle (deg)	74.25	73	73	73	73
Handlebar Width (mm)	720	720	720	720	720
Stem Length (mm)	60	70	70	80	90
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	350	350	400	400	400
Crank Length (mm)	170	175	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Trail 29 Geometry ORE down tube, butted tube sets, externally relieved head tube, forged dropouts, reinforced disc mount, replaceable alloy derailleur hanger
FORK	SR Suntour XCT, coil spring, hydraulic lock-out w/Multi-Circuit Damping, 80/100mm of travel (size specific)
STEM	Stout, 3D-forged alloy, 31.8mm clamp, 6-degree rise
HANDLEBARS	Stout, alloy, 8-degree backsweep, 6-degree upsweep, 10mm rise, 720mm width, 31.8mm
GRIPS	Specialized MTB lock-on
FRONT BRAKE	Shimano BR-M375, mechanical disc, resin pads, 180/160mm rotor
REAR BRAKE	Shimano BR-M375, mechanical disc, resin pads, 160mm rotor
FRONT DERAILLEUR	Shimano Altus, 34.9mm clamp, down-swing, 7/8-speed
REAR DERAILLEUR	Shimano Acera, SGS cage, 7/8-speed
SHIFT LEVERS	Shimano EF510, EZ Fire Plus, 8-speed
CASSETTE	Sunrace, 8-speed, 11-34t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Forged alloy, square taper spindle w/chainguard
CHAINRINGS	44/32/22T
BOTTOM BRACKET	Square taper, 73mm, internal bearings
RIMS	Stout 29, alloy disc, double-wall, pinned joint, 20mm inner width, 32h
FRONT HUB	Shimano Center Lock, disc, 9x100mm QR, 32h
REAR HUB	Shimano Center Lock, disc, 10x135mm QR, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Ground Control Sport, 29x2.1", 60TPI, wire bead, Flak Jacket protection
REAR TIRE	Ground Control Sport, 29x2.1", 60TPI, wire bead, Flak Jacket protection
SADDLE	Body Geometry Henge Sport, steel rails, 143mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
81217-7002	ROCKHOPPER 29	CNDYRED/HYP	S
81217-7003			M
81217-7004			L
81217-7005			XL
81217-7006			XXL
81217-7102	ROCKHOPPER 29	WRMCHAR/NRDCCRED/TL	S
81217-7103			M
81217-7104			L
81217-7105			XL
81217-7106			XXL

PITCH COMP 650B



BLK/HYP



INK/NRDCRED

There's no better time to get out and hit the trail than right now, and with a bike like the Pitch Comp 650b, this is truer than ever. It features a hardtail design that makes it efficient at climbing and rolling on the flats, while being sturdy and dependable on descents.

- The frame is constructed from lightweight A1 Premium Aluminum in order to provide a compliant, durable platform to support our acclaimed Sport Trail 650b Geometry. Combined, you get a bike that's extremely versatile, making it equally capable on the climbs and descents.
- Custom SR Suntour 650b fork features our Multi-Circuit Damping technology to eliminate any "pogo" effect by delivering 80/100mm (size-specific) of hydraulic damped suspension that smooths out rough terrain.
- Shimano Deore rear derailleur provides crisp, reliable shifting that you can count on when the going gets rough. With it, you'll be able to precisely move through the wide, 11-34t gear range to make cruising the flats almost as easy climbing those hills.

PITCH					
SIZE	XS	S	M	L	XL
Stack (mm)	580	580	580	580	599
Reach (mm)	370	391	410	429	449
Head-Tube Length (mm)	100	100	100	100	120
Head-Tube Angle (deg)	70.5	70.5	70.5	70.5	70.5
B-B Height (mm)	301	301	301	301	301
B-B Drop (mm)	48	48	48	48	48
Trail (mm)	79	79	79	79	79
Fork Length (full) (mm)	475	475	475	475	475
Fork Rake/Offset (mm)	42	42	42	42	42
Front-Center (mm)	605	626	645	664	690
Chain-Stay Length (mm)	425	425	425	425	425
Wheelbase (mm)	1025	1046	1065	1084	1110
Top-Tube Length (horizontal) (mm)	536	557	587	606	632
Bike Stand-Over Height (mm)	694	733	780	792	835
Seat-Tube Length (mm)	330	394	444	460	510
Seat-Tube Angle (deg)	74	74	73	73	73
Handlebar Width (mm)	720	720	720	720	720
Stem Length (mm)	60	60	70	80	90
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	300	350	350	400	400
Crank Length (mm)	170	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Sport Trail 650b Geometry, butted tube sets, externally relieved head tube, forged dropouts, reinforced disc mount, replaceable alloy derailleur hanger
FORK	SR Suntour XCR 32 650b, coil spring, custom Multi-Circuit Damping, 80/100mm of travel (size specific)
STEM	Stout 3D-forged alloy, 31.8mm, 6-degree rise
HANDLEBARS	Stout bar, 15mm rise, 9-degree backsweep, 5-degree upsweep, 720mm width, 31.8mm
GRIPS	Specialized MTB Grip, lock-on
FRONT BRAKE	Shimano BR-M315, hydraulic disc, resin pads
REAR BRAKE	Shimano BR-M315, hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	Shimano Altus, 34.9mm clamp, down-swing
REAR DERAILLEUR	Shimano Deore, Shadow design, SGS cage
SHIFT LEVERS	Shimano Altus, 9-speed
CASSETTE	Sunrace, 9-speed, 11-34t
CHAIN	KMC X9, 9-speed w/reusable MissingLink
CRANKSET	Stout, forged alloy construction
CHAINRINGS	44/32/22T
BOTTOM BRACKET	Square taper, 73mm, internal bearings
RIMS	Stout 650b, alloy, disc only, double-wall, 25mm inner width, 32h
FRONT HUB	Shimano Center Lock, disc, 9x100mm QR, 32h
REAR HUB	Shimano Center Lock, disc, 10x135mm QR, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Ground Control Sport, 650bx2.1", 60TPI, wire bead, Flak Jacket protection
REAR TIRE	Ground Control Sport, 650bx2.1", 60TPI, wire bead, Flak Jacket protection
SADDLE	Body Geometry mountain, steel rails, 143mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
85517-5001	PITCH COMP 650B	BLK/HYP	XS
85517-5002			S
85517-5003			M
85517-5004			L
85517-5005			XL
85517-5101	PITCH COMP 650B	INK/NRDCRED	XS
85517-5102			S
85517-5103			M
85517-5104			L
85517-5105			XL

PITCH SPORT 650B



CHAR/BLK



RKTRED/BLK

We know that picking a mountain bike can be a daunting process, what with all of the options and technology floating around out there. But while some suspension platforms and tech pass like fads in the wind, hardtails have stuck around since the advent of the mountain bike. That's why we built our Pitch Sport 650b around a hardtail design.

- The frame is constructed from lightweight A1 Premium Aluminum in order to provide a compliant, durable platform to support our acclaimed Sport Trail 650b Geometry. Combined, you get a bike that's extremely versatile, making it equally capable on the climbs and descents.
- Custom SR Suntour 650b fork pairs a coil spring with our Multi-Circuit Damping technology to eliminate any "pogo" effect by delivering 80/100mm (size-specific) of hydraulic damped suspension that smooths out rough terrain.
- A Shimano Alivio rear derailleur controls the rear shifting with durable aplomb. It shifts along a wide gear range, 11-34t, so you can ride confidently knowing that you'll always have the right gear for the hill at hand.

PITCH					
SIZE	XS	S	M	L	XL
Stack (mm)	580	580	580	580	599
Reach (mm)	370	391	410	429	449
Head-Tube Length (mm)	100	100	100	100	120
Head-Tube Angle (deg)	70.5	70.5	70.5	70.5	70.5
B-B Height (mm)	301	301	301	301	301
B-B Drop (mm)	48	48	48	48	48
Trail (mm)	79	79	79	79	79
Fork Length (full) (mm)	475	475	475	475	475
Fork Rake/Offset (mm)	42	42	42	42	42
Front-Center (mm)	605	626	645	664	690
Chain-Stay Length (mm)	425	425	425	425	425
Wheelbase (mm)	1025	1046	1065	1084	1110
Top-Tube Length (horizontal) (mm)	536	557	587	606	632
Bike Stand-Over Height (mm)	694	733	780	792	835
Seat-Tube Length (mm)	330	394	444	460	510
Seat-Tube Angle (deg)	74	74	73	73	73
Handlebar Width (mm)	720	720	720	720	720
Stem Length (mm)	60	60	70	80	90
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	300	350	350	400	400
Crank Length (mm)	170	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Sport Trail 650b Geometry, butted tube sets, externally relieved head tube, forged dropouts, reinforced disc mount, replaceable alloy derailleur hanger
FORK	SR Suntour XCM 650b, coil spring, custom Multi-Circuit Damping, 80/100mm of travel (size specific)
STEM	Stout 3D-forged alloy, 31.8mm, 6-degree rise
HANDLEBARS	Stout bar, 15mm rise, 9-degree backsweep, 5-degree upsweep, 720mm width, 31.8mm
GRIPS	Specialized MTB Grip, lock-on
FRONT BRAKE	Shimano BR-M315, hydraulic disc, resin pads
REAR BRAKE	Shimano BR-M315, hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	Shimano Altus, 34.9mm clamp, down-swing
REAR DERAILLEUR	Shimano Alivio, Shadow design, SGS cage
SHIFT LEVERS	Shimano Altus, 8-speed
CASSETTE	Sunrace, 8-speed, 11-34t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Stout, forged alloy construction
CHAINRINGS	44/32/22T
BOTTOM BRACKET	Square taper, 73mm, internal bearings
RIMS	Stout 650b, alloy, disc only, double-wall, 25mm inner width, 32h
FRONT HUB	Shimano Center Lock, disc, 9x100mm QR, 32h
REAR HUB	Shimano Center Lock, disc, 10x135mm QR, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Ground Control Sport, 650bx2.1", 60TPI, wire bead, Flak Jacket protection
REAR TIRE	Ground Control Sport, 650bx2.1", 60TPI, wire bead, Flak Jacket protection
SADDLE	Body Geometry mountain, steel rails, 143mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
85517-6001	PITCH SPORT 650B	CHAR/BLK	XS
85517-6002			S
85517-6003			M
85517-6004			L
85517-6005			XL
85517-6101	PITCH SPORT 650B	RKTRED/BLK	XS
85517-6102			S
85517-6103			M
85517-6104			L
85517-6105			XL

PITCH 650B



LTBLU/NRDRED



MONGRN/BLK



BLK/NENBLU

You've thought about it—probably even got out on the dirt or gravel a few times—and now's the time to pull the trigger on a fully-fledged mountain bike. Well, you're in the right place. The Pitch 650b features everything you need to start getting off the road and out on some trails.

- The frame is constructed from lightweight A1 Premium Aluminum in order to provide a compliant, durable platform to support our acclaimed Sport Trail 650b Geometry. Combined, you get a bike that's extremely versatile, making it equally capable on the climbs and descents.
- Custom SR Suntour 650b fork pairs a coil spring with our Multi-Circuit Damping technology to eliminate any "pogo" effect by delivering 80/100mm (size-specific) of hydraulic damped suspension that smooths out rough terrain.
- A Shimano Acera rear derailleur is built to with durability in mind, so you can rest assured that you'll have a reliable shifting partner for the long trails ahead.

PITCH					
SIZE	XS	S	M	L	XL
Stack (mm)	580	580	580	580	599
Reach (mm)	370	391	410	429	449
Head-Tube Length (mm)	100	100	100	100	120
Head-Tube Angle (deg)	70.5	70.5	70.5	70.5	70.5
B-B Height (mm)	301	301	301	301	301
B-B Drop (mm)	48	48	48	48	48
Trail (mm)	79	79	79	79	79
Fork Length (full) (mm)	475	475	475	475	475
Fork Rake/Offset (mm)	42	42	42	42	42
Front-Center (mm)	605	626	645	664	690
Chain-Stay Length (mm)	425	425	425	425	425
Wheelbase (mm)	1025	1046	1065	1084	1110
Top-Tube Length (horizontal) (mm)	536	557	587	606	632
Bike Stand-Over Height (mm)	694	733	780	792	835
Seat-Tube Length (mm)	330	394	444	460	510
Seat-Tube Angle (deg)	74	74	73	73	73
Handlebar Width (mm)	720	720	720	720	720
Stem Length (mm)	60	60	70	80	90
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	300	350	350	400	400
Crank Length (mm)	170	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Sport Trail 650b Geometry, butted tube sets, externally relieved head tube, forged dropouts, reinforced disc mount, replaceable alloy derailleur hanger
FORK	SR Suntour XCT 650b, coil spring, custom Multi-Circuit Damping, 80/100mm travel
STEM	Stout 3D-forged alloy, 31.8mm, 6-degree rise
HANDLEBARS	Stout bar, 15mm rise, 9-degree backsweep, 5-degree upsweep, 720mm width, 31.8mm
GRIPS	Specialized MTB Grip, lock-on
FRONT BRAKE	Shimano BR-M375, mechanical disc, resin pads, 180/160mm rotor
REAR BRAKE	Shimano BR-M375, mechanical disc, resin pads, 160mm rotor
FRONT DERAILLEUR	Shimano Altus, 34.9mm clamp, down-swing, 7/8-speed
REAR DERAILLEUR	Shimano Acera, SGS cage, 8-speed
SHIFT LEVERS	Shimano EF510, EZ Fire Plus, 8-speed
CASSETTE	Sunrace, 8-speed, 11-34t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Forged alloy, square taper spindle w/chainguard
CHAINRINGS	44/32/22T
BOTTOM BRACKET	Square taper, 73mm, internal bearings
RIMS	Stout 650b, alloy, disc only, double-wall, 25mm inner width, 32h
FRONT HUB	Shimano Center Lock, disc, 9x100mm QR, 32h
REAR HUB	Shimano Center Lock, disc, 10x135mm QR, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Ground Control Sport, 650bx2.1", 60TPI, wire bead, Flak Jacket protection
REAR TIRE	Ground Control Sport, 650bx2.1", 60TPI, wire bead, Flak Jacket protection
SADDLE	Body Geometry mountain, steel rails, 143mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
85517-7101	PITCH 650B	LTBLU/NRDRED	XS
85517-7102			S
85517-7103			M
85517-7104			L
85517-7105			XL
85517-7201	PITCH 650B	MONGRN/BLK	XS
85517-7202			S
85517-7203			M
85517-7204			L
85517-7205			XL
85517-7001	PITCH 650B	BLK/NENBLU	XS
85517-7002			S
85517-7003			M
85517-7004			L
85517-7005			XL

HARDROCK DISC 650B



BLK/BLK/HYP



NRDCRED/BLK/KLSIL

No matter your height or experience level, our Hardrock will fit you perfectly. And with durable, performance-driven components, powerful disc brakes, a bump absorbing suspension fork, and our nimble, playful Sport Trail 650b Geometry, you'll be left feeling confident and inspired.

- The frame is constructed from A1 Premium Aluminum in order to provide a lightweight, durable platform to support our acclaimed Sport Trail 650b Geometry. Combined, you get a bike that's efficient on climbs and eager on descents.
- SR Suntour 650b fork features a coil spring that delivers 75mm of trail absorbing travel.
- A Shimano Tourney seven-speed rear derailleur gives you plenty of gear range to make climbing hills a breeze.

HARDROCK 650B					
SIZE	XS	S	M	L	XL
Stack (mm)	583	583	583	583	602
Reach (mm)	370	391	410	429	449
Head-Tube Length (mm)	100	100	100	100	120
Head-Tube Angle (deg)	70.5	70.5	70.5	70.5	70.5
B-B Height (mm)	305	305	305	305	305
B-B Drop (mm)	48	48	48	48	48
Trail (mm)	75	75	75	75	75
Fork Length (full) (mm)	480	480	480	480	480
Fork Rake/Offset (mm)	48	48	48	48	48
Front-Center (mm)	612	633	652	671	697
Chain-Stay Length (mm)	425	425	425	425	425
Wheelbase (mm)	1032	1053	1072	1091	1117
Top-Tube Length (horizontal) (mm)	537	558	588	607	633
Bike Stand-Over Height (mm)	687	724	761	775	813
Seat-Tube Length (mm)	313	373	432	460	510
Seat-Tube Angle (deg)	74	74	73	73	73
Handlebar Width (mm)	700	700	700	700	700
Stem Length (mm)	60	70	70	90	90
Seat Post Length (mm)	300	350	350	400	400
Crank Length (mm)	170	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	A1 Premium Aluminum, forged 3D drop outs, reinforced disc mount, alloy replaceable derailleur hanger
FORK	SR Suntour M3030 650b, 1-1/8" steel steerer, 75mm of travel, 9mm axle, coil spring w/preload adjust
STEM	3D-forged alloy, 31.8mm clamp, 6-degree rise
HANDLEBARS	Flat bar, double-buttressed 6061 alloy, 700mm width, 10-degree upsweep, 4-degree upsweep, 31.8mm
GRIPS	Specialized MTB Grip, lock-on
FRONT BRAKE	Tektro MD-M280, mechanical disc, 160mm rotor
REAR BRAKE	Tektro MD-M280, mechanical disc, 160mm rotor
FRONT DERAILLEUR	Shimano Tourney, top-swing, 34.9mm clamp, 7-speed
REAR DERAILLEUR	Shimano Tourney, 7-speed
SHIFT LEVERS	Shimano EF500, EZ Fire Plus, 7-speed
CASSETTE	Sunrace, 7-speed, 11-34t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Samox, forged alloy, square taper spindle
CHAINRINGS	42/34/24T w/chainguard
BOTTOM BRACKET	Square taper, 73mm, internal bearings
RIMS	650b, disc, alloy, double-wall, pin joint, 25mm inner width, 32h
FRONT HUB	Specialized disc, double-sealed, loose ball bearings, 9mm QR
REAR HUB	Specialized disc, loose ball bearings, QR, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Fast Trak Sport, 650bx2.0", 60TPI, wire bead, Flak Jacket protection
REAR TIRE	Fast Trak Sport, 650bx2.0", 60TPI, wire bead, Flak Jacket protection
SADDLE	Body Geometry mountain, steel rails, 143mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
81117-7201	HARDROCK DISC 650B	BLK/BLK/HYP	XS
81117-7202			S
81117-7203			M
81117-7204			L
81117-7205			XL
81117-7301	HARDROCK DISC 650B	NRDCRED/BLK/KLSIL	XS
81117-7302			S
81117-7303			M
81117-7304			L
81117-7305			XL

HARDROCK 650B



NENBLU/BLK/WHT



BLK/CHAR/RKTRED

We can't help ourselves but to over deliver when it comes to making sure that you have the best possible ride. And with durable, performance-driven components, reliable V-brakes, a bump absorbing suspension fork, and Sport Trail 650b Geometry, the Hardrock V 650b is more than enough bike to get you out there riding dirty.

- The frame is constructed from A1 Premium Aluminum in order to provide a lightweight, durable platform to support our acclaimed Sport Trail 650b Geometry. Combined, you get a bike that's efficient on climbs and eager on descents.
- SR Suntour 650b fork features a coil spring that delivers 75mm of trail absorbing travel.
- A Shimano Tourney seven-speed rear derailleur gives you plenty of gear range to make climbing hills a breeze.

HARDROCK 650B					
SIZE	XS	S	M	L	XL
Stack (mm)	583	583	583	583	602
Reach (mm)	370	391	410	429	449
Head-Tube Length (mm)	100	100	100	100	120
Head-Tube Angle (deg)	70.5	70.5	70.5	70.5	70.5
B-B Height (mm)	305	305	305	305	305
B-B Drop (mm)	48	48	48	48	48
Trail (mm)	75	75	75	75	75
Fork Length (full) (mm)	480	480	480	480	480
Fork Rake/Offset (mm)	48	48	48	48	48
Front-Center (mm)	612	633	652	671	697
Chain-Stay Length (mm)	425	425	425	425	425
Wheelbase (mm)	1032	1053	1072	1091	1117
Top-Tube Length (horizontal) (mm)	537	558	588	607	633
Bike Stand-Over Height (mm)	687	724	761	775	813
Seat-Tube Length (mm)	313	373	432	460	510
Seat-Tube Angle (deg)	74	74	73	73	73
Handlebar Width (mm)	700	700	700	700	700
Stem Length (mm)	60	70	70	90	90
Seat Post Length (mm)	300	350	350	400	400
Crank Length (mm)	170	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	A1 Premium Aluminum, 3D forged dropouts, alloy replaceable derailleur hanger
FORK	SR Suntour M3030 650b, 1-1/8" steel steerer, 75mm of travel, 9mm axle, coil spring w/preload adjust
STEM	3D-forged alloy, 31.8mm clamp, 6-degree rise
HANDLEBARS	Flat bar, double-buttressed 6061 alloy, 700mm width, 10-degree upsweep, 4-degree upsweep, 31.8mm
GRIPS	Specialized MTB Grip, lock-on
FRONT BRAKE	V-brake, linear pull
REAR BRAKE	V-brake, linear pull
FRONT DERAILLEUR	Shimano Tourney, top-swing, 34.9mm clamp, 7-speed
REAR DERAILLEUR	Shimano Tourney, 7-speed
SHIFT LEVERS	Shimano EF500, EZ Fire Plus, 7-speed
CASSETTE	Shimano Tourney freewheel, 7-speed, 14-34t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Samox, forged alloy, square taper spindle
CHAINRINGS	42/34/24T w/chainguard
BOTTOM BRACKET	Square taper, 73mm, internal bearings
RIMS	650b, V-brake, alloy, double-wall, CNC sidewalls, pin joint, 25mm wide, 32h
FRONT HUB	Specialized V-brake, alloy, loose ball bearings, 9mm, QR
REAR HUB	Specialized V-brake, loose ball bearings, QR, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Fast Trak Sport, 650bx2.0", 60TPI, wire bead, Flak Jacket protection
REAR TIRE	Fast Trak Sport, 650bx2.0", 60TPI, wire bead, Flak Jacket protection
SADDLE	Body Geometry mountain, steel rails, 143mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
81117-7101	HARDROCK 650B	NENBLU/BLK/WHT	XS
81117-7102			S
81117-7103			M
81117-7104			L
81117-7105			XL
81117-7001	HARDROCK 650B	BLK/CHAR/RKTRED	XS
81117-7002			S
81117-7003			M
81117-7004			L
81117-7005			XL

S-WORKS DEMO 8



CNDYRED/BLK/HYP

Relentless, fast, aggressive—no matter how you describe it, downhill racing is demanding. Starting with the bike, you're inserting control into a borderline uncontrollable situation wherever you can. But when it comes to harnessing gravity's pull, while also maintaining confident handling, it simply doesn't get any better than the S-Work Demo 8.

- The frame features a full FACT 11m carbon fiber construction for low weight and heightened levels of strength and stiffness, which is amplified by its asymmetrical frame design that still leaves plenty of access. This has also been paired with our proven S3 Geometry that increases maneuverability and responsiveness, while the 200mm of travel at the rear makes the bike capable of taking on the biggest of hits in stride.
- RockShox BoXXer Team 650b fork is nothing short of legendary. With 200mm of travel, a Charger Damper for maximum efficiency, and Power Buldge reinforced lower legs that allow oversized bushings for incredible stiffness, it's easy to see why it's such a fan favorite for gravity fiends.
- Custom SRAM Guide RS brakes w/ Code calipers provide powerful, precise, and highly adjustable braking. Their based on a four-piston caliper design that puts out smooth, dependable stopping power, while the Reach Adjust feature allows you to customize the position for easy, one-finger lever pulls. And with SRAM's SwingLink technology, the cam system minimizes deadband without sacrificing modulation.

DEMO 650				
SIZE	S	M	L	XL
Stack (mm)	614	614	614	614
Reach (mm)	395	420	440	460
Head-Tube Length (mm)	105	105	105	105
Head-Tube Angle (deg)	63.5	63.5	63.5	63.5
B-B Height (mm)	342	342	342	342
B-B Drop (mm)	12	12	12	12
Trail (mm)	118	118	118	118
Fork Length (full) (mm)	590	590	590	590
Fork Rake/Offset (mm)	52	52	52	52
Front-Center (mm)	754	779	799	819
Chain-Stay Length (mm)	430	430	430	430
Wheelbase (mm)	1183	1208	1228	1248
Top-Tube Length (horizontal) (mm)	571	596	616	636
Bike Stand-Over Height (mm)	698	698	698	698
Seat-Tube Length (mm)	367	367	367	367
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	800	800	800	800
Stem Length (mm)	45	45	45	45
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	367	367	367	367
Crank Length (mm)	165	165	165	165

SPECS

All specs are subject to change without notice.

FRAME	FACT 11m, S3 Geometry, carbon front triangle, full carbon link and rear end, FACT IS construction, BB30, full internal cable routing, 135mm dropouts, lipped and sealed cartridge bearing pivots, replaceable derailleur hanger, 200mm of travel
REAR SHOCK	Custom Öhlins TTX, Twin-Tube design, high and low-speed compression adjust, rebound adjust, 9.5x3"
FORK	RockShox BoXXer Team 650b, coil spring, S: Extra soft spring, M: Soft spring, L: Medium spring, XL: Firm spring, 200mm of travel, charger damper, compression adjust, rebound adjust, alloy steerer, 48mm offset, Maxle Lite DH
STEM	Specialized P.Series MTB, forged alloy, 4-bolt, 45mm
HANDLEBARS	Specialized DH, FACT carbon, 6-degree upsweep, 8-degree backsweep, 27mm rise, 780mm, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Custom SRAM Guide, Guide lever with Code 4-piston caliper, hydraulic disc, metallic pads, 200mm rotor
REAR BRAKE	Custom SRAM Guide, Guide lever with Code 4-piston caliper, hydraulic disc, metallic pads, 180mm rotor
REAR DERAILLEUR	SRAM X01 DH, short cage, 7-speed
SHIFT LEVERS	XO DH, 7-speed, trigger
CASSETTE	SRAM X01 DH, 7-speed, 10-24t
CHAIN	SRAM PC-1130, 11-speed w/PowerLink
CRANKSET	SRAM X0 DH, BB30, carbon arms, triple base w/Gamut bashguard 165mm
CHAINRINGS	SRAM 34T
BOTTOM BRACKET	SRAM BB30, 83mm
RIMS	Roval 650b, alloy, 24mm inner width, 32h
FRONT HUB	Specialized disc, alloy flange & disc mount, sealed cartridge bearings, 20mm thru-axle, 32h
REAR HUB	Custom DT Swiss 350, 135mm spacing, SRAM XD driver, 54T ratchet, 12mm thru-axle, 32h
SPOKES	DT Swiss Competition, stainless, black 1.8/2.0"
FRONT TIRE	Butcher, DH casing, 650bx2.5", 60TPI, wire bead
REAR TIRE	Slaughter, DH casing, 650bx2.3", 60TPI, wire bead
SADDLE	Phenom Expert, Adaptive Edge design, hollow titanium rails, 143mm
SEATPOST	Thomson, alloy, straight, 12-degree clamp

PART NO.	DESCRIPTION	COLOR	SIZE
99917-0002	DEMO SW 8 CARBON	CNDYRED/BLK/HYP	SHORT
99917-0003			MEDIUM
99917-0004			LONG
99917-0005			EXTRA LONG

DEMO 8 | CARBON



LTBLU/NRDCRED



BLK

When it comes to the stiffness, lightweight, and strength required for downhill, you just can't beat a carbon fiber frame construction. That's while you'll find our carbon FACT 10m frame was used to create the acclaimed Demo 8 | Carbon.

- The frame features a full FACT 10m carbon fiber construction for low weight and heightened levels of strength and stiffness, which is amplified by its asymmetrical frame design that still leaves plenty of access. This has also been paired with our proven S3 Geometry that increases maneuverability and responsiveness, while the 200mm of travel at the rear makes the bike capable of taking on the biggest of hits in stride.
- RockShox BoXXer RC 650b fork is purposefully designed for the most demanding terrain on earth. With 200mm of travel, Motion Control IS damping for maximum efficiency, and Power Buldge reinforced lower legs that allow oversized bushings for incredible stiffness, it'll leave you with nothing but confidence.
- SRAM Guide RS brakes provide powerful, precise, and highly adjustable braking. Their based on a four-piston caliper design that puts out smooth, dependable stopping power, while the Reach Adjust feature allows you to customize the position for easy, one-finger lever pulls. And with SRAM's SwingLink technology, the cam system minimizes deadband without sacrificing modulation.

DEMO 650

SIZE	S	M	L	XL
Stack (mm)	614	614	614	614
Reach (mm)	395	420	440	460
Head-Tube Length (mm)	105	105	105	105
Head-Tube Angle (deg)	63.5	63.5	63.5	63.5
B-B Height (mm)	342	342	342	342
B-B Drop (mm)	12	12	12	12
Trail (mm)	118	118	118	118
Fork Length (full) (mm)	590	590	590	590
Fork Rake/Offset (mm)	52	52	52	52
Front-Center (mm)	754	779	799	819
Chain-Stay Length (mm)	430	430	430	430
Wheelbase (mm)	1183	1208	1228	1248
Top-Tube Length (horizontal) (mm)	571	596	616	636
Bike Stand-Over Height (mm)	698	698	698	698
Seat-Tube Length (mm)	367	367	367	367
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	800	800	800	800
Stem Length (mm)	45	45	45	45
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	300	300	300	300
Crank Length (mm)	165	165	165	165

SPECS

All specs are subject to change without notice.

FRAME	FACT 10m carbon, S3 Geometry, carbon front triangle, carbon link and seatstay, FACT IS construction, BB30, full internal cable routing, 135mm dropouts, lipped and sealed cartridge bearing pivots, replaceable derailleur hanger, 200mm of travel
REAR SHOCK	Custom Öhlins TTX, Twin-Tube design, high and low-speed compression adjust, rebound adjust, 9.5x3"
FORK	RockShox BoXXer RC 650b, S: Extra soft spring, M: Soft spring, L: Medium spring, XL: Firm spring, 200mm of travel, compression adjust, rebound adjust, alloy steerer, 48mm offset, Maxle Lite DH
STEM	Specialized P.Series MTB, forged alloy, 4-bolt, 45mm
HANDLEBARS	Specialized DH, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 25mm rise, 800mm, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide R, hydraulic disc, metallic pads, 200mm Centerline Rotor
REAR BRAKE	SRAM Guide R, hydraulic disc, metallic pads, 180mm rotor
REAR DERAILLEUR	SRAM GX DH, medium cage, 7-speed
SHIFT LEVERS	SRAM GX, 7-speed, trigger
CASSETTE	SRAM PG-720 DH, 11-25t
CHAIN	SRAM PC-1110, 11-speed w/PowerLink
CRANKSET	SRAM Descendant, BB30, 7050 alloy arms, 165mm
CHAINRINGS	SRAM 36T
BOTTOM BRACKET	SRAM BB30, 83mm
RIMS	Roval 650b, alloy, 24mm inner width, 32h
FRONT HUB	Specialized disc, alloy flange & disc mount, sealed cartridge bearings, 20mm thru-axle, 32h
REAR HUB	Specialized disc, 12x135mm spacing, sealed cartridge bearings, 32h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Butcher, DH casing, 650bx2.5", 60TPI, wire bead
REAR TIRE	Slaughter, DH casing, 650bx2.3", 60TPI, wire bead
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized, 6061 alloy, 2-bolt clamp, 0mm setback, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
94517-3102	DEMO 8 CARBON	LTBLU/NRDCRED	SHORT
94517-3103			MEDIUM
94517-3104			LONG
94517-3105			EXTRA LONG
94517-3002	DEMO 8 CARBON	BLK	SHORT
94517-3003			MEDIUM
94517-3004			LONG
94517-3005			EXTRA LONG

DEMO 8 | ALLOY



MONGRN/RKTRED/WHT



WRMCHAR/BLK

No material has earned its keep on the downhill circuit like our M5 aluminum. The reasons for this are stacking, but primarily, it can all be summed up by stiffness, light overall weight, and strength. That's why you'll find that our Demo 8 | Alloy was constructed from it.

- M5 alloy construction works in tandem with our S3 Geometry, an asymmetric frame design, and a 1.5" forged head tube to create the ultimate race machine. The design is relatively compact in order increase maneuverability and responsiveness, while the 200mm of travel at the rear makes the bike capable of taking on the biggest of hits in stride. And to fill out all of the details that make the difference on race day, we've included an ISCG '05 mount for chain guides and a rear derailleur protector to keep you shifting smoothly through rock gardens and unexpected strikes.
- RockShox BoXXer RC 650b fork is purposefully designed for the most demanding terrain on earth. With 200mm of travel, Motion Control IS damping for maximum efficiency, and Power Buldge reinforced lower legs that allow oversized bushings for incredible stiffness, it'll leave you with nothing but confidence.
- SRAM Guide R brakes provide powerful, precise, and highly adjustable braking. Their based on a four-piston caliper design that puts out smooth, dependable stopping power, while the Reach Adjust feature allows you to customize the position for easy, one-finger lever pulls. And with SRAM's SwingLink technology, the cam system minimizes deadband without sacrificing modulation.

DEMO 650

SIZE	S	M	L	XL
Stack (mm)	614	614	614	614
Reach (mm)	395	420	440	460
Head-Tube Length (mm)	105	105	105	105
Head-Tube Angle (deg)	63.5	63.5	63.5	63.5
B-B Height (mm)	342	342	342	342
B-B Drop (mm)	12	12	12	12
Trail (mm)	118	118	118	118
Fork Length (full) (mm)	590	590	590	590
Fork Rake/Offset (mm)	52	52	52	52
Front-Center (mm)	754	779	799	819
Chain-Stay Length (mm)	430	430	430	430
Wheelbase (mm)	1183	1208	1228	1248
Top-Tube Length (horizontal) (mm)	571	596	616	636
Bike Stand-Over Height (mm)	698	698	698	698
Seat-Tube Length (mm)	367	367	367	367
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	800	800	800	800
Stem Length (mm)	45	45	45	45
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	300	300	300	300
Crank Length (mm)	165	165	165	165

SPECS

All specs are subject to change without notice.

FRAME	M5 alloy, S3 Geometry, carbon link and seatstay, BB30, full internal cable routing, 135mm dropouts, lipped and sealed cartridge bearing pivots, replaceable derailleur hanger, 200mm of travel
REAR SHOCK	FOX/Specialized Van RC, rebound & compression adjust, 9.5x3.0"
FORK	RockShox BoXXer RC 650b, S: Extra soft spring, M: Soft spring, L: Medium spring, XL: Firm spring, 200mm of travel, compression adjust, rebound adjust, alloy steerer, 48mm offset, Maxle Lite DH
STEM	Specialized P.Series MTB, forged alloy, 4-bolt, 45mm
HANDLEBARS	Specialized DH, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 25mm rise, 800mm, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide R, hydraulic disc, metallic pads, 200mm Centerline rotor
REAR BRAKE	SRAM Guide R, hydraulic disc, metallic pads, 180mm rotor
REAR DERAILLEUR	SRAM GX Type 2.1, short cage, 10-speed
SHIFT LEVERS	SRAM X7, 10-speed, trigger
CASSETTE	SRAM PG-1030, 10-speed, 11-36t
CHAIN	SRAM PC-1031, 10-speed w/PowerLink
CRANKSET	SRAM Descendant, BB30, 7050 alloy arms, 32T chainring, 165mm
CHAINRINGS	SRAM 36T
BOTTOM BRACKET	SRAM BB30, 83mm
RIMS	Roval 650b, alloy, 24mm inner width, 32h
FRONT HUB	Specialized disc, alloy flange & disc mount, sealed cartridge bearings, 20mm thru-axle, 32h
REAR HUB	Specialized disc, 12x135mm spacing, sealed cartridge bearings, 32h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Butcher, DH casing, 650bx2.5", 60TPI, wire bead
REAR TIRE	Slaughter, DH casing, 650bx2.3", 60TPI, wire bead
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized, 6061 alloy, 2-bolt clamp, 0mm setback, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
94516-5102	DEMO 8 ALLOY	MONGRN/RKTRED/WHT	SHORT
94516-5103			MEDIUM
94516-5104			LONG
94516-5105			EXTRA LONG
94516-5202	DEMO 8 ALLOY	WRMCHAR/BLK	SHORT
94516-5203			MEDIUM
94516-5204			LONG
94516-5205			EXTRA LONG

DEMO 8 II ALLOY



WRMCHAR/RKTRED/BLK

What happens when you combine our World-Cup-proven S3 Geometry, an asymmetric frame design, a revolutionary Öhlins rear shock, and a build kit that serves up nothing but pure performance? You get our Demo 8 II Alloy, of course.

- M5 alloy construction works in tandem with our S3 Geometry, an asymmetric frame design, and a 1.5" forged head tube to create the ultimate race machine. The design is relatively compact in order to increase maneuverability and responsiveness, while the 200mm of travel at the rear makes the bike capable of taking on the biggest of hits in stride. And to fill out all of the details that make the difference on race day, we've included an ISCG '05 mount for chain guides and a rear derailleur protector to keep you shifting smoothly through rock gardens and unexpected strikes.
- RockShox BoXXer Team 650b fork is nothing short of legendary. With 200mm of coil-sprung travel with frame size-specific spring feel, a Charger Damper for maximum efficiency, and Power Buldge reinforced lower legs that allow oversized bushings for incredible stiffness, it's easy to see why it's such a fan favorite for gravity fiends.
- SRAM Guide RS brakes w/ Code calipers provide powerful, precise, and highly adjustable braking. Their based on a four-piston caliper design that puts out smooth, dependable stopping power, while the Reach Adjust feature allows you to customize the position for easy, one-finger lever pulls. And with SRAM's SwingLink technology, the cam system minimizes deadband without sacrificing modulation.

DEMO 650

SIZE	S	M	L	XL
Stack (mm)	614	614	614	614
Reach (mm)	395	420	440	460
Head-Tube Length (mm)	105	105	105	105
Head-Tube Angle (deg)	63.5	63.5	63.5	63.5
B-B Height (mm)	342	342	342	342
B-B Drop (mm)	12	12	12	12
Trail (mm)	118	118	118	118
Fork Length (full) (mm)	590	590	590	590
Fork Rake/Offset (mm)	52	52	52	52
Front-Center (mm)	754	779	799	819
Chain-Stay Length (mm)	430	430	430	430
Wheelbase (mm)	1183	1208	1228	1248
Top-Tube Length (horizontal) (mm)	571	596	616	636
Bike Stand-Over Height (mm)	698	698	698	698
Seat-Tube Length (mm)	367	367	367	367
Seat-Tube Angle (deg)	74	74	74	74
Handlebar Width (mm)	800	800	800	800
Stem Length (mm)	45	45	45	45
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	367	367	367	367
Crank Length (mm)	165	165	165	165

SPECS

All specs are subject to change without notice.

FRAME	M5 alloy, S3 Geometry, carbon link and seatstay, BB30, full internal cable routing, 135mm dropouts, lipped and sealed cartridge bearing pivots, replaceable derailleur hanger, 200mm of travel
REAR SHOCK	Custom Öhlins TTX, Twin-Tube design, high and low-speed compression adjust, rebound adjust, 9.5x3"
FORK	RockShox BoXXer Team 650b, coil spring, S: Extra soft spring, M: Soft spring, L: Medium spring, XL: Firm spring, 200mm of travel, charger damper, compression adjust, rebound adjust, alloy steerer, 48mm offset, Maxle Lite DH
STEM	Specialized P-Series MTB, forged alloy, 4-bolt, 45mm
HANDLEBARS	Specialized DH, 7050 alloy, 8-degree backsweep, 6-degree upsweep, 25mm rise, 800mm, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide RS lever, hydraulic disc, organic pads, Code calipers, 200mm rotor
REAR BRAKE	SRAM Guide RS, hydraulic disc, organic pads, Guide S4 4-piston caliper, 180mm rotor
REAR DERAILLEUR	SRAM XO Type 2.1, short cage, 10-speed
SHIFT LEVERS	SRAM X9, 10-speed, trigger
CASSETTE	SRAM PG-1030, 10-speed, 11-36t
CHAIN	SRAM PC-1031, 10-speed w/PowerLink
CRANKSET	SRAM XO DH, BB30, carbon arms, triple base w/Gamut bashguard 165mm
CHAINRINGS	SRAM 36T
BOTTOM BRACKET	SRAM BB30, 83mm
RIMS	Roval 650b, alloy, 24mm inner width, 32h
FRONT HUB	Specialized disc, alloy flange & disc mount, sealed cartridge bearings, 20mm thru-axle, 32h
REAR HUB	Custom DT Swiss 350, 135mm spacing, SRAM XD driver, 54T ratchet, 12mm thru-axle, 32h
SPOKES	DT Swiss Industry, stainless, 3x, 2.0"
FRONT TIRE	Butcher, DH casing, 650bx2.5", 60TPI, wire bead
REAR TIRE	Slaughter, DH casing, 650bx2.3", 60TPI, wire bead
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Thomson, alloy, straight, 12-degree clamp

PART NO.	DESCRIPTION	COLOR	SIZE
94516-1002	DEMO 8 II ALLOY	WRMCHAR/RKTRED/BLK	SHORT
94516-1003			MEDIUM
94516-1004			LONG
94516-1005			EXTRA LONG

S-WORKS DEMO 8 FRAME



CNDYRED/BLK/HYP

Let's not kid ourselves—downhill is all about speed. And when it comes to squeezing every last ounce of fast out of a track, your machine needs to be just as fine-tuned as your skills. That's why we offer our legendary, World-Cup-proven S-Works Demo 8 as a frameset.

- The frame features a full FACT 11m carbon fiber construction for low weight and heightened levels of strength and stiffness, which is amplified by its asymmetrical frame design that still leaves plenty of access. This has also been paired with our proven S3 Geometry that increases maneuverability and responsiveness, while the 200mm of travel at the rear makes the bike capable of taking on the biggest of hits in stride.
- Custom Öhlins rear shock delivers unparalleled DH performance. It offers high/low speed compression adjust that stands independent of the rebound adjust, enabling you to fine-tune the shock for the track at hand. It's 200mm of coil-sprung travel that stands without rival, and you won't find anywhere else.
- Thomson alloy seatpost features one of the most durable constructions out there, without coming at the expense of a high overall weight.

SPECS	All specs are subject to change without notice.
FRAME	FACT 11m, S3 Geometry, carbon front triangle, full carbon link and rear end, FACT IS construction, BB30, full internal cable routing, 135mm dropouts, lipped and sealed cartridge bearing pivots, replaceable derailleur hanger, 200mm of travel
REAR SHOCK	Custom Öhlins TTX, Twin-Tube design, high and low-speed compression adjust, rebound adjust, 9.5x3"
BOTTOM BRACKET	SRAM BB30, 83mm
SEATPOST	Thomson, alloy, straight, 12-degree clamp

PART NO.	DESCRIPTION	COLOR	SIZE
79917-0002	DEMO SW 8 CARBON FRM	CNDYRED/BLK/HYP	SHORT
79917-0003			MEDIUM
79917-0004			LONG
79917-0005			EXTRA LONG

DEMO 650				
SIZE	S	M	L	XL
Stack (mm)	614	614	614	614
Reach (mm)	395	420	440	460
Head-Tube Length (mm)	105	105	105	105
Head-Tube Angle (deg)	63.5	63.5	63.5	63.5
B-B Height (mm)	342	342	342	342
B-B Drop (mm)	12	12	12	12
Trail (mm)	118	118	118	118
Fork Length (full) (mm)	590	590	590	590
Fork Rake/Offset (mm)	52	52	52	52
Front-Center (mm)	754	779	799	819
Chain-Stay Length (mm)	430	430	430	430
Wheelbase (mm)	1183	1208	1228	1248
Top-Tube Length (horizontal) (mm)	571	596	616	636
Bike Stand-Over Height (mm)	698	698	698	698
Seat-Tube Length (mm)	367	367	367	367
Seat-Tube Angle (deg)	74	74	74	74
Seat Post Length (mm)	367	367	367	367

DEMO 8 ALLOY FRAME



BLK/GLDORG/WHT

Let's not kid ourselves—downhill is all about speed. And when it comes to squeezing every last ounce of fast out of a track, your machine needs to be just as fine-tuned as your skills. That's why we offer our legendary, World-Cup-proven S-Works Demo 8 as a frameset.

- M5 alloy construction works in tandem with our S3 Geometry, an asymmetric frame design, and a 1.5" forged head tube to create the ultimate race machine. The design is relatively compact in order increase maneuverability and responsiveness, while the 200mm of travel at the rear makes the bike capable of taking on the biggest of hits in stride. And to fill out all of the details that make the difference on race day, we've included an ISCG '05 mount for chain guides and a rear derailleur protector to keep you shifting smoothly through rock gardens and unexpected strikes.
- Custom Öhlins rear shock delivers unparalleled DH performance. It offers high/low speed compression adjust that stands independent of the rebound adjust, enabling you to fine-tune the shock for the track at hand. It's 200mm of coil-sprung travel that stands without rival, and you won't find anywhere else.
- Thomson alloy seatpost features one of the most durable constructions out there, without coming at the expense of a high overall weight.

SPECS	All specs are subject to change without notice.
FRAME	M5 alloy, S3 Geometry, carbon link and seatstay, BB30, full internal cable routing, 135mm dropouts, lipped and sealed cartridge bearing pivots, replaceable derailleur hanger, 200mm of travel
REAR SHOCK	Custom Öhlins TTX, Twin-Tube design, high and low-speed compression adjust, rebound adjust, 9.5x3"
BOTTOM BRACKET	SRAM BB30, 83mm
SEATPOST	Thomson, alloy, straight, 12-degree clamp

PART NO.	DESCRIPTION	COLOR	SIZE
74516-1002	DEMO 8 ALLOY FRM	BLK/GLDORG/WHT	SHORT
74516-1003			MEDIUM
74516-1004			LONG
74516-1005			EXTRA LONG

DEMO 650				
SIZE	S	M	L	XL
Stack (mm)	614	614	614	614
Reach (mm)	395	420	440	460
Head-Tube Length (mm)	105	105	105	105
Head-Tube Angle (deg)	63.5	63.5	63.5	63.5
B-B Height (mm)	342	342	342	342
B-B Drop (mm)	12	12	12	12
Trail (mm)	118	118	118	118
Fork Length (full) (mm)	590	590	590	590
Fork Rake/Offset (mm)	52	52	52	52
Front-Center (mm)	754	779	799	819
Chain-Stay Length (mm)	430	430	430	430
Wheelbase (mm)	1183	1208	1228	1248
Top-Tube Length (horizontal) (mm)	571	596	616	636
Bike Stand-Over Height (mm)	698	698	698	698
Seat-Tube Length (mm)	367	367	367	367
Seat-Tube Angle (deg)	74	74	74	74
Seat Post Length (mm)	367	367	367	367

S-WORKS FATBOY



CARB/BLK/RKTRED

What started as "serious fun" has quickly become a serious change to what we want out of bike. The fat revolution is here, and with races becoming more and more prevalent, we knew that our much-heralded Fatboy could stand to go on a diet. Say hello to the S-Works Fatboy Carbon.

- An immaculate FACT carbon fiber construction ensures that the frame is lightweight and plenty stiff in all the right places. Internal cable routing is also incorporated; ensuring that slush, sand, snow, or dirt will have no bearing on performance out on the trail
- A FACT carbon fiber fork provides tons of compliance and absorbs chatter, while simultaneously keeping the overall weight of the bike down
- HED Big Deal carbon wheels are light, fast, and 85mm-wide to make sure that you get all of the traction and floatation that fat bikes are known for, only without a weight penalty or having to make any sacrifices to climbing prowess

FATBOY CARBON

SIZE	S	M	L	XL
Stack (mm)	602	602	617	632
Reach (mm)	395	420	437	458
Head-Tube Length (mm)	94	94	110	125
Head-Tube Angle (deg)	70.5	70.5	70.5	70.5
B-B Height (mm)	307	307	307	307
B-B Drop (mm)	60	60	60	60
Trail (mm)	80	80	80	80
Fork Length (full) (mm)	496	496	496	496
Fork Rake/Offset (mm)	47	47	47	47
Front-Center (mm)	640	665	687	713
Chain-Stay Length (mm)	455	455	455	455
Wheelbase (mm)	1088	1113	1135	1161
Top-Tube Length (horizontal) (mm)	579	604	626	651
Bike Stand-Over Height (mm)	738.5	752	778.3	807.5
Seat-Tube Length (mm)	394	434	470	520
Seat-Tube Angle (deg)	73	73	73	73
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	60	60	75	75
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	350	350	400	400
Crank Length (mm)	170	175	175	175

SPECS

All specs are subject to change without notice.

FRAME	FACT 10m, full carbon frame, 12x197mm thru-axle rear, internal cable routing, ISCG XC tabs, suspension corrected for 100mm of travel
FORK	Carbon, 46mm offset, tapered steerer, 150mm axle spacing
STEM	Syntace F109, 6-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Trail, FACT carbon, 6-degree upsweep, 8-degree backsweep, 27mm rise, 750mm width, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide RS carbon, hydraulic disc, organic pads, carbon lever, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide RS carbon, hydraulic disc, organic pads, carbon lever, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM XX1 Type 2.1, 11-speed
SHIFT LEVERS	SRAM XX1, 11-speed, trigger
CASSETTE	SRAM XX1, 11-speed, 10-42t
CHAIN	SRAM XX1, 11-speed
RIMS	HED Big Deal, carbon, single wall, tubeless, 85mm wide, 32h
FRONT HUB	DT Swiss Big Ride 350, 6-bolt, 15x150mm thru-axle, 32h
REAR HUB	DT Swiss Big Ride 350, 6-bolt, 12x197mm thru-axle, XD driver, 32h
SPOKES	DT Swiss Revolution
FRONT TIRE	Fast Trak, Control Casing, 26x4.0", 120TPI, 2Bliss Ready, folding bead
REAR TIRE	Fast Trak, Control Casing, 26x4.0", 120TPI, 2Bliss Ready, folding bead
SADDLE	Body Geometry Phenom Expert, hollow titanium rails, 143mm
SEATPOST	Race Face Next SL, 0mm offset, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
95916-0002	FATBOY S-WORKS CARBON	CARB/BLK/RKTRED	S
95916-0003			M
95916-0004			L
95916-0005			XL

FATBOY EXPERT CARBON



WHT/BLK/RED



CARB/BLK/BLU

We know that we're not blowing any minds when we say carbon is pretty cool. Compared to an alloy frame construction, it keeps weight down, does an exceptional job of absorbing bumps and vibrations, and it allows us to take more liberties to fine tune the ride quality. For these reasons, we made the Fatboy Expert Carbon.

- An immaculate FACT carbon fiber construction ensures that the frame is lightweight and plenty stiff in all the right places. Internal cable routing is also incorporated; ensuring that slush, sand, snow, or dirt will have no bearing on performance out on the trail
- A FACT carbon fiber fork provides tons of compliance and absorbs chatter, while simultaneously keeping the overall weight of the bike down
- Alloy rims have been laced to DT Swiss 370 hubs to form a wheelset that's dependable, rugged, and efficient. So whether you're trail riding or plowing through the snow, these wheels will be the perfect mix of performance and strength

FATBOY CARBON				
SIZE	S	M	L	XL
Stack (mm)	602	602	617	632
Reach (mm)	395	420	437	458
Head-Tube Length (mm)	94	94	110	125
Head-Tube Angle (deg)	70.5	70.5	70.5	70.5
B-B Height (mm)	307	307	307	307
B-B Drop (mm)	60	60	60	60
Trail (mm)	80	80	80	80
Fork Length (full) (mm)	496	496	496	496
Fork Rake/Offset (mm)	47	47	47	47
Front-Center (mm)	640	665	687	713
Chain-Stay Length (mm)	455	455	455	455
Wheelbase (mm)	1088	1113	1135	1161
Top-Tube Length (horizontal) (mm)	579	604	626	651
Bike Stand-Over Height (mm)	738.5	752	778.3	807.5
Seat-Tube Length (mm)	394	434	470	520
Seat-Tube Angle (deg)	73	73	73	73
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	60	60	70	70
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	350	350	400	400
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 10m, full carbon frame, 12x197mm thru-axle rear, internal cable routing, ISCG XC tabs, suspension corrected for 100mm of travel
FORK	Carbon, 46mm offset, tapered steerer, 150mm axle spacing
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized Mini-rise, 7050 alloy, 8-backsweep, 6-upsweep, 10mm rise, 750mm width, 31.8mm clamp
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 200/180mm rotor
REAR BRAKE	SRAM Guide R, hydraulic disc, organic pads, Guide S4 4-piston caliper, 180/160mm rotor
REAR DERAILLEUR	SRAM XO1, carbon cage, 11-speed
SHIFT LEVERS	SRAM XO1, 11-speed, trigger
CASSETTE	SRAM XG-1180, 11-speed, 10-42t
CHAIN	SRAM XX1, 11-speed
RIMS	HED Big Deal, carbon, single wall, tubeless, 85mm wide, 32h
FRONT HUB	Specialized Stout XC, alloy disc, double-sealed cartridge bearings, 15x150mm thru-axle, 32h
REAR HUB	Stout XC Pro, disc alloy, SRAM XD driver body, sealed cartridge bearings, 12x197mm thru-axle, 32h
SPOKES	Stainless, butted, 2.0/1.8/2.0mm, black
FRONT TIRE	Ground Control 2Bliss Ready, 26x4.0", 120TPI, 2Bliss Ready, folding bead
REAR TIRE	Ground Control Fat, Control casing, 26x4.0", 120TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Phenom Expert, Adaptive Edge design, hollow titanium rails, 143mm
SEATPOST	Race Face Next SL, 0mm offset, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
99516-3102	FATBOY EXPERT CARBON	WHT/BLK/RED	S
99516-3103			M
99516-3104			L
99516-3105			XL
99516-3002	FATBOY EXPERT CARBON	CARB/BLK/BLU	S
99516-3003			M
99516-3004			L
99516-3005			XL

FATBOY COMP CARBON



RKTRED/BLK/GRY



CARB/WRMPRLWHT/RED

Every now and again, we're all faced with going on a diet, and the same is true for our Fatboy. With the new Fatboy Comp Carbon, we've elevated the fat bike platform to a higher level of performance, strength, and efficiency.

- An immaculate FACT carbon fiber construction ensures that the frame is lightweight and plenty stiff in all the right places. Internal cable routing is also incorporated; ensuring that slush, sand, snow, or dirt will have no bearing on performance out on the trail
- A FACT carbon fiber fork provides tons of compliance and absorbs chatter, while simultaneously keeping the overall weight of the bike down
- Alloy rims have been laced to our XC Pro hubs to form a wheelset that's dependable, rugged, and efficient. So whether you're trail riding or plowing through the snow, these wheels will be the perfect mix of performance and strength

FATBOY CARBON				
SIZE	S	M	L	XL
Stack (mm)	602	602	617	632
Reach (mm)	395	420	437	458
Head-Tube Length (mm)	94	94	110	125
Head-Tube Angle (deg)	70.5	70.5	70.5	70.5
B-B Height (mm)	307	307	307	307
B-B Drop (mm)	60	60	60	60
Trail (mm)	80	80	80	80
Fork Length (full) (mm)	496	496	496	496
Fork Rake/Offset (mm)	47	47	47	47
Front-Center (mm)	640	665	687	713
Chain-Stay Length (mm)	455	455	455	455
Wheelbase (mm)	1088	1113	1135	1161
Top-Tube Length (horizontal) (mm)	579	604	626	651
Bike Stand-Over Height (mm)	738.5	752	778.3	807.5
Seat-Tube Length (mm)	394	434	470	520
Seat-Tube Angle (deg)	73	73	73	73
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	60	60	75	75
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	350	350	400	400
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 10m, full carbon frame, 12x197mm thru-axle rear, internal cable routing, ISCG XC tabs, suspension corrected for 100mm of travel
FORK	Carbon, 46mm offset, tapered steerer, 150mm axle spacing
STEM	Specialized Trail, 3D forged alloy, 4-bolt, 6-degree rise
HANDLEBARS	Specialized XC, butted 6061 alloy, 8-degree backsweep, 6-degree upsweep, 10mm rise, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Shimano Deore, hydraulic disc, resin pads, post mount, 160mm rotor
REAR BRAKE	Shimano Deore, hydraulic disc, resin pads, 160mm rotor
REAR DERAILLEUR	SRAM XO, long cage, 10-speed
SHIFT LEVERS	SRAM X9, 10-speed, trigger
CASSETTE	Sunrace, 10-speed, 11-42t
CHAIN	10-speed, EXTRA lightweight hollow outer links w/reusable Missing Link # CL559R
CRANKSET	RaceFace Turbine Cinch crankset, alloy, 30mm spindle, direct-mount chainring, 76.5mm chainline, 11-speed
RIMS	Specialized 26" disc front, 21mm depth, 86mm internal width, 32h
FRONT HUB	Specialized Stout XC, alloy disc, double-sealed cartridge bearings, 15x150mm thru-axle, 32h
REAR HUB	Stout XC, disc alloy, SRAM XD driver body, sealed cartridge bearings, 12x148mm thru-axle, 32h
SPOKES	Stainless, butted, 2.0/1.8/2.0mm, black
FRONT TIRE	Ground Control 2Bliss Ready, 26x4.0", 120TPI, 2Bliss Ready, folding bead
REAR TIRE	Ground Control Fat, Control casing, 26x4.0", 120TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Alloy, 2-bolt clamp, 12.5mm offset, 30.9mm, anti-corrosion hardware

PART NO.	DESCRIPTION	COLOR	SIZE
99516-5402	FATBOY COMP CARBONRKTRED/BLK/GRY		S
99516-5403			M
99516-5404			L
99516-5405			XL
99516-5302	FATBOY COMP CARBONCARB/WRMPRLWHT/RED		S
99516-5303			M
99516-5304			L
99516-5305			XL

FATBOY



BLK/BBYBLU/RKTRED



WHT/BLK/NRDCCRED

Going fat isn't just a fun way to ride—it's a ride revolution. The security and control that the wheel system found on our Fatboy provides is unparalleled. You get dramatically more traction, grip, and floatation than with traditional mountain tires, all without sacrificing much to climbing efficiency.

- The frame features an M5 alloy construction that provides the ideal blend of efficiency and durability, while the geometry creates a roomy top tube and short chainstays for easy climbing and confident descending
- A FACT carbon fiber fork provides tons of compliance and absorbs chatter, while simultaneously keeping the overall weight of the bike down
- Tough, ultra-wide alloy rims are dependable and rugged. So whether you're trail riding or plowing through the snow, these wheels will be the perfect mix of performance and strength

FATBOY RIGID				
SIZE	S	M	L	XL
Stack (mm)	590	600	614	628
Reach (mm)	395	420	437	458
Head-Tube Length (mm)	110	120	135	150
Head-Tube Angle (deg)	70.5	70.5	70.5	70.5
B-B Height (mm)	316	316	316	316
B-B Drop (mm)	60	60	60	60
Trail (mm)	84	84	84	84
Fork Length (full) (mm)	467	467	467	467
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	634	663	685	711
Chain-Stay Length (mm)	455	455	455	455
Wheelbase (mm)	1083	1111	1133	1159
Top-Tube Length (horizontal) (mm)	576	603	625	650
Bike Stand-Over Height (mm)	754	786	812	840
Seat-Tube Length (mm)	394	445	483	533
Seat-Tube Angle (deg)	73	73	73	73
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	60	60	70	70
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	350	350	400	400
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	M5 Aluminum, fully butted w/smooth welding, tapered head tube and seat tube, 100mm of travel, forged post mount 160mm disc drop outs, internal routing, forged bottom bracket shell, 197x12mm thru-axle rear
FORK	Carbon, 46mm offset, tapered steerer, 150mm axle spacing
STEM	Specialized Stout, 3D-forged alloy, 4-bolt, 6-degree rise, anti-corrosion hardware
HANDLEBARS	Double-buttressed alloy, 9-degree backsweep, 5-degree upsweep, 15mm rise, 750mm width, 31.8mm
GRIPS	Specialized Sip Grip, half-waffle, S/M: regular thickness, L/XL: XL thickness
FRONT BRAKE	Tektro Gemini, hydraulic disc, resin pads, i-Spec compatible, 180mm rotor
REAR BRAKE	Tektro Gemini, hydraulic disc, resin pads, i-spec compatible, 160mm rotor
REAR DERAILLEUR	SRAM X7 Type 2.1, long cage, 10-speed
SHIFT LEVERS	SRAM X7, 10-speed, trigger
CASSETTE	Sunrace, 10-speed, 11-42t
CHAIN	10-speed, extra lightweight hollow outer links w/reusable Missing Link # CL559R
CRANKSET	RaceFace Aeffect Cinch, 28T chainring, 11-speed, threaded BB
RIMS	Specialized 26" disc front, 21mm depth, 86mm internal width, 32h
FRONT HUB	Specialized Stout XC, alloy disc, double-sealed cartridge bearings, 15x150mm thru-axle, 32h
REAR HUB	Stout XC, disc alloy, SRAM XD driver body, sealed cartridge bearings, 12x148mm thru-axle, 32h
SPOKES	Stainless, 14g, black
FRONT TIRE	Ground Control Fat, Control casing, 26x4.6", 120TPI, Aramid folding bead, 2Bliss Ready
REAR TIRE	Ground Control Fat, Control casing, 26x4.6", 120TPI, Aramid folding bead, 2Bliss Ready
SADDLE	Body Geometry Henge Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Alloy, 2-bolt clamp, 12.5mm offset, 30.9mm, anti-corrosion hardware

PART NO.	DESCRIPTION	COLOR	SIZE
99517-7002	FATBOY	BLK/BBYBLU/RKTRED	S
99517-7003			M
99517-7004			L
99517-7005			XL
99517-7102	FATBOY	WHT/BLK/NRDCCRED	S
99517-7103			M
99517-7104			L
99517-7105			XL

FATBOY SE



NRDCRED/HYP



CHAR/BLK

If having fun for the sake of having fun sounds appealing to you, "going fat" will change the way you ride forever. The security and control that the wheel system found here on our Fatboy SE provides is unparalleled.

- The frame features an M4 alloy construction that provides the ideal blend of efficiency and durability, while the geometry creates a roomy top tube and short chainstays for easy climbing and confident descending.
- Our alloy fork with air-formed legs is lightweight and pairs up perfectly with the fat wheel system to soak up trail chatter and bumps.
- Durable alloy rims have been laced to Stout XC hubs to form a wheelset that's dependable, rugged, and efficient. So whether you're trail riding or plowing through the snow, these wheels will be the perfect mix of performance and strength.

FATBOY RIGID				
SIZE	S	M	L	XL
Stack (mm)	590	600	614	628
Reach (mm)	395	420	437	458
Head-Tube Length (mm)	110	120	135	150
Head-Tube Angle (deg)	70.5	70.5	70.5	70.5
B-B Height (mm)	316	316	316	316
B-B Drop (mm)	60	60	60	60
Trail (mm)	84	84	84	84
Fork Length (full) (mm)	467	467	467	467
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	634	663	685	711
Chain-Stay Length (mm)	455	455	455	455
Wheelbase (mm)	1083	1111	1133	1159
Top-Tube Length (horizontal) (mm)	576	603	625	650
Bike Stand-Over Height (mm)	754	786	812	840
Seat-Tube Length (mm)	394	445	483	533
Seat-Tube Angle (deg)	73	73	73	73
Handlebar Width (mm)	750	750	750	750
Stem Length (mm)	60	60	70	70
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	350	350	400	400
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized M4 aluminum, fully-butted tubing w/smooth welds, tapered head tube, post-mount disc dropouts, 190mm rear hub spacing, replaceable alloy derailleur hanger
FORK	Specialized, alloy, air-formed legs, tapered alloy steerer, 135mm hub spacing, open QR dropouts
STEM	Ahead 3D-forged alloy, 31.8mm clamp, 6-degree rise
HANDLEBARS	Double-butted alloy, 9-degree backsweep, 5-degree upsweep, 15mm rise, 750mm width, 31.8mm
GRIPS	Specialized MTB Grip, lock-on
FRONT BRAKE	Tektro Aries, mechanical disc, organic pads, 160mm rotor
REAR BRAKE	Tektro Aries, mechanical disc, organic pads, 160mm rotor
FRONT DERAILLEUR	SRAM X5, low direct-mount, 2x10
REAR DERAILLEUR	SRAM X5, long cage, 10-speed
SHIFT LEVERS	SRAM X5, 10-speed, trigger
CHAIN	KMC X10EPT Anti-Rust, 10-speed, w/reusable MissingLink
CRANKSET	Custom Samox, forged alloy, 2x10, Cr-Mo spindle, 104mm BCD spider
BOTTOM BRACKET	BB30, sealed cartridge bearings
RIMS	Specialized 26" disc front, 21mm depth, 86mm internal width, 32h
FRONT HUB	Specialized Stout XC 135, disc alloy, loose ball bearings, bolt-on axle, 32h
REAR HUB	Specialized disc, sealed cartridge bearings, alloy body cassette, 10mm steel QR, 32h
SPOKES	Stainless, 14g, black
FRONT TIRE	Ground Control Fat, 26x4.6", 60TPI, wire bead
REAR TIRE	Ground Control Fat, 24x4.6", 60TPI, wire bead
SADDLE	Body Geometry Henge Sport, steel rails, 143mm
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
99517-7202	FATBOY SE	NRDCRED/HYP	S
99517-7203			M
99517-7204			L
99517-7205			XL
99515-7602	FATBOY SE	CHAR/BLK	S
99515-7603			M
99515-7604			L
99515-7605			XL

FATBOY 24



BLK/RKTRED/TEAL



HYP GRN/CYAN/RYL BLU



BLK/TUR/TUR/HYP GRN



WHT/PNK/FUCHSIA/INDIGO

So Junior wants to get rad just like Mom and Dad? Well, our Fatboy 24 has your kid's name all over it. It has all the same benefits as our "big kid" Fatboy, only it's built on 24-inch wheels for an ultra-low standover height and kids' size. Fat is fun for the whole family.

- The frame features an A1 Premium Aluminum construction that provides the ideal blend of efficiency and durability, while the geometry creates a roomy top tube and short chainstays for easy climbing and confident descending.
- Our A1 Premium Aluminum fork is lightweight and pairs up perfectly with the fat wheel system to soak up trail chatter and bumps.
- Our Fatboy alloy rims serve as the foundation of a wheelset that's dependable, rugged, and efficient. So whether Junior is doing some trail riding or plowing through the snow, these wheels will be the perfect mix of performance and strength.

FATBOY 24	
SIZE	24.0
Stack (mm)	535
Reach (mm)	372
Head-Tube Length (mm)	120
Head-Tube Angle (deg)	69.5
B-B Height (mm)	305
B-B Drop (mm)	41
Trail (mm)	83
Fork Length (full) (mm)	420
Fork Rake/Offset (mm)	43
Front-Center (mm)	604
Chain-Stay Length (mm)	425
Wheelbase (mm)	1026
Top-Tube Length (horizontal) (mm)	536
Bike Stand-Over Height (mm)	634
Seat-Tube Length (mm)	304
Seat-Tube Angle (deg)	73
Handlebar Width (mm)	660
Stem Length (mm)	60
Seat Post Length (mm)	350
Crank Length (mm)	160

SPECS	All specs are subject to change without notice.
FRAME	2015 Fatboy 24", fully butted A1 Premium Aluminum, ZeroStack head tube, 100mm wide threaded bottom bracket, 170mm rear hub spacing
FORK	Specialized A1 Premium Aluminum, 1-1/8" alloy steerer
STEM	Alloy, 7-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, alloy, 9-degree backsweep, 4-degree upsweep, 15mm rise, 600mm width, 31.8mm
GRIPS	Specialized Body Geometry XCT Women's, lock-on
FRONT BRAKE	Tektro Aries, mechanical disc, organic pads, 160mm rotor
REAR BRAKE	Tektro Aries, mechanical disc, organic pads, 160mm rotor
REAR DERAILLEUR	SRAM X4, long cage, 6-/7-/8-speed
SHIFT LEVERS	SRAM, 9-speed, trigger
CASSETTE	Sunrace, 9-speed, 11-36t
CHAIN	KMC X9, 9-speed w/reusable MissingLink
CRANKSET	9-speed, 28T chainring w/chainguard
BOTTOM BRACKET	Square taper, 100x151.5mm, internal bearings
RIMS	Specialized Stout XC 90, disc, alloy, single wall, 90mm wide, sleeve joint, 32h
FRONT HUB	Specialized Stout XC 135, disc alloy, loose ball bearings, bolt-on axle, 32h
REAR HUB	Specialized disc, loose ball bearings, 9-/10-speed cassette body, 10mm steel axle, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Ground Control Fat, 24x4.0", 60TPI, wire bead
REAR TIRE	Ground Control Fat, 24x2.0", 60TPI, wire bead
SADDLE	Specialized Youth, steel rails
SEATPOST	Alloy, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
99515-7513	FATBOY 24	BLK/RKTRED/TEAL	12
99515-7413	FATBOY 24	HYP GRN/CYAN/RYL BLU	12
99515-7813	FATBOY 24	BLK/TUR/TUR/HYP GRN	12
99515-7913	FATBOY 24	WHT/PNK/FUCHSIA/INDIGO	12

FATBOY 20



RYL BLU/MOTO ORG/GAL ORG



WHT/TUR/TUR/PNK



CORAL/INDIGO/INDIGO/CORAL



CHAR/TEAL/HYP GRN

So Junior wants to get rad just like Mom and Dad? Well, our Fatboy 20 has your kid's name all over it. It has all the same benefits as our "big kid" Fatboy, only it's built on 20-inch wheels for an ultra-low standover height and kids' size. The family that eats trails together stays together.

- The frame features an A1 Premium Aluminum construction that provides the ideal blend of efficiency and durability, while the geometry creates a roomy top tube and short chainstays for easy climbing and confident descending.
- Our A1 Premium Aluminum fork is lightweight and pairs up perfectly with the fat wheel system to soak up trail chatter and bumps.
- Our Fatboy alloy rims serve as the foundation of a wheelset that's dependable, rugged, and efficient. So whether Junior is doing some trail riding or plowing through the snow, these wheels will be the perfect mix of performance and strength.

FATBOY 20	
SIZE	20.0
Stack (mm)	464
Reach (mm)	319
Head-Tube Length (mm)	120
Head-Tube Angle (deg)	69
B-B Height (mm)	264
B-B Drop (mm)	25
Trail (mm)	75
Fork Length (full) (mm)	360
Fork Rake/Offset (mm)	35
Front-Center (mm)	526
Chain-Stay Length (mm)	390
Wheelbase (mm)	914
Top-Tube Length (horizontal) (mm)	470
Bike Stand-Over Height (mm)	583
Seat-Tube Length (mm)	280
Seat-Tube Angle (deg)	72
Handlebar Width (mm)	640
Stem Length (mm)	60
Seat Post Length (mm)	300
Crank Length (mm)	127

SPECS	All specs are subject to change without notice.
FRAME	2015 Fatboy 24", fully butted A1 Premium Aluminum, ZeroStack head tube, 100mm wide threaded bottom bracket, 170mm rear hub spacing
FORK	Specialized A1 Premium Aluminum, 1-1/8" alloy steerer
STEM	Alloy, 7-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, alloy, 9-degree backsweep, 4-degree upsweep, 15mm rise, 600mm width, 31.8mm
GRIPS	Specialized Body Geometry XCT Women's, lock-on
FRONT BRAKE	Tektro Aries, mechanical disc, organic pads, 160mm rotor
REAR BRAKE	Tektro Aries, mechanical disc, organic pads, 160mm rotor
REAR DERAILLEUR	SRAM X4, long cage, 6-/7-/8-speed
SHIFT LEVERS	SRAM, 9-speed, trigger
CASSETTE	Sunrace, 9-speed, 11-36t
CHAIN	KMC X9, 9-speed w/reusable MissingLink
CRANKSET	9-speed, 28T chainring w/chainguard
BOTTOM BRACKET	Square taper, 100x151.5mm, internal bearings
FRONT HUB	Specialized Stout XC 135, disc alloy, loose ball bearings, bolt-on axle, 32h
REAR HUB	Specialized disc, loose ball bearings, 9-/10-speed cassette body, 10mm steel axle, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Ground Control Fat, 20x4.0", 60TPI, wire bead
REAR TIRE	Ground Control Fat 20x4.0", 60TPI, wire bead
SADDLE	Specialized Youth, steel rails
SEATPOST	Alloy, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
99515-7311	FATBOY 20	RYL BLU/MOTO ORG/GAL ORG	11
99515-7611	FATBOY 20	WHT/TUR/TUR/PNK	11
99515-7711	FATBOY 20	CORAL/INDIGO/INDIGO/CORAL	11
99515-7211	FATBOY 20	CHAR/TEAL/HYP GRN	11

FATBOY CARBON FRAMESET



WHT/BLK/RED



CARB/BLK/BLU

What started as "serious fun" has quickly become a serious change to what we want out of bike. The fat revolution is here, and with races becoming more and more prevalent, we knew that our much-heralded Fatboy could stand to go on a diet. Introducing the new Fatboy Carbon.

- An immaculate, FACT 10m carbon fiber construction ensures that the frame is lightweight and plenty stiff in all the right places. Internal cable routing is also incorporated; ensuring that slush, sand, snow, or dirt will have no bearing on performance out on the trail.
- A FACT carbon fiber fork provides tons of compliance and absorbs chatter, while simultaneously keeping the overall weight of the bike down.

SPECS	All specs are subject to change without notice.
FRAME	FACT 10m, full carbon frame, 12x197mm thru-axle rear, internal cable routing, ISCG XC tabs, suspension corrected for 100mm of travel
FORK	Carbon, 46mm offset, tapered steerer, 150mm axle spacing

PART NO.	DESCRIPTION	COLOR	SIZE
79516-1102	FATBOY CARBON FRAMESET	WHT/BLK/RED	S
79516-1103			M
79516-1104			L
79516-1105			XL
79516-1002	FATBOY CARBON FRAMESET	CARB/BLK/BLU	S
79516-1003			M
79516-1004			L
79516-1005			XL

FATBOY CARBON				
SIZE	S	M	L	XL
Stack (mm)	602	602	617	632
Reach (mm)	395	420	437	458
Head-Tube Length (mm)	94	94	110	125
Head-Tube Angle (deg)	70.5	70.5	70.5	70.5
B-B Height (mm)	307	307	307	307
B-B Drop (mm)	60	60	60	60
Trail (mm)	80	80	80	80
Fork Length (full) (mm)	496	496	496	496
Fork Rake/Offset (mm)	47	47	47	47
Front-Center (mm)	640	665	687	713
Chain-Stay Length (mm)	455	455	455	455
Wheelbase (mm)	1088	1113	1135	1161
Top-Tube Length (horizontal) (mm)	579	604	626	651
Bike Stand-Over Height (mm)	738.5	752	778.3	807.5
Seat-Tube Length (mm)	394	434	470	520
Seat-Tube Angle (deg)	73	73	73	73



WHTPRP/GLDFLK

Whether you're going huge at the dirt park or tearing it up slopestyle, the P.Series P.Slope will complement your style. It features a durable single-pivot, full-suspension chassis that's designed to smooth out landings with its 100mm of travel up front and 85mm in the back.

- The frame is constructed from A1 Premium Aluminum in order to keep the overall weight at a minimum, while also ensuring that the bike is plenty tough to take a hit. And when it comes to cool features that make the difference, you get forged horizontal dropouts and integrated chain tensioners to keep the rear wheel locked in place, ISCG 05 to run chainguides, and a tough, forged bottom bracket shell.
- A FOX FLOAT rear shock with the all-new DPS damper sits at the rear, controlling a smooth 85mm of travel. It features a new dual-piston design that let's you select your level of firmness, plus a revamped air spring that creates a more supple ride quality than ever.
- The RockShox Pike DJ fork includes the same stout 35mm chassis as its big brother, along with the revolutionary Charger damper and Solo Air system. The only real difference is in its 100mm of travel. But what does this mean for you? It means that you get a stiff construction that'll power through berms, and serve-up loads of bottom-out progression upon landing.

P SLOPE	
SIZE	22.5
Stack (mm)	580
Reach (mm)	423
Head-Tube Length (mm)	123
Head-Tube Angle (deg)	69.5
B-B Height (mm)	322
B-B Drop (mm)	16
Trail (mm)	78
Fork Length (full) (mm)	493
Fork Rake/Offset (mm)	45
Front-Center (mm)	682
Chain-Stay Length (mm)	389
Wheelbase (mm)	1070
Top-Tube Length (horizontal) (mm)	541
Bike Stand-Over Height (mm)	712
Seat-Tube Length (mm)	355
Seat-Tube Angle (deg)	78.5
Handlebar Width (mm)	750
Stem Length (mm)	40
Seat Post Length (mm)	150
Crank Length (mm)	170

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, concentric bottom bracket, fully-butted tapered head tube, forged BB30 bottom bracket shell, integrated ISCG '05 tabs, forged horizontal dropouts, integrated chain tensioners, 85mm of travel
REAR SHOCK	FOX FLOAT w/DPS damper, 200x50mm, 85mm of travel
FORK	RockShox Pike DJ 26, Solo Air spring, 1-1/8x1.5" tapered alloy steer, external rebound, Motion Control low-speed compression, tooled Floodgate, 32mm alloy stanchions and mag lowers, 15x100mm Maxle thru-axle
STEM	Forged Alloy, 31.8mm clamp, 40mm
HANDLEBARS	Specialized P.Series MTB Dirt, 6061 alloy, 9-degree backsweep, 6-degree upsweep, 38mm rise, 750mm width, 31.8mm
GRIPS	Specialized P.Grip, lock-on
FRONT BRAKE	SRAM Level, hydraulic disc, 160mm rotor
REAR BRAKE	SRAM Level, hydraulic disc, 160mm rotor
CHAIN	KMC K810SL, single-speed, 1/2x3/32"
CRANKSET	Stout DJ PRO crankset, 30mm alloy spindle, 170mm
CHAINRINGS	30T
BOTTOM BRACKET	BB30, sealed cartridge bearings
RIMS	P.26, alloy, double-wall, triple void, 32mm inner width, 32h
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x100mm thru-axle, 32h
REAR HUB	P. Series Dirt Jump, alloy disc hub, sealed cartridge bearings, single speed w/ 14t 3/32" cog, 10mm Cr-Mo axle, 32h
SPOKES	Stainless, 14g, black
FRONT TIRE	Renegade Slopestyle, 26x2.1", 60TPI, wire bead
REAR TIRE	Renegade Slopestyle, 26x2.1", 60TPI, wire bead
SADDLE	Soder Dirt, steel rails
SEATPOST	Alloy, 2-bolt clamp, 12.5mm offset, 30.9mm, anti-corrosion hardware

PART NO.	DESCRIPTION	COLOR	SIZE
91917-8022	P.SLOPE	WHTPRP/GLDFLK	22.5" TT

P.3 PRO



BLK/REDFLKTNT

The P.Series P.3 Pro takes all of the P.3 hallmarks and elevates them with an incredible spec.

- The frame is constructed from A1 Premium Aluminum in order to keep the overall weight at a minimum, while also ensuring that the bike is plenty tough to take a hit. And when it comes to cool features that make the difference, you get forged horizontal dropouts and integrated chain tensioners to keep the rear wheel locked in place, ISCG 05 to run chainguides, and a tough, forged shell surrounding the BB30 bottom bracket.
- Manitou Circus Expert features 100mm of air-sprung travel and stiff 32mm stanchions. You also get Manitou's acclaimed TPC rebound damper and a stiff, sturdy 15mm thru-axle.
- The Stout DJ PRO crankset features an ultra-tough 30mm spindle, a nearly bulletproof construction, and a 30T chainring.

P 26	
SIZE	22.5
Stack (mm)	546
Reach (mm)	413
Head-Tube Length (mm)	128
Head-Tube Angle (deg)	70.5
B-B Height (mm)	331
B-B Drop (mm)	7
Trail (mm)	77
Fork Length (full) (mm)	457
Fork Rake/Offset (mm)	40
Front-Center (mm)	646
Chain-Stay Length (mm)	383
Wheelbase (mm)	1029
Top-Tube Length (horizontal) (mm)	570
Bike Stand-Over Height (mm)	338
Seat-Tube Length (mm)	304
Seat-Tube Angle (deg)	74
Handlebar Width (mm)	750
Stem Length (mm)	40
Seat Post Length (mm)	200
Crank Length (mm)	170

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, fully-butted tubing, tapered head tube, BB30 forged BB shell, integrated ISCG 05 tabs, forged horizontal dropouts, integrated chain tensioners
FORK	Manitou Circus Expert, Air spring, Absolute+ w/ Jump Stack, TPC rebound damping, 32mm stanchions, 100mm travel, 15mm thru-axle
STEM	Forged Alloy, 31.8mm clamp, 40mm
HANDLEBARS	Specialized P.Series MTB Dirt, 6061 alloy, 9-degree backsweep, 6-degree upsweep, 38mm rise, 750mm width, 31.8mm
GRIPS	Specialized P.Grip, lock-on
FRONT BRAKE	SRAM Level, hydraulic disc, 160mm rotor
REAR BRAKE	SRAM Level, hydraulic disc, 160mm rotor
CHAIN	KMC Z610H, single-speed, 1/2"x3/32"
CRANKSET	Stout DJ PRO crankset, 30mm alloy spindle, 170mm
CHAINRINGS	30T
BOTTOM BRACKET	BB30, sealed cartridge bearings
RIMS	P.26, alloy, double-wall, triple void, 32mm inner width, 32h
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x100mm thru-axle, 32h
REAR HUB	P. Series Dirt Jump, alloy disc hub, sealed cartridge bearings, single speed w/ 14t 3/32" cog, 10mm Cr-Mo axle, 32h
SPOKES	Stainless, 14g, black
FRONT TIRE	Renegade Slopestyle, 26x2.1", 60TPI, wire bead
REAR TIRE	Renegade Slopestyle, 26x2.1", 60TPI, wire bead
SADDLE	P.Series Dirt, steel rails
SEATPOST	Specialized, 6061 alloy, 2-bolt clamp, 0mm setback, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
91917-1022	P.3 PRO	BLK/REDFLKTNT	22.5" TT



TLTNT/BLK

The P.Series P.3 doesn't put out fluff and sparkly stuff. It simply delivers a bombproof ride quality that mixes advanced technology and top-shelf materials with geometry that's proven in the street, park, and dirt.

- The frame is constructed from A1 Premium Aluminum in order to keep the overall weight at a minimum, while also ensuring that the bike is plenty tough to take a hit. And when it comes to cool features that make the difference, you get forged horizontal dropouts and integrated chain tensioners to keep the rear wheel locked in place, ISCG 05 to run chainguides, and a tough, forged shell surrounding the BB30 bottom bracket.
- Manitou Circus Sport features 100mm of air-sprung travel and stiff 32mm stanchions. You also get Manitou's acclaimed FFD damper, compression and rebound adjust to dial-in the performance, and a beefy 1.5" tapered steerer for extra strength and stiffness.
- The Stout DJ Expert crankset features an ultra-tough 30mm Cr-Mo spindle, a nearly bulletproof construction, and a 30T chainring.

P 26	
SIZE	22.5
Stack (mm)	546
Reach (mm)	413
Head-Tube Length (mm)	128
Head-Tube Angle (deg)	70.5
B-B Height (mm)	331
B-B Drop (mm)	7
Trail (mm)	77
Fork Length (full) (mm)	457
Fork Rake/Offset (mm)	40
Front-Center (mm)	646
Chain-Stay Length (mm)	383
Wheelbase (mm)	1029
Top-Tube Length (horizontal) (mm)	570
Bike Stand-Over Height (mm)	338
Seat-Tube Length (mm)	304
Seat-Tube Angle (deg)	74
Handlebar Width (mm)	750
Stem Length (mm)	40
Seat Post Length (mm)	200
Crank Length (mm)	170

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, fully-butted tubing, tapered head tube, BB30 forged BB shell, integrated ISCG 05 tabs, forged horizontal dropouts, integrated chain tensioners
FORK	Manitou Circus Sport, Firm spring, FFD damping, TPC rebound damping, 32mm stanchions, 100mm of travel, 15mm thru-axle
STEM	Forged Alloy, 31.8mm clamp, 40mm
HANDLEBARS	Specialized P.Series MTB Dirt, 6061 alloy, 9-degree backsweep, 6-degree upsweep, 38mm rise, 750mm width, 31.8mm
GRIPS	Specialized P.Grip, lock-on
FRONT BRAKE	Tektro, hydraulic disc, organic pads
REAR BRAKE	Tektro HD-M285, hydraulic disc, organic pads
CHAIN	KMC Z610H, single-speed, 1/2"x3/32"
CRANKSET	Stout DJ Expert cranks, 30mm Cr-Mo spindle, 170mm
CHAINRINGS	30T
BOTTOM BRACKET	BB30, sealed cartridge bearings
RIMS	P.26, alloy, double-wall, triple void, 32mm inner width, 32h
FRONT HUB	Specialized disc, alloy, sealed cartridge bearings, 15x100mm thru-axle, 32h
REAR HUB	P. Series Dirt Jump, alloy disc hub, sealed cartridge bearings, single speed w/ 14t 3/32" cog, 10mm Cr-Mo axle, 32h
SPOKES	Stainless, 14g, black
FRONT TIRE	Renegade Slopestyle, 26x2.1", 60TPI, wire bead
REAR TIRE	Renegade Slopestyle, 26x2.1", 60TPI, wire bead
SADDLE	P.Series Dirt, steel rails
SEATPOST	Specialized, 6061 alloy, 2-bolt clamp, 0mm setback, 30.9mm

PART NO.	DESCRIPTION	COLOR	SIZE
91917-7022	P.3	TLTNT/BLK	22.5" TT

S-WORKS VENGE VIAS DISC ETAP



METWHT/CARB/BLK

The S-Works Venge ViAS Disc w/ eTap is more than just a bike. When the first Venge launched, it changed aerodynamics, but now, we've designed a complete, cohesive speed system. Nearly every single piece of it was redesigned from the ground up.

- The Rider-First Engineered™, FACT 11r frame design have made the Venge the stiffest, most aerodynamic bike that we've ever created. Every tube shape, trailing edge, and design cue was influenced by hours of testing in our Win Tunnel, computational fluid dynamics, 3D printed prototypes, and real-world rider feedback. And ultimately, this resulted in the fastest bike we've ever made.
- Designed in our Win Tunnel, the fork features a top-end S-Works FACT 11r carbon construction that helps to cut through air like a hot knife through butter.
- SRAM eTap, 11-speed shifters glimpse into the future of shifting. They communicate wirelessly with the front and rear derailleurs for a ground-breaking level of performance, while offering new, intuitive shift capabilities.

VENGE NO 46						
SIZE	49	52	54	56	58	61
Stack (mm)	505	526	543	564	591	612
Reach (mm)	386	385	386	395	401	408
Head-Tube Length (mm)	110	130	150	170	200	220
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	270	270	272.5	272.5	274	274
B-B Drop (mm)	71.5	71.5	69	69	68	67.5
Trail (mm)	63	58	58	55	55	52
Fork Length (full) (mm)	358	358	358	358	358	358
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front-Center (mm)	575	575	581	592	606	613
Chain-Stay Length (mm)	410	410	410	410	410	410
Wheelbase (mm)	974	974	981	992	1006	1014
Top-Tube Length (horizontal) (mm)	518	536	547	565	581	600
Bike Stand-Over Height (mm)	730	755	775	795	826	850
Seat-Tube Length (mm)	441	461	481	501	524	554
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	85	95	105	115	115	115
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	330	330	380	380	380	380
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 11r carbon, Rider-First Engineered™, Win Tunnel Engineered, internal cable routing, 12x142mm thru-axle, carbon OSBB
FORK	FACT carbon, full monocone
STEM	Venge ViAS aero stem
HANDLEBARS	S-Works Aerofly ViAS, 25mm
TAPE	Specialized Roubaix
FRONT BRAKE	2016 SRAM Red Disc
REAR BRAKE	2016 SRAM Red Disc
FRONT DERAILLEUR	SRAM eTap, braze-on
REAR DERAILLEUR	SRAM eTap, 11-speed
SHIFT LEVERS	SRAM eTap Hydro
CASSETTE	SRAM Red 22, 11-28t
CHAIN	SRAM Red 22, 11-speed
CRANKSET	S-Works FACT carbon, OSBB, Quarq Power Meter, w/CeramicSpeed ceramic bearings
CHAINRINGS	52/36T
BOTTOM BRACKET	OSBB, CeramicSpeed bearings
FRONT WHEEL	Rapide CLX 64 Disc, thru-axle
REAR WHEEL	Rapide CLX 64 Disc, thru-axle
FRONT HUB	Roval tubeless plugs, 25-piece bag x 2
REAR HUB	80mm alloy tubeless valve
FRONT TIRE	S-Works Turbo Tubular, 700x22mm
REAR TIRE	S-Works Turbo Tubular, 700x24mm
SADDLE	Body Geometry S-Works Power, carbon rails, 143mm
SEATPOST	Specialized Venge, FACT carbon

PART NO.	DESCRIPTION	COLOR	SIZE
99017-0452	SW VENGE DISC VIAS ETAP	METWHT/CARB/BLK	52
99017-0454			54
99017-0456			56
99017-0458			58
99017-0461			61

VENGE VIAS PRO DISC UDI2



TARBLK/CHAR

The Venge ViAS Pro Disc w/ Ultegra Di2 is a bike built for sheer speed. Every facet of it was born in our Win Tunnel, and the result is a bike with supreme braking and a 116-second advantage, compared to the Tarmac, over 40km.

- The Rider-First Engineered™, FACT 11r frame design have made the Venge the stiffest, most aerodynamic bike that we've ever created. Every tube shape, trailing edge, and design cue was influenced by hours of testing in our Win Tunnel, computational fluid dynamics, 3D printed prototypes, and real-world rider feedback. And ultimately, this resulted in the fastest bike we've ever made.
- Designed in our Win Tunnel, the fork features a FACT carbon construction that helps to cut through air like a hot knife through butter.
- Shimano Ultegra Di2 shifting offers 11-speeds of electronic wonderment. Shifts are as precise as it gets, dropping chains becomes a rarity, and the trim adjust up front ensures that chain rub is a thing of the past—no matter how extreme your cross-chaining gets.

VENGE NO 46						
SIZE	49	52	54	56	58	61
Stack (mm)	505	526	543	564	591	612
Reach (mm)	386	385	386	395	401	408
Head-Tube Length (mm)	110	130	150	170	200	220
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	270	270	272.5	272.5	274	274
B-B Drop (mm)	71.5	71.5	69	69	68	67.5
Trail (mm)	63	58	58	55	55	52
Fork Length (full) (mm)	358	358	358	358	358	358
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front-Center (mm)	575	575	581	592	606	613
Chain-Stay Length (mm)	410	410	410	410	410	410
Wheelbase (mm)	974	974	981	992	1006	1014
Top-Tube Length (horizontal) (mm)	518	536	547	565	581	600
Bike Stand-Over Height (mm)	730	755	775	795	826	850
Seat-Tube Length (mm)	441	461	481	501	524	554
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	85	95	105	115	115	115
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	330	330	380	380	380	380
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 11r carbon, Rider-First Engineered™, Win Tunnel Engineered, internal cable routing, 12x142mm thru-axle, carbon OSBB
FORK	FACT carbon, full monocoque
STEM	Venge ViAS aero stem
HANDLEBARS	S-Works Aerofly ViAS, 25mm
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	Shimano, hydraulic, Ice-Tech resin pads w/fins
REAR BRAKE	Shimano Ultegra, hydraulic, resin pads w/fins
FRONT DERAILLEUR	Shimano Ultegra Di2 6870, 11-speed, braze-on
REAR DERAILLEUR	Shimano Ultegra Di2, 6870, 11-speed
SHIFT LEVERS	Shimano R785 Di2, 11-speed
CASSETTE	Shimano Ultegra, 11-speed, 11-28t
CHAIN	Shimano Ultegra, 11-speed
CRANKSET	Pro 52/36T
CHAINRINGS	52/36T
BOTTOM BRACKET	Enduro BB30
FRONT WHEEL	Rapide CL 64 Disc, thru-axle
REAR WHEEL	Rapide CL 64 Disc, thru-axle
FRONT HUB	Roval tubeless plugs, 25-piece bag x 2
REAR HUB	80mm alloy tubeless valve
FRONT TIRE	S-Works Turbo, 700x24mm, 220TPI, folding bead, BlackBelt protection
REAR TIRE	S-Works Turbo, 700x24mm, 220TPI, folding bead, BlackBelt protection
SADDLE	Body Geometry Power Pro, carbon rails, 143mm
SEATPOST	Specialized Venge, FACT carbon

PART NO.	DESCRIPTION	COLOR	SIZE
97817-1049	VENGE PRO DISC VIAS UDI2	TARBLK/CHAR	49
97817-1052			52
97817-1054			54
97817-1056			56
97817-1058			58
97817-1061			61

VENGE VIAS EXPERT DISC ULTEGRA



METWHT TARBLK CLN

The Venge ViAS Expert Disc w/ Ultegra delivers World Tour performance at a price that competitive riders will find more than palatable. Every facet of it was born in our Win Tunnel, and the result is a bike with supreme braking and a 116-second advantage, compared to the Tarmac, over 40km.

- The Rider-First Engineered™, FACT 11r frame design have made the Venge the stiffest, most aerodynamic bike that we've ever created. Every tube shape, trailing edge, and design cue was influenced by hours of testing in our Win Tunnel, computational fluid dynamics, 3D printed prototypes, and real-world rider feedback. And ultimately, this resulted in the fastest bike we've ever made.
- Designed in our Win Tunnel, the fork features a FACT carbon construction that helps to cut through air like a hot knife through butter.
- Shimano Ultegra hydraulic disc brakes provide exceptional power and modulation, finally marrying the Venge's unrivaled aerodynamic design with braking that excels in any condition.

VENGE							
SIZE	46	49	52	54	56	58	61
Stack (mm)	489	505	526	543	564	591	612
Reach (mm)	377	386	385	386	395	401	408
Head-Tube Length (mm)	100	110	130	150	170	200	220
Head-Tube Angle (deg)	70	72.25	73	73	73.5	73.5	74
B-B Height (mm)	267	270	270	272.5	272.5	274	274
B-B Drop (mm)	73	71.5	71.5	69	69	68	67.5
Trail (mm)	73	63	58	58	55	55	52
Fork Length (full) (mm)	358	358	358	358	358	358	358
Fork Rake/Offset (mm)	44	44	44	44	44	44	44
Front-Center (mm)	575	575	575	581	592	606	613
Chain-Stay Length (mm)	410	410	410	410	410	410	410
Wheelbase (mm)	974	974	974	981	992	1006	1014
Top-Tube Length (horizontal) (mm)	511	518	536	547	565	581	600
Bike Stand-Over Height (mm)	692	730	755	775	795	826	850
Seat-Tube Length (mm)	425	441	461	481	501	524	554
Seat-Tube Angle (deg)	75	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	380	400	420	420	420	440	440
Stem Length (mm)	70	80	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143	143
Seat Post Length (mm)	330	330	330	380	380	380	380
Crank Length (mm)	165	170	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 11r carbon, Rider-First Engineered™, Win Tunnel Engineered, internal cable routing, 12x142mm thru-axle, carbon OSBB
FORK	FACT carbon, full monocone
STEM	Specialized Pro 4-bolt alloy
HANDLEBARS	Specialized S-Works AeroFy w/out holes, 25mm
TAPE	Specialized Roubaix
FRONT BRAKE	Shimano, hydraulic, Ice-Tech resin pads w/fins
REAR BRAKE	Shimano Ultegra, hydraulic, resin pads w/fins
FRONT DERAILLEUR	Shimano Ultegra, braze-on
REAR DERAILLEUR	Shimano Ultegra, 11-speed
SHIFT LEVERS	Shimano ST-RS685, 11-speed
CASSETTE	Shimano Ultegra, 11-speed, 11-28t
CHAIN	Shimano Ultegra, 11-speed
CRANKSET	Specialized Pro carbon
CHAINRINGS	52/36T
BOTTOM BRACKET	Enduro BB30
FRONT WHEEL	DT R460 Disc Pro, thru-axle, 2Bliss Ready
REAR WHEEL	DT R460 Disc Pro, thru-axle, 2Bliss Ready
FRONT TIRE	S-Works Turbo, 700x24mm, 220TPI, folding bead, BlackBelt protection
REAR TIRE	S-Works Turbo, 700x24mm, 220TPI, folding bead, BlackBelt protection
SADDLE	Body Geometry Power Expert, hollow titanium rails, 143mm
SEATPOST	Specialized Venge, FACT carbon

PART NO.	DESCRIPTION	COLOR	SIZE
97817-3049	VENGE EXPERT DISC VIAS	METWHT TARBLK CLN	49
97817-3052			52
97817-3054			54
97817-3056			56
97817-3058			58
97817-3061			61

VENGE ELITE



TARBLK/RKTRED/METWHT



GLOSS TARBLK/TEAMYEL/METWHT

SAGAN WC

When we say that "aero is everything," we mean it. That's because we believe that advanced aerodynamics provide an advantage that'll enhance any ride. And likewise, we believe that every rider should have access to the fruits of our labor in the Win Tunnel, which is why we created the Venge Elite.

- The FACT 10r frame design have made the Venge the stiffest, most aerodynamic bike that we've ever created. Every tube shape, trailing edge, and design cue was influenced by hours of testing in our Win Tunnel, computational fluid dynamics, 3D printed prototypes, and real-world rider feedback. And ultimately, this resulted in the fastest bike we've ever made.
- Designed in our Win Tunnel, the fork features a FACT carbon construction that helps to cut through air like a hot knife through butter.
- Shimano 105 11-speed shifting provides reliable movement along a wide range of gears.

VENGE 10R

SIZE	49	52	54	56	58	61
Stack (mm)	504	526	543	564	591	612
Reach (mm)	385	385	386	395	401	407
Head-Tube Length (mm)	100	120	140	160	190	210
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	270	270	272.5	272.5	274	274
B-B Drop (mm)	72	72	69	69	68	68
Trail (mm)	62	57	57	56	56	53
Fork Length (full) (mm)	368	368	368	368	368	368
Fork Rake/Offset (mm)	45	45	45	43	43	43
Front-Center (mm)	575	575	582	591	605	612
Chain-Stay Length (mm)	405	405	405	405	407	410
Wheelbase (mm)	969	970	977	986	1002	1012
Top-Tube Length (horizontal) (mm)	515	536	547	565	582	600
Bike Stand-Over Height (mm)	741	766	789	809	834	860
Seat-Tube Length (mm)	467	487	507	527	547	577
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	75	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	300	300	300	350	350	350
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS

All specs are subject to change without notice.

FRAME	Specialized FACT 10r carbon, FACT IS construction, aero-shaped tubing, compact race design, tapered 1-1/8" to 1-3/8" head tube, internal cable routing, carbon OSBB
FORK	FACT carbon, full monocone
STEM	Specialized Pro SL, alloy, 4-bolt
HANDLEBARS	S-Works Aerofly
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	Shimano 105
REAR BRAKE	Shimano 105
FRONT DERAILLEUR	Shimano 105, braze-on
REAR DERAILLEUR	Shimano 105, 11-speed
SHIFT LEVERS	Shimano 105 STI, 11-speed
CASSETTE	Shimano 105, 11-speed, 11-28t
CHAIN	KMC X11, 11-speed
CRANKSET	Praxis Zayante, 7075-T6 alloy chainrings
CHAINRINGS	52/36T
BOTTOM BRACKET	Praxis
FRONT WHEEL	Axis Elite, QR
REAR WHEEL	Axis Elite, QR
FRONT TIRE	S-Works Turbo, 700x24mm, 220TPI, folding bead, BlackBelt protection
REAR TIRE	S-Works Turbo, 700x24mm, 220TPI, folding bead, BlackBelt protection
SADDLE	Body Geometry Power Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized Venge, FACT carbon

PART NO.	DESCRIPTION	COLOR	SIZE
97817-4149	VENGE ELITE	TARBLK/RKTRED/METWHT	49
97817-4152			52
97817-4154			54
97817-4156			56
97817-4158			58
97817-4161			61
97817-4249	VENGE ELITE	GLOSS TARBLK/TEAMYEL/METWHT	49
97817-4252			52
97817-4254			54
97817-4256			56
97817-4258			58
97817-4261			61
97817-4049	VENGE ELITE	SAGAN WC	49
97817-4052			52
97817-4054			54
97817-4056			56
97817-4058			58
97817-4061			61

S-WORKS VENGE VIAS DISC FRAMESET



METWHT/CARB/BLK



MONGRN/TEAMVEL/BLK

The S-Works Venge ViAS Disc frameset is more than just a bike. When the first Venge launched, it changed aerodynamics, but now, we've designed a complete, cohesive speed system. Nearly every single piece of it was redesigned from the ground up.

- The Rider-First Engineered™, FACT 11r frame design have made the Venge the stiffest, most aerodynamic bike that we've ever created. Every tube shape, trailing edge, and design cue was influenced by hours of testing in our Win Tunnel, computational fluid dynamics, 3D printed prototypes, and real-world rider feedback. And ultimately, this resulted in the fastest bike we've ever made.
- Designed in our Win Tunnel, the fork features a top-end S-Works FACT 11r carbon construction that helps to cut through air like a hot knife through butter.
- With its FACT carbon construction, the Venge seatpost provides impeccable power transfer and aerodynamic advantage, while still allowing for ample compliance for long days in the saddle.

SPECS **All specs are subject to change without notice.**

FRAME	FACT 11r carbon, Rider-First Engineered™, Win Tunnel Engineered, internal cable routing, 12x142mm thru-axle, carbon OSBB
FORK	FACT carbon, full monocoque
BOTTOM BRACKET	OSBB, CeramicSpeed bearings
SEATPOST	Specialized Venge, FACT carbon

PART NO.	DESCRIPTION	COLOR	SIZE
79017-0246	SW VENGE DISC VIAS FRMSET	METWHT/CARB/BLK	46
79017-0249			49
79017-0252			52
79017-0254			54
79017-0256			56
79017-0258			58
79017-0261			61
79017-0946	SW VENGE DISC VIAS FRMSET	MONGRN/TEAMVEL/BLK	46
79017-0949			49
79017-0952			52
79017-0954			54
79017-0956			56
79017-0958			58
79017-0961			61

VENGE							
SIZE	46	49	52	54	56	58	61
Stack (mm)	489	505	526	543	564	591	612
Reach (mm)	377	386	385	386	395	401	408
Head-Tube Length (mm)	100	110	130	150	170	200	220
Head-Tube Angle (deg)	70	72.25	73	73	73.5	73.5	74
B-B Height (mm)	267	270	270	272.5	272.5	274	274
B-B Drop (mm)	73	71.5	71.5	69	69	68	67.5
Trail (mm)	73	63	58	58	55	55	52
Fork Length (full) (mm)	358	358	358	358	358	358	358
Fork Rake/Offset (mm)	44	44	44	44	44	44	44
Front-Center (mm)	575	575	575	581	592	606	613
Chain-Stay Length (mm)	410	410	410	410	410	410	410
Wheelbase (mm)	974	974	974	981	992	1006	1014
Top-Tube Length (horizontal) (mm)	511	518	536	547	565	581	600
Bike Stand-Over Height (mm)	692	730	755	775	795	826	850
Seat-Tube Length (mm)	425	441	461	481	501	524	554
Seat-Tube Angle (deg)	75	75.5	74	73.5	73.25	73	72.5

S-WORKS TARMAC ETAP



CARB/FLORED/METWHT

The S-Works Tarmac has picked up multiple Grand Tour victories and two World Championships since its debut, proving it with an illustrious pedigree. Its Rider-First Engineered™ design ensures peak performance across every size range, and now, the Tarmac is available with SRAM's much anticipated eTap groupset.

- Featuring our Rider-First Engineered™ design that ensures every frame size has the same legendary climbing responsiveness and descending prowess you'd expect from a Tarmac. The S-Works FACT 11r frameset is our highest quality carbon frame, offering the ideal blend of light overall weight and targeted stiffness.
- S-Works-specific FACT full carbon fork with tapered construction provides incredible front end stiffness and steering response for instantaneous accelerations and high-speed descents.
- SRAM eTap, 11-speed shifters glimpse into the future of shifting. They communicate wirelessly with the front and rear derailleurs for a ground-breaking level of performance, while offering new, intuitive shift capabilities.

TARMAC RFE						
SIZE	49	52	54	56	58	61
Stack (mm)	504	526	543	564	591	612
Reach (mm)	386	386	387	395	402	408
Head-Tube Length (mm)	100	120	140	160	190	210
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	270	270	272.5	272.5	274	274
B-B Drop (mm)	71.5	71.5	69	69	67.5	67.5
Trail (mm)	62	57	57	56	56	53
Fork Length (full) (mm)	368	368	368	368	368	368
Fork Rake/Offset (mm)	45	45	45	43	43	43
Front-Center (mm)	576	576	583	591	605	612
Chain-Stay Length (mm)	405	405	405	405	407	410
Wheelbase (mm)	970	970	978	986	1003	1013
Top-Tube Length (horizontal) (mm)	518	537	548	565	582	600
Bike Stand-Over Height (mm)	730	755	775	795	826	850
Seat-Tube Length (mm)	431	462	481	501	522	553
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	75	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	350	350	350	400	400	400
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	S-Works FACT 11r carbon, OSBB, full internal, electronic-specific routing, internally integrated seat clamp, 130mm rear spacing
FORK	S-Works FACT carbon, full monocoque, size-specific taper
STEM	S-Works SL, alloy, titanium bolts, 6-degree rise
HANDLEBARS	S-Works SL carbon Shallow Drop, 125mm drop, 75mm reach
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	SRAM Red 22
REAR BRAKE	SRAM Red 22
FRONT DERAILLEUR	SRAM eTap, braze-on
REAR DERAILLEUR	SRAM eTap, 11-speed
SHIFT LEVERS	SRAM eTap
CASSETTE	SRAM Red 22, 11-speed, 11-28t
CHAIN	SRAM Red 22, 11-speed
CRANKSET	SRAM Red 22
CHAINRINGS	52/36T
BOTTOM BRACKET	SRAM BB30, 83mm
FRONT WHEEL	Roval CLX 40, carbon 40mm depth rim, carbon hub shell, CeramicSpeed bearings, 18h
REAR WHEEL	Roval CLX 40, carbon 40mm depth rim, DT Swiss 240 internals, CeramicSpeed bearings, 24h
FRONT TIRE	Turbo Cotton, 700x24mm
REAR TIRE	Turbo Cotton, 700x24mm
SADDLE	Body Geometry S-Works Toupé, carbon rails, 143mm
SEATPOST	S-Works FACT carbon, 20mm offset

PART NO.	DESCRIPTION	COLOR	SIZE
97017-0149	SW TARMAC ETAP	CARB/FLORED/METWHT	49
97017-0152			52
97017-0154			54
97017-0156			56
97017-0158			58
97017-0161			61

S-WORKS TARMAC DISC ETAP



CARB/FLORED/METWHT

The S-Works Tarmac Disc eTap is nothing short of revolutionary, utilizing the impeccable power and reliability of SRAM's hydraulic brakes and world's first & only wireless shifting, SRAM eTap.

- Featuring our Rider-First Engineered™ design that ensures every frame size has the same legendary climbing responsiveness and descending prowess you'd expect from a Tarmac. The S-Works FACT 11r disc frameset is our highest quality carbon frame, offering the ideal blend of light overall weight, targeted stiffness, and incredible stopping power.
- S-Works-specific FACT full carbon fork with tapered construction provides incredible front end stiffness and steering response for instantaneous accelerations and high-speed descents.
- SRAM Red® eTap 11-speed shifters provide a glimpse into the future of shifting, and double as brake levers for the SRAM Red hydraulic disc brakes. They communicate wirelessly with the front and rear derailleurs for a ground-breaking level of performance, while offering new, intuitive shift capabilities.

TARMAC RFE						
SIZE	49	52	54	56	58	61
Stack (mm)	504	526	543	564	591	612
Reach (mm)	386	386	387	395	402	408
Head-Tube Length (mm)	100	120	140	160	190	210
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	270	270	272.5	272.5	274	274
B-B Drop (mm)	71.5	71.5	69	69	67.5	67.5
Trail (mm)	62	57	57	56	56	53
Fork Length (full) (mm)	368	368	368	368	368	368
Fork Rake/Offset (mm)	45	45	45	43	43	43
Front-Center (mm)	576	576	583	591	605	612
Chain-Stay Length (mm)	405	405	405	405	407	410
Wheelbase (mm)	970	970	978	986	1003	1013
Top-Tube Length (horizontal) (mm)	518	537	548	565	582	600
Bike Stand-Over Height (mm)	730	755	775	795	826	850
Seat-Tube Length (mm)	431	462	481	501	522	553
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	75	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	350	350	350	400	400	400
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	S-Works FACT 11r carbon, disc only design, OSBB, full internal, electronic-specific routing, internally integrated seat clamp, QR, 135mm rear spacing
FORK	S-Works FACT carbon, full monocoque, size-specific taper, disc
STEM	S-Works SL, alloy, titanium bolts, 6-degree rise
HANDLEBARS	S-Works SL carbon Shallow Drop, 125mm drop, 75mm reach
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	SRAM Red disc, 160mm
REAR BRAKE	SRAM Red disc, 140mm
FRONT DERAILLEUR	SRAM eTap, braze-on
REAR DERAILLEUR	SRAM eTap, 11-speed
SHIFT LEVERS	SRAM eTap Hydro
CASSETTE	SRAM Red 22, 11-speed, 11-28t
CHAIN	SRAM Red 22, 11-speed
CRANKSET	SRAM Red 22
CHAINRINGS	52/36T
BOTTOM BRACKET	SRAM BB30, 83mm
FRONT WHEEL	Roval CLX 32 Disc, Win Tunnel Engineered, 32mm depth, CeramicSpeed bearings, 18h
REAR WHEEL	Roval CLX 32 Disc, Win Tunnel Engineered, 32mm depth, DT Swiss 240 internals, CeramicSpeed bearings, 24h
FRONT TIRE	Turbo Cotton, 700x24mm
REAR TIRE	Turbo Cotton, 700x24mm
SADDLE	Body Geometry S-Works Toupé, carbon rails, 143mm
SEATPOST	S-Works FACT carbon, 20mm offset

PART NO.	DESCRIPTION	COLOR	SIZE
97017-0249	SW TARMAC DISC ETAP	CARB/FLORED/METWHT	49
97017-0252			52
97017-0254			54
97017-0256			56
97017-0258			58
97017-0261			61

S-WORKS TARMAC DURA-ACE



CARB/RKTRED/METWHT

There's no better vantage point than from the top step of a podium, and no bike in recent years has studied the race landscape from this height more than our S-Works Tarmac Dura-Ace.

- Featuring our Rider-First Engineered™ design that ensures every frame size has the same legendary climbing responsiveness and descending prowess you'd expect from a Tarmac. The S-Works FACT 11r frameset is our highest quality carbon frame, offering the ideal blend of lightweight and targeted stiffness.
- S-Works-specific FACT full carbon fork with tapered construction provides incredible front end stiffness and steering response for instantaneous accelerations and high-speed descents.
- The Roval CLX 32 wheelset merges aero with an astonishingly low climbing weight, making them the first choice for anyone whose rides see plenty of gains and long bouts in the wind.

TARMAC RFE						
SIZE	49	52	54	56	58	61
Stack (mm)	504	526	543	564	591	612
Reach (mm)	386	386	387	395	402	408
Head-Tube Length (mm)	100	120	140	160	190	210
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	270	270	272.5	272.5	274	274
B-B Drop (mm)	71.5	71.5	69	69	67.5	67.5
Trail (mm)	62	57	57	56	56	53
Fork Length (full) (mm)	368	368	368	368	368	368
Fork Rake/Offset (mm)	45	45	45	43	43	43
Front-Center (mm)	576	576	583	591	605	612
Chain-Stay Length (mm)	405	405	405	405	407	410
Wheelbase (mm)	970	970	978	986	1003	1013
Top-Tube Length (horizontal) (mm)	518	537	548	565	582	600
Bike Stand-Over Height (mm)	730	755	775	795	826	850
Seat-Tube Length (mm)	431	462	481	501	522	553
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	75	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	350	350	350	400	400	400
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	S-Works FACT 11r carbon, OSBB, full internal cable routing, internally integrated seat clamp, 130mm rear spacing
FORK	S-Works FACT carbon, full monocoque, size-specific taper
STEM	S-Works SL, alloy, titanium bolts, 6-degree rise
HANDLEBARS	S-Works SL carbon Shallow Drop, 125mm drop, 75mm reach
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	Shimano Dura-Ace
REAR BRAKE	Shimano Dura-Ace
FRONT DERAILLEUR	Shimano Dura-Ace 9100, 11-speed, braze-on
REAR DERAILLEUR	Shimano Dura-Ace 9100, 11-speed
SHIFT LEVERS	Shimano Dura-Ace 9100, 11-speed
CASSETTE	Shimano Dura-Ace 9100, 11-speed, 11-28t
CHAIN	Shimano HG901, 11-speed
CRANKSET	Shimano Dura-Ace
CHAINRINGS	52/36T
BOTTOM BRACKET	Praxis BB30
FRONT WHEEL	Roval CLX 32, Win Tunnel Engineered, 32mm depth, CeramicSpeed bearings, 18h
REAR WHEEL	Roval CLX 32, Win Tunnel Engineered, 32mm depth, DT Swiss 240 internals, CeramicSpeed bearings, 24h
FRONT TIRE	Turbo Cotton, 700x24mm
REAR TIRE	Turbo Cotton, 700x24mm
SADDLE	Body Geometry S-Works Toupé, carbon rails, 143mm
SEATPOST	S-Works FACT carbon, 20mm offset

PART NO.	DESCRIPTION	COLOR	SIZE
97017-0349	SW TARMAC DA	CARB/RKTRED/METWHT	49
97017-0352			52
97017-0354			54
97017-0356			56
97017-0358			58
97017-0361			61

TARMAC PRO DISC ULTEGRA Di2



CARB/CHAR/HYP

If you're obsessed with marginal gains and have the wallet to back it up, we made S-Works for you. If you're obsessed with phenomenal performance and still having money left over for a cappuccino at the end of a hard training ride, look no further than the Tarmac Pro Disc with Ultegra Di2.

- The FACT 10r carbon frame combines the lightweight performance and compliance of our top-end carbon production methods with our Rider-First Engineered™ design that ensures every frame size has the same legendary climbing responsiveness and descending prowess you'd expect from a Tarmac. Even better, it's specifically designed for disc brakes, so you'll never have to compromise performance for stopping power.
- S-Works FACT full carbon fork with tapered construction provides incredible front end stiffness and steering response for instantaneous accelerations and high-speed descents.
- Shimano Ultegra Di2 shifting offers 11-speeds of electronic wonderment. Shifts are as precise as it gets and the trim adjust up front ensures that chain rub is a thing of the past—no matter how extreme your cross-chaining gets.

TARMAC RFE						
SIZE	49	52	54	56	58	61
Stack (mm)	504	526	543	564	591	612
Reach (mm)	386	386	387	395	402	408
Head-Tube Length (mm)	100	120	140	160	190	210
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	270	270	272.5	272.5	274	274
B-B Drop (mm)	71.5	71.5	69	69	67.5	67.5
Trail (mm)	62	57	57	56	56	53
Fork Length (full) (mm)	368	368	368	368	368	368
Fork Rake/Offset (mm)	45	45	45	43	43	43
Front-Center (mm)	576	576	583	591	605	612
Chain-Stay Length (mm)	405	405	405	405	407	410
Wheelbase (mm)	970	970	978	986	1003	1013
Top-Tube Length (horizontal) (mm)	518	537	548	565	582	600
Bike Stand-Over Height (mm)	730	755	775	795	826	850
Seat-Tube Length (mm)	431	462	481	501	522	553
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	75	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	350	350	350	400	400	400
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 10r carbon, disc only, OSBB, full internal, electronic-specific routing, internally integrated seat clamp, QR, 135mm spacing
FORK	S-Works FACT carbon, full monocoque, size-specific taper, disc
STEM	Specialized Pro SL, alloy, 4-bolt
HANDLEBARS	Specialized Expert Shallow Drop, alloy, 123mm drop, 75mm reach
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	Shimano BR-785, hydraulic disc, Ice-Tech resin pads w/fins, 160mm
REAR BRAKE	Shimano BR-785, hydraulic disc, Ice-Tech resin pads w/fins, 140mm
FRONT DERAILLEUR	Shimano Ultegra Di2 6870, 11-speed, braze-on
REAR DERAILLEUR	Shimano Ultegra Di2, 6870, 11-speed
SHIFT LEVERS	Shimano R785 Di2, 11-speed
CASSETTE	Shimano Ultegra, 11-speed, 11-28t
CHAIN	Shimano HG70, 11-speed
CRANKSET	Specialized Pro carbon
BOTTOM BRACKET	Enduro BB30
FRONT WHEEL	Roval CL 40 disc, carbon 40mm rim depth, carbon hub shell, 18h
REAR WHEEL	Roval CL 40 disc, carbon 40mm rim depth, DT Swiss 350 internals, 24h
FRONT TIRE	S-Works Turbo, 700x24mm, 220TPI, folding bead, BlackBelt protection
REAR TIRE	S-Works Turbo, 700x24mm, 220TPI, folding bead, BlackBelt protection
SADDLE	Toupé Pro, Adaptive Edge design, carbon rails, 143mm
SEATPOST	S-Works FACT carbon, 20mm offset

PART NO.	DESCRIPTION	COLOR	SIZE
90617-1049	TARMAC PRO DISC UDI2	CARB/CHAR/HYP	49
90617-1052			52
90617-1054			54
90617-1056			56
90617-1058			58
90617-1061			61

TARMAC PRO ULTEGRA Di2



NAVY/BBYBLU/RKTRED

If you're obsessed with marginal gains and have the wallet to back it up, we made S-Works for you. If you're obsessed with phenomenal performance and still having money left over for a cappuccino at the end of a hard training ride, look no further than the Tarmac Pro with Ultegra Di2.

- The FACT 10r carbon frame combines the lightweight performance and compliance of our top-end carbon production methods with our Rider-First Engineered™ design that ensures every frame size has the same legendary climbing responsiveness and descending prowess you'd expect from a Tarmac.
- S-Works FACT full carbon fork with tapered construction provides incredible front end stiffness and steering response for instantaneous accelerations and high-speed descents.
- Shimano Ultegra Di2 shifting offers 11-speeds of electronic wonderment. Shifts are as precise as it gets and the trim adjust up front ensures that chain rub is a thing of the past—no matter how extreme your cross-chaining gets.

TARMAC RFE						
SIZE	49	52	54	56	58	61
Stack (mm)	504	526	543	564	591	612
Reach (mm)	386	386	387	395	402	408
Head-Tube Length (mm)	100	120	140	160	190	210
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	270	270	272.5	272.5	274	274
B-B Drop (mm)	71.5	71.5	69	69	67.5	67.5
Trail (mm)	62	57	57	56	56	53
Fork Length (full) (mm)	368	368	368	368	368	368
Fork Rake/Offset (mm)	45	45	45	43	43	43
Front-Center (mm)	576	576	583	591	605	612
Chain-Stay Length (mm)	405	405	405	405	407	410
Wheelbase (mm)	970	970	978	986	1003	1013
Top-Tube Length (horizontal) (mm)	518	537	548	565	582	600
Bike Stand-Over Height (mm)	730	755	775	795	826	850
Seat-Tube Length (mm)	431	462	481	501	522	553
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	75	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	350	350	350	400	400	400
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 10r carbon, OSBB, full internal cable routing, internally integrated seat clamp, 130mm rear spacing
FORK	S-Works FACT carbon, full monocoque, size-specific taper
STEM	Specialized Pro SL, alloy, 4-bolt
HANDLEBARS	Specialized Expert Shallow Drop, alloy, 123mm drop, 75mm reach
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	Shimano Ultegra
REAR BRAKE	Shimano Ultegra
FRONT DERAILLEUR	Shimano Ultegra Di2 6870, 11-speed, braze-on
REAR DERAILLEUR	Shimano Ultegra Di2, 6870, 11-speed
SHIFT LEVERS	Shimano Ultegra Di2, 6870, 11-speed
CASSETTE	Shimano Ultegra, 11-speed, 11-28t
CHAIN	Shimano HG70, 11-speed
CRANKSET	Specialized Pro carbon
BOTTOM BRACKET	Enduro BB30
FRONT WHEEL	Roval CL 40, carbon 40mm rim depth, carbon hub shell, 18h
REAR WHEEL	Roval CL 40, carbon 40mm rim depth, DT Swiss 350 internals, 24h
FRONT TIRE	S-Works Turbo, 700x24mm, 220TPI, folding bead, BlackBelt protection
REAR TIRE	S-Works Turbo, 700x24mm, 220TPI, folding bead, BlackBelt protection
SADDLE	Toupé Pro, Adaptive Edge design, carbon rails, 143mm
SEATPOST	S-Works FACT carbon, 20mm offset

PART NO.	DESCRIPTION	COLOR	SIZE
90617-1149	TARMAC PRO UD12	NAVY/BBYBLU/RKTRED	49
90617-1152			52
90617-1154			54
90617-1156			56
90617-1158			58
90617-1161			61

CMLN/TARBLK

Where cutting-edge technology and value meet, you'll find our Tarmac Expert with SRAM eTap.

- The FACT 10r carbon frame combines the lightweight performance and compliance of our top-end carbon production methods with our Rider-First Engineered™ design that ensures every frame size has the same legendary climbing responsiveness and descending prowess you'd expect from a Tarmac.
- FACT full carbon fork with tapered construction provides incredible front end stiffness and steering response for instantaneous accelerations and high-speed descents.
- SRAM eTap, 11-speed shifters glimpse into the future of shifting. They communicate wirelessly with the front and rear derailleurs for a ground-breaking level of performance, while offering new, intuitive shift capabilities.

TARMAC RFE						
SIZE	49	52	54	56	58	61
Stack (mm)	504	526	543	564	591	612
Reach (mm)	386	386	387	395	402	408
Head-Tube Length (mm)	100	120	140	160	190	210
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	270	270	272.5	272.5	274	274
B-B Drop (mm)	71.5	71.5	69	69	67.5	67.5
Trail (mm)	62	57	57	56	56	53
Fork Length (full) (mm)	368	368	368	368	368	368
Fork Rake/Offset (mm)	45	45	45	43	43	43
Front-Center (mm)	576	576	583	591	605	612
Chain-Stay Length (mm)	405	405	405	405	407	410
Wheelbase (mm)	970	970	978	986	1003	1013
Top-Tube Length (horizontal) (mm)	518	537	548	565	582	600
Bike Stand-Over Height (mm)	730	755	775	795	826	850
Seat-Tube Length (mm)	431	462	481	501	522	553
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	75	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	350	350	350	400	400	400
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 10r carbon, OSBB, full internal cable routing, internally integrated seat clamp, 130mm rear spacing
FORK	S-Works FACT carbon, full monocoque, size-specific taper
STEM	Specialized Pro SL, alloy, 4-bolt
HANDLEBARS	Specialized Expert Shallow Drop, alloy, 123mm drop, 75mm reach
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	SRAM Force
REAR BRAKE	SRAM Force
FRONT DERAILLEUR	SRAM eTap, braze-on
REAR DERAILLEUR	SRAM eTap, 11-speed
SHIFT LEVERS	SRAM eTap
CASSETTE	SRAM PG-1170, 11-speed
CHAIN	SRAM PC-1170, 11-speed
CRANKSET	SRAM S952, Yaw BB30
CHAINRINGS	52/36T
BOTTOM BRACKET	SRAM BB30, 83mm
FRONT WHEEL	DT R460 Pro
REAR WHEEL	DT R460 Pro
FRONT TIRE	S-Works Turbo, 700x24mm, 220TPI, folding bead, BlackBelt protection
REAR TIRE	S-Works Turbo, 700x24mm, 220TPI, folding bead, BlackBelt protection
SADDLE	Toupé Expert Gel, Adaptive Edge design, hollow titanium rails, 143mm
SEATPOST	S-Works FACT carbon, 20mm offset

PART NO.	DESCRIPTION	COLOR	SIZE
90617-3449	TARMAC EXPERT ETAP	CMLN/TARBLK	49
90617-3452			52
90617-3454			54
90617-3456			56
90617-3458			58
90617-3461			61

TARMAC EXPERT DISC



MONGRN/TEAMYEL



INK/NRDCCRED

Chances are, you're not going to be competing in a Grand Tour this year, but when it comes to your training rides and local races, it's hard to top the Tarmac Expert Disc.

- The FACT 10r carbon frame combines the lightweight performance and compliance of our top-end carbon production methods with our Rider-First Engineered™ design that ensures every frame size has the same legendary climbing responsiveness and descending prowess you'd expect from a Tarmac. Even better, it's specifically designed for disc brakes, so you'll never have to compromise performance for stopping power.
- S-Works FACT full carbon fork with a tapered construction provides incredible front end stiffness and steering response for instantaneous accelerations and high-speed descents. It's also designed for disc brakes, so you won't experience any lurch or degradation in performance.
- Shimano BR-785 hydraulic disc brakes deliver smooth modulation and lever feel, and more importantly, incredible stopping power in any condition.

TARMAC RFE

SIZE	49	52	54	56	58	61
Stack (mm)	504	526	543	564	591	612
Reach (mm)	386	386	387	395	402	408
Head-Tube Length (mm)	100	120	140	160	190	210
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	270	270	272.5	272.5	274	274
B-B Drop (mm)	71.5	71.5	69	69	67.5	67.5
Trail (mm)	62	57	57	56	56	53
Fork Length (full) (mm)	368	368	368	368	368	368
Fork Rake/Offset (mm)	45	45	45	43	43	43
Front-Center (mm)	576	576	583	591	605	612
Chain-Stay Length (mm)	405	405	405	405	407	410
Wheelbase (mm)	970	970	978	986	1003	1013
Top-Tube Length (horizontal) (mm)	518	537	548	565	582	600
Bike Stand-Over Height (mm)	730	755	775	795	826	850
Seat-Tube Length (mm)	431	462	481	501	522	553
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	75	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	350	350	350	400	400	400
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS

All specs are subject to change without notice.

FRAME	FACT 10r carbon, OSBB, full internal cable routing, internally integrated seat clamp, 135mm rear spacing
FORK	S-Works FACT carbon, full monocoque, size-specific taper, disc
STEM	Specialized Pro SL, alloy, 4-bolt
HANDLEBARS	Specialized Expert Shallow Drop, alloy, 123mm drop, 75mm reach
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	Shimano BR-785, hydraulic disc, Ice-Tech resin pads w/fins, 160mm
REAR BRAKE	Shimano BR-785, hydraulic disc, Ice-Tech resin pads w/fins, 140mm
FRONT DERAILLEUR	Shimano Ultegra 6800, 11-speed, braze-on
REAR DERAILLEUR	Shimano Ultegra 6800, 11-speed
SHIFT LEVERS	Shimano ST-RS685, 11-speed
CASSETTE	Shimano Ultegra, 11-speed, 11-28t
CHAIN	Shimano HG70, 11-speed
CRANKSET	FSA SL-K Light
CHAINRINGS	52/36T
BOTTOM BRACKET	BB30 bearings
FRONT WHEEL	DT Swiss R460 Disc Pro, QR
REAR WHEEL	DT Swiss R460 Disc Pro, QR
FRONT TIRE	S-Works Turbo, 700x24mm, 220TPI, folding bead, BlackBelt protection
REAR TIRE	S-Works Turbo, 700x24mm, 220TPI, folding bead, BlackBelt protection
SADDLE	Toupé Expert Gel, Adaptive Edge design, hollow titanium rails, 143mm
SEATPOST	S-Works FACT carbon, 20mm offset

PART NO.	DESCRIPTION	COLOR	SIZE
90617-3349	TARMAC EXPERT DISC	MONGRN/TEAMYEL	49
90617-3352			52
90617-3354			54
90617-3356			56
90617-3358			58
90617-3361			61
90617-3249	TARMAC EXPERT DISC	INK/NRDCCRED	49
90617-3252			52
90617-3254			54
90617-3256			56
90617-3258			58
90617-3261			61

TARMAC EXPERT



METWHT/TARBLK



TARBLK/RKTRD/METWHT

Chances are, you're not going to be competing in a Grand Tour this year, but when it comes to your training rides and local races, it's hard to top the Tarmac Expert.

- The FACT 10r carbon frame combines the lightweight performance and compliance of our top-end carbon production methods with our Rider-First Engineered™ design that ensures every frame size has the same legendary climbing responsiveness and descending prowess you'd expect from a Tarmac.
- S-Works FACT full carbon fork with tapered construction provides incredible front end stiffness and steering response for instantaneous accelerations and high-speed descents.
- The DT Swiss R460 Pro wheelsset can be considered a "jack of all trades." It features an ample width for interfacing nicely with wider tires, while its alloy construction is both sturdy and stiff, making it ideal for climbing, railing corners, and taking a hit when those pesky potholes sneak up on you.

TARMAC RFE W/64CM

SIZE	49	52	54	56	58	61	64
Stack (mm)	504	526	543	564	591	612	636
Reach (mm)	386	386	387	395	402	408	415
Head-Tube Length (mm)	100	120	140	160	190	210	235
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74	74
B-B Height (mm)	270	270	272.5	272.5	274	274	274.5
B-B Drop (mm)	71.5	71.5	69	69	67.5	67.5	67.5
Trail (mm)	62	57	57	56	56	53	50
Fork Length (full) (mm)	368	368	368	368	368	368	368
Fork Rake/Offset (mm)	45	45	45	43	43	43	43
Front-Center (mm)	576	576	583	591	605	612	645
Chain-Stay Length (mm)	405	405	405	405	407	410	410
Wheelbase (mm)	970	970	978	986	1003	1013	1016
Top-Tube Length (horizontal) (mm)	518	537	548	565	582	600	621
Bike Stand-Over Height (mm)	730	755	775	795	826	850	850
Seat-Tube Length (mm)	431	462	481	501	522	553	584
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5	72.5
Handlebar Width (mm)	400	420	420	420	440	440	440
Stem Length (mm)	75	90	100	100	110	110	120
Saddle Width (mm)	143	143	143	143	143	143	143
Seat Post Length (mm)	350	350	350	400	400	400	400
Crank Length (mm)	170	170	172.5	172.5	175	175	175

SPECS

All specs are subject to change without notice.

FRAME	FACT 10r carbon, OSBB, full internal cable routing, internally integrated seat clamp, 130mm spacing
FORK	S-Works FACT carbon, full monocoque, size-specific taper
STEM	Specialized Pro SL, alloy, 4-bolt
HANDLEBARS	Specialized Expert Shallow Drop, alloy, 123mm drop, 75mm reach
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	Shimano Ultegra
REAR BRAKE	Shimano Ultegra
FRONT DERAILLEUR	Shimano Ultegra 6800, 11-speed, braze-on
REAR DERAILLEUR	Shimano Ultegra 6800, 11-speed
SHIFT LEVERS	Shimano Ultegra 6800, 11-speed
CASSETTE	Shimano Ultegra 6800, 11-speed, 11-28t
CHAIN	Shimano HG70, 11-speed
CRANKSET	FSA SL-K Light
CHAINRINGS	52/36T
BOTTOM BRACKET	BB30 bearings
FRONT WHEEL	DT Swiss R460 Pro, QR
REAR WHEEL	DT Swiss R460 Pro, QR
FRONT TIRE	S-Works Turbo, 700x24mm, 220TPI, folding bead, BlackBelt protection
REAR TIRE	S-Works Turbo, 700x24mm, 220TPI, folding bead, BlackBelt protection
SADDLE	Toupé Expert Gel, Adaptive Edge design, hollow titanium rails, 143mm
SEATPOST	S-Works FACT carbon, 20mm offset

PART NO.	DESCRIPTION	COLOR	SIZE
90617-3049	TARMAC EXPERT	METWHT/TARBLK	49
90617-3052			52
90617-3054			54
90617-3056			56
90617-3058			58
90617-3061			61
90617-3064			64
90617-3149	TARMAC EXPERT	TARBLK/RKTRD/METWHT	49
90617-3152			52
90617-3154			54
90617-3156			56
90617-3158			58
90617-3161			61
90617-3164			64

TARMAC COMP DISC



RKTRED/TEAMYEL/TARBLK



CARB/WHT

If you're looking to take your riding to the next level, our Tarmac Comp Disc is one of the fastest and most economical ways to do so.

- The FACT 9r carbon frame combines the lightweight performance and compliance of our top-end carbon production methods with our Rider-First Engineered™ design that ensures every frame size has the same legendary climbing responsiveness and descending prowess you'd expect from a Tarmac.
- S-Works FACT full carbon fork with tapered construction provides incredible front end stiffness and steering response for instantaneous accelerations and high-speed descents. It's also designed for disc brakes, so you won't experience any lurch or degradation in performance.
- Shimano BR-785 hydraulic disc brakes deliver smooth modulation and lever feel, and more importantly, incredible stopping power in any condition.

TARMAC RFE						
SIZE	49	52	54	56	58	61
Stack (mm)	504	526	543	564	591	612
Reach (mm)	386	386	387	395	402	408
Head-Tube Length (mm)	100	120	140	160	190	210
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	270	270	272.5	272.5	274	274
B-B Drop (mm)	71.5	71.5	69	69	67.5	67.5
Trail (mm)	62	57	57	56	56	53
Fork Length (full) (mm)	368	368	368	368	368	368
Fork Rake/Offset (mm)	45	45	45	43	43	43
Front-Center (mm)	576	576	583	591	605	612
Chain-Stay Length (mm)	405	405	405	405	407	410
Wheelbase (mm)	970	970	978	986	1003	1013
Top-Tube Length (horizontal) (mm)	518	537	548	565	582	600
Bike Stand-Over Height (mm)	730	755	775	795	826	850
Seat-Tube Length (mm)	431	462	481	501	522	553
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	70	80	90	100	100	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	300	300	350	400	400	400
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 9r carbon, threaded BB, full internal cable routing, internally integrated seat clamp, 135mm rear spacing
FORK	S-Works FACT carbon, full monocoque, size-specific taper, disc
STEM	3D-forged alloy, 7-degree rise
HANDLEBARS	Specialized Shallow Drop Comp, 6061 double-buttet alloy, 125mm drop, 70mm reach, 31.8mm
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	Shimano BR-785, hydraulic disc, Ice-Tech resin pads w/fins, 160mm
REAR BRAKE	Shimano BR-785, hydraulic disc, Ice-Tech resin pads w/fins, 140mm
FRONT DERAILLEUR	Shimano Ultegra 6800, 11-speed, braze-on
REAR DERAILLEUR	Shimano Ultegra 6800, 11-speed
SHIFT LEVERS	Shimano ST-RS685, 11-speed
CASSETTE	Shimano 105 5800, 11-speed, 11-28t
CHAIN	KMC X11, 11-speed
CRANKSET	Shimano Ultegra Compact
CHAINRINGS	52/36T
BOTTOM BRACKET	Shimano
FRONT WHEEL	Axis Elite Disc, QR
REAR WHEEL	Axis Elite Disc, QR
FRONT TIRE	S-Works Turbo, 700x24mm, 220TPI, folding bead, BlackBelt protection
REAR TIRE	S-Works Turbo, 700x24mm, 220TPI, folding bead, BlackBelt protection
SADDLE	Toupé Comp Gel, Adaptive Edge design, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized Comp carbon, single bolt

PART NO.	DESCRIPTION	COLOR	SIZE
90617-5449	TARMAC COMP DISC	RKTRED/TEAMYEL/TARBLK	49
90617-5452			52
90617-5454			54
90617-5456			56
90617-5458			58
90617-5461			61
90617-5349	TARMAC COMP DISC	CARB/WHT	49
90617-5352			52
90617-5354			54
90617-5356			56
90617-5358			58
90617-5361			61

TARMAC COMP



RKTRED/TARBLK



CARB/CHAR

While there's a certain degree of truth in applying terms like "upgrade" or "value" to our Tarmac Comp, we prefer to refrain doing so. Why? Because the Tarmac Comp stands on its own two wheels as a bike that's born to perform and able to take your riding and racing to the next level.

- The FACT 9r carbon frame combines the lightweight performance and compliance of our top-end carbon production methods with our Rider-First Engineered™ design that ensures every frame size has the same legendary climbing responsiveness and descending prowess you'd expect from a Tarmac.
- S-Works FACT full carbon fork with tapered construction provides incredible front end stiffness and steering response for instantaneous accelerations and high-speed descents.
- A Shimano Ultegra 6800 compact crankset is stiff and durable, while its 50/34T chainrings leave you with tons of spin when the roads start to get steep.

TARMAC COMP RFE W/64

SIZE	49	52	54	56	58	61	64
Stack (mm)	504	526	543	564	591	612	636
Reach (mm)	386	386	387	395	402	408	415
Head-Tube Length (mm)	100	120	140	160	190	210	235
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74	74
B-B Height (mm)	270	270	272.5	272.5	274	274	274.5
B-B Drop (mm)	71.5	71.5	69	69	67.5	67.5	67.5
Trail (mm)	62	57	57	56	56	53	50
Fork Length (full) (mm)	368	368	368	368	368	368	368
Fork Rake/Offset (mm)	45	45	45	43	43	43	43
Front-Center (mm)	576	576	583	591	605	612	645
Chain-Stay Length (mm)	405	405	405	405	407	410	410
Wheelbase (mm)	970	970	978	986	1003	1013	1016
Top-Tube Length (horizontal) (mm)	518	537	548	565	582	600	621
Bike Stand-Over Height (mm)	730	755	775	795	826	850	850
Seat-Tube Length (mm)	431	462	481	501	522	553	584
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5	72.5
Handlebar Width (mm)	400	420	420	420	440	440	440
Stem Length (mm)	70	80	90	100	100	110	120
Saddle Width (mm)	143	143	143	143	143	143	143
Seat Post Length (mm)	300	300	350	400	400	400	400
Crank Length (mm)	170	170	172.5	172.5	175	175	175

SPECS

All specs are subject to change without notice.

FRAME	FACT 9r carbon, threaded BB, full internal cable routing, internally integrated seat clamp, 130mm rear spacing
FORK	S-Works FACT carbon, full monocoque, size-specific taper
STEM	3D-forged alloy, 7-degree rise
HANDLEBARS	Specialized Shallow Drop Comp, 6061 double-butt alloy, 125mm drop, 70mm reach, 31.8mm
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	Shimano Ultegra
REAR BRAKE	Shimano Ultegra
FRONT DERAILLEUR	Shimano Ultegra 6800, 11-speed, braze-on
REAR DERAILLEUR	Shimano Ultegra 6800, 11-speed
SHIFT LEVERS	Shimano Ultegra 6800, 11-speed
CASSETTE	Shimano 105 5800, 11-speed, 11-28t
CHAIN	KMC X11, 11-speed
CRANKSET	Shimano Ultegra Compact
BOTTOM BRACKET	Shimano
FRONT WHEEL	DT Swiss R460, QR
REAR WHEEL	DT Swiss R460, QR
FRONT TIRE	S-Works Turbo, 700x24mm, 220TPI, folding bead, BlackBelt protection
REAR TIRE	S-Works Turbo, 700x24mm, 220TPI, folding bead, BlackBelt protection
SADDLE	Toupé Comp Gel, Adaptive Edge design, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized Comp carbon, single bolt

PART NO.	DESCRIPTION	COLOR	SIZE
90617-5149	TARMAC COMP	RKTRED/TARBLK	49
90617-5152			52
90617-5154			54
90617-5156			56
90617-5158			58
90617-5161			61
90617-5049	TARMAC COMP	CARB/CHAR	49
90617-5052			52
90617-5054			54
90617-5056			56
90617-5058			58
90617-5061			61

TARMAC SL4 COMP UDI2



BLK/WHT

The Tarmac SL4 Comp UDi2 combines all of the complete performance that the Tarmac is known the world over for with the precise electronic shifting of Shimano's Ultegra Di2. Consider it the perfect bike to grow along with you as you explore the open roads ahead.

You'll also find an identical, Grand-Tour-winning geometry, plus a FACT 9r carbon fiber construction that's nearly mirrors what you'll find under the likes of Peter Sagan and Alberto Contador.

For the spec, we selected components that deliver the best bang for your buck, durable DT R460 wheels, Shimano Ultegra 6870 Di2 shifting, and a bevy of Body Geometry components that maximize performance by providing the utmost in comfort.

- The FACT 9r carbon frame has all the stiffness and performance you need in a lightweight package, making climbing and descending the best part of any ride.
- The FACT full carbon fiber fork provides incredible front end stiffness and steering input for rapid accelerations and speedy descents.
- Shimano Ultegra 6870 Di2 shifting provides 11 speeds of precise electronic shifting that's right on par in the performance department with its Dura-Ace cousin, only with a few added grams to the recipe.

TARMAC RFE						
SIZE	49	52	54	56	58	61
Stack (mm)	504	526	543	564	591	612
Reach (mm)	386	386	387	395	402	408
Head-Tube Length (mm)	100	120	140	160	190	210
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	270	270	272.5	272.5	274	274
B-B Drop (mm)	71.5	71.5	69	69	67.5	67.5
Trail (mm)	62	57	57	56	56	53
Fork Length (full) (mm)	368	368	368	368	368	368
Fork Rake/Offset (mm)	45	45	45	43	43	43
Front-Center (mm)	576	576	583	591	605	612
Chain-Stay Length (mm)	405	405	405	405	407	410
Wheelbase (mm)	970	970	978	986	1003	1013
Top-Tube Length (horizontal) (mm)	518	537	548	565	582	600
Bike Stand-Over Height (mm)	730	755	775	795	826	850
Seat-Tube Length (mm)	431	462	481	501	522	553
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	70	80	90	100	100	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	300	300	350	350	350	350
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FORK	Tarmac Comp, carbon Monocoque
STEM	3D-forged alloy, 7-degree rise
HANDLEBARS	Specialized Shallow Drop Comp, 6061 double-buttressed alloy, 125mm drop, 70mm reach, 31.8mm
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	Shimano Ultegra
REAR BRAKE	Shimano Ultegra
FRONT DERAILLEUR	Shimano Ultegra Di2 6870, 11-speed, braze-on
REAR DERAILLEUR	Shimano Ultegra Di2, 6870, 11-speed
SHIFT LEVERS	Shimano Ultegra Di2, 11-speed
CASSETTE	Shimano 105, 11-speed, 11-28t
CHAIN	KMC X11, 11-speed
CRANKSET	Shimano Ultegra Compact
CHAINRINGS	52/36T
BOTTOM BRACKET	Shimano
FRONT WHEEL	DT R460
REAR WHEEL	DT R460
FRONT TIRE	Turbo Pro, 700x23mm, 127TPI, folding bead, BlackBelt protection
REAR TIRE	Turbo Pro, 700x23mm, 127TPI, folding bead, BlackBelt protection
SADDLE	Toupé Comp Gel, Adaptive Edge design, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized Comp carbon, single bolt

PART NO.	DESCRIPTION	COLOR	SIZE
90617-5649	TARMAC SL4 COMP UDI2	BLK/WHT	49
90617-5652			52
90617-5654			54
90617-5656			56
90617-5658			58
90617-5661			61

TARMAC SL4 ELITE



CARB/WHT



HYP/TARBLK

Few bikes invoke podium dreams and longing like our Tarmac, and with the Tarmac SL4 Elite, you get your slice of the Tarmac performance lineage at a price that's more than favorable.

- The FACT 9r carbon frame combines lightweight performance and compliance to ensure that you receive the legendary climbing responsiveness and descending prowess you'd expect from a Tarmac.
- S-Works FACT full carbon fork with tapered construction provides incredible front end stiffness and steering response for instantaneous accelerations and high-speed descents.
- Significantly lighter than comparable wheelsets in its class, these tough Axis Elite wheels offer tremendous value in one smooth-rolling package.

TARMAC SL4						
SIZE	49	52	54	56	58	61
Stack (mm)	505	526	543	564	591	612
Reach (mm)	386	386	387	395	402	408
Head-Tube Length (mm)	100	120	140	160	190	210
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	270	270	272.5	272.5	274	274
B-B Drop (mm)	72	72	69	69	68	68
Trail (mm)	63	58	58	55	55	52
Fork Length (full) (mm)	368	368	368	368	368	368
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front-Center (mm)	575	576	582	591	607	614
Chain-Stay Length (mm)	405	405	405	405	407	410
Wheelbase (mm)	970	970	977	987	1004	1014
Top-Tube Length (horizontal) (mm)	517	537	548	565	583	601
Bike Stand-Over Height (mm)	730	755	775	795	826	850
Seat-Tube Length (mm)	460	490	510	530	550	580
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	70	80	90	100	100	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	300	300	350	350	350	350
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	FACT 9r carbon, threaded BB, full internal cable routing, internally integrated seat clamp, 130mm rear spacing
FORK	S-Works FACT carbon, full monocoque, size-specific taper
STEM	3D-forged alloy, 7-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized S-Wrap
FRONT BRAKE	Shimano Ultegra
REAR BRAKE	Shimano Ultegra
FRONT DERAILLEUR	Shimano Ultegra 6800, 11-speed, braze-on
REAR DERAILLEUR	Shimano Ultegra 6800, 11-speed
SHIFT LEVERS	Shimano Ultegra 6800, 11-speed
CASSETTE	Shimano 105 5800, 11-speed, 11-28t
CHAIN	KMC X11, 11-speed
CRANKSET	Praxis Zayante
CHAINRINGS	Praxis 7075 alloy, 50/34T
BOTTOM BRACKET	Praxis BB
FRONT WHEEL	Axis Elite, QR
REAR WHEEL	Axis Elite, QR
FRONT TIRE	Specialized Espoir Elite, 700x23mm, 60TPI
REAR TIRE	Specialized Espoir Elite, 700x23mm, 60TPI
SADDLE	Body Geometry Toupé Sport, steel rails, 143mm
SEATPOST	Specialized Comp carbon, single bolt

PART NO.	DESCRIPTION	COLOR	SIZE
90617-4049	TARMAC SL4 ELITE	CARB/WHT	49
90617-4052			52
90617-4054			54
90617-4056			56
90617-4058			58
90617-4061			61
90617-4149	TARMAC SL4 ELITE	HYP/TARBLK	49
90617-4152			52
90617-4154			54
90617-4156			56
90617-4158			58
90617-4161			61

TARMAC SL4 SPORT



MXORG/BRTYEL/TARBLK



TARBLK/TEAMYEL

You're cutting your teeth in this whole road cycling thing, and your appetite for performance is insatiable. And it's for riders like you that we made our Tarmac Sport. It has all of the performance hallmarks of its more expensive brethren; only its components are suited to the reliability required of hard riding while you're learning the ropes.

- The FACT 9r carbon frame combines lightweight performance and compliance to ensure that you receive the legendary climbing responsiveness and descending prowess you'd expect from a Tarmac.
- S-Works FACT full carbon fork with tapered construction provides incredible front end stiffness and steering response for instantaneous accelerations and high-speed descents.
- Significantly lighter than comparable wheelsets in its class, these tough Axis Elite wheels offer tremendous value in one smooth-rolling package.

TARMAC SL4

SIZE	49	52	54	56	58	61
Stack (mm)	505	526	543	564	591	612
Reach (mm)	386	386	387	395	402	408
Head-Tube Length (mm)	100	120	140	160	190	210
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	270	270	272.5	272.5	274	274
B-B Drop (mm)	72	72	69	69	68	68
Trail (mm)	63	58	58	55	55	52
Fork Length (full) (mm)	368	368	368	368	368	368
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front-Center (mm)	575	576	582	591	607	614
Chain-Stay Length (mm)	405	405	405	405	407	410
Wheelbase (mm)	970	970	977	987	1004	1014
Top-Tube Length (horizontal) (mm)	517	537	548	565	583	601
Bike Stand-Over Height (mm)	730	755	775	795	826	850
Seat-Tube Length (mm)	460	490	510	530	550	580
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	70	80	90	100	100	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	300	300	350	350	350	350
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS

All specs are subject to change without notice.

FRAME	FACT 9r carbon, threaded BB, full internal cable routing, internally integrated seat clamp, 130mm rear spacing
FORK	S-Works FACT carbon, full monocoque, size-specific taper
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized S-Wrap
FRONT BRAKE	Shimano Tiagra
REAR BRAKE	Shimano Tiagra
FRONT DERAILLEUR	Shimano 105 5800, 11-speed, braze-on
REAR DERAILLEUR	Shimano 105 5800, 11-speed
SHIFT LEVERS	Shimano 105 5800, 11-speed
CASSETTE	Shimano 105 5800, 11-speed, 11-28t
CHAIN	KMC X11, 11-speed
CRANKSET	Praxis Alba
CHAINRINGS	52/36T
BOTTOM BRACKET	Praxis
FRONT WHEEL	Axis Elite, QR
REAR WHEEL	Axis Elite, QR
FRONT TIRE	Specialized Espoir Elite, 700x23mm, 60TPI
REAR TIRE	Specialized Espoir Elite, 700x23mm, 60TPI
SADDLE	Body Geometry Toupé Sport, steel rails, 143mm
SEATPOST	Specialized Comp carbon, single bolt

PART NO.	DESCRIPTION	COLOR	SIZE
90617-6049	TARMAC SL4 SPORT	MXORG/BRTYEL/TARBLK	49
90617-6052			52
90617-6054			54
90617-6056			56
90617-6058			58
90617-6061			61
90617-6249	TARMAC SL4 SPORT	TARBLK/TEAMYEL	49
90617-6252			52
90617-6254			54
90617-6256			56
90617-6258			58
90617-6261			61

S-WORKS TARMAC FRAMESET



ASTANA



CARB/RKTRED/METWHT



ETIXX-QUICKSTEP



METWHT/NVY/RKTRED

The S-Works Tarmac is a racing thoroughbred, combining the pinpoint handling of a classic race bike with the performance of immaculately constructed carbon fiber. And now, you're able to build the Tarmac frameset to your exact specifications.

- Featuring our Rider-First Engineered™ design that ensures every frame size has the same legendary climbing responsiveness and descending prowess you'd expect from a Tarmac. The S-Works FACT 11r frameset is our highest quality carbon frame, offering the ideal blend of light overall weight and targeted stiffness.
- S-Works-specific FACT full carbon fork with tapered construction provides incredible front end stiffness and steering response for instantaneous accelerations and high-speed descents.
- With its high-modulus construction, the S-Works FACT full carbon seatpost provides impeccable power transfer, while still allowing for ample compliance for long days in the saddle.

SPECS

All specs are subject to change without notice.

FRAME	S-Works FACT 11r carbon, OSBB, full internal cable routing, internally integrated seat clamp, 130mm rear spacing
FORK	S-Works FACT carbon, full monocoque, size-specific taper
BOTTOM BRACKET	OSBB, CeramicSpeed bearings
SEATPOST	S-Works FACT carbon, 20mm offset, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
77017-0049	SW TARMAC FRMSET	ASTANA	49
77017-0052			52
77017-0054			54
77017-0056			56
77017-0058			58
77017-0061			61
77017-0349	SW TARMAC FRMSET	CARB/RKTRED/METWHT	49
77017-0352			52
77017-0354			54
77017-0356			56
77017-0358			58
77017-0361			61
77017-0149	SW TARMAC FRMSET	ETIXX-QUICKSTEP	49
77017-0152			52
77017-0154			54
77017-0156			56
77017-0158			58
77017-0161			61
77017-0749	SW TARMAC FRMSET	METWHT/NVY/RKTRED	49
77017-0752			52
77017-0754			54
77017-0756			56
77017-0758			58
77017-0761			61

* Part numbers continued on next page.

TARMAC RFE						
SIZE	49	52	54	56	58	61
Stack (mm)	504	526	543	564	591	612
Reach (mm)	386	386	387	395	402	408
Head-Tube Length (mm)	100	120	140	160	190	210
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	270	270	272.5	272.5	274	274
B-B Drop (mm)	71.5	71.5	69	69	67.5	67.5
Trail (mm)	62	57	57	56	56	53
Fork Length (full) (mm)	368	368	368	368	368	368
Fork Rake/Offset (mm)	45	45	45	43	43	43
Front-Center (mm)	576	576	583	591	605	612
Chain-Stay Length (mm)	405	405	405	405	407	410
Wheelbase (mm)	970	970	978	986	1003	1013
Top-Tube Length (horizontal) (mm)	518	537	548	565	582	600
Bike Stand-Over Height (mm)	730	755	775	795	826	850
Seat-Tube Length (mm)	431	462	481	501	522	553
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Seat Post Length (mm)	350	350	350	400	400	400

S-WORKS TARMAC FRAMESET



LTTUR/BLK



MONGRN/TEAMYEL/TARBLK



BLK/CARB/HYP



TARBLK



TINKOFF

PART NO.	DESCRIPTION	COLOR	SIZE
77017-0449	SW TARMAC FRMSET	LTTUR/BLK	49
77017-0452			52
77017-0454			54
77017-0456			56
77017-0458			58
77017-0461			61
77017-0549	SW TARMAC FRMSET	MONGRN/TEAMYEL/TARBLK	49
77017-0552			52
77017-0554			54
77017-0556			56
77017-0558			58
77017-0561			61
77017-0649	SW TARMAC FRMSET	BLK/CARB/HYP	49
77017-0652			52
77017-0654			54
77017-0656			56
77017-0658			58
77017-0661			61

PART NO.	DESCRIPTION	COLOR	SIZE
77017-0849	SW TARMAC FRMSET	TARBLK	49
77017-0852			52
77017-0854			54
77017-0856			56
77017-0858			58
77017-0861			61
77017-0249	SW TARMAC FRMSET	TINKOFF	49
77017-0252			52
77017-0254			54
77017-0256			56
77017-0258			58
77017-0261			61

S-WORKS TARMAC DISC FRAMESET



BLK

MONGRN/TEAMVEL/TARBLK

You're a person of impeccable taste. Detail oriented, demanding—you need your race rig to be just the right way and no off-the-shelf build is ever going to cut it. We get it, and that's why made our S-Works Tarmac Disc Frameset for riders just like you.

- Featuring our Rider-First Engineered™ design that ensures every frame size has the same legendary climbing responsiveness and descending prowess you'd expect from a Tarmac. The S-Works FACT 11r frameset is our highest quality carbon frame, offering the ideal blend of light overall weight and targeted stiffness. Even better, it's specifically designed for disc brakes, so you'll never have to compromise performance for stopping power.
- S-Works-specific FACT full carbon fork with tapered construction provides incredible front end stiffness and steering response for instantaneous accelerations and high-speed descents. It's also designed for disc brakes, so you won't experience any lurch or degradation in performance.
- With its high-modulus construction, the S-Works FACT full carbon seatpost provides impeccable power transfer, while still allowing for ample compliance for long days in the saddle.

SPECS	All specs are subject to change without notice.
FRAME	S-Works FACT 11r carbon Disc, OSBB, full internal cable routing, internally integrated seat clamp, 135mm rear spacing
FORK	S-Works FACT carbon, full monocoque, size-specific taper
BOTTOM BRACKET	OSBB, CeramicSpeed bearings
SEATPOST	S-Works FACT carbon, 20mm offset, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
74917-0449	SW TARMAC DISC FRMSET	MONGRN/TEAMVEL/TARBLK	49
74917-0452			52
74917-0454			54
74917-0456			56
74917-0458			58
74917-0461			61
74917-0049	SW TARMAC DISC FRMSET	BLK	49
74917-0052			52
74917-0054			54
74917-0056			56
74917-0058			58
74917-0061			61

TARMAC RFE						
SIZE	49	52	54	56	58	61
Stack (mm)	504	526	543	564	591	612
Reach (mm)	386	386	387	395	402	408
Head-Tube Length (mm)	100	120	140	160	190	210
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	270	270	272.5	272.5	274	274
B-B Drop (mm)	71.5	71.5	69	69	67.5	67.5
Trail (mm)	62	57	57	56	56	53
Fork Length (full) (mm)	368	368	368	368	368	368
Fork Rake/Offset (mm)	45	45	45	43	43	43
Front-Center (mm)	576	576	583	591	605	612
Chain-Stay Length (mm)	405	405	405	405	407	410
Wheelbase (mm)	970	970	978	986	1003	1013
Top-Tube Length (horizontal) (mm)	518	537	548	565	582	600
Bike Stand-Over Height (mm)	730	755	775	795	826	850
Seat-Tube Length (mm)	431	462	481	501	522	553
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Seat Post Length (mm)	350	350	350	400	400	400

TARMAC PRO FRAMESET



CARB/CHAR/HYP

Remember all those commercials with blind taste tests that we're so popular in the '90s? Well, if it were safe, we'd love to do the same thing between our Tarmac Pro Frameset and its S-Works cousin. That's because we designed it to be so flawless, so perfect that the only difference most will feel is the huge wad of cash left over in their wallet.

- The FACT 10r carbon frame combines the lightweight performance and compliance of our top-end carbon production methods with our Rider-First Engineered™ design that ensures every frame size has the same legendary climbing responsiveness and descending prowess you'd expect from a Tarmac.
- S-Works FACT full carbon fork with tapered construction provides incredible front end stiffness and steering response for instantaneous accelerations and high-speed descents.

SPECS	All specs are subject to change without notice.
FRAME	FACT 10r carbon, OSBB, full internal cable routing, internally integrated seat clamp, 130mm rear spacing
FORK	S-Works FACT carbon, full monocone, size-specific taper
BOTTOM BRACKET	Praxis 6806 bearings
SEATPOST	S-Works FACT carbon, 20mm offset, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
70617-1049	TARMAC PRO FRMSET	CARB/CHAR/HYP	49
70617-1052			52
70617-1054			54
70617-1056			56
70617-1058			58
70617-1061			61
70617-1064			64

TARMAC RFE W/64CM							
SIZE	49	52	54	56	58	61	64
Stack (mm)	504	526	543	564	591	612	636
Reach (mm)	386	386	387	395	402	408	415
Head-Tube Length (mm)	100	120	140	160	190	210	235
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74	74
B-B Height (mm)	270	270	272.5	272.5	274	274	274.5
B-B Drop (mm)	71.5	71.5	69	69	67.5	67.5	67.5
Trail (mm)	62	57	57	56	56	53	50
Fork Length (full) (mm)	368	368	368	368	368	368	368
Fork Rake/Offset (mm)	45	45	45	43	43	43	43
Front-Center (mm)	576	576	583	591	605	612	645
Chain-Stay Length (mm)	405	405	405	405	407	410	410
Wheelbase (mm)	970	970	978	986	1003	1013	1016
Top-Tube Length (horizontal) (mm)	518	537	548	565	582	600	621
Bike Stand-Over Height (mm)	730	755	775	795	826	850	850
Seat-Tube Length (mm)	431	462	481	501	522	553	584
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5	72.5
Seat Post Length (mm)	350	350	350	400	400	400	350

ALLEZ DSW SL SPRINT EXPERT



MONGRN/TEAMVEL/BLK

The Allez DSW SL Sprint Expert is one of the most advanced alloy road bikes we've ever made, designed with the singular focus of being a reliable crit-racing weapon.

- E5 Premium Aluminum frame with Allez D'Aluisio Smartweld Technology refocuses weld locations, allowing for more material to be placed where it's needed for increased stiffness and compliance where you really need it.
- Our top-tier S-Works FACT carbon fiber fork provides incredible stiffness and front end steering response, while also efficiently absorbing road chatter.
- The Praxis Zayante crankset is an incredibly stiff and light crankset with supreme ramping for precise shifts between the rings.

ALLEZ DSW SL SPRINT						
SIZE	49	52	54	56	58	61
Stack (mm)	502	514	533	554	583	604
Reach (mm)	375	380	385	395	400	405
Head-Tube Length (mm)	100	110	130	150	180	200
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	272.5	272.5	272.5	272.5	272.5	272.5
B-B Drop (mm)	69	69	69	69	69	69
Trail (mm)	63	58	58	55	55	52
Fork Length (full) (mm)	368	368	368	368	368	368
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front-Center (mm)	564	566	577	589	602	608
Chain-Stay Length (mm)	405	405	405	405	405	407
Wheelbase (mm)	959	961	972	984	997	1005
Top-Tube Length (horizontal) (mm)	519	527	538	554	567	578
Bike Stand-Over Height (mm)	732.3	745.8	765.5	784.3	808.3	833.8
Seat-Tube Length (mm)	460	480	500	520	540	570
Seat-Tube Angle (deg)	74	74	74	74	74	74
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	80	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	330	330	330	330	330	330
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized E5 Premium Aluminum w/D'Aluisio Smartweld Sprint Technology, hydroformed aluminum tubing, tapered head tube, OSBB
FORK	S-Works FACT full carbon, size-specific taper
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized S-Wrap
FRONT BRAKE	Shimano 105
REAR BRAKE	Shimano 105
FRONT DERAILLEUR	Shimano 105, braze-on
REAR DERAILLEUR	Shimano Ultegra, 11-speed
SHIFT LEVERS	Shimano Ultegra, 11-speed
CASSETTE	Shimano 105, 11-speed, 11-28t
CHAIN	KMC X11, 11-speed w/reusable MissingLink
CRANKSET	Praxis Zayante, 7075-T6 alloy chainrings
CHAINRINGS	52/36T
BOTTOM BRACKET	Praxis
FRONT WHEEL	Axis Elite, QR
REAR WHEEL	Axis Elite, QR
FRONT TIRE	Turbo Pro, 700x24mm, 60TPI, folding bead, BlackBelt protection
REAR TIRE	Turbo Pro, 700x24mm, 60TPI, folding bead, BlackBelt protection
SADDLE	Body Geometry Toupé Sport, steel rails, 143mm
SEATPOST	Specialized Venge, FACT carbon

PART NO.	DESCRIPTION	COLOR	SIZE
90017-3049	ALLEZ DSW SL SPRINT EXPERT	MONGRN/TEAMVEL/BLK	49
90017-3052			52
90017-3054			54
90017-3056			56
90017-3058			58
90017-3061			61

ALLEZ DSW SL SPRINT COMP



MXORG/BRTYEL/BLK



BLK/RKTRED

Climbs, corners, flat-out sprints—the Allez DSW SL Sprint Comp does it all. Even better, it performs all of the above at a price that's affordable for any racer's budget.

- E5 Premium Aluminum frame with Allez D'Aluisio Smartweld Technology refocuses weld locations, allowing for more material to be placed where it's needed for increased stiffness and compliance where you really need it.
- Our top-tier S-Works FACT carbon fiber fork provides incredible stiffness and front end steering response, while also efficiently absorbing road chatter.
- The Praxis Alba 2D crankset is an incredibly stiff crankset with supreme ramping for precise shifts between the rings.

ALLEZ DSW SL SPRINT

SIZE	49	52	54	56	58	61
Stack (mm)	502	514	533	554	583	604
Reach (mm)	375	380	385	395	400	405
Head-Tube Length (mm)	100	110	130	150	180	200
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	272.5	272.5	272.5	272.5	272.5	272.5
B-B Drop (mm)	69	69	69	69	69	69
Trail (mm)	63	58	58	55	55	52
Fork Length (full) (mm)	368	368	368	368	368	368
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front-Center (mm)	564	566	577	589	602	608
Chain-Stay Length (mm)	405	405	405	405	405	407
Wheelbase (mm)	959	961	972	984	997	1005
Top-Tube Length (horizontal) (mm)	519	527	538	554	567	578
Bike Stand-Over Height (mm)	732.3	745.8	765.5	784.3	808.3	833.8
Seat-Tube Length (mm)	460	480	500	520	540	570
Seat-Tube Angle (deg)	74	74	74	74	74	74
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	80	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	330	330	330	330	330	330
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS

All specs are subject to change without notice.

FRAME	Specialized E5 Premium Aluminum w/D'Aluisio Smartweld Sprint Technology, hydroformed aluminum tubing, tapered head tube, OSBB
FORK	S-Works FACT full carbon, size-specific taper
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized S-Wrap
FRONT BRAKE	AXIS 2.0
REAR BRAKE	AXIS 2.0
FRONT DERAILLEUR	Shimano 105, braze-on
REAR DERAILLEUR	Shimano 105, 11-speed
SHIFT LEVERS	Shimano 105 STI, 11-speed
CASSETTE	Shimano 105, 11-speed, 11-28t
CHAIN	KMC X11, 11-speed w/reusable MissingLink
CRANKSET	Praxis Alba 2D
CHAINRINGS	52/36T
BOTTOM BRACKET	Praxis
FRONT WHEEL	Axis Elite, QR
REAR WHEEL	Axis Elite, QR
FRONT TIRE	Turbo Pro, 700x24mm, 60TPI, folding bead, BlackBelt protection
REAR TIRE	Turbo Pro, 700x24mm, 60TPI, folding bead, BlackBelt protection
SADDLE	Body Geometry Toupé Sport, steel rails, 143mm
SEATPOST	Specialized Venge, FACT carbon

PART NO.	DESCRIPTION	COLOR	SIZE
90017-5149	ALLEZ DSW SL SPRINT COMP	MXORG/BRTYEL/BLK	49
90017-5152			52
90017-5154			54
90017-5156			56
90017-5158			58
90017-5161			61
90017-5049	ALLEZ DSW SL SPRINT COMP	BLK/RKTRED	49
90017-5052			52
90017-5054			54
90017-5056			56
90017-5058			58
90017-5061			61

ALLEZ DSW SL SPRINT ELITE



METWHT/TARBLK

If you're getting into gran fondos, weekend epics, or racing, you need a bike that's reliable, stiff, and value-packed. You need the Allez DSW SL Sprint Elite. It has all the performance you need to explore the world of cycling, from a stiff alloy construction and carbon fork to a durable Tiagra groupset.

- E5 Premium Aluminum frame with Allez D'Aluisio Smartweld Sprint Technology refocuses weld locations, allowing for more material to be placed where it's needed for increased stiffness and compliance where you really need it.
- Our top-tier S-Works FACT carbon fiber fork provides incredible stiffness and front end steering response, while also efficiently absorbing road chatter.
- The Praxis Alba 2D crankset is an incredibly stiff crankset with supreme ramping for precise shifts between the rings.

ALLEZ DSW SL SPRINT

SIZE	49	52	54	56	58	61
Stack (mm)	502	514	533	554	583	604
Reach (mm)	375	380	385	395	400	405
Head-Tube Length (mm)	100	110	130	150	180	200
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	272.5	272.5	272.5	272.5	272.5	272.5
B-B Drop (mm)	69	69	69	69	69	69
Trail (mm)	63	58	58	55	55	52
Fork Length (full) (mm)	368	368	368	368	368	368
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front-Center (mm)	564	566	577	589	602	608
Chain-Stay Length (mm)	405	405	405	405	405	407
Wheelbase (mm)	959	961	972	984	997	1005
Top-Tube Length (horizontal) (mm)	519	527	538	554	567	578
Bike Stand-Over Height (mm)	732.3	745.8	765.5	784.3	808.3	833.8
Seat-Tube Length (mm)	460	480	500	520	540	570
Seat-Tube Angle (deg)	74	74	74	74	74	74
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	80	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	330	330	330	330	330	330
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS

All specs are subject to change without notice.

FRAME	Specialized E5 Premium Aluminum w/D'Aluisio Smartweld Sprint Technology, hydroformed aluminum tubing, tapered head tube, OSBB
FORK	S-Works FACT full carbon, size-specific taper
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized S-Wrap
FRONT BRAKE	AXIS 1.0
REAR BRAKE	AXIS 1.0
FRONT DERAILLEUR	Shimano Tiagra, braze-on
REAR DERAILLEUR	Shimano Tiagra 4700, 10-speed
SHIFT LEVERS	Shimano Tiagra STI, 10-speed
CASSETTE	Shimano Tiagra, 10-speed, 12-28t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	Praxis Alba 2D
CHAINRINGS	52/36T
BOTTOM BRACKET	Praxis
FRONT WHEEL	Axis Sport
REAR WHEEL	Axis Sport
FRONT TIRE	Espoir Sport, 700x25mm, 60TPI, wire bead, double BlackBelt protection
REAR TIRE	Espoir Sport, 700x25mm, 60TPI, wire bead, double BlackBelt protection
SADDLE	Body Geometry Toupé Sport, steel rails, 143mm
SEATPOST	Specialized Venge, FACT carbon

PART NO.	DESCRIPTION	COLOR	SIZE
90017-4149	ALLEZ DSW SL SPRINT ELITE	METWHT/TARBLK	49
90017-4152			52
90017-4154			54
90017-4156			56
90017-4158			58
90017-4161			61

ALLEZ E5 ELITE



METWHT/TARBLK



INK/RKTRED

There's no denying it, we're still in love with aluminum road bikes. And when it comes to transforming this passion into a labor of love, we make a bike like the Allez E5 Elite.

- E5 Premium Aluminum frame features fully manipulated tubing with smooth welds that increase stiffness and efficiency, while looking just as good as it performs.
- A FACT carbon fiber fork provides incredible stiffness and front end steering response, while also efficiently absorbing road chatter.
- Shimano Tiagra 10-speed shifting is precise, reliable, and ready for years of hard riding.

ALLEZ E5 ELITE

SIZE	49	52	54	56	58	61
Stack (mm)	505	527	548	574	606	632
Reach (mm)	387	387	387	392	397	401
Head-Tube Length (mm)	100	120	145	170	205	230
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	270	270	272.5	272.5	274	274
B-B Drop (mm)	72	72	69	69	68	68
Trail (mm)	62	57	57	54	54	51
Fork Length (full) (mm)	369	369	369	369	369	369
Fork Rake/Offset (mm)	45	45	45	45	45	45
Front-Center (mm)	578	578	585	593	607	613
Chain-Stay Length (mm)	405	407	407	407	410	410
Wheelbase (mm)	972	974	982	990	1008	1014
Top-Tube Length (horizontal) (mm)	518	538	549	565	582	600
Bike Stand-Over Height (mm)	736	759	783	805	834	860
Seat-Tube Length (mm)	460	490	510	530	550	580
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	80	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	300	300	350	350	350	350
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS

All specs are subject to change without notice.

FRAME	Specialized E5 Premium Aluminum, fully-manipulated tubing w/smooth welds, 1-1/8" lower bearing
FORK	FACT carbon fiber
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized S-Wrap
FRONT BRAKE	AXIS 1.0
REAR BRAKE	AXIS 1.0
FRONT DERAILLEUR	Shimano Tiagra, clamp-on
REAR DERAILLEUR	Shimano Tiagra 4700, 10-speed
SHIFT LEVERS	Shimano Tiagra STI, 10-speed
CASSETTE	Shimano Tiagra, 10-speed, 12-28t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	Praxis Alba
CHAINRINGS	50/34T
BOTTOM BRACKET	Praxis
FRONT WHEEL	Axis Sport
REAR WHEEL	Axis Sport
FRONT TIRE	Espoir Sport, 700x25mm, 60TPI, wire bead, double BlackBelt protection
REAR TIRE	Espoir Sport, 700x25mm, 60TPI, wire bead, double BlackBelt protection
SADDLE	Body Geometry Toupé Sport, steel rails, 143mm
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90017-4349	ALLEZ E5 ELITE	METWHT/TARBLK	49
90017-4352			52
90017-4354			54
90017-4356			56
90017-4358			58
90017-4361			61
90017-4249	ALLEZ E5 ELITE	INK/RKTRED	49
90017-4252			52
90017-4254			54
90017-4256			56
90017-4258			58
90017-4261			61

ALLEZ E5 SPORT



TARBLK/FLORED/WHT



MONGRN/TARBLK/RKTRED

The Allez E5 Sport is versatile and value-packed. That's because its stiff alloy construction, carbon fork, and Shimano Sora shifting make sure that it's ready to take on all of your weekend rides with complete confidence. Go out and get after it.

- E5 Premium Aluminum frame features fully manipulated tubing with smooth welds that increase stiffness and efficiency, while looking just as good as it performs.
- A FACT carbon fiber fork provides incredible stiffness and front end steering response, while also efficiently absorbing road chatter.
- Shimano Sora 9-speed shifting is nothing short of legendary. It's built to last over the long haul, and it's well-equipped to deliver precise shifts across a wide range of gears.

ALLEZ E5

SIZE	49	52	54	56	58	61
Stack (mm)	505	527	548	574	606	632
Reach (mm)	387	387	387	392	397	401
Head-Tube Length (mm)	100	120	145	170	205	230
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	270	270	272.5	272.5	274	274
B-B Drop (mm)	72	72	69	69	68	68
Trail (mm)	62	57	57	54	54	51
Fork Length (full) (mm)	369	369	369	369	369	369
Fork Rake/Offset (mm)	45	45	45	45	45	45
Front-Center (mm)	578	578	585	593	607	613
Chain-Stay Length (mm)	405	407	407	407	410	410
Wheelbase (mm)	972	974	982	990	1008	1014
Top-Tube Length (horizontal) (mm)	518	538	549	565	582	600
Bike Stand-Over Height (mm)	736	759	783	805	834	860
Seat-Tube Length (mm)	460	490	510	530	550	580
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	80	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	300	300	350	350	350	350
Crank Length (mm)	170	170	170	175	175	175

SPECS

All specs are subject to change without notice.

FRAME	Specialized E5 Premium Aluminum, fully-manipulated tubing w/smooth welds, 1-1/8" lower bearing
FORK	FACT carbon fiber
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized S-Wrap
FRONT BRAKE	AXIS 1.0
REAR BRAKE	AXIS 1.0
FRONT DERAILLEUR	Shimano Sora, clamp-on
REAR DERAILLEUR	Shimano Sora, 9-speed
SHIFT LEVERS	Shimano Sora STI
CASSETTE	Sunrace, 9-speed, 11-32t
CHAIN	KMC X9, 9-speed w/reusable MissingLink
CRANKSET	Shimano Sora Compact
CHAINRINGS	50/34T
BOTTOM BRACKET	Shimano
FRONT WHEEL	Axis Sport
REAR WHEEL	Axis Sport
FRONT TIRE	Espoir Sport, 700x25mm, 60TPI, wire bead, double BlackBelt protection
REAR TIRE	Espoir Sport, 700x25mm, 60TPI, wire bead, double BlackBelt protection
SADDLE	Body Geometry Toupé Sport, steel rails, 143mm
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90017-6149	ALLEZ E5 SPORT	TARBLK/FLORED/WHT	49
90017-6152			52
90017-6154			54
90017-6156			56
90017-6158			58
90017-6161			61
90017-6049	ALLEZ E5 SPORT	MONGRN/TARBLK/RKTRED	49
90017-6052			52
90017-6054			54
90017-6056			56
90017-6058			58
90017-6061			61

ALLEZ E5



BLK/WHT

If you're just finding your cycling legs, this is the best place to start. The Allez E5's premium alloy frame is built for versatility, combining sturdy, confident handling with the rocket-like feeling of a race bike. And for durability, it includes a FACT carbon fork and reliable Claris shifting.

- E5 Premium Aluminum frame features fully manipulated tubing with smooth welds that increase stiffness and efficiency, while looking just as good as it performs.
- A FACT carbon fiber fork provides incredible stiffness and front end steering response, while also efficiently absorbing road chatter.
- Shimano Claris 2400 9-speed shifting is built to last over the long haul, and it's well-equipped to deliver precise shifts across a wide range of gears.

ALLEZ E5						
SIZE	49.0	52.0	54.0	56.0	58.0	61.0
Stack (mm)	505	527	548	574	606	632
Reach (mm)	387	387	387	392	397	401
Head-Tube Length (mm)	100	120	145	170	205	230
Head-Tube Angle (deg)	72.25	73	73	73.5	73.5	74
B-B Height (mm)	270	270	272.5	272.5	274	274
B-B Drop (mm)	72	72	69	69	68	68
Trail (mm)	62	57	57	54	54	51
Fork Length (full) (mm)	369	369	369	369	369	369
Fork Rake/Offset (mm)	45	45	45	45	45	45
Front-Center (mm)	578	578	585	593	607	613
Chain-Stay Length (mm)	405	407	407	407	410	410
Wheelbase (mm)	972	974	982	990	1008	1014
Top-Tube Length (horizontal) (mm)	518	538	549	565	582	600
Bike Stand-Over Height (mm)	736	759	783	805	834	860
Seat-Tube Length (mm)	460	490	510	530	550	580
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	80	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	300	300	350	350	350	350
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized E5 Premium Aluminum, fully-manipulated tubing w/smooth welds, 1-1/8" lower bearing
FORK	FACT carbon fiber
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized S-Wrap
FRONT BRAKE	Tektro, caliper, dual pivot
REAR BRAKE	Tektro, caliper, short reach, dual pivot
FRONT DERAILLEUR	Shimano Claris 2400, clamp-on
REAR DERAILLEUR	Shimano Claris 2400, 8-speed
SHIFT LEVERS	Shimano Claris 2400 STI
CASSETTE	Sunrace, 8-speed, 11-32t
CHAIN	KMC Z7, 8-speed w/reusable MissingLink
CRANKSET	FSA Gossamer Pro, Direct mount ABS, MegaExo Integrated Interface, 68mm English BB, 9-/10-speed, forged 6066 aluminum, 144mm Q-factor
CHAINRINGS	50/34T
BOTTOM BRACKET	FSA
FRONT WHEEL	Axis Sport
REAR WHEEL	Axis Sport
FRONT TIRE	Espoir Sport, 700x25mm, 60TPI, wire bead, double BlackBelt protection
REAR TIRE	Espoir Sport, 700x25mm, 60TPI, wire bead, double BlackBelt protection
SADDLE	Body Geometry Toupé Sport, steel rails, 143mm
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90017-7149	ALLEZ E5	BLK/WHT	49
90017-7152			52
90017-7154			54
90017-7156			56
90017-7158			58
90017-7161			61



TARBLK/FLORED

The Allez Jr. is specifically designed for younger riders looking to up their game. With its 650C-specific frame and reliable components, the Allez Jr. gives young riders all the performance they need to tackle the roads ahead.

- Specialized A1 Premium Aluminum frame combines smooth welds and smaller geometries to produce a high-performance frame made just for younger riders.
- Specialized alloy fork is stiff and responsive for out of the saddle efforts and expert handling.
- microSHIFT R482 shifters control Shimano Claris 2400 derailleurs for precise shifting that'll withstand years of abuse.

ALLEZ JR	
SIZE	44.0
Stack (mm)	490
Reach (mm)	358
Head-Tube Length (mm)	130
Head-Tube Angle (deg)	72
B-B Height (mm)	236.5
B-B Drop (mm)	49
Trail (mm)	50
Fork Length (full) (mm)	346
Fork Rake/Offset (mm)	41
Front-Center (mm)	547
Chain-Stay Length (mm)	380
Wheelbase (mm)	921
Top-Tube Length (horizontal) (mm)	480
Bike Stand-Over Height (mm)	665
Seat-Tube Length (mm)	400
Seat-Tube Angle (deg)	76
Handlebar Width (mm)	360
Stem Length (mm)	60
Seat Post Length (mm)	300
Crank Length (mm)	160

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, fully-manipulated tubing w/smooth welds, 1-1/8" lower bearing
FORK	Alloy, 1-1/8" alloy steer, 45mm crown
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized S-Wrap
FRONT BRAKE	Tektro, caliper, dual pivot
REAR BRAKE	Tektro, caliper, short reach, dual pivot
FRONT DERAILLEUR	Shimano Claris 2400, clamp-on
REAR DERAILLEUR	Shimano Claris 2400, 8-speed
SHIFT LEVERS	microSHIFT R482, short reach, 8-speed
CASSETTE	Sunrace, 8-speed, 11-32t
CHAIN	KMC Z7, 8-speed w/reusable MissingLink
CRANKSET	Square taper, BCD spider110 Alloy forged Crankarm 160MM*Sandblast black, Alloy stamped ring 46T*Sandblast Anodized black, Steel stamped ring 34T*ED BK, WITHOUT BB 8S
CHAINRINGS	46/34T
BOTTOM BRACKET	BSA, square taper, cartridge bearings
FRONT WHEEL	Axis Sport JR
REAR WHEEL	Axis Sport JR
FRONT TIRE	Turbo Elite, 650x23mm, 60TPI, folding bead, BlackBelt protection
REAR TIRE	Turbo Elite, 650x23mm, 60TPI, folding bead, BlackBelt protection
SADDLE	Specialized Youth, steel rails
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90017-7044	ALLEZ JR. (650C)	TARBLK/FLORED	44

ROUBAIX SL4 COMP UDI2



CARB/METWHTSIL

The Roubaix SL4 Comp UDi2 is what you might call an "upgrade," as this endurance-bred bike is head and shoulders above its competition. It's a serious step-up from first-time road bikes, and to make sure of it, it's been outfitted with Shimano's innovative Ultegra Di2 electronic drivetrain.

- The SL4 FACT 8r carbon frame has all of the road absorbing, engineered compliance that you'd expect from a bike born on the cobbles, yet its compact endurance race design provides all of the responsiveness and performance you need for long days in the saddle.
- FACT carbon fork is optimized for stiffness and responsive steering, while road chatter and vibration are significantly reduced via our proprietary Zertz elastomer inserts.
- Shimano Ultegra Di2 shifters provide next-level shifting that's guaranteed to always be crisp, precise, and right on the money.

ROUBAIX SL4						
SIZE	49	52	54	56	58	61
Stack (mm)	528	547	564	590	622	643
Reach (mm)	378	379	380	387	392	398
Head-Tube Length (mm)	125	145	165	190	225	245
Head-Tube Angle (deg)	72	72	72	72.5	72.5	73
B-B Height (mm)	269.5	269.5	271	271	272.5	272.5
B-B Drop (mm)	73	73	71.5	71.5	70	70
Trail (mm)	60	60	60	57	57	53
Fork Length (full) (mm)	368	368	368	368	368	368
Fork Rake/Offset (mm)	49	49	49	49	49	49
Front-Center (mm)	582	589	596	606	621	628
Chain-Stay Length (mm)	412	412	415	415	418	420
Wheelbase (mm)	983	990	1000	1011	1029	1039
Top-Tube Length (horizontal) (mm)	514	536	547	565	582	601
Bike Stand-Over Height (mm)	730	756	776	798	829	851
Seat-Tube Length (mm)	445	475	495	515	540	565
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	70	80	90	100	100	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	350	350	350	350	350	350
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized SL4 FACT 10r carbon, 1-1/8" to 1-3/8" head tube, compact race design, Zertz, inter10al rear brake cable, OSBB
FORK	FACT carbon fiber, full carbon monocoque, Zertz inserts
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	Shimano 105
REAR BRAKE	Shimano 105
FRONT DERAILLEUR	Shimano Ultegra Di2 6870, 11-speed, braze-on
REAR DERAILLEUR	Shimano Ultegra Di2, 11-speed
SHIFT LEVERS	Shimano Ultegra Di2, 11-speed
CASSETTE	Shimano 105, 11-speed, 11-32t
CHAIN	KMC X11, 11-speed
CRANKSET	Praxis Zayante, 7075-T6
CHAINRINGS	Praxis, alloy, 50/34T
BOTTOM BRACKET	Praxis
FRONT WHEEL	Axis Elite, QR
REAR WHEEL	Axis Elite, QR
FRONT TIRE	Turbo Pro, 700x26mm, 60TPI, folding bead, BlackBelt protection
REAR TIRE	Turbo Pro, 700x26mm, 60TPI, folding bead, BlackBelt protection
SADDLE	Phenom Comp GT, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized CG-R, FACT carbon, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
94417-5549	ROUBAIX SL4 COMP UDI2 RIM	CARB/METWHTSIL	49
94417-5552			52
94417-5554			54
94417-5556			56
94417-5558			58
94417-5561			61

ROUBAIX SL4 SPORT



CARB/FLORED



CARB/HYP/METWHTSIL

Hitting a sweet spot between performance and value, the Roubaix SL4 Sport benefits from the ride quality that emanates from our Endurance Geometry, vibration-damping Zertz inserts, and Shimano 105 groupset. So it's guaranteed to thrive on long rides through rough country.

- The SL4 FACT 8r carbon frame has all of the road absorbing, engineered compliance that you'd expect from a bike born on the cobbles, yet its compact endurance race design provides all of the responsiveness and performance you need for long days in the saddle.
- FACT carbon fork is optimized for stiffness and responsive steering, while road chatter and vibration are significantly reduced via our proprietary Zertz elastomer inserts.
- A stiff, lightweight alloy Praxis Alba 2D crankset is there to punch well above its weight class, minimizing energy loss while you're hammering away on the pedals.

ROUBAIX SL4						
SIZE	49	52	54	56	58	61
Stack (mm)	528	547	564	590	622	643
Reach (mm)	378	379	380	387	392	398
Head-Tube Length (mm)	125	145	165	190	225	245
Head-Tube Angle (deg)	72	72	72	72.5	72.5	73
B-B Height (mm)	269.5	269.5	271	271	272.5	272.5
B-B Drop (mm)	73	73	71.5	71.5	70	70
Trail (mm)	60	60	60	57	57	53
Fork Length (full) (mm)	368	368	368	368	368	368
Fork Rake/Offset (mm)	49	49	49	49	49	49
Front-Center (mm)	582	589	596	606	621	628
Chain-Stay Length (mm)	412	412	415	415	418	420
Wheelbase (mm)	983	990	1000	1011	1029	1039
Top-Tube Length (horizontal) (mm)	514	536	547	565	582	601
Bike Stand-Over Height (mm)	730	756	776	798	829	851
Seat-Tube Length (mm)	445	475	495	515	540	565
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	70	80	90	100	100	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	350	350	350	350	350	350
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized SL4 FACT 10r carbon, 1-1/8" to 1-3/8" head tube, compact race design, Zertz, internal rear brake cable, OSBB
FORK	FACT carbon fiber, full carbon monocoque, Zertz inserts
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	AXIS 1.0
REAR BRAKE	AXIS 1.0
FRONT DERAILLEUR	Shimano 105, braze-on
REAR DERAILLEUR	Shimano 105, GS cage, 11-speed
SHIFT LEVERS	Shimano 105 STI, 11-speed
CASSETTE	Shimano 105, 11-speed, 11-32t
CHAIN	KMC X11, 11-speed
CRANKSET	Praxis Alba
CHAINRINGS	Praxis, alloy, 50/34T
BOTTOM BRACKET	Praxis
FRONT WHEEL	Axis Elite, QR
REAR WHEEL	Axis Elite, QR
FRONT TIRE	Turbo Pro, 700x26mm, 60TPI, folding bead, BlackBelt protection
REAR TIRE	Turbo Pro, 700x26mm, 60TPI, folding bead, BlackBelt protection
SADDLE	Phenom Comp GT, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized CG-R, FACT carbon, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
94417-6149	ROUBAIX SL4 SPORT RIM	CARB/FLORED	49
94417-6152			52
94417-6154			54
94417-6156			56
94417-6158			58
94417-6161			61
94417-6049	ROUBAIX SL4 SPORT RIM	CARB/HYP/METWHTSIL	49
94417-6052			52
94417-6054			54
94417-6056			56
94417-6058			58
94417-6061			61

ROUBAIX SL4



METWHTSIL/TARBLK



INK/NRDCRED/SIL

The Roubaix SL4 makes sure that you have what you need to explore the road less traveled, while keeping room in your wallet for a mid-ride brew. And with Endurance Geometry, vibration-damping Zertz inserts, and Shimano's 10-speed Tiagra groupset, you won't have to sacrifice a thing.

- The SL4 FACT 8r carbon frame has all of the road absorbing, engineered compliance that you'd expect from a bike born on the cobbles, yet its compact endurance race design provides all of the responsiveness and performance you need for long days in the saddle.
- FACT carbon fork is optimized for stiffness and responsive steering, while road chatter and vibration are significantly reduced via our proprietary Zertz elastomer inserts.
- A stiff, lightweight alloy Praxis Alba 2D crankset is there to punch well above its weight class, minimizing energy loss while you're hammering away on the pedals.

ROUBAIX SL4						
SIZE	49	52	54	56	58	61
Stack (mm)	528	547	564	590	622	643
Reach (mm)	378	379	380	387	392	398
Head-Tube Length (mm)	125	145	165	190	225	245
Head-Tube Angle (deg)	72	72	72	72.5	72.5	73
B-B Height (mm)	269.5	269.5	271	271	272.5	272.5
B-B Drop (mm)	73	73	71.5	71.5	70	70
Trail (mm)	60	60	60	57	57	53
Fork Length (full) (mm)	368	368	368	368	368	368
Fork Rake/Offset (mm)	49	49	49	49	49	49
Front-Center (mm)	582	589	596	606	621	628
Chain-Stay Length (mm)	412	412	415	415	418	420
Wheelbase (mm)	983	990	1000	1011	1029	1039
Top-Tube Length (horizontal) (mm)	514	536	547	565	582	601
Bike Stand-Over Height (mm)	730	756	776	798	829	851
Seat-Tube Length (mm)	445	475	495	515	540	565
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	70	80	90	100	100	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	350	350	350	350	350	350
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized SL4 FACT 10r carbon, 1-1/8" to 1-3/8" head tube, compact race design, Zertz, internal rear brake cable, OSBB
FORK	FACT carbon fiber, full carbon monocoque, Zertz inserts
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized Roubaix w/stickygel
FRONT BRAKE	AXIS 1.0
REAR BRAKE	AXIS 1.0
FRONT DERAILLEUR	Shimano Tiagra, braze-on
REAR DERAILLEUR	Shimano Tiagra, long cage, 10-speed
SHIFT LEVERS	Shimano Tiagra STI, 10-speed
CASSETTE	Shimano Tiagra, 10-speed, 11-34t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	Praxis Alba
CHAINRINGS	Praxis, alloy, 50/34T
BOTTOM BRACKET	Praxis
FRONT WHEEL	Axis Elite, QR
REAR WHEEL	Axis Elite, QR
FRONT TIRE	Espoir Elite, 700x25mm
REAR TIRE	Espoir Elite, 700x25mm
SADDLE	Body Geometry Toupé Sport, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized CG-R, FACT carbon, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
94417-7149	ROUBAIX SL4 RIM	METWHTSIL/TARBLK	49
94417-7152			52
94417-7154			54
94417-7156			56
94417-7158			58
94417-7161			61
94417-7049	ROUBAIX SL4 RIM	INK/NRDCRED/SIL	49
94417-7052			52
94417-7054			54
94417-7056			56
94417-7058			58
94417-7061			61

SHIV EXPERT



CARB/RKTRED

The Shiv Expert has been designed with the sole intention of making you faster. The aerodynamically optimized FACT 10r carbon frame and fork offer lightweight performance, and they've been coupled with the bulletproof Shimano Ultegra drivetrain in order to make this Shiv ready to go straight out of the box.

- The FACT 10r carbon frame is lightweight and extremely responsive. It features crosswind-optimized airfoils for enhanced aerodynamic performance, while the Control Tower Fit System and Fuelselage Integrated Hydration System provide versatile fit options and nutrition integration.
- FACT Aero carbon fork utilizes our most advanced carbon construction methods to provide precise steering and rider input, while also improving overall aerodynamics.
- Significantly lighter than comparable wheelsets in its class, these tough Axis Elite wheels offer tremendous value in one smooth-rolling package.

SHIV					
SIZE	XS	S	M	L	XL
Stack (mm)	495	514	540	565	590
Reach (mm)	365	385	405	425	445
Head-Tube Length (mm)	99	115	139	163	189
Head-Tube Angle (deg)	70.25	71.5	72	72.5	72.5
B-B Height (mm)	258	258	258	258	258
B-B Drop (mm)	72	72	72	72	72
Trail (mm)	65	58	60	57	57
Fork Length (full) (mm)	367	367	367	367	367
Fork Rake/Offset (mm)	50	50	45	45	45
Front-Center (mm)	574	590	609	632	659
Chain-Stay Length (mm)	395	395	395	395	395
Wheelbase (mm)	958	974	993	1016	1044
Top-Tube Length (horizontal) (mm)	479	504	530	555	581
Bike Stand-Over Height (mm)	752	772	797	822	847
Seat-Tube Length (mm)	505	525	551	577	603
Seat-Tube Angle (deg)	77	77	77	77	77
Stem Length (mm)	90	90	90	90	90
Seat Post Length (mm)	350	350	350	350	350
Crank Length (mm)	165	170	172.5	172.5	175

SPECS

All specs are subject to change without notice.

FRAME	Specialized FACT 10r carbon, FACT IS construction, crosswind-optimized airfoils, 1-1/8" bearings, OSBB, Control Tower Fit System, Fuelselage Integrated Hydration System
FORK	Specialized FACT FUCI Aero carbon
STEM	3D-forged alloy, 7-degree rise
HANDLEBARS	Specialized Shiv Alloy Aerobars
TAPE	Specialized S-Wrap w/gel
FRONT BRAKE	Specialized Aero, side pull
REAR BRAKE	Specialized Aero, side pull
FRONT DERAILLEUR	Shimano Ultegra, braze-on
REAR DERAILLEUR	Shimano Ultegra, 11-speed
SHIFT LEVERS	Shimano Dura Ace TT, 11-Speed
CASSETTE	Shimano Ultegra, 11-speed, 11-28t
CHAIN	Shimano Ultegra, 11-speed
CRANKSET	FSA SL-K Light
CHAINRINGS	52/36T
BOTTOM BRACKET	BB30
FRONT WHEEL	Axis Elite, 20h
REAR WHEEL	Axis Elite, 24h
FRONT TIRE	Turbo Pro, 700x24mm, 60TPI, folding bead, BlackBelt protection
REAR TIRE	Turbo Pro, 700x24mm, 60TPI, folding bead, BlackBelt protection
SADDLE	Body Geometry Sitero Expert, hollow titanium rails
SEATPOST	Shiv Aero, FACT carbon, +/-12.5mm and +/-37.5mm setback

PART NO.	DESCRIPTION	COLOR	SIZE
97417-3001	SHIV EXPERT	CARB/RKTRED	XS
97417-3002			S
97417-3003			M
97417-3004			L
97417-3005			XL

SHIV SPORT



CHAR/TARBLK/RKTRED

The Shiv Sport was designed with one goal in mind—making you faster over the bike leg of your race, without setting you back six month's rent. So whether you're looking to go after your first triathlon or set a new PR, you can ride with confidence that it's up to the task.

- The FACT 10r carbon frame is lightweight and extremely responsive. It features crosswind-optimized airfoils for enhanced aerodynamic performance, while the Control Tower Fit System and Fuelselage Integrated Hydration System provide versatile fit options and nutrition integration.
- FACT Aero carbon fork utilizes our most advanced carbon construction methods to provide precise steering and rider input, while also improving overall aerodynamics.
- Significantly lighter than comparable wheelsets in its class, these tough Axis Elite wheels offer tremendous value in one smooth-rolling package.

SHIV					
SIZE	XS	S	M	L	XL
Stack (mm)	495	514	540	565	590
Reach (mm)	365	385	405	425	445
Head-Tube Length (mm)	99	115	139	163	189
Head-Tube Angle (deg)	70.25	71.5	72	72.5	72.5
B-B Height (mm)	258	258	258	258	258
B-B Drop (mm)	72	72	72	72	72
Trail (mm)	65	58	60	57	57
Fork Length (full) (mm)	367	367	367	367	367
Fork Rake/Offset (mm)	50	50	45	45	45
Front-Center (mm)	574	590	609	632	659
Chain-Stay Length (mm)	395	395	395	395	395
Wheelbase (mm)	958	974	993	1016	1044
Top-Tube Length (horizontal) (mm)	479	504	530	555	581
Bike Stand-Over Height (mm)	752	772	797	822	847
Seat-Tube Length (mm)	505	525	551	577	603
Seat-Tube Angle (deg)	77	77	77	77	77
Stem Length (mm)	90	90	90	90	90
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	350	350	350	350	350
Crank Length (mm)	165	170	172.5	172.5	175

SPECS All specs are subject to change without notice.

FRAME	Specialized FACT 10r carbon, FACT IS construction, crosswind-optimized airfoils, 1-1/8" bearings, OSBB, Control Tower Fit System, Fuelselage Integrated Hydration System
FORK	Specialized FACT FUCI Aero carbon
STEM	3D-forged alloy, 7-degree rise
HANDLEBARS	Specialized Shiv Alloy Aerobars
TAPE	Specialized S-Wrap w/gel
FRONT BRAKE	Specialized Aero, side pull
REAR BRAKE	Specialized Aero, side pull
FRONT DERAILLEUR	Shimano Tiagra, braze-on
REAR DERAILLEUR	Shimano Tiagra 4700, 10-speed
SHIFT LEVERS	microSHIFT TT
CASSETTE	Shimano Tiagra, 10-speed, 12-28t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	Praxis Alba 2D
CHAINRINGS	52/36T
BOTTOM BRACKET	Praxis BB
FRONT WHEEL	Axis Elite, 20h
REAR WHEEL	Axis Elite, 24h
FRONT TIRE	Espoir Sport 700x23mm
REAR TIRE	Espoir Sport 700x23mm
SADDLE	Body Geometry Sitero Comp, hollow Cr-Mo rails
SEATPOST	Shiv Aero, FACT carbon, +/-12.5mm and +/-37.5mm setback

PART NO.	DESCRIPTION	COLOR	SIZE
97417-6001	SHIV SPORT	CHAR/TARBLK/RKTRED	XS
97417-6002			S
97417-6003			M
97417-6004			L
97417-6005			XL

SHIV ELITE



CARB/WHT



PRPTNT/HYP/CLGRY

The Shiv Elite is the perfect weapon for tackling your first triathlon or setting a new PR. It blends wind-cheating aerodynamics with lightweight and durable components, like a drivetrain derived from a Shimano 105 & Praxis mix, and it's purpose-built for tackling your next race. In a nutshell, it goes all-out to make you faster.

- The FACT 10r carbon frame is lightweight and extremely responsive. It features crosswind-optimized airfoils for enhanced aerodynamic performance, while the Control Tower Fit System and Fuelselage Integrated Hydration System provide versatile fit options and nutrition integration.
- FACT Aero carbon fork utilizes our most advanced carbon construction methods to provide precise steering and rider input, while also improving overall aerodynamics.
- Significantly lighter than comparable wheelsets in its class, these tough Axis Elite wheels offer tremendous value in one smooth-rolling package.

SHIV					
SIZE	XS	S	M	L	XL
Stack (mm)	495	514	540	565	590
Reach (mm)	365	385	405	425	445
Head-Tube Length (mm)	99	115	139	163	189
Head-Tube Angle (deg)	70.25	71.5	72	72.5	72.5
B-B Height (mm)	258	258	258	258	258
B-B Drop (mm)	72	72	72	72	72
Trail (mm)	65	58	60	57	57
Fork Length (full) (mm)	367	367	367	367	367
Fork Rake/Offset (mm)	50	50	45	45	45
Front-Center (mm)	574	590	609	632	659
Chain-Stay Length (mm)	395	395	395	395	395
Wheelbase (mm)	958	974	993	1016	1044
Top-Tube Length (horizontal) (mm)	479	504	530	555	581
Bike Stand-Over Height (mm)	752	772	797	822	847
Seat-Tube Length (mm)	505	525	551	577	603
Seat-Tube Angle (deg)	77	77	77	77	77
Stem Length (mm)	90	90	90	90	90
Seat Post Length (mm)	350	350	350	350	350
Crank Length (mm)	165	170	172.5	172.5	175

SPECS All specs are subject to change without notice.

FRAME	Specialized FACT 10r carbon, FACT IS construction, crosswind-optimized airfoils, 1-1/8" lower bearing, OSBB, Control Tower Fit System, Fuelselage Integrated Hydration System
REAR SHOCK	Stainless steel pivots
FORK	Specialized FACT FUCI Aero carbon
STEM	3D-forged alloy, 7-degree rise
HANDLEBARS	Specialized Shiv Alloy Aerobars
TAPE	Specialized S-Wrap w/gel
FRONT BRAKE	Specialized Aero, side pull
REAR BRAKE	Specialized Aero, side pull
FRONT DERAILLEUR	Shimano 105, braze-on
REAR DERAILLEUR	Shimano 105, 11-speed
SHIFT LEVERS	Shimano Dura Ace TT, 11-Speed
CASSETTE	Shimano 105, 11-speed, 11-28t
CHAIN	KMC X11, 11-speed
CRANKSET	Praxis Zayante, 7075-T6 alloy chainrings
CHAINRINGS	52/36T
BOTTOM BRACKET	Praxis
FRONT WHEEL	Axis Elite, QR
REAR WHEEL	Axis Elite, QR
FRONT TIRE	Turbo Pro, 700x24mm, 60TPI, folding bead, BlackBelt protection
REAR TIRE	Turbo Pro, 700x24mm, 60TPI, folding bead, BlackBelt protection
SADDLE	Body Geometry Sitero Comp, hollow Cr-Mo rails
SEATPOST	Shiv Aero, FACT carbon, +/-12.5mm and +/-37.5mm setback

PART NO.	DESCRIPTION	COLOR	SIZE
97417-4001	SHIV ELITE	CARB/WHT	XS
97417-4002			S
97417-4003			M
97417-4004			L
97417-4005			XL
97417-4101	SHIV ELITE	PRPTNT/HYP/CLGRY	XS
97417-4102			S
97417-4103			M
97417-4104			L
97417-4105			XL

S-WORKS SHIV MODULE



RKTRED/NENYEL/BLK

On the bike leg of any triathlon, speed and efficiency win the game. The S-Works Shiv is the ultimate speed weapon for any triathlon distance, and it's purpose-built to take your bike leg to the next level.

- S-Works FACT 11r carbon frame is made with our highest quality construction methods and features crosswind-optimized airfoils for enhanced aerodynamics. Meanwhile, the Control Tower Fit System and Fuelselage Hydration System ensure that your fit and hydration are always optimized.
- FACT Aero carbon fork utilizes our most advanced carbon construction methods in order to provide precise steering and rider input, while also improving overall aerodynamics.
- The Shiv Aero seatpost is constructed from FACT carbon fiber for the ultimate in lightweight performance. It features both a 12.5mm and 37.5mm setback fit option.

SPECS	All specs are subject to change without notice.
FRAME	Specialized FACT 11r carbon, FACT IS construction, crosswind-optimized airfoils, 1-1/8" bearings, OSBB, Control Tower Fit System, Fuelselage Integrated Hydration System
FORK	Specialized FACT FUCI Aero carbon
STEM	S-Works Shiv aero stem
HANDLEBARS	Specialized carbon Integrated Aerobar
TAPE	S-Wrap
FRONT BRAKE	Specialized Aero, side pull
REAR BRAKE	Specialized Aero, side pull
BOTTOM BRACKET	OSBB, CeramicSpeed bearings
SEATPOST	Shiv Aero, FACT carbon, +/-12.5mm and +/-37.5mm setback

PART NO.	DESCRIPTION	COLOR	SIZE
79117-0401	SW SHIV MODULE	RKTRED/NENYEL/BLK	XS
79117-0402			S
79117-0403			M
79117-0404			L
79117-0405			XL

SHIV					
SIZE	XS	S	M	L	XL
Stack (mm)	495	514	540	565	590
Reach (mm)	365	385	405	425	445
Head-Tube Length (mm)	99	115	139	163	189
Head-Tube Angle (deg)	70.25	71.5	72	72.5	72.5
B-B Height (mm)	258	258	258	258	258
B-B Drop (mm)	72	72	72	72	72
Trail (mm)	65	58	60	57	57
Fork Length (full) (mm)	367	367	367	367	367
Fork Rake/Offset (mm)	50	50	45	45	45
Front-Center (mm)	574	590	609	632	659
Chain-Stay Length (mm)	395	395	395	395	395
Wheelbase (mm)	958	974	993	1016	1044
Top-Tube Length (horizontal) (mm)	479	504	530	555	581
Bike Stand-Over Height (mm)	752	772	797	822	847
Seat-Tube Length (mm)	505	525	551	577	603
Seat-Tube Angle (deg)	77	77	77	77	77
Stem Length (mm)	90/60	90/60	90/60	90/60	90/60
Seat Post Length (mm)	350	350	350	350	350
Crank Length (mm)	170.0	172.5	172.5	175.0	

S-WORKS SHIV TT MODULE



CARB/WHT

Every second matters in the "race against the clock," which is why the S-Works Shiv TT Module refuses to overlook anything in its pursuit of speed. Perhaps this is why it's won everything from the World Championships to innumerable Tour de France stages.

- The FACT 11r carbon frame features our most advanced carbon construction methods in order to reduce aerodynamic drag and optimize rider input and overall stiffness. The oversized bottom bracket ensures maximum power transfer and rigidity, while the design also falls within the strict UCI requirements.
- UCI-legal S-Works FACT carbon fork features a full monocoque design that's been optimized to reduce aerodynamic drag, while also providing direct and responsive steering while in the TT position.
- Our Carbon Aero bar is UCI-legal and Win-Tunnel-optimized to reduce frontal drag, while also providing the versatility necessary to accommodate a wide range of fit options for maximum power, efficiency, and comfort.

SPECS	All specs are subject to change without notice.
FRAME	S-Works FACT 11r carbon, OSBB, horizontal dropouts, integrated brakes
FORK	S-Works FACT carbon, full monocoque, UCI-legal
STEM	Specialized Integrated carbon, UCI-legal
HANDLEBARS	Specialized carbon Aero bar, UCI-legal
FRONT BRAKE	Specialized Aero, center pull
REAR BRAKE	Specialized Aero, side pull
CHAINRINGS	53/39T
BOTTOM BRACKET	OSBB, CeramicSpeed bearings
SEATPOST	Specialized Shiv Team, straight/forward offset, 400mm

PART NO.	DESCRIPTION	COLOR	SIZE
79117-0501	SW SHIV TT MODULE	CARB/WHT	XS
79117-0502			S
79117-0503			M
79117-0504			L
79117-0506			XL

SHIV TT					
SIZE	XS	S	M	L	XL
Stack (mm)	488	502	502	502	502
Reach (mm)	375	390	405	420	440
Head-Tube Length (mm)	90	100	100	100	100
Head-Tube Angle (deg)	70.75	72	72	72	72
B-B Height (mm)	258	258	258	258	258
B-B Drop (mm)	72	72	72	72	72
Trail (mm)	62	55	55	55	55
Fork Length (full) (mm)	367	367	367	367	367
Fork Rake/Offset (mm)	50	50	50	50	50
Front-Center (mm)	578	587	601	616	636
Chain-Stay Length (mm)	390	390	390	390	390
Wheelbase (mm)	956	965	980	995	1015
Top-Tube Length (horizontal) (mm)	510	529	539	547	563
Bike Stand-Over Height (mm)	745	806	806	806	806
Seat-Tube Length (mm)	504	565	563	561	560
Seat-Tube Angle (deg)	74.5	74.5	75	75.75	76.25
Seat Post Length (mm)	400	400	400	400	400
Crank Length (mm)	170.0	170.0	172.5	172.5	175.0

S-WORKS CRUX



OAKGRN/TARBLK/RKTRED

With multiple Cyclocross World Championships to its name, the CruX has more than proven itself in the lung-searing race discipline of 'cross. The S-Works CruX is the ultimate CX weapon and features our top-of-the-line S-Works FACT 11r carbon frame, front and rear thru-axles.

- Our top-of-the-line FACT 11r carbon frame comes equipped with thru-axles, and it takes advantage of our highest quality carbon production methods in order to create a bike that's as responsive as it is lightweight.
- The internally routed FACT carbon disc fork features a thru-axle design, and it increases steering response and rider input for the tight turns and all-out efforts demanded in CX.
- Terra Pro 2Bliss Ready tires offer a tread that's ideal for muddy course conditions. Their sharp-edged tread has the added benefit of clearing well in the aforementioned, plus it delivers plenty of bite in the corners and rolls well through most sand.

CRUX CARBON SW

SIZE	46	49	52	54	56	58	61
Stack (mm)	522	540	554	566	583	597	618
Reach (mm)	366	369	376	379	384	387	393
Head-Tube Length (mm)	100	115	125	140	155	170	190
Head-Tube Angle (deg)	69.5	70.5	71.5	71.5	72	72.5	73
B-B Height (mm)	279	279	279	281	281	283	283
B-B Drop (mm)	71	71	71	69	69	67	67
Trail (mm)	76	70	63	65	62	59	56
Fork Length (full) (mm)	400	400	400	400	400	400	400
Fork Rake/Offset (mm)	51	51	51	49	49	49	49
Front-Center (mm)	593	594	596	601	606	609	616
Chain-Stay Length (mm)	425	425	425	425	425	425	425
Wheelbase (mm)	1008	1008	1010	1016	1022	1025	1032
Top-Tube Length (horizontal) (mm)	501	509	535	547	559	569	588
Bike Stand-Over Height (mm)	725	754	773	790	807	825	849
Seat-Tube Length (mm)	470	490	510	530	550	570	600
Seat-Tube Angle (deg)	75.5	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	380	400	420	420	420	440	440
Stem Length (mm)	75	75	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143	143
Seat Post Length (mm)	350	350	350	350	350	350	350
Crank Length (mm)	170	170	170	172.5	172.5	175	175

SPECS

All specs are subject to change without notice.

FRAME	S-Works FACT 11r carbon, 142mm thru-axle, disc mount, OSBB
FORK	CruX carbon disc, thru-axle
STEM	S-Works SL, alloy, titanium bolts, 6-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized CX Pro w/stickygel
FRONT BRAKE	Shimano BR-785, hydraulic disc, Ice-Tech resin pads w/fins
REAR BRAKE	Shimano BR-785, hydraulic disc, Ice-Tech resin pads w/fins
FRONT DERAILLEUR	Shimano Dura-Ace, braze-on
REAR DERAILLEUR	Shimano Dura-Ace, 11-speed
SHIFT LEVERS	Shimano ST-RS685, 11-speed
CASSETTE	Shimano Dura-Ace, 11-speed, 11-28t
CHAIN	Shimano HG901, 11-speed
CRANKSET	S-Works
CHAINRINGS	Praxis 46/36T
BOTTOM BRACKET	OSBB, CeramicSpeed bearings
FRONT WHEEL	CLX 32 Disc, thru-axle, 2Bliss Ready
REAR WHEEL	CLX 32 Disc, thru-axle, 2Bliss Ready
FRONT TIRE	Terra Pro 2Bliss Ready, 700x33mm
REAR TIRE	Terra Pro 2Bliss Ready, 700x33mm
SADDLE	Phenom Expert, Adaptive Edge design, hollow titanium rails, 143mm
SEATPOST	Specialized CG-R, FACT carbon, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
99317-0046	SW CRUX	OAKGRN/TARBLK/RKTRED	46
99317-0049			49
99317-0052			52
99317-0054			54
99317-0056			56
99317-0058			58
99317-0061			61

CRUX EXPERT X1



CARB/CHAR/BRTPNK

When it comes to cyclocross, the CruX Expert X1 has everything you need and nothing you don't. And with its SRAM Force 1 one-by drivetrain, it's designed for no-nonsense performance with minimal upkeep.

- The carbon frame was constructed from FACT 10r carbon fiber, so it experiences minimal weight gains in comparison to the S-Works version, while retaining all of the rigidity and responsiveness required of 'cross racing. And to promote this ride quality, it's also equipped with a thru-axle design.
- The internally routed FACT carbon disc fork features a thru-axle design, and it increases steering response and rider input for the tight turns and all-out efforts demanded in CX.
- SRAM Force shift levers deliver crisp, reliable shifting in nasty conditions, which is furthered by a one-by shift setup that makes dropping chains on the course a thing of the past. Say goodbye to front derailleurs and hello to hassle-free racing.

CRUX CARBON

SIZE	46	49	52	54	56	58	61
Stack (mm)	522	540	554	566	583	597	618
Reach (mm)	366	369	376	379	384	387	393
Head-Tube Length (mm)	100	115	125	140	155	170	190
Head-Tube Angle (deg)	69.5	70.5	71.5	71.5	72	72.5	73
B-B Height (mm)	279	279	279	281	281	283	283
B-B Drop (mm)	71	71	71	69	69	67	67
Trail (mm)	76	70	63	65	62	59	56
Fork Length (full) (mm)	400	400	400	400	400	400	400
Fork Rake/Offset (mm)	51	51	51	49	49	49	49
Front-Center (mm)	593	594	596	601	606	609	616
Chain-Stay Length (mm)	425	425	425	425	425	425	425
Wheelbase (mm)	1008	1008	1010	1016	1022	1025	1032
Top-Tube Length (horizontal) (mm)	501	509	535	547	559	569	588
Bike Stand-Over Height (mm)	725	754	773	790	807	825	849
Seat-Tube Length (mm)	470	490	510	530	550	570	600
Seat-Tube Angle (deg)	75.5	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	380	400	420	420	420	440	440
Stem Length (mm)	70	80	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143	143
Seat Post Length (mm)	350	350	350	350	350	350	350
Crank Length (mm)	170	170	170	172.5	172.5	175	175

SPECS

All specs are subject to change without notice.

FRAME	Specialized FACT 10r carbon, 142mm thru-axle, 1-3/8" lower bearing, disc mount, OSBB
FORK	CruX carbon disc, thru-axle
STEM	3D-forged alloy, 7-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized CX Pro w/stickygel
FRONT BRAKE	SRAM Force Hydraulic disc
REAR BRAKE	SRAM Force Hydraulic disc
REAR DERAILLEUR	SRAM Force 1, medium cage, 11-speed
SHIFT LEVERS	SRAM Force, 11-speed, hydraulic disc
CASSETTE	SRAM PG-1170, 11-speed, 11-32t
CHAIN	SRAM PC-1170, 11-speed
CRANKSET	SRAM Force 1
CHAINRINGS	SRAM X-Sync, 40T
BOTTOM BRACKET	SRAM BB30, 83mm
FRONT WHEEL	DT R460 Disc Pro, thru-axle
REAR WHEEL	DT R460 Disc Pro, thru-axle
FRONT TIRE	Terra Pro 2Bliss Ready, 700x33mm
REAR TIRE	Terra Pro 2Bliss Ready, 700x33mm
SADDLE	Phenom Expert, Adaptive Edge design, hollow titanium rails, 143mm
SEATPOST	Specialized CG-R, FACT carbon, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
91417-3046	CRUX EXPERT X1	CARB/CHAR/BRTPNK	46
91417-3049			49
91417-3052			52
91417-3054			54
91417-3056			56
91417-3058			58
91417-3061			61

CRUX ELITE X1



RKTRED/TARBLK/MONGRN



TARBLK/NENBLU/TEAMYEL

It's no secret that 'cross doesn't play favorites out on the course—only the strong survive. And when it comes to bikes, this is especially true. That's why our CruX Elite X1 was built to deliver a no-nonsense approach to the discipline.

- The carbon frame was constructed from our FACT 10r carbon fiber, so it experiences minimal weight gains in comparison to the S-Works version, while retaining all of the rigidity and responsiveness required of 'cross racing. And to promote this ride quality, it's also equipped with a thru-axle design.
- The internally routed FACT carbon disc fork features a thru-axle design, and it increases steering response and rider input for the tight turns and all-out efforts demanded in CX.
- SRAM Rival shift levers deliver reliable shifting in nasty conditions, which is furthered by a one-by shift setup that makes dropping chains on the course a thing of the past. Say goodbye to front derailleurs and hello to hassle-free racing.

CRUX CARBON ELITE							
SIZE	46	49	52	54	56	58	61
Stack (mm)	522	540	554	566	583	597	618
Reach (mm)	366	369	376	379	384	387	393
Head-Tube Length (mm)	100	115	125	140	155	170	190
Head-Tube Angle (deg)	69.5	70.5	71.5	71.5	72	72.5	73
B-B Height (mm)	279	279	279	281	281	283	283
B-B Drop (mm)	71	71	71	69	69	67	67
Trail (mm)	76	70	63	65	62	59	56
Fork Length (full) (mm)	400	400	400	400	400	400	400
Fork Rake/Offset (mm)	51	51	51	49	49	49	49
Front-Center (mm)	593	594	596	601	606	609	616
Chain-Stay Length (mm)	425	425	425	425	425	425	425
Wheelbase (mm)	1008	1008	1010	1016	1022	1025	1032
Top-Tube Length (horizontal) (mm)	501	509	535	547	559	569	588
Bike Stand-Over Height (mm)	725	754	773	790	807	825	849
Seat-Tube Length (mm)	470	490	510	530	550	570	600
Seat-Tube Angle (deg)	75.5	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	380	400	420	420	420	440	440
Stem Length (mm)	70	80	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143	143
Seat Post Length (mm)	300	300	300	350	350	350	350
Crank Length (mm)	170	170	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized FACT 10r carbon, 1-3/8" lower bearing, disc mount, OSBB
FORK	CruX carbon disc, thru-axle
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized CX Pro Gel
FRONT BRAKE	SRAM Rival, hydraulic disc
REAR BRAKE	SRAM Rival, hydraulic disc
REAR DERAILLEUR	SRAM Rival 1, medium cage, 11-speed
SHIFT LEVERS	SRAM Rival, 11-speed
CASSETTE	SRAM PG-1130, 11-speed, 11-32t
CHAIN	SRAM PC-1130, 11-speed w/PowerLink
CRANKSET	SRAM Rival 1
CHAINRINGS	SRAM X-Sync, 40T
BOTTOM BRACKET	SRAM BB30, 83mm
FRONT WHEEL	DT R460 Disc, thru-axle
REAR WHEEL	DT R460 Disc, thru-axle
FRONT TIRE	Terra Pro 2Bliss Ready, 700x33mm
REAR TIRE	Terra Pro 2Bliss Ready, 700x33mm
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
91417-4046	CRUX ELITE X1	RKTRED/TARBLK/MONGRN	46
91417-4049			49
91417-4052			52
91417-4054			54
91417-4056			56
91417-4058			58
91417-4061			61
91417-4146	CRUX ELITE X1	TARBLK/NENBLU/TEAMYEL	46
91417-4149			49
91417-4152			52
91417-4154			54
91417-4156			56
91417-4158			58
91417-4161			61

CRUX SPORT E5



RKTRED/LTBLU/NVY



NRBLK/CHAR/FLKSIL

Whether you're just getting into cyclocross or exploring the road less traveled, the CruX Sport E5 is the perfect bike to help you get out there and get after it.

- The frame was constructed from our E5 Premium Aluminum in order to provide a stiff, lightweight, and responsive frame that's purpose-built to withstand the rigorous demands of cyclocross. You'll find that the tubing is also formed to make shouldering the bike a breeze, while the semi-compact geometry creates predictable handling and explosive accelerations in the absolute worst of conditions.
- The FACT carbon disc fork was designed to increase steering response and rider input for the tight turns and all-out efforts demanded in CX.
- The Tracer Sport tires have a fast tread for all-around cyclocross riding and racing. This tread covers all courses, with center knobs to provide ample traction and siped shoulder knobs that adapt to hard and loose ground. It's also lightweight, making it easy to accelerate.

CRUX E5							
SIZE	46	49	52	54	56	58	61
Stack (mm)	522	540	554	566	583	597	618
Reach (mm)	366	370	375	379	384	387	392
Head-Tube Length (mm)	100	115	125	140	155	170	190
Head-Tube Angle (deg)	69.5	70.5	71.5	71.5	72	72.5	73
B-B Height (mm)	279	279	279	281	281	283	283
B-B Drop (mm)	71	71	71	69	69	67	67
Trail (mm)	76	70	63	65	62	59	56
Fork Length (full) (mm)	400	400	400	400	400	400	400
Fork Rake/Offset (mm)	51	51	51	49	49	49	49
Front-Center (mm)	593	595	595	601	606	609	615
Chain-Stay Length (mm)	425	425	425	425	425	425	425
Wheelbase (mm)	1008	1009	1009	1016	1022	1025	1031
Top-Tube Length (horizontal) (mm)	501	510	534	547	559	569	587
Bike Stand-Over Height (mm)	725	761	773	790	807	825	849
Seat-Tube Length (mm)	460	490	520	540	560	580	610
Seat-Tube Angle (deg)	75.5	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	380	400	420	420	420	440	440
Stem Length (mm)	70	80	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143	143
Seat Post Length (mm)	300	300	300	350	350	350	350
Crank Length (mm)	170	170	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized E5 Premium Aluminum, 142mm thru-axle, fully-manipulated tubing, semi-compact race design, shaped top tube, 1-3/8" lower bearing, internal cable routing, integrated headset, OSBB
FORK	CruX carbon disc, thru-axle, QR
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized CX Pro Gel
FRONT BRAKE	Shimano BR-785, hydraulic disc, Ice-Tech resin pads w/fins
REAR BRAKE	Shimano BR-785, hydraulic disc, Ice-Tech resin pads w/fins
FRONT DERAILLEUR	Shimano 105, braze-on
REAR DERAILLEUR	Shimano 105, 11-speed
SHIFT LEVERS	Shimano ST-RS505, 11-speed
CASSETTE	Shimano 105, 11-speed, 11-28t
CHAIN	KMC X11, 11-speed w/reusable MissingLink
CRANKSET	Praxis Alba 2D
CHAINRINGS	Praxis 46/36T
BOTTOM BRACKET	Praxis OSBB
FRONT WHEEL	Axis Elite Disc, QR
REAR WHEEL	Axis Elite Disc, QR
FRONT TIRE	Tracer Sport, 700x33mm, 60TPI, wire bead
REAR TIRE	Tracer Sport, 700x33mm, 60TPI, wire bead
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
91417-6146	CRUX SPORT E5	RKTRED/LTBLU/NVY	46
91417-6149			49
91417-6152			52
91417-6154			54
91417-6156			56
91417-6158			58
91417-6161			61
91417-6046	CRUX SPORT E5	NRBLK/CHAR/FLKSIL	46
91417-6049			49
91417-6052			52
91417-6054			54
91417-6056			56
91417-6058			58
91417-6061			61

CRUX E5



TARBLK/HYP/METWHT



TARBLK/FLORED/METWHT

It doesn't matter if you're racing cyclocross or racing down a fire road, our CruX E5 will deliver tremendous performance at an undeniable value.

- The frame was constructed from our E5 Premium Aluminum in order to provide a stiff, lightweight, and responsive frame that's purpose-built to withstand the rigorous demands of cyclocross. You'll find that the tubing is also formed to make shouldering the bike a breeze, while the semi-compact geometry creates predictable handling and explosive accelerations in the absolute worst of conditions.
- The FACT carbon disc fork was designed to increase steering response and rider input for the tight turns and all-out efforts demanded in CX.
- The Tracer Sport tires have a fast tread for all-around cyclocross riding and racing. This tread covers all courses, with center knobs to provide ample traction and siped shoulder knobs that adapt to hard and loose ground. It's also lightweight, making it easy to accelerate.

CRUX E5							
SIZE	46	49	52	54	56	58	61
Stack (mm)	522	540	554	566	583	597	618
Reach (mm)	366	370	375	379	384	387	392
Head-Tube Length (mm)	100	115	125	140	155	170	190
Head-Tube Angle (deg)	69.5	70.5	71.5	71.5	72	72.5	73
B-B Height (mm)	279	279	279	281	281	283	283
B-B Drop (mm)	71	71	71	69	69	67	67
Trail (mm)	76	70	63	65	62	59	56
Fork Length (full) (mm)	400	400	400	400	400	400	400
Fork Rake/Offset (mm)	51	51	51	49	49	49	49
Front-Center (mm)	593	595	595	601	606	609	615
Chain-Stay Length (mm)	425	425	425	425	425	425	425
Wheelbase (mm)	1008	1009	1009	1016	1022	1025	1031
Top-Tube Length (horizontal) (mm)	501	510	534	547	559	569	587
Bike Stand-Over Height (mm)	725	761	773	790	807	825	849
Seat-Tube Length (mm)	460	490	520	540	560	580	610
Seat-Tube Angle (deg)	75.5	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	380	400	420	420	420	440	440
Stem Length (mm)	70	80	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143	143
Seat Post Length (mm)	300	300	300	350	350	350	350
Crank Length (mm)	170	170	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized E5 Premium Aluminum, 142mm thru-axle, fully-manipulated tubing, semi-compact race design, shaped top tube, 1-3/8" lower bearing, internal cable routing, integrated headset, OSBB
FORK	CruX carbon disc, thru-axle, QR
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized CX Pro Gel
FRONT BRAKE	Tektro Spyre, mechanical disc
REAR BRAKE	Tektro Spyre, mechanical disc, dual pivot
FRONT DERAILLEUR	Shimano Tiagra, braze-on
REAR DERAILLEUR	Shimano Tiagra, long cage, 10-speed
SHIFT LEVERS	Shimano Tiagra STI, 10-speed
CASSETTE	Shimano Tiagra, 10-speed, 11-32t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	Praxis Alba 2D
CHAINRINGS	46/36T
BOTTOM BRACKET	Praxis OSBB
FRONT WHEEL	Axis Sport Disc, QR
REAR WHEEL	Axis Sport Disc, QR
FRONT TIRE	Tracer Sport, 700x33mm, 60TPI, wire bead
REAR TIRE	Tracer Sport, 700x33mm, 60TPI, wire bead
SADDLE	Body Geometry Toupe Sport, steel rails, 143mm
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
91417-7146	CRUX E5	TARBLK/HYP/METWHT	46
91417-7149			49
91417-7152			52
91417-7154			54
91417-7156			56
91417-7158			58
91417-7161			61
91417-7046	CRUX E5	TARBLK/FLORED/METWHT	46
91417-7049			49
91417-7052			52
91417-7054			54
91417-7056			56
91417-7058			58
91417-7061			61

CRUX PRO DISC FRAMESET



FLORED/NVY/LTBLU

The CruX Pro Disc frameset is a 'cross-optimized warrior. With its FACT 10r carbon frame, disc brake mounts, and CG-R carbon fiber seatpost, it's ready to be built up exactly how you want it. Add to that SWAT™ Box compatibility and a third bottle mount on the down tube for water or a tool Keg, and you have the foundation for a real course crusher.

- The carbon frame was constructed from our FACT 10r carbon fiber that puts performance first without breaking the bank. It retains all of the rigidity and responsiveness required of 'cross racing and to promote ride quality, it's also equipped with a thru-axle design with 142mm rear spacing for all wheel compatibility.
- The internally routed FACT carbon disc fork features a thru-axle design, and it increases steering response and rider input for the tight turns and all-out efforts demanded in CX.
- The CG-R seatpost is constructed from our high quality FACT carbon fiber, and when combined with the elastomer insert, it helps reduce rider fatigue and increase compliance.

SPECS	All specs are subject to change without notice.
FRAME	Specialized FACT 10r carbon, 142mm thru-axle, 1-3/8" lower bearing, disc mount, OSBB
FORK	CruX carbon disc, thru-axle, QR
BOTTOM BRACKET	Enduro BB30
SEATPOST	Specialized CG-R, FACT carbon, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
71417-1046	CRUX PRO FRMSET	FLORED/NVY/LTBLU	46
71417-1049			49
71417-1052			52
71417-1054			54
71417-1056			56
71417-1058			58
71417-1061			61

CRUX CARBON							
SIZE	46	49	52	54	56	58	61
Stack (mm)	522	540	554	566	583	597	618
Reach (mm)	366	369	376	379	384	387	393
Head-Tube Length (mm)	100	115	125	140	155	170	190
Head-Tube Angle (deg)	69.5	70.5	71.5	71.5	72	72.5	73
B-B Height (mm)	279	279	279	281	281	283	283
B-B Drop (mm)	71	71	71	69	69	67	67
Trail (mm)	76	70	63	65	62	59	56
Fork Length (full) (mm)	400	400	400	400	400	400	400
Fork Rake/Offset (mm)	51	51	51	49	49	49	49
Front-Center (mm)	593	594	596	601	606	609	616
Chain-Stay Length (mm)	425	425	425	425	425	425	425
Wheelbase (mm)	1008	1008	1010	1016	1022	1025	1032
Top-Tube Length (horizontal) (mm)	501	509	535	547	559	569	588
Bike Stand-Over Height (mm)	725	754	773	790	807	825	849
Seat-Tube Length (mm)	470	490	510	530	550	570	600
Seat-Tube Angle (deg)	75.5	75.5	74	73.5	73.25	73	72.5
Seat Post Length (mm)	350	350	350	350	350	350	350

LANGSTER ATLANTIS



ATLANTIS

The Langster Atlantis takes bike design to an entirely new level. It has all of the performance features that the Langster is known for, like a stiff A1 Premium aluminum construction and an aggressive track geometry, only its aesthetic is inspired by the world of steampunk.

- A1 Premium Aluminum frame with track-specific geometry has fully manipulated tubing and impressive overall stiffness, making the Langster a formidable threat on both the track and the streets.
- Specialized FACT carbon fork increases front end rigidity, while also providing excellent steering response for the unique demands of the track.
- Axis Elite Track wheels deliver the no-holds-barred rigidity required of track racing, feeling like they're slicing the razor's edge when it comes to throwing down a sprint.

LANGSTER STREET							
SIZE	46	49	52	54	56	58	61
Stack (mm)	480	488	503	517	537	556	573
Reach (mm)	362	372	384	390	403	409	420
Head-Tube Length (mm)	95	100	115	130	150	170	190
Head-Tube Angle (deg)	71	72	73	73	74	74	74
B-B Height (mm)	285	285	287.5	287.5	290	290	292.5
B-B Drop (mm)	55	55	52.5	52.5	50	50	47.5
Trail (mm)	69	63	56	56	50	50	50
Fork Length (full) (mm)	369	369	369	369	369	369	369
Fork Rake/Offset (mm)	45	45	45	45	45	45	45
Front-Center (mm)	558	562	571	581	591	603	619
Chain-Stay Length (mm)	396	396	395	395	394	394	393
Wheelbase (mm)	948	952	960	970	980	992	1008
Top-Tube Length (horizontal) (mm)	499	512	528	538	557	568	584
Bike Stand-Over Height (mm)	713	733	763	780	802	821	846
Seat-Tube Length (mm)	410	440	480	500	520	540	570
Seat-Tube Angle (deg)	74	74	74	74	74	74	74
Handlebar Width (mm)	640	640	640	640	640	640	640
Stem Length (mm)	70	80	90	100	100	110	110
Seat Post Length (mm)	300	300	350	350	350	350	350
Crank Length (mm)	165	165	165	167.5	170	170	172.5

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Track Geometry, fully-manipulated tubing, compact design, integrated headset
FORK	FACT carbon fiber
STEM	3D-forged alloy, 7-degree rise
HANDLEBARS	Langster
TAPE	Wood
FRONT BRAKE	Tektro, dual-pivot, long reach
REAR BRAKE	Tektro, calliper, long reach, dual pivot
CASSETTE	17t track cog, thread-on, steel lock ring
CHAIN	KMC Z510HX, single-speed
CRANKSET	144mm BCD spider, alloy crankarms
CHAINRINGS	48T
BOTTOM BRACKET	Square taper
FRONT WHEEL	Axis Elite Track
REAR WHEEL	Axis Elite Track
FRONT TIRE	Turbo Cotton, 700x24mm
REAR TIRE	Turbo Cotton, 700x24mm
SADDLE	Leather spring saddle
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90717-7146	LANGSTER ATLANTIS	ATLANTIS	46
90717-7149			49
90717-7152			52
90717-7154			54
90717-7156			56
90717-7158			58
90717-7161			61

LANGSTER DURANGO



DURANGO

The Langster Durango pays homage to the hometown of the very first UCI Mountain Bike World Champion, and six-time NORBA CX USA National Champion, Ned "the Lung" Overend.

- A1 Premium Aluminum frame with track-specific geometry has fully manipulated tubing and impressive overall stiffness, making the Langster a formidable threat on both the track and the streets.
- Specialized FACT carbon fork increases front end rigidity, while also providing excellent steering response for the unique demands of the track.
- Axis Elite Track wheels deliver the no-holds-barred rigidity required of track racing, feeling like they're slicing the razor's edge when it comes to throwing down a sprint.

LANGSTER STREET

SIZE	46	49	52	54	56	58	61
Stack (mm)	480	488	503	517	537	556	573
Reach (mm)	362	372	384	390	403	409	420
Head-Tube Length (mm)	95	100	115	130	150	170	190
Head-Tube Angle (deg)	71	72	73	73	74	74	74
B-B Height (mm)	285	285	287.5	287.5	290	290	292.5
B-B Drop (mm)	55	55	52.5	52.5	50	50	47.5
Trail (mm)	69	63	56	56	50	50	50
Fork Length (full) (mm)	369	369	369	369	369	369	369
Fork Rake/Offset (mm)	45	45	45	45	45	45	45
Front-Center (mm)	558	562	571	581	591	603	619
Chain-Stay Length (mm)	396	396	395	395	394	394	393
Wheelbase (mm)	948	952	960	970	980	992	1008
Top-Tube Length (horizontal) (mm)	499	512	528	538	557	568	584
Bike Stand-Over Height (mm)	713	733	763	780	802	821	846
Seat-Tube Length (mm)	410	440	480	500	520	540	570
Seat-Tube Angle (deg)	74	74	74	74	74	74	74
Handlebar Width (mm)	620	620	620	620	620	620	620
Stem Length (mm)	70	80	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143	143
Seat Post Length (mm)	300	300	350	350	350	350	350
Crank Length (mm)	165	165	165	167.5	170	170	172.5

SPECS

All specs are subject to change without notice.

FRAME	Specialized A1 Premium Aluminum, Track Geometry, fully-manipulated tubing, compact design, integrated headset
FORK	FACT carbon fiber
STEM	3D-forged alloy, 7-degree rise
HANDLEBARS	Langster flat bar
TAPE	Wood lock-on Grips
FRONT BRAKE	Tektro, dual-pivot, long reach
REAR BRAKE	Tektro, calliper, long reach, dual pivot
CASSETTE	17t track cog, thread-on, steel lock ring
CHAIN	KMC Z510HX, single-speed
CRANKSET	144mm BCD spider, alloy crankarms
CHAINRINGS	48T
BOTTOM BRACKET	Square taper
FRONT WHEEL	Axis Elite Track
REAR WHEEL	Axis Elite Track
FRONT TIRE	Turbo Cotton, 700x24mm
REAR TIRE	Turbo Cotton, 700x24mm
SADDLE	Body Geometry Toupé Comp Gel, hollow Cr-Mo rails, 143mm
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90717-7246	LANGSTER DURANGO	DURANGO	46
90717-7249			49
90717-7252			52
90717-7254			54
90717-7256			56
90717-7258			58
90717-7261			61



BLK/FLORED

With an A1 Premium Aluminum frame, track-specific geometry, a FACT carbon fiber fork, and a tough-as-nails build kit, you'll find this Langster to be just as comfortable riding on the boards of the velodrome as it is along the streets of the city.

- A1 Premium Aluminum frame with track-specific geometry has fully manipulated tubing and impressive overall stiffness, making the Langster a formidable threat on both the track and the streets.
- Specialized FACT carbon fork increases front end rigidity, while also providing excellent steering response for the unique demands of the track.
- Axis Sport Track wheels provide plenty of stiffness and explosive power for sprints to the line, as well as enough strength and durability for everyday riding.

LANGSTER STREET							
SIZE	46	49	52	54	56	58	61
Stack (mm)	480	488	503	517	537	556	573
Reach (mm)	362	372	384	390	403	409	420
Head-Tube Length (mm)	95	100	115	130	150	170	190
Head-Tube Angle (deg)	71	72	73	73	74	74	74
B-B Height (mm)	285	285	287.5	287.5	290	290	292.5
B-B Drop (mm)	55	55	52.5	52.5	50	50	47.5
Trail (mm)	69	63	56	56	50	50	50
Fork Length (full) (mm)	369	369	369	369	369	369	369
Fork Rake/Offset (mm)	45	45	45	45	45	45	45
Front-Center (mm)	558	562	571	581	591	603	619
Chain-Stay Length (mm)	396	396	395	395	394	394	393
Wheelbase (mm)	948	952	960	970	980	992	1008
Top-Tube Length (horizontal) (mm)	499	512	528	538	557	568	584
Bike Stand-Over Height (mm)	713	733	763	780	802	821	846
Seat-Tube Length (mm)	410	440	480	500	520	540	570
Seat-Tube Angle (deg)	74	74	74	74	74	74	74
Handlebar Width (mm)	390	390	390	390	390	390	390
Stem Length (mm)	70	80	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143	143
Seat Post Length (mm)	300	300	350	350	350	350	350
Crank Length (mm)	165	165	165	167.5	170	170	172.5

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Track Geometry, fully-manipulated tubing, compact design, integrated headset
FORK	FACT carbon fiber
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Langster Comp, short drop
TAPE	Specialized S-Wrap
FRONT BRAKE	Tektro, dual-pivot, long reach
REAR BRAKE	Tektro, calliper, long reach, dual pivot
CASSETTE	17t track cog, thread-on, steel lock ring
CHAIN	KMC Z510HX, single-speed
CRANKSET	144mm BCD spider, alloy crankarms
CHAINRINGS	48T
BOTTOM BRACKET	Square taper
FRONT WHEEL	Axis Sport Track
REAR WHEEL	Axis Sport Track
FRONT TIRE	Espoir Sport, 700x25mm, 60TPI, wire bead, double BlackBelt protection
REAR TIRE	Espoir Sport, 700x25mm
SADDLE	Body Geometry Toupé Sport, steel rails, 143mm
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90717-7046	LANGSTER	BLK/FLORED	46
90717-7049			49
90717-7052			52
90717-7054			54
90717-7056			56
90717-7058			58
90717-7061			61

LANGSTER STREET



INK/METWHTSIL/MONGRN

The Langster Street is the pinnacle of simplistic, performance-focused bike design. With its stiff and responsive A1 Premium Aluminum frame and durable build kit, the Langster Street is a city bike distilled down to its purest form.

- A1 Premium Aluminum frame with track-specific geometry has fully manipulated tubing and impressive overall stiffness, making the Langster a formidable threat on both the track and the streets.
- Specialized FACT carbon fork increases front end rigidity, while also providing excellent steering response for the unique demands of the track.
- Axis Sport Track wheels provide plenty of stiffness and explosive power for sprints to the line, as well as enough strength and durability for everyday riding.

LANGSTER STREET							
SIZE	46	49	52	54	56	58	61
Stack (mm)	480	488	503	517	537	556	573
Reach (mm)	362	372	384	390	403	409	420
Head-Tube Length (mm)	95	100	115	130	150	170	190
Head-Tube Angle (deg)	71	72	73	73	74	74	74
B-B Height (mm)	285	285	287.5	287.5	290	290	292.5
B-B Drop (mm)	55	55	52.5	52.5	50	50	47.5
Trail (mm)	69	63	56	56	50	50	50
Fork Length (full) (mm)	369	369	369	369	369	369	369
Fork Rake/Offset (mm)	45	45	45	45	45	45	45
Front-Center (mm)	558	562	571	581	591	603	619
Chain-Stay Length (mm)	396	396	395	395	394	394	393
Wheelbase (mm)	948	952	960	970	980	992	1008
Top-Tube Length (horizontal) (mm)	499	512	528	538	557	568	584
Bike Stand-Over Height (mm)	713	733	763	780	802	821	846
Seat-Tube Length (mm)	410	440	480	500	520	540	570
Seat-Tube Angle (deg)	74	74	74	74	74	74	74
Handlebar Width (mm)	390	400	400	400	420	420	420
Stem Length (mm)	70	80	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143	143
Seat Post Length (mm)	300	300	350	350	350	350	350
Crank Length (mm)	165	165	165	167.5	170	170	172.5

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Track Geometry, fully-manipulated tubing, compact design, integrated headset
FORK	FACT carbon fiber
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Cowhorn, alloy
TAPE	Specialized S-Wrap
FRONT BRAKE	Tektro, dual-pivot, long reach
REAR BRAKE	Tektro, caliper, long reach, dual pivot
CASSETTE	17t track cog, thread-on, steel lock ring
CHAIN	KMC Z510HX, single-speed
CRANKSET	144mm BCD spider, alloy crankarms
CHAINRINGS	48T
BOTTOM BRACKET	Square taper
FRONT WHEEL	Axis Sport Track
REAR WHEEL	Axis Sport Track
FRONT TIRE	Espoir Sport, 700x25mm, 60TPI, wire bead, double BlackBelt protection
REAR TIRE	Threshold, 700x28mm, 60TPI, wire bead, BlackBelt protection
SADDLE	Body Geometry Toupé Sport, steel rails, 143mm
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90717-7346	LANGSTER STREET	INK/METWHTSIL/MONGRN	46
90717-7349			49
90717-7352			52
90717-7354			54
90717-7356			56
90717-7358			58
90717-7361			61

DIVERGE EXPERT



DRTYWHT/CARB/MRTN

Be prepared for anything, from smooth tarmac to the rough and loose tracks out there, with the Diverge Expert. Its geometry and bundles of tire clearance inspire confidence over any surface, while Shimano's Ultegra groupset and hydraulic brakes offer heaps of precision and stopping power.

- The Specialized FACT 10r carbon frame combines the lightweight performance and compliance of our top-end carbon production with a unique geometry that's designed to smooth out even the harshest roads for more confident and predictable handling.
- FACT carbon fork w/ proprietary Zertz inserts absorbs and damps road chatter & vibration without compromising on the rigidity needed for performing at speed and tracking dutifully on the descents.
- Roubaix Pro 700x25/28mm tires are well suited for smooth and rough roads alike. That's because they're fast like any competitive road tire, only they feature a bead-to-bead Endurant casing, plus our BlackBelt technology for puncture protection. This way, they roll smooth over any terrain.

DIVERGE COMP CARBON CEN

SIZE	49	52	54	56	58	61
Stack (mm)	526	544	565	590	622	643
Reach (mm)	378	378	380	387	391	398
Head-Tube Length (mm)	100	120	140	165	200	220
Head-Tube Angle (deg)	71.25	71.25	72	72.5	72.5	73
B-B Height (mm)	270	270	271.5	271.5	273	273
B-B Drop (mm)	77	77	76	76	74	74
Trail (mm)	64	64	59	56	56	53
Fork Length (full) (mm)	390	390	390	390	390	390
Fork Rake/Offset (mm)	51	51	51	51	51	51
Front-Center (mm)	589	596	597	608	622	630
Chain-Stay Length (mm)	412	412	415	415	418	420
Wheelbase (mm)	989	995	1001	1011	1029	1039
Top-Tube Length (horizontal) (mm)	514	534	547	565	581	601
Bike Stand-Over Height (mm)	714	740	764	785	829	851
Seat-Tube Length (mm)	418	447	466	485	530	555
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	75	90	100	100	110	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	350	350	350	350	350	350
Crank Length (mm)	170	170	172.5	172.5	175	175

SPECS

All specs are subject to change without notice.

FRAME	Specialized FACT 10r carbon, tapered head tube, OSBB
FORK	Specialized FACT carbon w/Zertz, tapered
STEM	Specialized Pro SL, alloy, 4-bolt
HANDLEBARS	Specialized Expert Shallow Drop, alloy, 123mm drop, 75mm reach
TAPE	Specialized Roubaix Tape w/sticky gel
FRONT BRAKE	Shimano BR-785, hydraulic disc, Ice-Tech resin pads w/fins
REAR BRAKE	Shimano BR-785, hydraulic disc, Ice-Tech resin pads w/fins
FRONT DERAILLEUR	Shimano Ultegra, braze-on
REAR DERAILLEUR	Shimano Ultegra, GS cage, 11-speed
SHIFT LEVERS	Shimano ST-RS685, 11-speed
CASSETTE	Shimano Ultegra, 11-speed, 11-32t
CHAIN	Shimano Ultegra, 11-speed
CRANKSET	FSA SL-K Light, four-arm
CHAINRINGS	48/32T
BOTTOM BRACKET	FSA BB30
FRONT WHEEL	DT R460 Disc SCS
REAR WHEEL	DT R460 Disc SCS
FRONT TIRE	Roubaix Pro 2BR, 700x30/32mm, 2Bliss Ready, 120TPI, folding bead, BlackBelt, Endurant casing
REAR TIRE	Roubaix Pro 2BR, 700x30/32mm, 2Bliss Ready, 120TPI, folding bead, BlackBelt, Endurant casing
SADDLE	Phenom Expert, Adaptive Edge design, hollow titanium rails, 143mm
SEATPOST	Specialized CG-R, FACT carbon, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
95417-3249	DIVERGE EXPERT M	DRTYWHT/CARB/MRTN	49
95417-3252			52
95417-3254			54
95417-3256			56
95417-3258			58
95417-3261			61

DIVERGE COMP



CARB/CARB/DRMSIL

The Diverge Comp is a fully-fledged exploration machine. The strong, nimble carbon frame is constructed with adventure-ready geometry and tons of tire clearance, and it's paired with Shimano's outstanding, 11-speed 105 groupset and hydraulic brakes for confident braking and shifting.

- The Specialized FACT 10r carbon frame combines the lightweight performance and compliance of our top-end carbon production with a unique geometry that's designed to smooth out even the harshest roads for more confident and predictable handling.
- FACT carbon fork w/ proprietary Zertz inserts absorbs and damps road chatter & vibration without compromising on the rigidity needed for performing at speed and tracking dutifully on the descents.
- Roubaix Pro 2Bliss Ready 700x30/32mm tires provide extraordinary traction and suppleness for both the road and dirt, while a tubeless design minimizes flats and allows lower tire pressures to be run. Add to this a 120TPI construction, and there isn't a surface where these tires won't thrive.

DIVERGE COMP CARBON

SIZE	49	52	54	56	58	61	64
Stack (mm)	526	544	565	590	622	643	658
Reach (mm)	378	378	380	387	391	398	409
Head-Tube Length (mm)	100	120	140	165	200	220	235
Head-Tube Angle (deg)	71.25	71.25	72	72.5	72.5	73	73
B-B Height (mm)	270	270	271.5	271.5	273	273	273
B-B Drop (mm)	77	77	76	76	74	74	74
Trail (mm)	64	64	59	56	56	53	53
Fork Length (full) (mm)	390	390	390	390	390	390	390
Fork Rake/Offset (mm)	51	51	51	51	51	51	51
Front-Center (mm)	589	596	597	608	622	630	645
Chain-Stay Length (mm)	412	412	415	415	418	420	420
Wheelbase (mm)	989	995	1001	1011	1029	1039	1054
Top-Tube Length (horizontal) (mm)	514	534	547	565	581	601	616
Bike Stand-Over Height (mm)	714	740	764	785	829	851	873.5
Seat-Tube Length (mm)	418	447	466	485	530	555	590
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5	72.5
Handlebar Width (mm)	400	420	420	420	440	440	440
Stem Length (mm)	80	90	100	100	110	110	120
Saddle Width (mm)	143	143	143	143	143	143	143
Seat Post Length (mm)	350	350	350	350	350	350	350
Crank Length (mm)	170	170	172.5	172.5	175	175	177.5

SPECS

All specs are subject to change without notice.

FRAME	Specialized FACT 10r carbon, tapered head tube, OSBB
FORK	Specialized FACT carbon w/Zertz, tapered
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized Roubaix Tape w/sticky gel
FRONT BRAKE	Shimano BR-785, hydraulic disc, Ice-Tech resin pads w/fins
REAR BRAKE	Shimano BR-785, hydraulic disc, Ice-Tech resin pads w/fins
FRONT DERAILLEUR	Shimano 105, braze-on
REAR DERAILLEUR	Shimano 105, GS cage, 11-speed
SHIFT LEVERS	Shimano ST-RS685, 11-speed
CASSETTE	Shimano 105, 11-speed, 11-32t
CHAIN	KMC X11, 11-speed
CRANKSET	Praxis Zayante, 7075-T6 alloy chainrings
CHAINRINGS	48/32T
BOTTOM BRACKET	Praxis BB30
FRONT WHEEL	DT R460 Disc SCS
REAR WHEEL	DT R460 Disc SCS
FRONT TIRE	Roubaix Pro 2BR, 700x30/32mm, 2Bliss Ready, 120TPI, folding bead, BlackBelt, Endurant casing
REAR TIRE	Roubaix Pro 2BR, 700x30/32mm, 2Bliss Ready, 120TPI, folding bead, BlackBelt, Endurant casing
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized CG-R, FACT carbon, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
95417-5049	DIVERGE COMP	CARB/CARB/DRMSIL	49
95417-5052			52
95417-5054			54
95417-5056			56
95417-5058			58
95417-5061			61
95417-5064			64

DIVERGE ELITE DSW



MXORG/GLDORG



BLK/RKTRED

The Diverge Elite DSW has everything you need to go farther down the road than you ever thought possible. It's packed with the same Zertz vibration-damping technology and adventure-ready handling as its pricier cousins, and it's built with a dependable Shimano drivetrain and mechanical disc brakes.

- An E5 Premium Aluminum frame features our proprietary D'Aluisio Smartweld technology for added stiffness, strength, and weight reduction, so you get a tremendous ride quality with the added assurance of durability that comes with an alloy construction.
- FACT carbon fork w/ proprietary Zertz inserts absorbs and damps road chatter & vibration without compromising on the rigidity needed for performing at speed and tracking dutifully on the descents.
- 700x30mm Espoir Sport tires are the perfect width for splitting your time between the road and dirt, providing excellent traction and suppleness. And to assist in minimizing flats, they also feature our double BlackBelt protection.

DIVERGE SMARTWELD

SIZE	49	52	54	56	58	61	64
Stack (mm)	526	544	565	590	622	643	658
Reach (mm)	378	378	380	387	391	398	409
Head-Tube Length (mm)	100	120	140	165	200	220	235
Head-Tube Angle (deg)	71.25	71.25	72	72.5	72.5	73	73
B-B Height (mm)	270	270	271.5	271.5	273	273	273
B-B Drop (mm)	77	77	76	76	74	74	74
Trail (mm)	64	64	59	56	56	53	53
Fork Length (full) (mm)	390	390	390	390	390	390	390
Fork Rake/Offset (mm)	51	51	51	51	51	51	51
Front-Center (mm)	589	596	597	608	622	630	645
Chain-Stay Length (mm)	412	412	415	415	418	420	420
Wheelbase (mm)	989	995	1001	1011	1029	1039	1054
Top-Tube Length (horizontal) (mm)	514	534	547	565	581	601	616
Bike Stand-Over Height (mm)	719	740	766	785	820	841	874.3
Seat-Tube Length (mm)	418	447	466	485	530	555	590
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5	72.5
Handlebar Width (mm)	400	420	420	420	440	440	440
Stem Length (mm)	80	90	100	100	110	110	120
Saddle Width (mm)	155	155	155	155	155	155	155
Seat Post Length (mm)	350	350	350	350	350	350	350
Crank Length (mm)	170	170	172.5	172.5	175	175	175

SPECS

All specs are subject to change without notice.

FRAME	Specialized E5 Premium Aluminum w/ D'Aluisio Smartweld technology, tapered head tube, OSBB
FORK	Specialized FACT carbon w/Zertz, tapered
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized S-Wrap
FRONT BRAKE	Tektro Spyre, mechanical disc
REAR BRAKE	Tektro Spyre, mechanical disc, dual pivot
FRONT DERAILLEUR	Shimano Tiagra, braze-on
REAR DERAILLEUR	Shimano Tiagra, long cage, 10-speed
SHIFT LEVERS	Shimano Tiagra STI, 10-speed
CASSETTE	Shimano Tiagra, 10-speed, 11-32t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	Praxis Alba 2D
CHAINRINGS	48/32T
BOTTOM BRACKET	Praxis BB30
FRONT WHEEL	Axis Elite Disc, thru-axle
REAR WHEEL	Axis Elite Disc, QR
FRONT TIRE	Espoir Sport, 700x30mm, 60TPI, wire bead, double BlackBelt protection
REAR TIRE	Espoir Sport, 700x30mm, 60TPI, wire bead, double BlackBelt protection
SADDLE	Body Geometry Toupé Sport, steel rails, 143mm
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
95417-4449	DIVERGE ELITE DSW	MXORG/GLDORG	49
95417-4452			52
95417-4454			54
95417-4456			56
95417-4458			58
95417-4461			61
95417-4464			64
95417-4349	DIVERGE ELITE DSW	BLK/RKTRED	49
95417-4352			52
95417-4354			54
95417-4356			56
95417-4358			58
95417-4361			61
95417-4364			64

DIVERGE SPORT A1



BLK/RKTRED/HYP

The best adventure tools are capable and reliable, which is why the Diverge Sport's A1 Premium Aluminum frame and carbon fork are designed to accommodate wide tires. This makes it ideal for super-stable handling over any terrain, while its resilient Sora drivetrain makes reliable shifting a breeze.

- A1 Premium Aluminum pairs with a unique, adventure-bound geometry that sets the stage for rugged durability, performance over any terrain, and a level of comfort and handling that's tough to beat.
- FACT carbon fork w/ proprietary Zertz inserts absorbs and damps road chatter & vibration without compromising on the rigidity needed for performing at speed and tracking dutifully on the descents. This fork is also compatible with our Plug + Play fenders for protection against the elements.
- 700x28mm Espoir Sport tires are the perfect width for splitting your time between the road and dirt, providing excellent traction and suppleness. And to assist in minimizing flats, they also feature our double BlackBelt protection.

DIVERGE A1						
SIZE	49	52	54	56	58	61
Stack (mm)	529	548	565	591	623	644
Reach (mm)	378	378	380	387	391	398
Head-Tube Length (mm)	94	114	134	159	194	214
Head-Tube Angle (deg)	72	72	72	72.5	72.5	73
B-B Height (mm)	272.5	272.5	274	274	275.5	275.5
B-B Drop (mm)	73	73	72	72	70	70
Trail (mm)	61	61	61	58	58	54
Fork Length (full) (mm)	400	400	400	400	400	400
Fork Rake/Offset (mm)	49	49	49	49	49	49
Front-Center (mm)	582	588	596	606	621	629
Chain-Stay Length (mm)	412	412	415	415	418	420
Wheelbase (mm)	983	989	1001	1011	1029	1039
Top-Tube Length (horizontal) (mm)	515	535	547	565	581	601
Bike Stand-Over Height (mm)	730	756	776	798	829	851
Seat-Tube Length (mm)	418	447	466	485	510	535
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	70	80	90	100	100	110
Saddle Width (mm)	155	155	155	155	155	155
Seat Post Length (mm)	300	300	300	350	350	350
Crank Length (mm)	165	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, threaded BB
FORK	FACT carbon fiber, alloy steerer/crown, Zertz inserts, post disc mount, Plug + Play fender mount
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized S-Wrap
FRONT BRAKE	Tektro Mira, mechanical disc
REAR BRAKE	Tektro Mira, mechanical disc brake
FRONT DERAILLEUR	Shimano Sora, braze-on
REAR DERAILLEUR	Shimano Sora, 9-speed
SHIFT LEVERS	Shimano Sora STI
CASSETTE	Sunrace, 9-speed, 11-32t
CHAIN	KMC X9, 9-speed w/reusable MissingLink
CRANKSET	Praxis Alba
CHAINRINGS	48/32T
BOTTOM BRACKET	Praxis BB
FRONT WHEEL	Axis Sport Disc, QR
REAR WHEEL	Axis Sport Disc, QR
FRONT TIRE	Specialized Espoir Sport, 60TPI, wire bead, double BlackBelt protection, 700x28mm
REAR TIRE	Specialized Espoir Sport, 60TPI, wire bead, double BlackBelt protection, 700x28mm
SADDLE	Toupe Sport
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
95417-6049	DIVERGE SPORT A1	BLK/RKTRED/HYP	49
95417-6052			52
95417-6054			54
95417-6056			56
95417-6058			58
95417-6061			61

DIVERGE A1



CNDYRED/FLORED



BLK/CHAR

Made for exploring the roads you thought a road bike could never venture on, the Diverge's A1 Premium Aluminum frame big tire clearance, carbon fork, and Shimano drivetrain will clock up miles with confident stability and handling.

- A1 Premium Aluminum pairs with a unique, adventure-bound geometry that sets the stage for rugged durability, performance over any terrain, and a level of comfort and handling that's tough to beat.
- FACT carbon fork w/ proprietary Zertz inserts absorbs and damps road chatter & vibration without compromising on the rigidity needed for performing at speed and tracking dutifully on the descents. This fork is also compatible with our Plug + Play fenders for protection against the elements.
- 700x28mm Espoir Sport tires are the perfect width for splitting your time between the road and dirt, providing excellent traction and suppleness. And to assist in minimizing flats, they also feature our double BlackBelt protection.

DIVERGE A1						
SIZE	49	52	54	56	58	61
Stack (mm)	529	548	565	591	623	644
Reach (mm)	378	378	380	387	391	398
Head-Tube Length (mm)	94	114	134	159	194	214
Head-Tube Angle (deg)	72	72	72	72.5	72.5	73
B-B Height (mm)	272.5	272.5	274	274	275.5	275.5
B-B Drop (mm)	73	73	72	72	70	70
Trail (mm)	61	61	61	58	58	54
Fork Length (full) (mm)	400	400	400	400	400	400
Fork Rake/Offset (mm)	49	49	49	49	49	49
Front-Center (mm)	582	588	596	606	621	629
Chain-Stay Length (mm)	412	412	415	415	418	420
Wheelbase (mm)	983	989	1001	1011	1029	1039
Top-Tube Length (horizontal) (mm)	515	535	547	565	581	601
Bike Stand-Over Height (mm)	730	756	776	798	829	851
Seat-Tube Length (mm)	418	447	466	485	510	535
Seat-Tube Angle (deg)	75.5	74	73.5	73.25	73	72.5
Handlebar Width (mm)	400	420	420	420	440	440
Stem Length (mm)	70	80	90	100	100	110
Saddle Width (mm)	155	155	155	155	155	155
Seat Post Length (mm)	300	300	300	350	350	350
Crank Length (mm)	165	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, threaded BB
FORK	FACT carbon fiber, alloy steerer/crown, Zertz inserts, post disc mount, Plug + Play fender mount
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Shallow Drop, alloy, 125mm drop, 70mm short-reach
TAPE	Specialized S-Wrap
FRONT BRAKE	Tektro Mira, mechanical disc
REAR BRAKE	Tektro Mira, mechanical disc brake
FRONT DERAILLEUR	Shimano Claris 2400, braze-on
REAR DERAILLEUR	Shimano Claris 2400, 8-speed
SHIFT LEVERS	Shimano Claris 2400 ST1
CASSETTE	Sunrace, 8-speed, 11-32t
CHAIN	KMC Z7, 8-speed w/reusable MissingLink
CRANKSET	FSA Gossamer Pro, Direct mount ABS, MegaExo Integrated Interface, 68mm English BB, 9-/10-speed, forged 6066 aluminum, 144mm Q-factor
CHAINRINGS	48/32T
BOTTOM BRACKET	FSA BB
FRONT WHEEL	Axis Sport Disc, QR
REAR WHEEL	Axis Sport Disc, QR
FRONT TIRE	Specialized Espoir Sport, 60TPI, wire bead, double BlackBelt protection, 700x28mm
REAR TIRE	Specialized Espoir Sport, 60TPI, wire bead, double BlackBelt protection, 700x28mm
SADDLE	Toupe Sport
SEATPOST	Alloy, 12.5mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
95417-7349	DIVERGE A1	CNDYRED/FLORED	49
95417-7352			52
95417-7354			54
95417-7356			56
95417-7358			58
95417-7361			61
95417-7249	DIVERGE A1	BLK/CHAR	49
95417-7252			52
95417-7254			54
95417-7256			56
95417-7258			58
95417-7261			61

SEQUOIA EXPERT



WHTMTN/GRPH

We believe that at the heart of every rider is an adventurer, ready to seek out new roads, regardless of whether they're paved or not. And for this reason, we created a bike that's built to handle anything. The Sequoia Expert combines road and adventure in a single, genre-shattering bike.

- The Sequoia is built from our Premium Cr-Mo, size-specific tubing. This ensures that every frame is strong, light, and capable, while every frame size rides exactly as we intended. This philosophy is furthered with our Adventure Geometry that provides ample confidence over rough and smooth terrain, alike. And lastly, we equipped this frame with fender & rack mounts to make sure you'll be well equipped whenever adventure strikes.
- A beefy FACT carbon fiber fork is sure to take the sting out of harsh roads. And when you're deep into said roads, you'll be thankful for the extra water bottle mount found on its fork leg.
- Hand-built Adventure Gear Cruzero wheels are cased in 700x42mm 2Bliss Ready tires to be tough, strong, and fast rolling. It's the ideal wheelset for anyone looking to skip town at speed.

SEQUOIA						
SIZE	50	52	54	56	58	61
Seat-Tube Length, B-B Center to Top (mm)	440	460	480	500	520	540
Top-Tube Length, Horizontal (mm)	508	522	550	570	587	603
B-B Drop (mm)	70	70	67	66.5	65	65
Chain-Stay Length (mm)	430	430	430	430	430	430
Seat-Tube Angle (deg)	75.5	75.5	74	73.5	73.3	73
Head-Tube Angle (deg)	70	70.5	71.5	71.5	72	72.5
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78	75	68	68	65	62
Front-Center (mm)	595	606	611	626	636	644
Wheelbase (mm)	1021	1032	1037	1053	1064	1071
Stand-Over Height (mm)	440	460	480	500	520	540
Head-Tube Length (mm)	100	120	140	160	180	200
Reach (mm)	366.7	378.4	384.8	393.8	402.1	408.8
Stack (mm)	534.6	555.4	576.3	594.7	614.2	635.3
Handlebar Width (mm)	400	420	440	440	460	460
Stem Length (mm)	80	90	90	100	100	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	350	400	400	400	400	400
Crank Length (mm)	165	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	Premium Cr-Mo size-specific tubing, internal light cable routing-ready, Adventure Geometry, flat disc mount, fender/rack mounts
FORK	Specialized FACT carbon, tapered, internal light cable routing, flat disc mount, waterbottle/rack/fender mounts
STEM	Specialized Pro SL, alloy, 4-bolt
HANDLEBARS	Specialized Adventure Gear Hover
TAPE	Specialized Adventure Gear S-Wrap Canvas Tape
FRONT BRAKE	SRAM Rival 1, hydraulic disc, 160mm rotor
REAR BRAKE	SRAM Rival 1, hydraulic disc, 160mm rotor
REAR DERAILLEUR	SRAM Force1 Type 2.1, long cage, 11-speed
SHIFT LEVERS	SRAM Force Hydraulic Disc
CASSETTE	Shimano Deore XT, 11-speed, 11-42t
CHAIN	KMC X11SL-1 DLC, 11-speed w/reusable MissingLink
CRANKSET	FSA SL-K Light crankset, ABS Compact BB386 EVO, PF30 System Interface, 10-/11-speed, hollow, 147mm Q-factor, 110 BCD
CHAINRINGS	Megatooth V2 XX1, 42T
BOTTOM BRACKET	FSA MegaEvo, threaded
FRONT WHEEL	Specialized Adventure Gear Cruzero
REAR WHEEL	Specialized Adventure Gear Cruzero
FRONT TIRE	Specialized Adventure Gear Sawtooth 2Bliss Ready, 700x42mm
REAR TIRE	Specialized Adventure Gear Sawtooth 2Bliss Ready, 700x42mm
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized CG-R, FACT carbon, single bolt, reflective, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90517-3150	SEQUOIA EXPERT	WHTMTN/GRPH	50
90517-3152			52
90517-3154			54
90517-3156			56
90517-3158			58
90517-3161			61

SEQUOIA ELITE



CALWHTSG/GRPH

If you've ever felt torn between a "traditional" road bike and a dedicated touring rig, you're not alone. Now, though, the Sequoia Elite gives you both by combining the two in one genre-bending bike. It has everything you need to hit the road and not look back.

- The Sequoia is built from our Premium Cr-Mo, size-specific tubing. This ensures that every frame is strong, light, and capable, while every frame size rides exactly as we intended. This philosophy is furthered with our Adventure Geometry that provides ample confidence over rough and smooth terrain, alike. And lastly, we equipped this frame with fender & rack mounts to make sure you'll be well equipped whenever adventure strikes.
- A beefy FACT carbon fiber fork is sure to take the sting out of harsh roads. And when you're deep into said roads, you'll be thankful for the extra water bottle mount found on its fork leg.
- Hand-built Adventure Gear Hayfield wheels are cased in 700x42mm 2Bliss Ready tires to be burly and tough as a mule. It's the ideal wheelset for anyone looking to skip town and not look back.

SEQUOIA						
SIZE	50	52	54	56	58	61
Seat-Tube Length, B-B Center to Top (mm)	440	460	480	500	520	540
Top-Tube Length, Horizontal (mm)	508	522	550	570	587	603
B-B Drop (mm)	70	70	67	66.5	65	65
Chain-Stay Length (mm)	430	430	430	430	430	430
Seat-Tube Angle (deg)	75.5	75.5	74	73.5	73.3	73
Head-Tube Angle (deg)	70	70.5	71.5	71.5	72	72.5
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78	75	68	68	65	62
Front-Center (mm)	595	606	611	626	636	644
Wheelbase (mm)	1021	1032	1037	1053	1064	1071
Stand-Over Height (mm)	440	460	480	500	520	540
Head-Tube Length (mm)	100	120	140	160	180	200
Reach (mm)	366.7	378.4	384.8	393.8	402.1	408.8
Stack (mm)	534.6	555.4	576.3	594.7	614.2	635.3
Handlebar Width (mm)	400	420	440	440	460	460
Stem Length (mm)	80	90	90	100	100	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	350	400	400	400	400	400
Crank Length (mm)	165	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	Premium Cr-Mo size-specific tubing, internal light cable routing-ready, Adventure Geometry, flat disc mount, fender/rack mounts
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Adventure Gear Hover
TAPE	Specialized Adventure Gear S-Wrap Canvas Tape
FRONT BRAKE	Shimano BR-RS505, hydraulic disc, resin pads
REAR BRAKE	Shimano 105, hydraulic disc
FRONT DERAILLEUR	Shimano 105, 31.8mm clamp w/28.6mm adapter, road double
REAR DERAILLEUR	Shimano 105, GS cage, 11-speed
SHIFT LEVERS	Shimano 105 hydraulic, 11-speed
CASSETTE	Sunrace, 11-speed, 11-36t
CHAIN	KMC X11-1, 11-speed w/reusable MissingLink
CRANKSET	FSA Gossamer Pro, alloy, MegaEVO BB, sub compact, 110mm BCD spider
CHAINRINGS	48/32T
BOTTOM BRACKET	FSA MegaEvo, threaded
FRONT WHEEL	Specialized Adventure Gear Hayfield
REAR WHEEL	Specialized Adventure Gear Hayfield
FRONT TIRE	Specialized Adventure Gear Sawtooth 2Bliss Ready, 700x42mm
REAR TIRE	Specialized Adventure Gear Sawtooth 2Bliss Ready, 700x42mm
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized alloy, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90517-4050	SEQUOIA ELITE	CALWHTSG/GRPH	50
90517-4052			52
90517-4054			54
90517-4056			56
90517-4058			58
90517-4061			61



BLK/GRPH

A 100 years ago, we didn't have road bikes and touring bikes—there were just bikes, and that didn't stop anyone from heading out into the wilderness. With this spirit, we built our groundbreaking Sequoia. It's reshaping long held ideas, and forever changing what we'll come to expect from a bike.

- The Sequoia is built from our Premium Cr-Mo, size-specific tubing. This ensures that every frame is strong, light, and capable, while every frame size rides exactly as we intended. This philosophy is furthered with our Adventure Geometry that provides ample confidence over rough and smooth terrain, alike. And lastly, we equipped this frame with fender & rack mounts to make sure you'll be well equipped whenever adventure strikes.
- A strong Cr-Mo fork will stand up to the weight of heavy loads without the bat of an eyelash. It's lightweight and features internal cable routing for your lights. And when you're miles from nowhere, you're especially going to appreciate its extra waterbottle mount.
- Hand-built Adventure Gear Hayfield wheels are cased in 700x42mm 2Bliss Ready tires to be burly and tough as a mule. It's the ideal wheelset for anyone looking to skip town and not look back.

SEQUOIA						
SIZE	50	52	54	56	58	61
Seat-Tube Length, B-B Center to Top (mm)	440	460	480	500	520	540
Top-Tube Length, Horizontal (mm)	508	522	550	570	587	603
B-B Drop (mm)	70	70	67	66.5	65	65
Chain-Stay Length (mm)	430	430	430	430	430	430
Seat-Tube Angle (deg)	75.5	75.5	74	73.5	73.3	73
Head-Tube Angle (deg)	70	70.5	71.5	71.5	72	72.5
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78	75	68	68	65	62
Front-Center (mm)	595	606	611	626	636	644
Wheelbase (mm)	1021	1032	1037	1053	1064	1071
Stand-Over Height (mm)	440	460	480	500	520	540
Head-Tube Length (mm)	100	120	140	160	180	200
Reach (mm)	366.7	378.4	384.8	393.8	402.1	408.8
Stack (mm)	534.6	555.4	576.3	594.7	614.2	635.3
Handlebar Width (mm)	400	420	440	440	460	460
Stem Length (mm)	80	90	90	100	100	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	350	400	400	400	400	400
Crank Length (mm)	165	170	172.5	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	Premium Cr-Mo size-specific tubing, internal light cable routing-ready, Adventure Geometry, flat disc mount, fender/rack mounts
FORK	Specialized Cr-Mo, internal light cable routing, flat disc mount, waterbottle/rack/fender mounts
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Adventure Gear Hover
TAPE	Specialized Adventure Gear S-Wrap Canvas Tape
FRONT BRAKE	Tektro Spyre, mechanical disc, 160mm rotor, dual pivot
REAR BRAKE	Tektro Spyre, mechanical disc, 160mm rotor, dual pivot
FRONT DERAILLEUR	Shimano Sora, 34.9mm clamp w/28.6mm adapter, 9-speed
REAR DERAILLEUR	Shimano Alivio, Shadow design, SGS cage, 9-speed
SHIFT LEVERS	Shimano Sora
CASSETTE	Shimano, 9-speed, 12-36t
CHAIN	SRAM PC-971 w/PowerLink
CRANKSET	FSA Vero, alloy, sub compact, 110mm BCD spider
CHAINRINGS	48/32T
BOTTOM BRACKET	BSA, square taper, cartridge bearings
FRONT WHEEL	Specialized Adventure Gear Hayfield
REAR WHEEL	Specialized Adventure Gear Hayfield
FRONT TIRE	Specialized Adventure Gear Sawtooth 2Bliss Ready, 700x42mm
REAR TIRE	Specialized Adventure Gear Sawtooth 2Bliss Ready, 700x42mm
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized alloy, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90517-7050	SEQUOIA	BLK/GRPH	50
90517-7052			52
90517-7054			54
90517-7056			56
90517-7058			58
90517-7061			61

SEQUOIA PRO MODULE

WHTMTN\BLK\GRPH

Consider the open road a blank sheet primed for a tale of adventure, and the Sequoia Pro Module your pen to write it with.

- The Sequoia is built from our heat treated, custom-butted, and size-specific Premium Cr-Mo & stainless steel tubing. This ensures that every frame is strong, light, and capable, while every frame size rides exactly as we intended. This philosophy is furthered with our Adventure Geometry that provides ample confidence over rough and smooth terrain, alike. And lastly, we equipped this frame with fender & rack mounts to make sure you'll be well equipped whenever adventure strikes.
- A beefy FACT carbon fiber fork is sure to take the sting out of harsh roads. And when you're deep into said roads, you'll be thankful for the extra water bottle mount found on its fork leg.

SPECS	All specs are subject to change without notice.
FRAME	Heat treated custom-butted Premium Cr-Mo & Stainless Steel size-specific tubing, internal light cable routing-ready, Adventure Geometry, flat disc mount, fender/rack mounts
FORK	Specialized FACT carbon, tapered, internal light cable routing, flat disc mount, waterbottle/rack/fender mounts
STEM	Specialized Pro SL, alloy, 4-bolt
HANDLEBARS	Specialized Adventure Gear Hover
TAPE	Specialized Adventure Gear S-Wrap Canvas Tape
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized CG-R, FACT carbon, single bolt, reflective, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
70517-3050	SEQUOIA PRO MODULE	WHTMTN\BLK\GRPH	50
70517-3052			52
70517-3054			54
70517-3056			56
70517-3058			58
70517-3061			61

SEQUOIA						
SIZE	50	52	54	56	58	61
Seat-Tube Length, B-B Center to Top (mm)	440	460	480	500	520	540
Top-Tube Length, Horizontal (mm)	508	522	550	570	587	603
B-B Drop (mm)	70	70	67	66.5	65	65
Chain-Stay Length (mm)	430	430	430	430	430	430
Seat-Tube Angle (deg)	75.5	75.5	74	73.5	73.3	73
Head-Tube Angle (deg)	70	70.5	71.5	71.5	72	72.5
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78	75	68	68	65	62
Front-Center (mm)	595	606	611	626	636	644
Wheelbase (mm)	1021	1032	1037	1053	1064	1071
Stand-Over Height (mm)	440	460	480	500	520	540
Head-Tube Length (mm)	100	120	140	160	180	200
Reach (mm)	366.7	378.4	384.8	393.8	402.1	408.8
Stack (mm)	534.6	555.4	576.3	594.7	614.2	635.3
Handlebar Width (mm)	400	420	440	440	460	460
Stem Length (mm)	80	90	90	100	100	110
Saddle Width (mm)	143	143	143	143	143	143
Seat Post Length (mm)	350	400	400	400	400	400



MNZTA/REDDRT

The AWOL Expert is equipped with everything you need to hit the road and head out on a great adventure. Starting at the frame, it features heat-treated, custom-butted Cr-Mo tubing that's sure to stand up to years of hard riding and abuse. The geometry is also what you would call "dialed," as it's at once comfortable, efficient, and purpose-built to carrying big loads.

- The custom butted Cr-Mo steel frame provides plenty of stiffness, while still maintaining all-day compliance and comfort. Along with the integrated fender and rack mounts on both the frame and Cr-Mo fork, the AWOL provides the perfect blend of versatility and performance.
- Butted Cr-Mo fork features both rack and fender mounts, combining rugged durability, confident steering, and more utility than the average layman will even know what to do with.
- Durable, 32h alloy wheels are built strong to support heavy loads without sacrificing performance. There's also a Shimano Dynamo front hub that generates electricity without requiring batteries, plus powerful disc brakes at both the front and rear.

AWOL - 1					
SIZE	XS	S	M	L	XL
Stack (mm)	565	589	617	640	664
Reach (mm)	379	386	392	404	409
Head-Tube Length (mm)	135	160	185	210	235
Head-Tube Angle (deg)	71	71	72	72	72
B-B Height (mm)	295.5	295.5	295.5	295.5	295.5
B-B Drop (mm)	70	70	70	70	70
Trail (mm)	73	73	66	66	66
Fork Length (full) (mm)	405	405	405	405	405
Fork Rake/Offset (mm)	50	50	50	50	50
Front-Center (mm)	618	622	626	646	658
Chain-Stay Length (mm)	455	455	455	455	455
Wheelbase (mm)	1064	1067	1072	1091	1104
Top-Tube Length (horizontal) (mm)	542	555	575	600	625
Bike Stand-Over Height (mm)	755	774	794	821	844
Seat-Tube Length (mm)	455	475	495	525	550
Seat-Tube Angle (deg)	75	74	73.5	73	72
Handlebar Width (mm)	400	420	440	440	460
Stem Length (mm)	50	50	60	70	70
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	350	350	350	350	350
Crank Length (mm)	165	170	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	Heat-treated custom-butted Premium Cr-Mo tubing, internal light cable routing-ready, Adventure Geometry, post disc mount, fender/rack mounts, kickstand plate
FORK	Butted premium Cr-Mo, unicrown, heat-treated
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Adventure Gear AWOL, alloy, 125mm drop, 70mm short-reach, 12-degree flare-out
TAPE	Specialized Adventure Gear S-Wrap Canvas Tape
FRONT BRAKE	TRP HY/RD, hydraulic disc, 160mm rotor
REAR BRAKE	TRP HY/RD, hydraulic disc, 160mm rotor
FRONT DERAILLEUR	Shimano Tiagra
REAR DERAILLEUR	Shimano Tiagra
SHIFT LEVERS	Shimano Tiagra
CASSETTE	Shimano, 10-speed, 11-36t
CHAIN	KMC X10EPT Anti-Rust, 10-speed, w/reusable MissingLink
CRANKSET	Shimano Tiagra
CHAINRINGS	50/39/30T
BOTTOM BRACKET	Shimano Tiagra
RIMS	Specialized 29" disc front, 6061-T6 aluminum, 32h
FRONT HUB	Shimano Dynamo hub, Center Lock disc, 32h
REAR HUB	Shimano Center Lock disc, 32h
SPOKES	Stainless, 14/15g w/self-locking threads
FRONT TIRE	Specialized Borough Armadillo, 60TPI, 700x45mm
REAR TIRE	Specialized Borough Armadillo, 60TPI, 700x45mm
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized CG-R, FACT carbon, single bolt, reflective, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
99417-3001	AWOL EXPERT	MNZTA/REDDRT	XS
99417-3002			S
99417-3003			M
99417-3004			L
99417-3005			XL

AWOL COMP



BLK/BNZ

Whether you're using it as an all-out commuter rig during the week, or you're exploring the road less traveled on the weekend, you'll find that the AWOL Comp is equally capable.

- The custom butted Cr-Mo steel frame provides plenty of stiffness, while still maintaining all-day compliance and comfort. Along with the integrated fender and rack mounts on both the frame and Cr-Mo fork, the AWOL provides the perfect blend of versatility and performance.
- Butted Cr-Mo fork features both rack and fender mounts, combining rugged durability, confident steering, and more utility than the average layman will even know what to do with.
- The alloy, double-wall disc wheels can stand up to mile after mile of adventure, while the Specialized Ground Control tires provide plenty of traction on varying terrain and come 2Bliss ready.

AWOL - 1

SIZE	XS	S	M	L	XL
Stack (mm)	565	589	617	640	664
Reach (mm)	379	386	392	404	409
Head-Tube Length (mm)	135	160	185	210	235
Head-Tube Angle (deg)	71	71	72	72	72
B-B Height (mm)	295.5	295.5	295.5	295.5	295.5
B-B Drop (mm)	70	70	70	70	70
Trail (mm)	73	73	66	66	66
Fork Length (full) (mm)	405	405	405	405	405
Fork Rake/Offset (mm)	50	50	50	50	50
Front-Center (mm)	618	622	626	646	658
Chain-Stay Length (mm)	455	455	455	455	455
Wheelbase (mm)	1064	1067	1072	1091	1104
Top-Tube Length (horizontal) (mm)	542	555	575	600	625
Bike Stand-Over Height (mm)	755	774	794	821	844
Seat-Tube Length (mm)	455	475	495	525	550
Seat-Tube Angle (deg)	75	74	73.5	73	72
Handlebar Width (mm)	400	420	440	440	460
Stem Length (mm)	50	50	60	70	70
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	350	350	350	350	350
Crank Length (mm)	165	170	172.5	175	175

SPECS

All specs are subject to change without notice.

FRAME	Heat-treated custom-butted Premium Cr-Mo tubing, internal light cable routing-ready, Adventure Geometry, post disc mount, fender/rack mounts, kickstand plate
FORK	Butted premium Cr-Mo, unicrown, heat-treated
HEADSET	FSA, Campy style, integrated cartridge bearings, 15mm cone spacer
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Adventure Gear AWOL, alloy, 125mm drop, 70mm short-reach, 12-degree flare-out
TAPE	Specialized Adventure Gear S-Wrap Canvas Tape
FRONT BRAKE	SRAM Rival 1, hydraulic disc, 160mm rotor
REAR BRAKE	SRAM Rival 1, hydraulic disc, 160mm rotor
BRAKE LEVERS	SRAM Rival 1, hydraulic disc
REAR DERAILLEUR	SRAM Rival 1, 11-speed
SHIFT LEVERS	SRAM Rival 1 DoubleTap, hydraulic disc, 11-speed
CASSETTE	SRAM XG-1150, 11-speed, 10-42t
CHAIN	X11-1 EPT Anti-Rust 11sp w/MissingLink
CRANKSET	FSA Gossamer Pro Megatooth, alloy, MegaEvo BB, 110mm BCD spider
CHAINRINGS	38T
BOTTOM BRACKET	FSA MegaEvo Road, 68mm, Di2 wiring compatible
RIMS	29" disc front, 6061-T6 aluminum, 32h
FRONT HUB	Specialized, Hi Lo disc, QR, 32h
REAR HUB	Specialized, Hi Lo disc, QR, 32h
SPOKES	Stainless, 14/15g w/self-locking threads
FRONT TIRE	Ground Control, 29x1.9", 60TPI, 2Bliss Ready, folding bead
REAR TIRE	Ground Control, 29x1.9", 60TPI, 2Bliss Ready, folding bead
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized alloy, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
99417-5001	AWOL COMP	BLK/BNZ	XS
99417-5002			S
99417-5003			M
99417-5004			L
99417-5005			XL



OAKGRN/TPE

If you have somewhere to go, we hope that it'll take you a while to get there. That's because our AWOL is born for the open road, and it's fully equipped for the rigors that come with it.

- The custom butted Cr-Mo steel frame provides plenty of stiffness, while still maintaining all-day compliance and comfort. Along with the integrated fender and rack mounts on both the frame and Cr-Mo fork, the AWOL provides the perfect blend of versatility and performance.
- Butted Cr-Mo fork features both rack and fender mounts, combining rugged durability, confident steering, and more utility than the average layman will even know what to do with.
- These durable, 32h alloy disc wheels are sure to stand up to mile after mile of adventure, while the 700x45mm Borough Sport tires provide plenty of traction on varying terrain.

AWOL - 1					
SIZE	XS	S	M	L	XL
Stack (mm)	565	589	617	640	664
Reach (mm)	379	386	392	404	409
Head-Tube Length (mm)	135	160	185	210	235
Head-Tube Angle (deg)	71	71	72	72	72
B-B Height (mm)	295.5	295.5	295.5	295.5	295.5
B-B Drop (mm)	70	70	70	70	70
Trail (mm)	73	73	66	66	66
Fork Length (full) (mm)	405	405	405	405	405
Fork Rake/Offset (mm)	50	50	50	50	50
Front-Center (mm)	618	622	626	646	658
Chain-Stay Length (mm)	455	455	455	455	455
Wheelbase (mm)	1064	1067	1072	1091	1104
Top-Tube Length (horizontal) (mm)	542	555	575	600	625
Bike Stand-Over Height (mm)	755	774	794	821	844
Seat-Tube Length (mm)	455	475	495	525	550
Seat-Tube Angle (deg)	75	74	73.5	73	72
Handlebar Width (mm)	400	420	440	440	460
Stem Length (mm)	50	50	60	70	70
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	350	350	350	350	350
Crank Length (mm)	165	170	172.5	175	175

SPECS	All specs are subject to change without notice.
FRAME	Heat-treated custom-butted Premium Cr-Mo tubing, internal light cable routing-ready, Adventure Geometry, post disc mount, fender/rack mounts, kickstand plate
FORK	Butted premium Cr-Mo, unicrown, heat-treated
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Adventure Gear AWOL, alloy, 125mm drop, 70mm short-reach, 12-degree flare-out
TAPE	Specialized Adventure Gear S-Wrap Canvas Tape
FRONT BRAKE	Tektro Spyre, mechanical disc, 160mm rotor, dual pivot
REAR BRAKE	Tektro Spyre, mechanical disc, 160mm rotor, dual pivot
FRONT DERAILLEUR	Shimano Sora
REAR DERAILLEUR	Shimano Alivio, Shadow design, SGS cage
SHIFT LEVERS	Shimano Sora
CASSETTE	Shimano, 9-speed, 12-36t
CHAIN	SRAM PC-971 w/PowerLink
CRANKSET	Shimano Sora
CHAINRINGS	50/39/30T
BOTTOM BRACKET	Shimano Sora
RIMS	Specialized 29" disc front, 6061-T6 aluminum, 32h
FRONT HUB	Shimano Center Lock disc, 32h
REAR HUB	Shimano Center Lock disc, 32h
SPOKES	Stainless, 14g w/self-locking threads
FRONT TIRE	Borough Sport, 700x45mm
REAR TIRE	Borough Sport, 700x45mm
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized alloy, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
99417-7001	AWOL	OAKGRN/TPE	XS
99417-7002			S
99417-7003			M
99417-7004			L
99417-7005			XL

AWOL EXPERT FRAMESET



MNZTA/REDDRT

The AWOL Expert Module is equipped with everything you need to hit the road and head out on a great adventure. Starting at the frame, it features heat-treated, custom-butted Cr-Mo tubing that's sure to stand up to years of hard riding and abuse.

- The custom butted Cr-Mo steel frame provides plenty of stiffness, while still maintaining all-day compliance and comfort. Along with the integrated fender and rack mounts on both the frame and Cr-Mo fork, the AWOL provides the perfect blend of versatility and performance.
- Butted Cr-Mo fork features both rack and fender mounts, combining rugged durability, confident steering, and more utility than the average layman will even know what to do with.

SPECS

All specs are subject to change without notice.

FRAME	Heat-treated custom-butted Reynolds 725 premium Cr-Mo tubing, Adventure Geometry, internal light cable routing-ready, post disc mount, fender/rack mount, kickstand plate, SWINGER dropouts (Rohloff Speedhub compatible with OEM2 axleplate)
FORK	Butted premium Cr-Mo, unicrown, heat-treated
STEM	Specialized, 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Adventure Gear AWOL, alloy, 125mm drop, 70mm short-reach, 12-degree flare-out
TAPE	Specialized Adventure Gear S-Wrap Canvas Tape
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized CG-R, FACT carbon, single bolt, reflective, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
79417-3001	AWOL EXPERT MODULE	MNZTA/REDDRT	XS
79417-3002			S
79417-3003			M
79417-3004			L
79417-3005			XL

AWOL - 1

SIZE	XS	S	M	L	XL
Stack (mm)	565	589	617	640	664
Reach (mm)	379	386	392	404	409
Head-Tube Length (mm)	135	160	185	210	235
Head-Tube Angle (deg)	71	71	72	72	72
B-B Height (mm)	295.5	295.5	295.5	295.5	295.5
B-B Drop (mm)	70	70	70	70	70
Trail (mm)	73	73	66	66	66
Fork Length (full) (mm)	405	405	405	405	405
Fork Rake/Offset (mm)	50	50	50	50	50
Front-Center (mm)	618	622	626	646	658
Chain-Stay Length (mm)	455	455	455	455	455
Wheelbase (mm)	1064	1067	1072	1091	1104
Top-Tube Length (horizontal) (mm)	542	555	575	600	625
Bike Stand-Over Height (mm)	755	774	794	821	844
Seat-Tube Length (mm)	455	475	495	525	550
Seat-Tube Angle (deg)	75	74	73.5	73	72
Handlebar Width (mm)	400	420	440	440	460
Stem Length (mm)	50	50	60	70	70
Saddle Width (mm)	143	143	143	143	143
Seat Post Length (mm)	350	350	350	350	350

TURBO S



BLK/RED

With its elegant design and smooth, powerful electric assist motor capable of an easy cruising speed of 45kph, the Turbo S is the ultimate e-bike. Coupled with powerful Shimano XT disc brakes and high-capacity battery, the Turbo S will take you places you never dreamed—and damn fast too.

- Its tough and elegant alloy frame with Performance Geometry makes riding at speed feel just as safe and natural as a non electric assist bike.
- The custom Turbo alloy fork is built tough for the higher speeds and includes fender and rack mounts to make sure you can ride no matter the weather.
- The custom Turbo SC Specialized motor is the most powerful version available and capable of smooth and rapid accelerations in any conditions.
- The Turbo Clean Cockpit puts all the controls at your thumb tips with an illuminated display and regenerative braking options to help keep your battery charged up in a pinch.
- The Turbo's integrated down tube battery has a self-locking key release to prevent theft as well as handy LED power indicators to give you charge levels at a glance.
- Eliminate range anxiety and create/navigate routes with the Mission Control App.

TURBO				
SIZE	S	M	L	XL
Stack (mm)	606	616	630	655
Reach (mm)	380	395	405	422
Head-Tube Length (mm)	179	189	204	230
Head-Tube Angle (deg)	71	71	71	71
B-B Height (mm)	289.5	289.5	289.5	289.5
B-B Drop (mm)	70	70	70	70
Trail (mm)	78	78	78	78
Fork Length (full) (mm)	402	402	402	402
Fork Rake/Offset (mm)	43	43	43	43
Front-Center (mm)	614	632	647	673
Chain-Stay Length (mm)	455	455	455	455
Wheelbase (mm)	1060	1078	1093	1119
Top-Tube Length (horizontal) (mm)	577	595	610	635
Bike Stand-Over Height (mm)	743	794	827	866
Seat-Tube Length (mm)	420	460	500	540
Seat-Tube Angle (deg)	72	72	72	72
Handlebar Width (mm)	680	680	680	680
Stem Length (mm)	70	90	90	100
Crank Length (mm)	170	175	175	175
Seatpost Length (mm)	350	350	350	350

SPECS

All specs are subject to change without notice.

FRAME	Turbo alloy, smooth welds, speed optimized geometry, fully-integrated down tube battery, internal cable routing, 700c, X12 thru-axle dropout, full fender/rack mounts
REAR SHOCK	Song Sun single cable guide for front light (not included in small parts)
FORK	Custom Turbo alloy, fender eyelets, Low Rider mounts
HEADSET	1-1/8" upper/lower, threadless, Campy style, cartridge bearings
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise, 31.8mm clamp, 60mm
HANDLEBARS	Specialized, flat bar, double-butt 6061 alloy, 9-degree backsweep, 31.8mm
GRIPS	Specialized Body Geometry XCT, dual compound, lock-on
FRONT BRAKE	Shimano XT, hydraulic disc, 180mm rotor
REAR BRAKE	Shimano XT, hydraulic disc, 180mm rotor
BRAKE LEVERS	included in XT brakekit
REAR DERAILLEUR	Shimano Deore XT, Shadow Plus, SGS cage, 11-speed
SHIFT LEVERS	Shimano XT, 11-speed, 1-spec
CASSETTE	Shimano XT, 11-speed, 11-40t
CHAIN	KMC X11, 11-speed w/reusable MissingLink
CRANKSET	Specialized Stout, 2 pc., w/ alloy bashguard
CHAINRINGS	48T
BOTTOM BRACKET	Samox
RIMS	Turbo 700c, alloy, double-wall, w/ eyelets, 36h
FRONT HUB	Specialized, Hi Lo disc, alloy, RCC bearing system, QR, 36h
SPOKES	Front: DT Swiss Champion 2.0mm; Rear: DT Swiss Alpine 2.34/2.0mm
FRONT TIRE	Specialized Nimbus Armadillo, 60TPI, wire bead, 700x45mm
REAR TIRE	Specialized Nimbus Armadillo, 60TPI, wire bead, 700x45mm
SADDLE	Body Geometry Targa Comp, hollow Cr-Mo rails, 155mm, w/ rear light integration
SEATPOST	Specialized, alloy, 2-bolt, 12.5mm offset, 30.9mm
MOTOR	Turbo SC Specialized Motor, 500Watt, X12 axle
USER INTERFACE	Turbo Clean Cockpit, integrated thumb control, illuminated display
BATTERY	Turbo Integrated down tube battery, self-locking key release, on-board or off-bike charge capable, LED power indicators, start-up diagnostic feature, magnetic connectors, 691Wh capacity, w/ ANT and Bluetooth
CHARGER	Custom Specialized, 42V4A, w/ Rosenberger plug
WIRING	Wiring harness

PART NO.	DESCRIPTION	COLOR	SIZE
95016-1002	TURBO S	BLK/RED	S
95016-1003			M
95016-1004			L
95016-1005			XL

TURBO X



BLK/CYAN

With its elegant design and smooth, powerful electric assist motor capable of an easy cruising speed of 28mph, the Turbo X is one of the most versatile e-bikes around. Coupled with its high-capacity battery and RockShox suspension fork to help smooth out the ride, the Turbo X will take you places you never dreamed—and damn fast too.

- Its tough and elegant alloy frame with Performance Geometry makes riding at speed feel just as safe and natural as a non electric assist bike.
- The RockShox Paragon suspension fork has 50mm of travel to smooth out any bumps, potholes, or other road debris that gets in the way.
- The custom Turbo S Specialized motor is the most powerful version available and capable of smooth and rapid accelerations in any conditions.
- The Turbo Clean Cockpit puts all the controls at your thumb tips, with an illuminated display and regenerative braking options to help keep your battery charged up in a pinch.
- The Turbo integrated down tube battery has a self-locking key release to prevent theft as well as handy LED power indicators to give you charge levels at a glance.
- Eliminate range anxiety and create/navigate routes with the Mission Control.

TURBO X				
SIZE	S	M	L	XL
Seat-Tube Length, B-B Center to Top (mm)	420	460	500	540
Top-Tube Length, Horizontal (mm)	584	602	615	635
B-B Drop (mm)	70	70	70	70
Chain-Stay Length (mm)	455	455	455	455
Seat-Tube Angle (deg)	72	72	72	72
Head-Tube Angle (deg)	70	70	70	70
Fork Rake (mm)	46	46	46	46
Trail (mm)	77	77	77	77
Front-Center (mm)	633	652	665	685
Wheelbase (mm)	1079	1097	1111	1131
Stand-Over Height (mm)	746	783	814	847
Head-Tube Length (mm)	155	165	175	185
Handle-Bar Width (mm)	580	580	580	580
Stem Length (mm)	80	80	90	100
Crank Length (mm)	170	175	175	175
Seat-Post Length (mm)	350	350	350	350

SPECS	All specs are subject to change without notice.
FRAME	Turbo alloy, smooth welds, suspension optimized geometry, fully-integrated down tube battery, internal cable routing, 700c, X12 thru-axle dropout, full fender/rack mounts
REAR SHOCK	0000050171, Cover for light cable hole near headtube (not included in small parts)
FORK	RockShox Paragon, 50mm travel
HEADSET	1-1/8" upper/lower, threadless, Campy style, cartridge bearings
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise, 31.8mm clamp, 60mm
HANDLEBARS	Specialized, flat bar, double-buffed 6061 alloy, 9-degree backsweep, 31.8mm
GRIPS	Specialized Body Geometry XCT, dual compound, lock-on
FRONT BRAKE	Shimano Deore BR-M506, resin pads, 180mm rotor
REAR BRAKE	Shimano Deore BR-M506, resin pads, 180mm rotor
BRAKE LEVERS	included in brakekit
REAR DERAILLEUR	Shimano Deore RD-M610 Shadow, 10-speed
SHIFT LEVERS	Shimano Deore, 10-speed
CASSETTE	Shimano, 10-speed, 11-36t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	Specialized Stout, 2 pc., w/ alloy bashguard
CHAINRINGS	48T
BOTTOM BRACKET	Samox
RIMS	700c, disc, alloy, double-wall, pin joint, 36h
FRONT HUB	Specialized, Hi Lo disc, alloy, RCC bearing system, QR, 36h
SPOKES	Stainless, 2.3/2.0/2.0mm
FRONT TIRE	Specialized Trigger Sport, 60TPI, wire bead, BlackBelt protection, 700x47mm
REAR TIRE	Specialized Trigger Sport, 60TPI, wire bead, BlackBelt protection, 700x47mm
SADDLE	Body Geometry Targa Sport, steel rails, 155mm
SEATPOST	Post Moderne Parallelogram, coil spring, rebound damper, 30.9 mm, 30mm travel
MOTOR	Turbo S Specialized Motor, 250Watt, X12 axle
USER INTERFACE	Turbo Clean Cockpit, integrated thumb control, illuminated display, regenerative braking
BATTERY	Turbo Integrated down tube battery, self-locking key release, on-board or off-bike charge capable, LED power indicators, start-up diagnostic feature, magnetic connectors, 562Wh capacity, w/ ANT and Bluetooth
CHARGER	Custom Specialized, 42V4A, w/ Rosenberger plug
WIRING	Wiring harness

PART NO.	DESCRIPTION	COLOR	SIZE
95016-3002	TURBO X USA	BLK/CYAN	S
95016-3003			M
95016-3004			L
95016-3005			XL

TURBO



DRM SIL/BLK

The Specialized Turbo combines speed and style through an innovative electric-assist motor, advanced electronics, and sleek design. Capable of a top speed of 28 mph, the Turbo delivers superhuman power to anyone who rides it.

- Sleek and sturdy alloy frame with Performance Geometry designed for high-speed riding
- Oversized alloy fork is strong and responsive—even at 28 mph
- Specialized Electrak Armadillo tires for performance and durability no matter the speed
- Direct Drive rear hub motor provides uber efficient power no matter the terrain
- Finest quality Li-Ion battery pulls maximum power w/ superfast charging times

2015 TURBO				
SIZE	S	M	L	XL
Seat-Tube Length, B-B Center to Top (mm)	420	460	500	540
Top-Tube Length, Horizontal (mm)	577	595	610	635
B-B Drop (mm)	70	70	70	70
Chain-Stay Length (mm)	455	455	455	455
Seat-Tube Angle (deg)	72	72	72	72
Head-Tube Angle (deg)	71	71	71	71
Fork Rake (mm)	43	43	43	43
Trail (mm)	75	75	75	75
Front-Center (mm)	614	632	647	672
Wheelbase (mm)	1060	1078	1093	1119
Stand-Over Height (mm)	743	794	827	866
Head-Tube Length (mm)	179	189	204	230
Handle-Bar Width (mm)	580	580	580	580
Stem Length (mm)	80	80	90	100
Crank Length (mm)	170	175	175	175
Seat-Post Length (mm)	350	350	350	350

SPECS	Specifications subject to change without notice.
FRAME	Turbo alloy, smooth welds, fully-integrated down tube battery, internal cable routing, X12 thru-axle dropout, fender/rack mounts
FORK	Custom Turbo alloy, fender eyelets/Low Rider mounts
HEADSET	Ahead, cartridge bearings, alloy top cap, 8mm cone spacer
STEM	Specialized 3D forged alloy, 4-bolt, 7-degree rise
HANDLEBARS	Specialized Stout XC, flat bar, double butted 6061 alloy, 9-degree backsweep, 4-degree upsweep, 31.8mm
GRIPS	Specialized Body Geometry XCT, dual compound, lock-on
FRONT BRAKE	Formula C1, dual piston, 180mm rotor
REAR BRAKE	Formula C1, dual piston, Clean Cockpit clamp, 180mm rotor
BRAKE LEVERS	Formula C1
REAR DERAILLEUR	SRAM X7 Type 2, 10-speed, long cage
SHIFT LEVERS	SRAM X7 SL, 10-speed
CASSETTE	SRAM PG 1030, 10-speed, 11-32
CHAIN	KMC X10, 10-speed, w/ reusable MissingLink
CRANKSET	Chainway, 2 pc., w/ alloy bashguard
CHAINRINGS	48T
BOTTOM BRACKET	FSA MegaExo, outer-style
PEDALS	Alloy, LSL sealed bearings, 9/16", w/ reflectors
RIMS	700c disc, alloy double-wall, pin joint, 36h
FRONT HUB	Specialized Hi Lo disc, alloy, RCC bearing system, QR, 36h
SPOKES	Stainless, 2.3/2.0/2.0mm
INNER TUBES	Standard, presta valve
SADDLE	Body Geometry Turbo, hollow Cr-Mo rails
SEATPOST	Specialized, alloy, 2-bolt, 12.5mm offset, 30.9mm
SEAT BINDER	Alloy, 34.9mm
MOTOR	Custom Specialized G45c X12
USER INTERFACE	Turbo Clean Cockpit w/ integrated thumb control, illuminated display
BATTERY	Turbo Integrated downtube battery, self-locking key release, on-board or outside bike charge capable, LED power indicators, start-up diagnostic feature, magnetic connectors, 468 Wh capacity
CHARGER	Custom Specialized
WIRING	Wiring harness

PART NO.	DESCRIPTION	COLOR	SIZE
95015-7402	TURBO	DRM SIL/BLK	S
95015-7403			M
95015-7404			L
95015-7405			XL

SIRRUS PRO CARBON



RFBLKTNT/BLK

Fitness is not a fad, and the SIRRUS proves you're taking your fitness journey seriously. The SIRRUS Pro Carbon combines a quality carbon frame and high-end components to deliver a comfortable and fast ride. As you push yourself to reach your goals, the SIRRUS will be a powerful ally to have on your health and wellbeing team.

- The FACT 9r carbon fiber frame is engineered and designed with our Fitness Geometry, helping you ride more efficiently in a position that will see you riding comfortably, mile-after-mile.
- Zertz inserts in the lightweight FACT carbon fiber fork absorb road vibration to make a smoother, more responsive ride, while the Plug + Play fender mounts give you the option to install rain-fighting fenders.
- Shimano Deore hydraulic disc brakes provide reliable stopping power in any condition—wet, snowy, sandy, or whatever else the road can throw at you.

SIRRUS CARBON				
SIZE	S	M	L	XL
Stack (mm)	574	591	616	650
Reach (mm)	395	403	410	420
Head-Tube Length (mm)	150	165	190	225
Head-Tube Angle (deg)	71	71.5	72	72
B-B Height (mm)	275	275	275	275
B-B Drop (mm)	70	70	70	70
Trail (mm)	65	62	58	58
Fork Length (full) (mm)	398	398	398	398
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	627	635	645	666
Chain-Stay Length (mm)	435	435	435	435
Wheelbase (mm)	1052	1060	1070	1091
Top-Tube Length (horizontal) (mm)	568	578	598	619
Bike Stand-Over Height (mm)	752.2	784.6	821.9	860.3
Seat-Tube Length (mm)	440	485	530	570
Seat-Tube Angle (deg)	73.3	73.5	73	73
Handlebar Width (mm)	580	600	600	620
Stem Length (mm)	90	90	105	105
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	300	300	350	350
Crank Length (mm)	170	172.5	172.5	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized FACT 9r carbon, Fitness Geometry, Zertz, internal cable routing, tapered/integrated headset, post disc mount, Plug + Play fender mount
FORK	Specialized FACT carbon, full monocoque, Zertz, post mount disc, Plug + Play fender mounts
STEM	Specialized Flowset, integrated, 3D forged alloy, 4-bolt, 12-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-butted alloy, 9-degree backsweep, 31.8mm
TAPE	Specialized Body Geometry Targa, lock-on, integrated bar ends
FRONT BRAKE	Shimano Deore hydraulic disc, resin pads with fins, 160mm Ice-Tech rotor
REAR BRAKE	Shimano Deore hydraulic disc, resin pads with fins, 140mm Ice-Tech rotor
FRONT DERAILLEUR	Shimano Ultegra, braze-on, road double
REAR DERAILLEUR	Shimano Ultegra, GS cage, 11-speed
SHIFT LEVERS	Shimano SL-RS700, RapidFire Plus, 11-speed
CASSETTE	Shimano 105, 11-speed, 11-32t
CHAIN	KMC X11SL-1 DLC, 11-speed w/reusable MissingLink
CRANKSET	FSA SL-K Light, hollow carbon monocoque crankarms, 147mm Q-factor, direct-mount
CHAINRINGS	48/32T w/chainguard
BOTTOM BRACKET	FSA MegaEvo Road, 68mm, Di2 wiring compatible
FRONT WHEEL	Axis Pro Deep
REAR WHEEL	Axis Pro Deep
FRONT TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
REAR TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
SADDLE	Body Geometry Phenom Expert, hollow titanium rails, 143mm
SEATPOST	Specialized CG-R, FACT carbon, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90917-1002	SIRRUS PRO CARBON	RFBLKTNT/BLK	S
90917-1003			M
90917-1004			L
90917-1005			XL

SIRRUS EXPERT CARBON X1



CARB/BLK/CHAR

We understand that fitness bikes can get a bad wrap. All too often, they err on the side of value over performance, leaving you feeling in between, and frankly, a little burned. But we're happy to say that our SIRRUS Expert Carbon X1 is out to change that.

- The FACT 9r carbon fiber frame is engineered and designed with our Fitness Geometry, helping you ride more efficiently in a position that will see you riding comfortably, mile-after-mile.
- Zertz inserts in the lightweight FACT carbon fiber fork absorb road vibration to make a smoother, more responsive ride, while the Plug + Play fender mounts give you the option to install rain-fighting fenders.
- Shimano Deore hydraulic disc brakes provide reliable stopping power in any condition—wet, snowy, sandy, or whatever else the road can throw at you.

SIRRUS CARBON				
SIZE	S	M	L	XL
Stack (mm)	574	591	616	650
Reach (mm)	395	403	410	420
Head-Tube Length (mm)	150	165	190	225
Head-Tube Angle (deg)	71	71.5	72	72
B-B Height (mm)	275	275	275	275
B-B Drop (mm)	70	70	70	70
Trail (mm)	65	62	58	58
Fork Length (full) (mm)	398	398	398	398
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	627	635	645	666
Chain-Stay Length (mm)	435	435	435	435
Wheelbase (mm)	1052	1060	1070	1091
Top-Tube Length (horizontal) (mm)	568	578	598	619
Bike Stand-Over Height (mm)	752.2	784.6	821.9	860.3
Seat-Tube Length (mm)	440	485	530	570
Seat-Tube Angle (deg)	73.3	73.5	73	73
Handlebar Width (mm)	580	600	600	620
Stem Length (mm)	90	90	105	105
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	300	300	350	350
Crank Length (mm)	170	172.5	172.5	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized FACT 9r carbon, Fitness Geometry, Zertz, X1-specific internal cable routing, tapered/integrated headset, post disc mount, Plug + Play fender mount
FORK	Specialized FACT carbon, full monocoque, Zertz, post mount disc, Plug + Play fender mounts
STEM	Specialized Flowset, integrated, 3D forged alloy, 4-bolt, 12-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-buttressed alloy, 9-degree backsweep, 31.8mm
TAPE	Specialized Body Geometry Targa, lock-on, integrated bar ends
FRONT BRAKE	Shimano Deore, hydraulic disc, resin pads, 160mm rotor
REAR BRAKE	Shimano Deore, hydraulic disc, resin pads, 160mm rotor
REAR DERAILLEUR	SRAM Rival 1, long cage, 11-speed
SHIFT LEVERS	SRAM SL-700, 11-speed, trigger
CASSETTE	Sunrace, 11-speed, 11-42t
CHAIN	KMC X11EL, 11-speed w/reusable MissingLink
CRANKSET	FSA Gossamer Pro, forged alloy, 110mm BCD spider
CHAINRINGS	40T
BOTTOM BRACKET	BB386 EVO
FRONT WHEEL	Axis Expert Deep
REAR WHEEL	Axis Expert Deep
FRONT TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
REAR TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized CG-R, FACT carbon, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90916-3202	SIRRUS EXPERT CARBON X1	CARB/BLK/CHAR	S
90916-3203			M
90916-3204			L
90916-3205			XL

SIRRUS EXPERT CARBON



CARB/CHAR/HYP



RED/BLK/CHAR

We understand that fitness bikes can get a bad wrap. All too often, they err on the side of value over performance, leaving you feeling in between, and frankly, a little burned. But we're happy to say that our Sirrus Expert Carbon is out to change that.

- The FACT 9r carbon fiber frame is engineered and designed with our Fitness Geometry, helping you ride more efficiently in a position that will see you riding comfortably, mile-after-mile.
- Zertz inserts in the lightweight FACT carbon fiber fork absorb road vibration to make a smoother, more responsive ride, while the Plug + Play fender mounts give you the option to install rain-fighting fenders.
- Shimano Deore hydraulic disc brakes provide reliable stopping power in any condition—wet, snowy, sandy, or whatever else the road can throw at you.

SIRRUS CARBON				
SIZE	S	M	L	XL
Stack (mm)	574	591	616	650
Reach (mm)	395	403	410	420
Head-Tube Length (mm)	150	165	190	225
Head-Tube Angle (deg)	71	71.5	72	72
B-B Height (mm)	275	275	275	275
B-B Drop (mm)	70	70	70	70
Trail (mm)	65	62	58	58
Fork Length (full) (mm)	398	398	398	398
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	627	635	645	666
Chain-Stay Length (mm)	435	435	435	435
Wheelbase (mm)	1052	1060	1070	1091
Top-Tube Length (horizontal) (mm)	568	578	598	619
Bike Stand-Over Height (mm)	752.2	784.6	821.9	860.3
Seat-Tube Length (mm)	440	485	530	570
Seat-Tube Angle (deg)	73.3	73.5	73	73
Handlebar Width (mm)	580	600	600	620
Stem Length (mm)	90	90	105	105
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	300	300	350	350
Crank Length (mm)	170	172.5	172.5	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized FACT 9r carbon, Fitness Geometry, Zertz, internal cable routing, tapered/integrated headset, post disc mount, Plug + Play fender mount
FORK	Specialized FACT carbon, full monocoque, Zertz, post mount disc, Plug + Play fender mounts
STEM	Specialized Flowset, integrated, 3D forged alloy, 4-bolt, 12-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-buttressed alloy, 9-degree backsweep, 31.8mm
TAPE	Specialized Body Geometry Targa, lock-on, integrated bar ends
FRONT BRAKE	Shimano Deore, hydraulic disc, resin pads, 160mm rotor
REAR BRAKE	Shimano Deore, hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	Shimano 105, braze-on, road double
REAR DERAILLEUR	Shimano 105, GS cage, 11-speed
SHIFT LEVERS	microSHIFT flatbar road, 11-speed
CASSETTE	Shimano 105, 11-speed, 11-32t
CHAIN	KMC X11-1, 11-speed w/reusable MissingLink
CRANKSET	FSA Gossamer Pro, forged aluminum, sub compact
CHAINRINGS	48/32T w/chainguard
BOTTOM BRACKET	BB386 EVO
FRONT WHEEL	Axis Expert Deep
REAR WHEEL	Axis Expert Deep
FRONT TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
REAR TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
SADDLE	Canopy Comp, hollow Cr-Mo rails, 155mm
SEATPOST	Specialized CG-R, FACT carbon, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90917-3002	SIRRUS EXPERT CARBON	CARB/CHAR/HYP	S
90917-3003			M
90917-3004			L
90917-3005			XL
90916-3102	SIRRUS EXPERT CARBON	RED/BLK/CHAR	S
90916-3103			M
90916-3104			L
90916-3105			XL

SIRRUS COMP CARBON



METWHTSIL/BLK/LTSIL



TARBLK/CNDYRED/LTSIL

Your road to fitness is filled with determination and steadfast resolve, so why shouldn't your bike support that? With our SIRRUS Comp Carbon, you get all of the performance features that you need to hit your goals head-on, and none of them that you don't.

- The FACT 9r carbon fiber frame is engineered and designed with our Fitness Geometry, helping you ride more efficiently in a position that will see you riding comfortably, mile-after-mile.
- Zertz inserts in the lightweight FACT carbon fiber fork absorb road vibration to make a smoother, more responsive ride, while the Plug + Play fender mounts give you the option to install rain-fighting fenders.
- Shimano Alivio hydraulic disc brakes dependable braking in any condition—wet, snowy, sandy, or whatever else the road can throw at you.

SIRRUS CARBON				
SIZE	S	M	L	XL
Stack (mm)	574	591	616	650
Reach (mm)	395	403	410	420
Head-Tube Length (mm)	150	165	190	225
Head-Tube Angle (deg)	71	71.5	72	72
B-B Height (mm)	275	275	275	275
B-B Drop (mm)	70	70	70	70
Trail (mm)	65	62	58	58
Fork Length (full) (mm)	398	398	398	398
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	627	635	645	666
Chain-Stay Length (mm)	435	435	435	435
Wheelbase (mm)	1052	1060	1070	1091
Top-Tube Length (horizontal) (mm)	568	578	598	619
Bike Stand-Over Height (mm)	752.2	784.6	821.9	860.3
Seat-Tube Length (mm)	440	485	530	570
Seat-Tube Angle (deg)	73.3	73.5	73	73
Handlebar Width (mm)	580	600	600	620
Stem Length (mm)	90	90	105	105
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	300	300	350	350
Crank Length (mm)	170	172.5	172.5	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized FACT 9r carbon, Fitness Geometry, Zertz, internal cable routing, tapered/integrated headset, post disc mount, Plug + Play fender mount
FORK	Specialized FACT carbon, full monocoque, Zertz, post mount disc, Plug + Play fender mounts
STEM	Specialized Flowset, integrated, 3D forged alloy, 4-bolt, 12-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-buttressed alloy, 9-degree backsweep, 31.8mm
TAPE	Specialized Body Geometry Targa, lock-on, integrated bar ends
FRONT BRAKE	Shimano Alivio hydraulic disc, resin pads, 160mm rotor
REAR BRAKE	Shimano Alivio hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	Shimano Tiagra 4700, 10-speed, braze-on
REAR DERAILLEUR	Shimano Tiagra, 10-speed, GS Cage
SHIFT LEVERS	microSHIFT flatbar road, 10-speed
CASSETTE	Shimano, 10-speed, 11-34t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	FSA Gossamer Pro, forged aluminum, MegaExo, sub compact
CHAINRINGS	48/32T w/chainguard
BOTTOM BRACKET	FSA MegaExo
FRONT WHEEL	Axis Elite Deep
REAR WHEEL	Axis Elite Deep
FRONT TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
REAR TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
SADDLE	Canopy Comp, hollow Cr-Mo rails, 155mm
SEATPOST	Specialized Pro Pave, FACT carbon, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90917-5002	SIRRUS COMP CARBON	METWHTSIL/BLK/LTSIL	S
90917-5003			M
90917-5004			L
90917-5005			XL
90917-5102	SIRRUS COMP CARBON	TARBLK/CNDYRED/LTSIL	S
90917-5103			M
90917-5104			L
90917-5105			XL

SIRRUS SPORT CARBON



CARB/NRDCCRED/CHAR

Sure, getting in shape takes hard work and plenty of sweat, but that doesn't mean there's no room for fun, right? Our Sirrus Sport Carbon was designed to liven-up your fitness routine with a host of smart performance features that'll have you smiling as you sweat.

- The FACT 9r carbon fiber frame is engineered and designed with our Fitness Geometry, helping you ride more efficiently in a position that will see you riding comfortably, mile-after-mile.
- Zertz inserts in the lightweight FACT carbon fiber fork absorb road vibration to make a smoother, more responsive ride, while the Plug + Play fender mounts give you the option to install rain-fighting fenders.
- Shimano M315 hydraulic disc brakes will have you stopping at a moment's notice in any imaginable condition.

SIRRUS CARBON				
SIZE	S	M	L	XL
Stack (mm)	574	591	616	650
Reach (mm)	395	403	410	420
Head-Tube Length (mm)	150	165	190	225
Head-Tube Angle (deg)	71	71.5	72	72
B-B Height (mm)	275	275	275	275
B-B Drop (mm)	70	70	70	70
Trail (mm)	65	62	58	58
Fork Length (full) (mm)	398	398	398	398
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	627	635	645	666
Chain-Stay Length (mm)	435	435	435	435
Wheelbase (mm)	1052	1060	1070	1091
Top-Tube Length (horizontal) (mm)	568	578	598	619
Bike Stand-Over Height (mm)	752.2	784.6	821.9	860.3
Seat-Tube Length (mm)	440	485	530	570
Seat-Tube Angle (deg)	73.3	73.5	73	73
Handlebar Width (mm)	580	600	600	620
Stem Length (mm)	90	90	105	105
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	300	300	350	350
Crank Length (mm)	170	172.5	172.5	175

SPECS

All specs are subject to change without notice.

FRAME	Specialized FACT 9r carbon, Fitness Geometry, Zertz, internal cable routing, tapered/integrated headset, post disc mount, Plug + Play fender mount
FORK	Specialized FACT carbon, full monocoque, Zertz, post mount disc, Plug + Play fender mounts
STEM	Specialized Flowset, integrated, 3D forged alloy, 4-bolt, 12-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-buttressed alloy, 9-degree backsweep, 31.8mm
TAPE	Specialized Body Geometry Targa, lock-on, integrated bar ends
FRONT BRAKE	Shimano M315 hydraulic disc, resin pads, 160mm rotor
REAR BRAKE	Shimano M315 hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	microSHIFT R9, braze-on 9-speed, road double
REAR DERAILLEUR	Shimano Alivio, 9-speed
SHIFT LEVERS	microSHIFT flatbar road, 9-speed
CASSETTE	Shimano, 9-speed, 11-34t
CHAIN	SRAM PC-971 w/PowerLink
CRANKSET	FSA Vero, forged alloy, sub compact, 110mm BCD spider
CHAINRINGS	48/32T w/chainguard
BOTTOM BRACKET	BB-7420Stw/Bolts w/RPM logo
RIMS	Disc, 6061 aluminum double-wall
FRONT HUB	Specialized Center Lock, loose ball bearings, 32h, 9mm QR
REAR HUB	Shimano Center Lock, disc, 10x135mm QR, 32h
SPOKES	Stainless, 14g w/self-locking threads
FRONT TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
REAR TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
SADDLE	Canopy Comp, hollow Cr-Mo rails, 155mm
SEATPOST	Alloy, 2-bolt, micro-adjust, 25mm offset, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90917-6202	SIRRUS SPORT CARBON	CARB/NRDCCRED/CHAR	S
90917-6203			M
90917-6204			L
90917-6205			XL

SIRRUS COMP CITY



CHAR/BLK

Our Sirrus Comp City understands that there's more to "value" than a dollar sign. That's why it's purpose-built to give you everything that you need to stay in shape, from a lightweight, corrosion-resistant aluminum frame to powerful hydraulic disc brakes.

- The frame was constructed from our E5 Premium Aluminum in order to build a bike with a respectable overall weight and responsive ride quality. It's also been paired with our Fitness Geometry, so you can rest assured that you'll be comfortable along your path to greater fitness.
- The Espoir Sport Reflect tires are reliable, fast, and enhanced for reflective safety. They feature a durable compound with low rolling resistance and plenty of grip. And with our double BlackBelt flat protection, you also gain reliability and durability where it counts.
- Our Canopy Comp saddle was designed for the utmost in comfort, keeping pressure off the soft tissue for a ride quality that's enjoyable—mile after mile.

SIRRUS COMP CITY				
SIZE	S	M	L	XL
Stack (mm)	574	591	616	650
Reach (mm)	398	406	413	422
Head-Tube Length (mm)	150	165	190	225
Head-Tube Angle (deg)	71	71.5	72	72
B-B Height (mm)	275	275	275	275
B-B Drop (mm)	70	70	70	70
Trail (mm)	65	62	58	58
Fork Length (full) (mm)	398	398	398	398
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	629	638	648	668
Chain-Stay Length (mm)	439	439	439	439
Wheelbase (mm)	1059	1068	1078	1097
Top-Tube Length (horizontal) (mm)	571	581	602	621
Bike Stand-Over Height (mm)	744.6	779.8	813.7	846.8
Seat-Tube Length (mm)	440	485	530	570
Seat-Tube Angle (deg)	73.25	73.5	73	73
Handlebar Width (mm)	580	580	600	600
Stem Length (mm)	90	90	105	105
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	300	300	350	350
Crank Length (mm)	170	170	172.5	172.5

SPECS

All specs are subject to change without notice.

FRAME	Specialized E5 Premium Aluminum, Fitness Geometry, fully-manipulated butted tubing w/smooth welds, internal cable routing, tapered/integrated headset, post disc mount, Plug + Play fender mount, reflective paint
FORK	Specialized FACT carbon fiber, alloy steerer/crown, Zertz inserts, post disc mount, Plug + Play fender mount, reflective paint
STEM	Specialized Flowset, integrated, 3D forged alloy, 4-bolt, 12-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-butted alloy, 9-degree backsweep, 31.8mm
TAPE	Specialized Body Geometry Targa, lock-on, integrated bar ends
FRONT BRAKE	Shimano Alivio hydraulic disc, resin pads, 160mm rotor
REAR BRAKE	Shimano Alivio hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	Shimano Tiagra, braze-on, road double
REAR DERAILLEUR	Shimano Tiagra, 10-speed, GS Cage
CASSETTE	Shimano, 10-speed, 11-34t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	FSA Gossamer Pro, forged aluminum, MegaExo, sub compact
CHAINRINGS	48/32T w/chainguard
BOTTOM BRACKET	FSA MegaExo
FRONT WHEEL	Axis Elite Deep
REAR WHEEL	Axis Elite Deep
FRONT TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
REAR TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
SADDLE	Canopy Comp, hollow Cr-Mo rails, 155mm
SEATPOST	Alloy, 2-bolt, micro-adjust, 25mm offset, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90917-5202	SIRRUS COMP CITY	CHAR/BLK	S
90917-5203			M
90917-5204			L
90917-5205			XL

SIRRUS ELITE



CNDYRED/NVY/BBYBLU



TARBLK/CBRBLU/BBYBLU

There's nothing elitist about our SIRRUS Elite. In fact, it's designed to help anyone along their path to fitness and health. Need proof? How do a durable, lightweight aluminum frame and a FACT carbon fiber fork sound? If you ask us, it sounds like you found your partner in health.

- The frame was constructed from our E5 Premium Aluminum in order to build a bike with a respectable overall weight and responsive ride quality. It's also been paired with our Fitness Geometry, so you can rest assured that you'll be comfortable along your path to greater fitness.
- Zertz inserts in the lightweight FACT carbon fiber fork absorb road vibration to make a smoother, more responsive ride, while the Plug + Play fender mounts give you the option to install rain-fighting fenders.
- Shimano M315 hydraulic disc brakes will have you stopping at a moment's notice in any imaginable condition.

SIRRUS E5 - 2017

SIZE	S	M	L	XL
Stack (mm)	574	591	616	650
Reach (mm)	398	406	413	422
Head-Tube Length (mm)	150	165	190	225
Head-Tube Angle (deg)	71	71.5	72	72
B-B Height (mm)	275	275	275	275
B-B Drop (mm)	70	70	70	70
Trail (mm)	65	62	58	58
Fork Length (full) (mm)	398	398	398	398
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	629	638	648	668
Chain-Stay Length (mm)	439	439	439	439
Wheelbase (mm)	1059	1068	1078	1097
Top-Tube Length (horizontal) (mm)	571	581	602	621
Bike Stand-Over Height (mm)	744.6	779.8	813.7	846.8
Seat-Tube Length (mm)	440	485	530	570
Seat-Tube Angle (deg)	73.25	73.5	73	73
Handlebar Width (mm)	580	580	600	600
Stem Length (mm)	90	90	105	105
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	300	300	350	350
Crank Length (mm)	170	170	172.5	172.5

SPECS

All specs are subject to change without notice.

FRAME	Specialized E5 Premium Aluminum, Fitness Geometry, fully-manipulated butted tubing w/smooth welds, internal cable routing, tapered/integrated headset, post disc mount, Plug + Play fender mount
FORK	FACT carbon fiber, alloy steerer/crown, Zertz inserts, post disc mount, Plug + Play fender mount
STEM	Specialized Flowset, integrated, 3D forged alloy, 4-bolt, 12-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-butted alloy, 9-degree backsweep, 31.8mm
TAPE	Specialized Body Geometry Targa, lock-on, integrated bar ends
FRONT BRAKE	Shimano M315 hydraulic disc, resin pads, 160mm rotor
REAR BRAKE	Shimano M315 hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	Shimano Sora, 9-speed
REAR DERAILLEUR	Shimano Sora, GS cage, 9-speed
SHIFT LEVERS	microSHIFT flatbar road, 9-speed
CASSETTE	Shimano, 9-speed, 11-34t
CHAIN	SRAM PC-971 w/PowerLink
CRANKSET	FSA Gossamer Pro, forged aluminum, MegaExo, sub compact
CHAINRINGS	48/32T w/chainguard
BOTTOM BRACKET	FSA MegaExo
FRONT WHEEL	Axis Sport Deep
REAR WHEEL	Axis Sport Deep
FRONT TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
REAR TIRE	Espoir Sport Reflect, 700x30mm, 60TPI, double BlackBelt protection
SADDLE	Canopy Sport, steel rails
SEATPOST	Alloy, 2-bolt, micro-adjust, 25mm offset, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90917-4002	SIRRUS ELITE	CNDYRED/NVY/BBYBLU	S
90917-4003			M
90917-4004			L
90917-4005			XL
90917-4102	SIRRUS ELITE	TARBLK/CBRBLU/BBYBLU	S
90917-4103			M
90917-4104			L
90917-4105			XL

SIRRUS SPORT



CHAR/CHRM/BLK



SPR/SLT/VALORG

As you push yourself towards your fitness goals, you need a partner that you can count on, and we're happy to say that the SIRRUS Sport fits the bill.

- The reliable and sturdy A1 Premium Aluminum frame features rack and fender mounts, allowing you to carry gear or to fend off road spray in inclement weather.
- Zertz inserts in the lightweight FACT carbon fiber fork absorb road vibration to make a smoother, more responsive ride, while the Plug + Play fender mounts give you the option to install rain-fighting fenders.
- Shimano M315 hydraulic disc brakes will have you stopping at a moment's notice in any imaginable condition.

SIRRUS A1					
SIZE	XS	S	M	L	XL
Stack (mm)	563	584	600	626	659
Reach (mm)	388	394	402	409	418
Head-Tube Length (mm)	130	150	165	190	225
Head-Tube Angle (deg)	70.5	71	71.5	72	72
B-B Height (mm)	281	281	281	281	281
B-B Drop (mm)	70	70	70	70	70
Trail (mm)	70	67	64	60	60
Fork Length (full) (mm)	410	410	410	410	410
Fork Rake/Offset (mm)	51	51	51	51	51
Front-Center (mm)	621	629	637	647	667
Chain-Stay Length (mm)	445	445	445	445	445
Wheelbase (mm)	1056	1065	1073	1082	1103
Top-Tube Length (horizontal) (mm)	555	570	580	600	620
Bike Stand-Over Height (mm)	716	750	786	821	859
Seat-Tube Length (mm)	395	440	485	530	570
Seat-Tube Angle (deg)	73.5	73.3	73.5	73	73
Handlebar Width (mm)	580	580	600	600	620
Stem Length (mm)	80	90	100	100	110
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	300	300	350	350	350
Crank Length (mm)	170	170	172.5	172.5	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Fitness Geometry, fully-manipulated butted tubing, integrated lower bearing, fender/rack mounts
FORK	FACT carbon fiber, alloy steerer/crown, Zertz inserts, post disc mount, Plug + Play fender mount
STEM	Alloy, 4-bolt, 7-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-buttet alloy, 9-degree backsweep, 31.8mm
TAPE	Specialized Body Geometry Targa, lock-on
FRONT BRAKE	Shimano M315 hydraulic disc, resin pads, 160mm rotor
REAR BRAKE	Shimano M315 hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	microSHIFT R9, 31.8mm clamp, 9-speed, road double
REAR DERAILLEUR	Shimano Alivio, 9-speed
SHIFT LEVERS	microSHIFT flatbar road, 9-speed
CASSETTE	Shimano, 9-speed, 11-34t
CHAIN	KMC X9, 9-speed w/reusable MissingLink
CRANKSET	FSA Vero, forged alloy, sub compact, 110mm BCD spider
CHAINRINGS	48/32T w/chainguard
BOTTOM BRACKET	BB-7420Stw/Bolts w/RPM logo
RIMS	Disc, 6061 aluminum double-wall
REAR HUB	Shimano Center Lock, disc, 10x135mm QR, 32h
SPOKES	Stainless, 14g w/self-locking threads
FRONT TIRE	Nimbus Reflect, 700x32mm, 26TPI, Flak Jacket protection
REAR TIRE	Nimbus Reflect, 700x32mm, 26TPI, Flak Jacket protection
SADDLE	Canopy Sport, steel rails
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
90917-6002	SIRRUS SPORT	CHAR/CHRM/BLK	S
90917-6003			M
90917-6004			L
90917-6005			XL
80917-6102	SIRRUS SPORT	SPR/SLT/VALORG	S
80917-6103			M
80917-6104			L
80917-6105			XL



NVY/BLK/NRDCRED

If your approach to fitness is no-nonsense and straightforward, our SIRRUS Disc is for you.

- The reliable and sturdy A1 Premium Aluminum frame features rack and fender mounts, allowing you to carry gear or to fend off road spray in inclement weather.
- A steel, straight blade fork provides a responsive ride, while the fender and rack mounts give you the option to install rain-fighting fenders and racks that can transport your gear around town.
- Mechanical disc brakes are reliable and powerful, without the hassle of brake bleeds and labor-intensive maintenance.

SIRRUS A1					
SIZE	XS	S	M	L	XL
Stack (mm)	563	584	600	626	659
Reach (mm)	388	394	402	409	418
Head-Tube Length (mm)	130	150	165	190	225
Head-Tube Angle (deg)	70.5	71	71.5	72	72
B-B Height (mm)	281	281	281	281	281
B-B Drop (mm)	70	70	70	70	70
Trail (mm)	70	67	64	60	60
Fork Length (full) (mm)	410	410	410	410	410
Fork Rake/Offset (mm)	51	51	51	51	51
Front-Center (mm)	621	629	637	647	667
Chain-Stay Length (mm)	445	445	445	445	445
Wheelbase (mm)	1056	1065	1073	1082	1103
Top-Tube Length (horizontal) (mm)	555	570	580	600	620
Bike Stand-Over Height (mm)	716	750	786	821	859
Seat-Tube Length (mm)	395	440	485	530	570
Seat-Tube Angle (deg)	73.5	73.3	73.5	73	73
Handlebar Width (mm)	580	580	600	600	620
Stem Length (mm)	80	80	80	100	100
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	300	300	350	350	350
Crank Length (mm)	170	170	172.5	172.5	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Fitness Geometry, fully-manipulated butted tubing, integrated lower bearing, fender/rack mounts
FORK	Steel, straight blades, IS disc mount, fender/rack mounts
STEM	Alloy, 4-bolt, 20-degree rise, 25.4mm clamp
HANDLEBARS	Specialized, alloy, 9-degree backsweep, 25.4mm
TAPE	Specialized Body Geometry Targa, lock-on
FRONT BRAKE	Mechanical disc, resin pads, 160mm
REAR BRAKE	Mechanical disc, resin pads, 160mm
FRONT DERAILLEUR	Shimano Tourney, top swing, dual pull, 31.8mm band clamp
REAR DERAILLEUR	Shimano Altus, 8-speed
SHIFT LEVERS	Shimano EF500, EZ Fire Plus, 8-speed
CASSETTE	Shimano, 8-speed, 11-32t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Stout, forged alloy
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	Disc, 6061 aluminum double-wall
FRONT HUB	Specialized disc, double-sealed, loose ball bearings, 9mm QR
REAR HUB	Specialized disc, loose ball bearings, for Shimano 8-/9-speed cassettes, QR
SPOKES	Stainless, 14g
FRONT TIRE	Nimbus Reflect, 700x32mm, 26TPI, Flak Jacket protection
REAR TIRE	Nimbus Reflect, 700x32mm, 26TPI, Flak Jacket protection
SADDLE	Canopy Sport, steel rails
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
80916-7402	SIRRUS DISC	NVY/BLK/NRDCRED	S
80916-7403			M
80916-7404			L
80916-7405			XL



BLK/WHT/CHAR



LTSIL/LTYEL/DRMSIL



LME/TI/OAKGRN

If you're going to get in shape you need to move, and nothing wants to help you move faster than our Sirrus. It takes a no-nonsense approach to its design, giving you everything that you need and nothing that you don't.

- The reliable and sturdy A1 Premium Aluminum frame features rack and fender mounts, allowing you to carry gear or to fend off road spray in inclement weather.
- A steel, straight blade fork provides a responsive ride, while the fender and rack mounts give you the option to install rain-fighting fenders and racks that can transport your gear around town.
- V-brakes are dependable and easy to maintain, so you won't have to worry about brake bleeds or labor-intensive maintenance to have awesome stopping power.

SIRRUS A1					
SIZE	XS	S	M	L	XL
Stack (mm)	563	584	600	626	659
Reach (mm)	388	394	402	409	418
Head-Tube Length (mm)	130	150	165	190	225
Head-Tube Angle (deg)	70.5	71	71.5	72	72
B-B Height (mm)	281	281	281	281	281
B-B Drop (mm)	70	70	70	70	70
Trail (mm)	70	67	64	60	60
Fork Length (full) (mm)	410	410	410	410	410
Fork Rake/Offset (mm)	51	51	51	51	51
Front-Center (mm)	621	629	637	647	667
Chain-Stay Length (mm)	445	445	445	445	445
Wheelbase (mm)	1056	1065	1073	1082	1103
Top-Tube Length (horizontal) (mm)	555	570	580	600	620
Bike Stand-Over Height (mm)	716	750	786	821	859
Seat-Tube Length (mm)	395	440	485	530	570
Seat-Tube Angle (deg)	73.5	73.3	73.5	73	73
Handlebar Width (mm)	580	580	600	600	620
Stem Length (mm)	80	80	80	100	100
Saddle Width (mm)	155	155	155	155	155
Seat Post Length (mm)	300	300	350	350	350
Crank Length (mm)	170	170	170	170	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Fitness Geometry, fully-manipulated butted tubing, integrated lower bearing, fender/rack mounts
FORK	Steel, straight blades, fender/rack mounts
STEM	Alloy, 4-bolt, 20-degree rise, 25.4mm clamp
HANDLEBARS	Specialized, alloy, 9-degree backsweep, 25.4mm
TAPE	Specialized Body Geometry Targa, lock-on
FRONT BRAKE	V-brake, linear pull
REAR BRAKE	V-brake, linear pull
FRONT DERAILLEUR	Shimano Tourney, top swing, dual pull, 31.8mm band clamp
REAR DERAILLEUR	Shimano Altus, 8-speed
SHIFT LEVERS	Shimano EF500, EZ Fire Plus, 8-speed
CASSETTE	Shimano, 8-speed, 11-32t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Stout, forged alloy
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	700c, 6061 aluminum double-wall
FRONT HUB	Specialized V-brake, alloy, loose ball bearings, 9mm, QR
REAR HUB	Specialized, 8-/9-speed cassette body, QR
SPOKES	Stainless, 14g
FRONT TIRE	Nimbus Reflect, 700x32mm, 26TPI, Flak Jacket protection
REAR TIRE	Nimbus Reflect, 700x32mm, 26TPI, Flak Jacket protection
SADDLE	Canopy Sport, steel rails
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
80916-7102	SIRRUS	BLK/WHT/CHAR	S
80916-7103			M
80916-7104			L
80916-7105			XL
80917-7102	SIRRUS	LTSIL/LTYEL/DRMSIL	S
80917-7103			M
80917-7104			L
80917-7105			XL
80917-7002	SIRRUS	LME/TI/OAKGRN	S
80917-7003			M
80917-7004			L
80917-7005			XL

CROSSTRAIL EXPERT CARBON



BLUTNT/BBYBLU/NRDRED

If gyms only had one machine, no one would go. The same could be said for riding. To achieve your fitness goals, you need to keep things lively and entertaining, and the versatility of the Crosstrail Expert Carbon does just that.

- Working with our Body Geometry team, we designed a frame that strikes the optimal balance between comfort and efficiency. The FACT 9r carbon fiber keeps the bike ultra-light and efficient, while the rack, fender, and disc mounts give you an incredibly versatile package.
- An SR Suntour NCX fork w/ Fitness Brain technology features 60mm of coil-sprung travel that takes the sting out of bumpy terrain, while an integrated remote lockout is coupled with our Fitness Brain technology to promote more climbing and pedaling efficiency.
- Braking duties are handled by Tektro Flow Set Control hydraulic disc brakes to ensure effective, consistent, and reliable power through any kind of terrain or condition.

CROSSTRAIL CARBON				
SIZE	S	M	L	XL
Seat-Tube Length, B-B Center to Top (mm)	372	422	472	522
Top-Tube Length, Horizontal (mm)	571	586	604	624
B-B Drop (mm)	65	65	65	65
Chain-Stay Length (mm)	445	445	445	445
Seat-Tube Angle (deg)	73	73	73	73
Head-Tube Angle (deg)	70	70.5	70.5	70.5
Fork Rake (mm)	43	43	43	43
Trail (mm)	78	75	75	75
Front-Center (mm)	631	641	660	680
Wheelbase (mm)	1068	1078	1097	1118
Stand-Over Height (mm)	732	769	806	840
Head-Tube Length (mm)	110	125	145	165
Reach (mm)	390	400	412	426
Stack (mm)	592	608	627	646
Handlebar Width (mm)	660	660	660	660
Stem Length (mm)	60	75	75	90
Saddle Width (mm)	143	143	143	143
Seat Post Length (mm)	350	350	350	350
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized FACT 9R carbon, Fitness Geometry, internal cable routing, integrated headset, flat mount disc, rack and Plug + Play fender mounts, 9mm QR
FORK	SR Suntour NCX w/Specialized Fitness Brain technology, 60mm of travel, 1-1/8" steerer, 12mm thru-axle
STEM	Specialized Flowset, integrated, 3D forged alloy, 4-bolt, 12-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-buttressed alloy, 9-degree backsweep, 31.8mm
GRIPS	Body Geometry Flow Set Control Grips, lock-on
FRONT BRAKE	Tektro Flow Set Control, hydraulic disc, carbon brake lever, metal pads, post mount, 160mm rotor
REAR BRAKE	Tektro Flow Set Control, hydraulic disc, carbon brake lever, metal pads, post mount, 140mm rotor
FRONT DERAILLEUR	microSHIFT XCD, 31.8mm clamp, 10-/11-speed, MTB double
REAR DERAILLEUR	Shimano Deore XT M8000, Shadow Plus, SGS cage, 11-speed
SHIFT LEVERS	Flow Set Control, 11-speed
CASSETTE	Sunrace, 11-42t, 11-speed
CHAIN	KMC X11EL, 11-speed w/reusable MissingLink
CRANKSET	FSA V-Drive, PF30 System Interface, MegaEVO BB, 10-/11-speed, hollow forged 7075 aluminum, 170mm Q-factor, direct-mount
CHAINRINGS	44/32T w/chainguard
BOTTOM BRACKET	FSA MegaEVO
RIMS	Disc 6061 double-wall
FRONT HUB	Axis Expert Disc
REAR HUB	Axis Expert Disc
FRONT TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
REAR TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
SADDLE	Body Geometry Phenom Comp, hollow Cr-Mo rails, 143mm
SEATPOST	Specialized CG-R, FACT carbon, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
92417-3002	CROSSTRAIL EXPERT CARBON	BLUTNT/BBYBLU/NRDRED	S
92417-3003			M
92417-3004			L
92417-3005			XL

CROSSTRAIL ELITE CARBON



REDTNT/BBYBLU/CBRBLU



SILTNT/GRPH/NRDCCRED

The most important part of fitness is that you're following a path, not what kind of terrain lies beneath your tires. So to make sure that you can mix things up between the road and dirt, our CrossTrail Elite Carbon comes equipped with everything you need to split your time between the road and the trail.

- Working with our Body Geometry team, we designed a frame that strikes the optimal balance between comfort and efficiency. The FACT 9r carbon fiber keeps the bike ultra-light and efficient, while the rack, fender, and disc mounts give you an incredibly versatile package.
- An SR Suntour NCX fork w/ Fitness Brain technology features 60mm of coil-sprung travel that takes the sting out of bumpy terrain, while an integrated remote lockout is coupled with our Fitness Brain technology to promote more climbing and pedaling efficiency.
- Braking duties are handled by Tektro Flow Set Control hydraulic disc brakes to ensure effective, consistent, and reliable power through any kind of terrain or condition.

CROSSTRAIL CARBON				
SIZE	S	M	L	XL
Seat-Tube Length, B-B Center to Top (mm)	372	422	472	522
Top-Tube Length, Horizontal (mm)	571	586	604	624
B-B Drop (mm)	65	65	65	65
Chain-Stay Length (mm)	445	445	445	445
Seat-Tube Angle (deg)	73	73	73	73
Head-Tube Angle (deg)	70	70.5	70.5	70.5
Fork Rake (mm)	43	43	43	43
Trail (mm)	78	75	75	75
Front-Center (mm)	631	641	660	680
Wheelbase (mm)	1068	1078	1097	1118
Stand-Over Height (mm)	732	769	806	840
Head-Tube Length (mm)	110	125	145	165
Reach (mm)	390	400	412	426
Stack (mm)	592	608	627	646
Handlebar Width (mm)	660	660	660	660
Stem Length (mm)	60	75	75	90
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	350	350	350	350
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized FACT 9R carbon, Fitness Geometry, internal cable routing, integrated headset, flat mount disc, rack and Plug + Play fender mounts
FORK	SR Suntour NCX w/Specialized Fitness Brain technology, 60mm of travel, 1-1/8" steerer, 12mm thru-axle
STEM	Specialized Flowset, integrated, 3D forged alloy, 4-bolt, 12-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-buttressed alloy, 9-degree backsweep, 31.8mm
GRIPS	Body Geometry Flow Set Control Grips, lock-on
FRONT BRAKE	Tektro Flow Set Control, hydraulic disc, carbon brake lever, metal pads, post mount, 160mm rotor
REAR BRAKE	Tektro Flow Set Control, hydraulic disc, carbon brake lever, metal pads, post mount, 140mm rotor
FRONT DERAILLEUR	microSHIFT XCD, 31.8mm clamp, 10-/11-speed, MTB double
REAR DERAILLEUR	Shimano SLX, Shadow Plus design, SGS cage, 10-speed
SHIFT LEVERS	Flow Set Control, 10-speed
CASSETTE	Sunrace, 11-40t, 10-speed
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	FSA V-Drive, MegaEXO BB, 10-/11-speed, hollow forged 7075 aluminum, 170mm Q-factor, direct-mount
CHAINRINGS	44/32T w/chainguard
BOTTOM BRACKET	FSA MegaEVO
RIMS	700c Disc 6061 double wall pin joint
FRONT HUB	Axis Sport Disc
REAR HUB	Axis Sport Disc
SPOKES	Stainless, 14g w/self-locking threads
FRONT TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
REAR TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
SADDLE	Canopy Comp, hollow Cr-Mo rails
SEATPOST	Alloy, 2-bolt, micro-adjust, 25mm offset, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
92417-4202	CROSSTRAIL ELITE CARBON	REDTNT/BBYBLU/CBRBLU	S
92417-4203			M
92417-4204			L
92417-4205			XL
92417-4302	CROSSTRAIL ELITE CARBON	SILTNT/GRPH/NRDCCRED	S
92417-4303			M
92417-4304			L
92417-4305			XL

CROSSTRAIL ELITE



TARBLK/CHAR/LTTUR

You take your fitness journey seriously, and the last thing that you need is to feel restrained by the tools that get you there. That's why our Crosstrail Elite comes equipped with a suspension fork with our Fitness BRAIN technology for fast, efficient, and intuitive use over any surface.

- Working with our Body Geometry team, we designed a frame that strikes the optimal balance between comfort and efficiency. The A1 SL Premium aluminum construction pairs weight savings with rugged durability, while the rack, fender, and disc mounts give you an incredibly versatile package.
- An SR Suntour NCX fork w/ Fitness Brain technology features 60mm of coil-sprung travel that takes the sting out of bumpy terrain, while an integrated remote lockout is coupled with our Fitness Brain technology to promote more climbing and pedaling efficiency.
- Braking duties are handled by Tektro Flow Set Control hydraulic disc brakes to ensure effective, consistent, and reliable power through any kind of terrain or condition.

CROSSTRAIL A1 SL				
SIZE	S	M	L	XL
Seat-Tube Length, B-B Center to Top (mm)	400	450	500	550
Top-Tube Length, Horizontal (mm)	572	587	604	624
B-B Drop (mm)	65	65	65	65
Chain-Stay Length (mm)	445	445	445	445
Seat-Tube Angle (deg)	73	73	73	73
Head-Tube Angle (deg)	70	70.5	70.5	70.5
Fork Rake (mm)	42	42	42	42
Trail (mm)	87	84	84	84
Front-Center (mm)	630	641	655	680
Wheelbase (mm)	1067	1078	1096	1117
Stand-Over Height (mm)	740	776	813.3	850
Head-Tube Length (mm)	110	125	145	165
Reach (mm)	390	400	412	426
Stack (mm)	594	611	630	648
Handlebar Width (mm)	660	660	660	660
Stem Length (mm)	60	75	75	90
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	350	350	350	350
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 SL Premium Aluminum, Fitness Geometry, fully-manipulated butted tubing, internal cable routing, flat mount disc, rack & Plug + Play mounts
HANDLEBARS	Specialized, double-buttressed alloy, 9-degree backsweep, 31.8mm
GRIPS	Body Geometry Flow Set Control Grips, lock-on
FRONT BRAKE	Tektro Flow Set Control, hydraulic disc, carbon brake lever, metal pads, post mount, 160mm rotor
REAR BRAKE	Tektro Flow Set Control, hydraulic disc, carbon brake lever, metal pads, post mount, 140mm rotor
FRONT DERAILLEUR	microSHIFT XCD, 31.8mm clamp, 10-/11-speed, MTB double
REAR DERAILLEUR	Shimano SLX, Shadow Plus design, SGS cage, 10-speed
SHIFT LEVERS	Flow Set Control, 10-speed
CASSETTE	Sunrace, 11-40t, 10-speed
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	FSA V-Drive, MegaEXO BB, 10-/11-speed, hollow forged 7075 aluminum, 170mm Q-factor, direct-mount
CHAINRINGS	44/32T w/chainguard
BOTTOM BRACKET	FSA MegaEVO
RIMS	700c Disc 6061 double wall pin joint
FRONT HUB	Axis Sport Disc
REAR HUB	Axis Sport Disc
SPOKES	Stainless, 14g w/self-locking threads
FRONT TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
REAR TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
SADDLE	Canopy Comp, hollow Cr-Mo rails

PART NO.	DESCRIPTION	COLOR	SIZE
82417-4102	CROSSTRAIL ELITE	TARBLK/CHAR/LTTUR	S
82417-4103			M
82417-4104			L
82417-4105			XL

CROSSTRAIL SPORT



NRDCRED/NVY/FLKSIL



RFPNK/NRBLK/HYP

Your fitness is important—that's why our Crosstrail Sport focuses on seamlessly blending comfort, versatility, and efficiency. It comes equipped with a suspension fork with our Fitness BRAIN technology that can tell the difference between pedaling inputs and trail bumps, so you won't be wasting any energy on your climbs.

- Working with our Body Geometry team, we designed a frame that strikes the optimal balance between comfort and efficiency. The A1 SL Premium aluminum construction pairs weight savings with rugged durability, while the rack, fender, and disc mounts give you an incredibly versatile package.
- An SR Suntour NEX fork w/ Fitness Brain technology features 55mm of coil-sprung travel that takes the sting out of bumpy terrain, while our Fitness Brain technology promotes more climbing and pedaling efficiency.
- Braking duties are handled by Tektro Vela hydraulic disc brakes to ensure effective, consistent, and reliable power through any kind of terrain or condition.

CROSSTRAIL A1 SL				
SIZE	S	M	L	XL
Seat-Tube Length, B-B Center to Top (mm)	400	450	500	550
Top-Tube Length, Horizontal (mm)	572	587	604	624
B-B Drop (mm)	65	65	65	65
Chain-Stay Length (mm)	445	445	445	445
Seat-Tube Angle (deg)	73	73	73	73
Head-Tube Angle (deg)	70	70.5	70.5	70.5
Fork Rake (mm)	42	42	42	42
Trail (mm)	87	84	84	84
Front-Center (mm)	630	641	655	680
Wheelbase (mm)	1067	1078	1096	1117
Stand-Over Height (mm)	740	776	813.3	850
Head-Tube Length (mm)	110	125	145	165
Reach (mm)	390	400	412	426
Stack (mm)	594	611	630	648
Handlebar Width (mm)	660	660	660	660
Stem Length (mm)	60	70	80	90
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	350	350	350	350
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 SL Premium Aluminum, Fitness Geometry, fully-manipulated butted tubing, internal cable routing, flat mount disc, rack & Plug + Play mounts
STEM	3D forged aluminum, 7-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-butt alloy, 9-degree backsweep, 31.8mm
GRIPS	Body Geometry Flow Set Control Grips, lock-on
FRONT BRAKE	Tektro Vela, hydraulic disc, post mount, organic pads, 160mm rotor
REAR BRAKE	Tektro Vela, hydraulic disc, flat mount, organic pads, 160mm rotor
FRONT DERAILLEUR	microSHIFT, 31.8mm clamp, 9-speed, MTB double
REAR DERAILLEUR	Shimano Alivio, Shadow design, SGS cage, 9-speed
SHIFT LEVERS	microSHIFT MTB, 9-speed
CASSETTE	Sunrace, 9-speed, 11-36t
CRANKSET	FSA Alpha Drive, forged 6061 aluminum
CHAINRINGS	44/32T w/chainguard
BOTTOM BRACKET	FSA BB-7420ST
RIMS	700c disc, 6061 aluminum double-wall
FRONT HUB	Specialized Center Lock, loose ball bearings, 32h, 9mm QR
REAR HUB	Shimano Center Lock disc, 8-/9-/10-speed freehub, 135mm axle, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
REAR TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
SADDLE	Canopy Sport, steel rails

PART NO.	DESCRIPTION	COLOR	SIZE
82417-6002	CROSSTRAIL SPORT	NRDCRED/NVY/FLKSIL	S
82417-6003			M
82417-6004			L
82417-6005			XL
82417-6102	CROSSTRAIL SPORT	RFPNK/NRBLK/HYP	S
82417-6103			M
82417-6104			L
82417-6105			XL

CROSSTRAIL DISC



CHAR/CNDYRED/TI



NVY/HYP/NRDCRED



OAKGRN/SPR/PDRGRN

Your fitness is important—that's why our Crosstrail Disc focuses on seamlessly blending comfort, versatility, and efficiency. It comes equipped with a suspension fork with our Fitness BRAIN technology that can tell the difference between pedaling inputs and trail bumps, so you won't be wasting any energy on your climbs.

- Working with our Body Geometry team, we designed a frame that strikes the optimal balance between comfort and efficiency. The A1 SL Premium aluminum construction pairs weight savings with rugged durability, while the rack, fender, and disc mounts give you an incredibly versatile package.
- Enjoy greater control over varying terrain with a custom, easy-adjust, Multi-Circuit Damping fork with 60mm of travel that's tuned for the trail.
- Braking duties are handled by Tektro hydraulic disc brakes to ensure effective, consistent, and reliable power through any kind of terrain or condition.

CROSSTRAIL A1 SL				
SIZE	S	M	L	XL
Seat-Tube Length, B-B Center to Top (mm)	400	450	500	550
Top-Tube Length, Horizontal (mm)	572	587	604	624
B-B Drop (mm)	65	65	65	65
Chain-Stay Length (mm)	445	445	445	445
Seat-Tube Angle (deg)	73	73	73	73
Head-Tube Angle (deg)	70	70.5	70.5	70.5
Fork Rake (mm)	42	42	42	42
Trail (mm)	87	84	84	84
Front-Center (mm)	630	641	655	680
Wheelbase (mm)	1067	1078	1096	1117
Stand-Over Height (mm)	740	776	813.3	850
Head-Tube Length (mm)	110	125	145	165
Reach (mm)	390	400	412	426
Stack (mm)	594	611	630	648
Handlebar Width (mm)	660	660	660	660
Stem Length (mm)	60	70	80	90
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	350	350	350	350
Crank Length (mm)	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 SL Premium Aluminum, Fitness Geometry, fully-manipulated butted tubing, internal cable routing, flat mount disc, rack & Plug + Play mounts
STEM	3D forged aluminum, 7-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-buttressed alloy, 9-degree backsweep, 31.8mm
GRIPS	Body Geometry Flow Set Control Grips, lock-on
FRONT BRAKE	Tektro, hydraulic disc, post mount, organic pads, 160mm rotor
REAR BRAKE	Tektro, hydraulic disc, flat mount, organic pads, 160mm rotor
FRONT DERAILLEUR	Shimano Tourney, top swing, for 7-/8-speed 31.8mm clamp
REAR DERAILLEUR	Shimano Altus, 8-speed
SHIFT LEVERS	Shimano Altus, 8-speed
CASSETTE	Sunrace, 8-speed, 11-34t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Stout, forged alloy w/chainguard
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	700c disc, 6061 aluminum double-wall
FRONT HUB	Specialized disc, double-sealed, loose ball bearings, 9mm QR
REAR HUB	Specialized disc, loose ball bearings, for Shimano 8-/9-speed cassettes, 9mm QR
SPOKES	Stainless, 14g
FRONT TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
REAR TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
SADDLE	Canopy Sport, steel rails

PART NO.	DESCRIPTION	COLOR	SIZE
82417-7002	CROSSTRAIL DISC	CHAR/CNDYRED/TI	S
82417-7003			M
82417-7004			L
82417-7005			XL
82417-7102	CROSSTRAIL DISC	NVY/HYP/NRDCRED	S
82417-7103			M
82417-7104			L
82417-7105			XL
82417-7202	CROSSTRAIL DISC	OAKGRN/SPR/PDRGRN	S
82417-7203			M
82417-7204			L
82417-7205			XL

CROSSTRAIL



CLGRY/LTTUR/CRL



TARBLK/CBRBLU/BBYBLU

The key to hitting your fitness goals is to mix things up a bit. That's why our Crosstrail comes equipped with a custom suspension fork with a lockout feature for fast and efficient use over any surface.

- Working with our Body Geometry team, we designed a frame that strikes the optimal balance between comfort and efficiency. The A1 SL Premium aluminum construction pairs weight savings with rugged durability, while the rack, fender, and disc mounts give you an incredibly versatile package.
- Enjoy greater control over varying terrain with a custom, easy-adjust, Multi-Circuit Damping fork with 60mm of travel that's tuned for the trail.
- V-brakes provide reliable stopping power and hassle-free maintenance, so you'll be able to spend more time riding and less time bleeding those brakes.

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 SL Premium Aluminum, Fitness Geometry, rack & Plug + Play mounts
STEM	3D forged aluminum, 7-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, double-butt alloy, 9-degree backsweep, 31.8mm
GRIPS	Body Geometry Flow Set Control Grips, lock-on
FRONT DERAILLEUR	Shimano Tourney, top swing, for 7-/8-speed 31.8mm clamp
REAR DERAILLEUR	Shimano Altus, 8-speed
SHIFT LEVERS	Shimano EF500, EZ Fire Plus, 8-speed
CASSETTE	Sunrace, 8-speed, 11-34t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Stout, forged alloy w/chainguard
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	700c, 6061 aluminum double-wall
FRONT HUB	Specialized, loose ball bearings, 32h, 9mm QR
REAR HUB	Specialized, loose ball bearings, 8-/9-speed cassette body, 32h, 9mm QR
SPOKES	Stainless, 14g
FRONT TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
REAR TIRE	Trigger Sport Reflect, 700x38mm, 60TPI, wire bead
SADDLE	Canopy Sport, steel rails

CROSSTRAIL A1				
SIZE	S	M	L	XL
Seat-Tube Length, B-B Center to Top (mm)	400	450	500	550
Top-Tube Length, Horizontal (mm)	572	587	604	624
B-B Drop (mm)	65	65	65	65
Chain-Stay Length (mm)	445	445	445	445
Seat-Tube Angle (deg)	73	73	73	73
Head-Tube Angle (deg)	70	70.5	70.5	70.5
Fork Rake (mm)	42	42	42	42
Trail (mm)	87	84	84	84
Front-Center (mm)	630	641	655	680
Wheelbase (mm)	1067	1078	1096	1117
Stand-Over Height (mm)	740	776	813.3	850
Head-Tube Length (mm)	110	125	145	165
Reach (mm)	390	400	412	426
Stack (mm)	594	611	630	648
Handlebar Width (mm)	660	660	660	660
Stem Length (mm)	60	70	80	90
Saddle Width (mm)	155	155	155	155
Seat Post Length (mm)	350	350	350	350
Crank Length (mm)	170	175	175	175

PART NO.	DESCRIPTION	COLOR	SIZE
82417-7302	CROSSTRAIL	CLGRY/LTTUR/CRL	S
82417-7303			M
82417-7304			L
82417-7305			XL
82417-7502	CROSSTRAIL	TARBLK/CBRBLU/BBYBLU	S
82417-7503			M
82417-7504			L
82417-7505			XL

CROSSROADS ELITE



BLKCP/BLK/RKTRED

If you're looking to take your fitness to the next level, look no further than the Crossroads Elite. It has everything you need to step your game up, from a lightweight and durable aluminum frame, a carbon fiber fork, and an enviable list of components that are purpose-built to last.

- The sturdy A1 Premium Aluminum frame combined with Specialized FACT carbon, straight blade fork delivers reliable handling for a confident ride.
- Durable and wide 700x45mm Specialized Borough Armadillo tires provide a stable ride on dirt paths and roads, and feature super-tough Armadillo puncture protection.
- The Body Geometry Comfort Gel saddle provides comfort and support while reducing soft tissue pressure.

CROSSROADS ELITE					
SIZE	S	M	L	XL	XXL
Stack (mm)	578	611	625	639	658
Reach (mm)	405	405	415	425	433
Head-Tube Length (mm)	165	195	210	225	245
Head-Tube Angle (deg)	69.5	70.5	70.5	70.5	70.5
B-B Height (mm)	292	292	292	292	292
B-B Drop (mm)	65	65	65	65	65
Trail (mm)	79	72	72	72	72
Fork Length (full) (mm)	400	400	400	400	400
Fork Rake/Offset (mm)	51	51	51	51	51
Front-Center (mm)	655	656	671	685	700
Chain-Stay Length (mm)	465	465	465	465	465
Wheelbase (mm)	1112	1113	1128	1143	1157
Top-Tube Length (horizontal) (mm)	604	615	630	645	660
Bike Stand-Over Height (mm)	717	755	790	832	879
Seat-Tube Length (mm)	385	430	480	540	610
Seat-Tube Angle (deg)	71	71	71	71	71
Handlebar Width (mm)	645	645	685	685	685
Stem Length (mm)	75	75	95	95	95
Crank Length (mm)	170	170	175	175	175
Seatpost Length (mm)	300	350	350	350	350

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Fitness Geometry, formed tubes, fender/rack mounts
FORK	Specialized FACT carbon, straight blades, aluminum steerer/crown, fender/rack mounts
HEADSET	Integrated loose ball bearings
STEM	Specialized, 3D forged alloy, 25-degree rise w/integrated top cap, 31.8mm clamp
HANDLEBARS	Specialized, alloy, 15-degree backsweep, 4-degree upsweep, 60mm rise, 31.8mm
TAPE	Specialized Body Geometry Contour, Kraton, lock-on
FRONT BRAKE	V-brake, alloy, linear pull
REAR BRAKE	V-brake, alloy, linear pull
BRAKE LEVERS	Alloy, Kraton pad
FRONT DERAILLEUR	Shimano Acera, 9-speed, top swing, dual pull
REAR DERAILLEUR	Shimano Acera, 9-speed
SHIFT LEVERS	Shimano Acera RapidFire Plus, SL type, 9-speed w/optical display
CASSETTE	Shimano, 9-speed, 11-34t
CHAIN	KMC X9, 9-speed w/reusable MissingLink
CRANKSET	Forged Alloy, 48/36/26T w/chainguard
CHAINRINGS	48/36/26T
BOTTOM BRACKET	Square taper, cartridge bearings
RIMS	700c, alloy, double-wall, CNC sidewalls, pin joint, 30mm, 28h
FRONT HUB	Double-sealed, loose ball, QR, 28h
REAR HUB	Specialized, double-sealed, QR, 28h
SPOKES	Stainless, 14g, black
FRONT TIRE	Specialized Borough Armadillo, 60TPI, 700x45mm
REAR TIRE	Specialized Borough Armadillo, 60TPI, 700x45mm
SADDLE	Body Geometry Comfort Gel, steel rails, 200mm
SEATPOST	Suspension Plus, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
82116-4002	CROSSROADS ELITE	BLKCP/BLK/RKTRED	S
82116-4003			M
82116-4004			L
82116-4005			XL
82116-4006			XXL

CROSSROADS ELITE STEP THROUGH



MRNBLU/TUR/CNDYRED

If you're looking to take your fitness to the next level, look no further than the Crossroads Elite Step Through. It has everything you need to step your game up, from a lightweight and durable aluminum frame, a carbon fiber fork, and a geometry that makes getting on and off the bike as easy as can be.

- The sturdy A1 Premium Aluminum frame combined with Specialized FACT carbon, straight blade fork delivers reliable handling for a confident ride.
- Durable and wide 700x45mm Specialized Borough Armadillo tires provide a stable ride on dirt paths and roads, and feature super-tough Armadillo puncture protection.
- The Body Geometry Comfort Gel saddle provides comfort and support while reducing soft tissue pressure.

CROSSROADS ELITE STEP THROUGH				
SIZE	XS	S	M	L
Stack (mm)	548	559	592	606
Reach (mm)	364	375	375	385
Head-Tube Length (mm)	135	145	175	190
Head-Tube Angle (deg)	69	69.5	70.5	70.5
B-B Height (mm)	292	292	292	292
B-B Drop (mm)	65	65	65	65
Trail (mm)	82	79	72	72
Fork Length (full) (mm)	400	400	400	400
Fork Rake/Offset (mm)	51	51	51	51
Front-Center (mm)	608	618	619	634
Chain-Stay Length (mm)	465	465	465	465
Wheelbase (mm)	1064	1075	1076	1091
Top-Tube Length (horizontal) (mm)	553	568	579	594
Bike Stand-Over Height (mm)	572	581	581	600
Seat-Tube Length (mm)	370	385	430	480
Seat-Tube Angle (deg)	71	71	71	71
Handlebar Width (mm)	645	645	645	645
Stem Length (mm)	75	75	95	95
Crank Length (mm)	170	170	170	170
Seatpost Length (mm)	300	300	350	350

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Fitness Geometry, step through, formed tubes, fender/rack mounts
FORK	Specialized FACT carbon, straight blades, aluminum steerer/crown, fender/rack mounts
HEADSET	Integrated loose ball bearings
STEM	Specialized, 3D forged alloy, 25-degree rise w/integrated top cap, 31.8mm clamp
HANDLEBARS	Specialized, alloy, 15-degree backsweep, 4-degree upsweep, 60mm rise, 31.8mm
TAPE	Specialized Body Geometry Contour, Kraton, lock-on
FRONT BRAKE	V-brake, alloy, linear pull
REAR BRAKE	V-brake, alloy, linear pull
BRAKE LEVERS	Alloy, Kraton pad
FRONT DERAILLEUR	Shimano Acera, 9-speed, top swing, dual pull
REAR DERAILLEUR	Shimano Acera, 9-speed
SHIFT LEVERS	Shimano Acera RapidFire Plus, SL type, 9-speed w/optical display
CASSETTE	Shimano, 9-speed, 11-34t
CHAIN	KMC X9, 9-speed w/reusable MissingLink
CRANKSET	Forged Alloy, 48/36/26T w/chainguard
CHAINRINGS	48/36/26T
BOTTOM BRACKET	Square taper, cartridge bearings
RIMS	700c, alloy, double-wall, CNC sidewalls, pin joint, 30mm, 28h
FRONT HUB	Double-sealed, loose ball, QR, 28h
REAR HUB	Specialized, double-sealed, QR, 28h
SPOKES	Stainless, 14g
FRONT TIRE	Specialized Borough Armadillo, 60TPI, 700x45mm
REAR TIRE	Specialized Borough Armadillo, 60TPI, 700x45mm
SADDLE	Body Geometry Women's Comfort Gel, steel rails, 200mm
SEATPOST	Suspension Plus, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
82116-4101	CROSSROADS ELITE STEP THROUGH	MRNBLU/TUR/CNDYRED	XS
82116-4102			S
82116-4103			M
82116-4104			L

CROSSROADS SPORT



GLDORG/BLK/MXORG



GRPH/BLK/BLU

Built with a component package that you can rely on, the Crossroads Sport is the perfect bike to add to your life. It's purpose-built to help you stay fit and healthy, and its wide 45mm tires deliver confident handling for when you're speeding along the bike path.

- Go faster with less effort with the lightweight and sturdy A1 Premium Aluminum frame.
- Durable and wide 700x45mm Borough tires provide a stable, traction-filled ride on dirt paths and roads alike, while our BlackBelt puncture protection works to nearly eliminate the threat of flats at the hands of road debris and thorns.
- The Body Geometry Comfort saddle provides comfort and support over the long haul, while also reducing soft tissue pressure.

CROSSROADS					
SIZE	S	M	L	XL	XXL
Stack (mm)	577	611	625	639	658
Reach (mm)	401	405	415	425	433
Head-Tube Length (mm)	145	175	190	205	225
Head-Tube Angle (deg)	69.5	70.5	70.5	70.5	70.5
B-B Height (mm)	291	291	291	291	291
B-B Drop (mm)	65	65	65	65	65
Trail (mm)	74	72	72	72	72
Fork Length (full) (mm)	410	410	410	410	410
Fork Rake/Offset (mm)	55	51	51	51	51
Front-Center (mm)	655	655	670	685	701
Chain-Stay Length (mm)	465	465	465	465	465
Wheelbase (mm)	1112	1113	1128	1143	1158
Top-Tube Length (horizontal) (mm)	600	615	630	645	660
Bike Stand-Over Height (mm)	718.3	755.5	790.5	831.5	880
Seat-Tube Length (mm)	385	430	480	540	610
Seat-Tube Angle (deg)	71	71	71	71	71
Handlebar Width (mm)	645	645	685	685	685
Stem Length (mm)	85	85	85	85	85
Saddle Width (mm)	200	200	200	200	200
Seat Post Length (mm)	300	350	350	350	350
Crank Length (mm)	165	170	175	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Fitness Geometry, formed tubes, fender/rack mounts
FORK	Steel, curved blades, fender/rack mounts
STEM	Quill, adjustable, alloy
HANDLEBARS	Specialized, alloy, 15-degree backsweep, 4-degree upsweep, 60mm rise, 645/685mm width, 25.4mm
TAPE	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	V-brake, linear pull
REAR BRAKE	V-brake, linear pull
FRONT DERAILLEUR	Shimano Altus, 31.8mm adapter, top-swing, 8-speed
REAR DERAILLEUR	Shimano Altus, 8-speed
SHIFT LEVERS	Shimano, EZ-Fire Plus, 8-speed
CASSETTE	Shimano, 8-speed, 11-32t
CHAIN	KMC Z7, 8-speed w/reusable MissingLink
CRANKSET	Shimano Altus triple crankset
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	Specialized, 700x45mm tube, Presta valve
FRONT HUB	Specialized V-brake, alloy, loose ball bearings, 9mm, QR
REAR HUB	Specialized, 8-/9-speed cassette body, QR
SPOKES	Stainless, 14g
FRONT TIRE	Borough, 700x45mm, 60TPI, BlackBelt protection
REAR TIRE	Borough, 700x45mm, 60TPI, BlackBelt protection
SADDLE	Body Geometry Comfort, steel rails, 200mm
SEATPOST	Dual-Bolt Diecast Head, AL6061 Post, Spring Suspension

PART NO.	DESCRIPTION	COLOR	SIZE
B2116-6202	CROSSROADS SPORT	GLDORG/BLK/MXORG	S
B2116-6203			M
B2116-6204			L
B2116-6205			XL
B2116-6206			XXL
B2115-6102	CROSSROADS SPORT	GRPH/BLK/BLU	S
B2115-6103			M
B2115-6104			L
B2115-6105			XL
B2115-6106			XXL

CROSSROADS SPORT STEP THROUGH



WHT/SIL/PNK



LTBLU/SIL/WHT

Built with a component package that you can rely on, the Crossroads Sport Step Through is the perfect bike to add to your life. It's purpose-built to help you stay fit and healthy, and its wide 45mm tires and step through design deliver the utmost in confidence.

- Go faster with less effort with the lightweight and sturdy A1 Premium Aluminum frame, while the step through design makes getting on and off the bike a breeze.
- Durable and wide 700x45mm Borough tires provide a stable, traction-filled ride on dirt paths and roads alike, while our BlackBelt puncture protection works to nearly eliminate the threat of flats at the hands of road debris and thorns.
- The Body Geometry Comfort saddle provides comfort and support over the long haul, while also reducing soft tissue pressure.

CROSSROADS STEP THROUGH

SIZE	XS	S	M	L
Stack (mm)	566	577	611	625
Reach (mm)	360	371	375	385
Head-Tube Length (mm)	135	145	175	190
Head-Tube Angle (deg)	69	69.5	70.5	70.5
B-B Height (mm)	291	291	291	291
B-B Drop (mm)	65	65	65	65
Trail (mm)	78	74	72	72
Fork Length (full) (mm)	410	410	410	410
Fork Rake/Offset (mm)	55	55	51	51
Front-Center (mm)	615	625	625	641
Chain-Stay Length (mm)	465	465	465	465
Wheelbase (mm)	1072	1082	1083	1098
Top-Tube Length (horizontal) (mm)	555	570	585	600
Bike Stand-Over Height (mm)	592.3	598.3	613.5	623
Seat-Tube Length (mm)	370	385	430	480
Seat-Tube Angle (deg)	71	71	71	71
Handlebar Width (mm)	645	645	645	645
Stem Length (mm)	85	85	85	85
Saddle Width (mm)	200	200	200	200
Seat Post Length (mm)	300	350	350	350
Crank Length (mm)	170	170	170	170

SPECS

All specs are subject to change without notice.

FRAME	Specialized A1 Premium Aluminum, Fitness Geometry, step through, formed tubes, fender/rack mounts
FORK	Steel, curved blades, fender/rack mounts
STEM	Quill, adjustable, alloy
HANDLEBARS	Specialized, alloy, 15-degree backsweep, 4-degree upsweep, 60mm rise, 645/685mm width, 25.4mm
TAPE	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	V-brake, linear pull
REAR BRAKE	V-brake, linear pull
FRONT DERAILLEUR	Shimano Altus, 31.8mm adapter, top-swing, 8-speed
REAR DERAILLEUR	Shimano Altus, 7-/8-speed
SHIFT LEVERS	Shimano EF510, EZ Fire Plus, 8-speed
CASSETTE	Shimano, 8-speed, 11-32t
CHAIN	KMC Z7, 8-speed w/reusable MissingLink
CRANKSET	Shimano Altus triple
CHAINRINGS	48/38/28T
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	700c, 6061 aluminum double-wall
FRONT HUB	Specialized V-brake, alloy, loose ball bearings, 9mm, QR
REAR HUB	Specialized, 8-/9-speed cassette body, QR
SPOKES	Stainless, 14g
FRONT TIRE	Borough, 700x45mm, 60TPI, BlackBelt protection
REAR TIRE	Borough, 700x45mm, 60TPI, BlackBelt protection
SADDLE	Body Geometry Comfort, steel rails, 200mm
SEATPOST	Dual-Bolt Diecast Head, AL6061 Post, Spring Suspension

PART NO.	DESCRIPTION	COLOR	SIZE
B2115-6501	CROSSROADS SPORT STEP THROUGH	WHT/SIL/PNK	XS
B2115-6502			S
B2115-6503			M
B2115-6504			L
B2116-6101	CROSSROADS SPORT STEP THROUGH	LTBLU/SIL/WHT	XS
B2116-6102			S
B2116-6103			M
B2116-6104			L



BLU/CL GRY/WHT



BLK/LT SIL

We want the Crossroads to be your companion along the road, or dirt path, to the fitter, better, and happier you. It's a tall order, but we're up for the challenge. To start, we included wide 45mm tires for confident handling as you're speeding along the bike path, and then came a hand-selected component package that's nothing short of reliable.

- Go faster with less effort with the lightweight and sturdy A1 Premium Aluminum frame.
- Durable and wide 700x45mm Borough tires provide a stable, traction-filled ride on dirt paths and roads alike, while our BlackBelt puncture protection works to nearly eliminate the threat of flats at the hands of road debris and thorns.
- The Body Geometry Comfort saddle provides comfort and support over the long haul, while also reducing soft tissue pressure.

CROSSROADS					
SIZE	S	M	L	XL	XXL
Stack (mm)	577	611	625	639	658
Reach (mm)	401	405	415	425	433
Head-Tube Length (mm)	145	175	190	205	225
Head-Tube Angle (deg)	69.5	70.5	70.5	70.5	70.5
B-B Height (mm)	291	291	291	291	291
B-B Drop (mm)	65	65	65	65	65
Trail (mm)	74	72	72	72	72
Fork Length (full) (mm)	410	410	410	410	410
Fork Rake/Offset (mm)	55	51	51	51	51
Front-Center (mm)	655	655	670	685	701
Chain-Stay Length (mm)	465	465	465	465	465
Wheelbase (mm)	1112	1113	1128	1143	1158
Top-Tube Length (horizontal) (mm)	600	615	630	645	660
Bike Stand-Over Height (mm)	718.3	755.5	790.5	831.5	880
Seat-Tube Length (mm)	385	430	480	540	610
Seat-Tube Angle (deg)	71	71	71	71	71
Handlebar Width (mm)	645	645	685	685	685
Stem Length (mm)	85	85	85	85	85
Saddle Width (mm)	200	200	200	200	200
Seat Post Length (mm)	300	350	350	350	350
Crank Length (mm)	170	170	170	170	170

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Fitness Geometry, formed tubes, fender/rack mounts
FORK	Steel, curved blades, fender/rack mounts
STEM	Quill, adjustable, alloy
HANDLEBARS	Specialized, alloy, 15-degree backsweep, 4-degree upsweep, 60mm rise, 645/685mm width, 25.4mm
TAPE	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	V-brake, linear pull
REAR BRAKE	V-brake, linear pull
FRONT DERAILLEUR	Shimano Altus, 31.8mm adapter, top-swing, 8-speed
REAR DERAILLEUR	Shimano Tourney, 7 speed
SHIFT LEVERS	Shimano Tourney, Revo-style, 7-speed
CASSETTE	Shimano Tourney freewheel, 7-speed, 14-34t
CHAIN	KMC Z7, 8-speed w/reusable MissingLink
CRANKSET	Shimano Altus triple crankset w/chainguard
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	700c, 6061 aluminum double-wall
FRONT HUB	Specialized V-brake, alloy, loose ball bearings, 9mm, QR
REAR HUB	Specialized V-brake, loose ball bearings, QR, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Borough, 700x45mm, 60TPI, BlackBelt protection
REAR TIRE	Borough, 700x45mm, 60TPI, BlackBelt protection
SADDLE	Body Geometry Comfort, steel rails, 200mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
B2115-7502	CROSSROADS	BLU/CL GRY/WHT	S
B2115-7503			M
B2115-7504			L
B2115-7505			XL
B2115-7506			XXL
B2115-7102	CROSSROADS	BLK/LT SIL	S
B2115-7103			M
B2115-7104			L
B2115-7105			XL
B2115-7106			XXL

CROSSROADS STEP THROUGH



DPNDGO/TUR/BRTPNK



EM GRN/SIL/WHT

We want the Crossroads to be your companion along the road, or dirt path, to the fitter, better, and happier you. It's a tall order, but we're up for the challenge. To start, we included wide 45mm tires for confident handling as you're speeding along the bike path, and then came a hand-selected component package that's nothing short of reliable.

- Go faster with less effort with the lightweight and sturdy A1 Premium Aluminum frame, while the step through design makes getting on and off the bike a breeze.
- Durable and wide 700x45mm Borough tires provide a stable, traction-filled ride on dirt paths and roads alike, while our BlackBelt puncture protection works to nearly eliminate the threat of flats at the hands of road debris and thorns.
- The Body Geometry Comfort saddle provides comfort and support over the long haul, while also reducing soft tissue pressure.

CROSSROADS STEP THROUGH

SIZE	XS	S	M	L
Stack (mm)	566	577	611	625
Reach (mm)	360	371	375	385
Head-Tube Length (mm)	135	145	175	190
Head-Tube Angle (deg)	69	69.5	70.5	70.5
B-B Height (mm)	291	291	291	291
B-B Drop (mm)	65	65	65	65
Trail (mm)	78	74	72	72
Fork Length (full) (mm)	410	410	410	410
Fork Rake/Offset (mm)	55	55	51	51
Front-Center (mm)	615	625	625	641
Chain-Stay Length (mm)	465	465	465	465
Wheelbase (mm)	1072	1082	1083	1098
Top-Tube Length (horizontal) (mm)	555	570	585	600
Bike Stand-Over Height (mm)	592.3	598.3	613.5	623
Seat-Tube Length (mm)	370	385	430	480
Seat-Tube Angle (deg)	71	71	71	71
Handlebar Width (mm)	645	645	645	645
Stem Length (mm)	85	85	85	85
Saddle Width (mm)	200	200	200	200
Seat Post Length (mm)	300	350	350	350
Crank Length (mm)	170	170	170	170

SPECS

All specs are subject to change without notice.

FRAME	Specialized A1 Premium Aluminum, Fitness Geometry, step through, formed tubes, fender/rack mounts
FORK	Steel, curved blades, fender/rack mounts
STEM	Quill, adjustable, alloy
HANDLEBARS	Specialized, alloy, 15-degree backsweep, 4-degree upsweep, 60mm rise, 645/685mm width, 25.4mm
TAPE	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	V-brake, linear pull
REAR BRAKE	V-brake, linear pull
FRONT DERAILLEUR	Shimano Altus, 31.8mm adapter, top-swing, 8-speed
REAR DERAILLEUR	Shimano Tourney, 7-speed
SHIFT LEVERS	Shimano Tourney, Revo-style, 7-speed
CASSETTE	Shimano Tourney freewheel, 7-speed, 14-34t
CHAIN	KMC Z7, 8-speed w/reusable MissingLink
CRANKSET	Shimano Altus, 48/38/28T w/chainguard
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	700c, 6061 aluminum double-wall
FRONT HUB	Specialized V-brake, alloy, loose ball bearings, 9mm, QR
REAR HUB	Specialized V-brake, loose ball bearings, QR, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Borough, 700x45mm, 60TPI, BlackBelt protection
REAR TIRE	Borough, 700x45mm, 60TPI, BlackBelt protection
SADDLE	Body Geometry Comfort, steel rails, 200mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
B2116-7201	CROSSROADS STEP THROUGH	DPNDGO/TUR/BRTPNK	XS
B2116-7202			S
B2116-7203			M
B2116-7204			L
B2115-7301	CROSSROADS STEP THROUGH	EM GRN/SIL/WHT	XS
B2115-7302			S
B2115-7303			M
B2115-7304			L

ALIBI SPORT EQ



CHAR/BLK

Are you ready to ride? No need to pump the tires or do any grimy maintenance—the Alibi has you covered with puncture-proof tires and an anti-rust chain. Combine that with gearing that will get you over anything and supportive Body Geometry contact points, and you'll never need an "excuse" to ride the Alibi.

- The hard-working & sturdy A1 Premium Aluminum frame is light and durable, and it also features rack and fender mounts for easy portage and dry riding in wet conditions. You'll also find that it's engineered with our Fitness Geometry, meaning that you'll go fast with maximum efficiency, but without the discomfort of an aggressive ride position. After all, the more comfortable you are, the longer you'll ride.
- The Alibi's anti-rust chain keeps rolling smoothly, even after a couple of confrontations with the elements, so you can spend more time riding and less time fixing.
- There's never a good time for a puncture, which is why the Nimbus Airless tires feature a puncture-proof core, offering incredible traction without the hassle of changing a tube.

ALIBI				
SIZE	S	M	L	XL
Seat-Tube Length, B-B Center to Top (mm)	390	439	476	532
Top-Tube Length, Horizontal (mm)	585	607	628	652
B-B Drop (mm)	70	70	65	65
Chain-Stay Length (mm)	445	445	445	445
Seat-Tube Angle (deg)	73	73	73	73
Head-Tube Angle (deg)	70	70	70	70
Fork Rake (mm)	51	51	51	51
Trail (mm)	75	75	75	75
Front-Center (mm)	661	684	707	732
Wheelbase (mm)	1096	1119	1144	1169
Stand-Over Height (mm)	714	766	790	834.5
Head-Tube Length (mm)	160	185	210	240
Reach (mm)	405	420	435	450
Stack (mm)	575	599	617	645
Handlebar Width (mm)	640	640	640	640
Stem Length (mm)	60	70	90	100
Saddle Width (mm)	175	175	175	175
Seat Post Length (mm)	350	350	350	350
Crank Length (mm)	165	170	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, formed tubes, fender/rack mounts
FORK	Specialized A1 Premium Aluminum, Cr-Mo steerer, fender/rack mounts
STEM	Forged Alloy, 17-degree rise, 31.8mm clamp
HANDLEBARS	640mm width, 15-degree backsweep, 55mm drop, 31.8mm
TAPE	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	V-brake, linear pull
REAR BRAKE	V-brake, linear pull
FRONT DERAILLEUR	Shimano Altus, 31.8mm adapter, top-swing, 8-speed
REAR DERAILLEUR	Shimano Altus, 8-speed
SHIFT LEVERS	Shimano EF500, EZ Fire Plus, 8-speed
CASSETTE	Shimano, 8-speed, 11-34t
CHAIN	KMC X8 EPT, 8-speed w/reusable MissingLink
CRANKSET	Shimano FC-TY501 triple, 6-/7-/8-speed
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
FRONT WHEEL	Alibi V-brake
REAR WHEEL	Alibi V-brake
FRONT TIRE	Nimbus Airless, 700x38mm
REAR TIRE	Nimbus Airless, 700x38mm
SADDLE	Milano, steel rails, 175mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
B6617-6202	ALIBI SPORT EQ	CHAR/BLK	SM
B6617-6203			MD
B6617-6204			LG
B6617-6205			XL

ALIBI SPORT EQ STEP THROUGH



TPE/LTTUR/BLK

Are you ready to ride? No need to pump the tires or do any grimy maintenance—the Alibi Sport Step Through has you covered with puncture-proof tires and an anti-rust chain.

- The hard-working & sturdy A1 Premium Aluminum frame is light and durable, and it also features rack and fender mounts for easy portage and dry riding in wet conditions. You'll also find that it's engineered with our Fitness Geometry, meaning that you'll go fast with maximum efficiency, but without the discomfort of an aggressive ride position. After all, the more comfortable you are, the longer you'll ride.
- The Alibi's anti-rust chain keeps rolling smoothly, even after a couple of confrontations with the elements, so you can spend more time riding and less time fixing.
- There's never a good time for a puncture, which is why the Nimbus Airless tires feature a puncture-proof core, offering incredible traction without the hassle of changing a tube.

ALIBI STEP THROUGH			
SIZE	S	M	L
Seat-Tube Length, B-B Center to Top (mm)	375	435	500
Top-Tube Length, Horizontal (mm)	583	607	620
B-B Drop (mm)	70	70	70
Chain-Stay Length (mm)	445	445	445
Seat-Tube Angle (deg)	73	73	73
Head-Tube Angle (deg)	70	70	70
Fork Rake (mm)	51	51	51
Trail (mm)	75	75	75
Front-Center (mm)	660	682	697
Wheelbase (mm)	1096	1118	1133
Stand-Over Height (mm)	512	532	567
Head-Tube Length (mm)	160	180	210
Reach (mm)	410	425	430
Stack (mm)	566	594	622
Handlebar Width (mm)	640	640	640
Stem Length (mm)	60	70	90
Saddle Width (mm)	175	175	175
Seat Post Length (mm)	350	350	350
Crank Length (mm)	165	170	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, step through design, formed tubes, fender/rack mounts
FORK	Specialized A1 Premium Aluminum, Cr-Mo steerer, fender/rack mounts
STEM	Forged Alloy, 17-degree rise, 31.8mm clamp
HANDLEBARS	31.8mm, 640mm width, 15-degree backsweep, 55mm drop
TAPE	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	V-brake, linear pull
REAR BRAKE	V-brake, linear pull
FRONT DERAILLEUR	Shimano Altus, 31.8mm adapter, top-swing, 8-speed
REAR DERAILLEUR	Shimano Altus, 8-speed
SHIFT LEVERS	Shimano EF500, EZ Fire Plus, 8-speed
CASSETTE	Shimano, 8-speed, 11-34t
CHAIN	KMC X8 EPT, 8-speed w/reusable MissingLink
CRANKSET	Shimano FC-TY501 triple, 6-/7-/8-speed
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
FRONT WHEEL	Alibi V-brake
REAR WHEEL	Alibi V-brake
FRONT TIRE	Nimbus Airless, 700x38mm
REAR TIRE	Nimbus Airless, 700x38mm
SADDLE	Milano, steel rails, 175mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
B6617-6302	ALIBI SPORT EQ STEP THROUGH	TPE/LTTUR/BLK	SM
B6617-6303			MD
B6617-6304			LG



NRDCRED/BLK



RFBLKTNT

When it comes time to ride, the last thing you want to do is fix this or pump that, right? We hear you loud and clear, which is why we made the Alibi Sport to be ready to roll whenever you are. It has an anti-rust chain that removes the need for dirty, grimy maintenance and puncture-proof, airless tires.

- The hard-working & sturdy A1 Premium Aluminum frame is light and durable, and it also features rack and fender mounts for easy portage and dry riding in wet conditions. You'll also find that it's engineered with our Fitness Geometry, meaning that you'll go fast with maximum efficiency, but without the discomfort of an aggressive ride position. After all, the more comfortable you are, the longer you'll ride.
- The Alibi's anti-rust chain keeps rolling smoothly, even after a couple of confrontations with the elements, so you can spend more time riding and less time fixing.
- There's never a good time for a puncture, which is why the Nimbus Airless tires feature a puncture-proof core, offering incredible traction without the hassle of changing a tube.

ALIBI				
SIZE	S	M	L	XL
Seat-Tube Length, B-B Center to Top (mm)	390	439	476	532
Top-Tube Length, Horizontal (mm)	585	607	628	652
B-B Drop (mm)	70	70	65	65
Chain-Stay Length (mm)	445	445	445	445
Seat-Tube Angle (deg)	73	73	73	73
Head-Tube Angle (deg)	70	70	70	70
Fork Rake (mm)	51	51	51	51
Trail (mm)	75	75	75	75
Front-Center (mm)	661	684	707	732
Wheelbase (mm)	1096	1119	1144	1169
Stand-Over Height (mm)	714	766	790	834.5
Head-Tube Length (mm)	160	185	210	240
Reach (mm)	405	420	435	450
Stack (mm)	575	599	617	645
Handlebar Width (mm)	640	640	640	640
Stem Length (mm)	60	70	90	100
Saddle Width (mm)	175	175	175	175
Seat Post Length (mm)	350	350	350	350
Crank Length (mm)	165	170	175	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, formed tubes, fender/rack mounts
FORK	Specialized A1 Premium Aluminum, Cr-Mo steerer, fender/rack mounts
STEM	Forged Alloy, 17-degree rise, 31.8mm clamp
HANDLEBARS	640mm width, 15-degree backsweep, 55mm drop, 31.8mm
TAPE	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	V-brake, linear pull
REAR BRAKE	V-brake, linear pull
FRONT DERAILLEUR	Shimano Altus, 31.8mm adapter, top-swing, 8-speed
REAR DERAILLEUR	Shimano Altus, 8-speed
SHIFT LEVERS	Shimano EF500, EZ Fire Plus, 8-speed
CASSETTE	Shimano, 8-speed, 11-34t
CHAIN	KMC X8 EPT, 8-speed w/reusable MissingLink
CRANKSET	Shimano FC-TY501 triple, 6-/7-/8-speed
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
FRONT WHEEL	Alibi V-brake
REAR WHEEL	Alibi V-brake
FRONT TIRE	Nimbus Airless, 700x38mm
REAR TIRE	Nimbus Airless, 700x38mm
SADDLE	Milano, steel rails, 175mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
B6617-6002	ALIBI SPORT	NRDCRED/BLK	SM
B6617-6003			MD
B6617-6004			LG
B6617-6005			XL
B6617-6102	ALIBI SPORT	RFBLKTNT	SM
B6617-6103			MD
B6617-6104			LG
B6617-6105			XL

ALIBI SPORT STEP THROUGH



LTTUR/GLD



MRN/LTCRL

When it comes time to ride, the last thing you want to do is fix this or pump that, right? We hear you loud and clear, which is why we made the Alibi Sport Step Through to be ready to roll whenever you are.

- The hard-working & sturdy A1 Premium Aluminum frame is light and durable, and it also features rack and fender mounts for easy portage and dry riding in wet conditions. You'll also find that it's engineered with our Fitness Geometry, meaning that you'll go fast with maximum efficiency, but without the discomfort of an aggressive ride position. After all, the more comfortable you are, the longer you'll ride.
- The Alibi's anti-rust chain keeps rolling smoothly, even after a couple of confrontations with the elements, so you can spend more time riding and less time fixing.
- There's never a good time for a puncture, which is why the Nimbus Airless tires feature a puncture-proof core, offering incredible traction without the hassle of changing a tube.

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, step through design, formed tubes, fender/rack mounts
FORK	Specialized A1 Premium Aluminum, Cr-Mo steerer, fender/rack mounts
STEM	Forged Alloy, 17-degree rise, 31.8mm clamp
HANDLEBARS	31.8mm, 640mm width, 15-degree backsweep, 55mm drop
TAPE	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	V-brake, linear pull
REAR BRAKE	V-brake, linear pull
FRONT DERAILLEUR	Shimano Altus, 31.8mm adapter, top-swing, 8-speed
REAR DERAILLEUR	Shimano Altus, 8-speed
SHIFT LEVERS	Shimano EF500, EZ Fire Plus, 8-speed
CASSETTE	Shimano, 8-speed, 11-34t
CHAIN	KMC X8 EPT, 8-speed w/reusable MissingLink
CRANKSET	Shimano FC-TY501 triple, 6-/7-/8-speed
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
FRONT WHEEL	Alibi V-brake
REAR WHEEL	Alibi V-brake
FRONT TIRE	Nimbus Airless, 700x38mm
REAR TIRE	Nimbus Airless, 700x38mm
SADDLE	Milano, steel rails, 175mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

ALIBI STEP THROUGH			
SIZE	S	M	L
Seat-Tube Length, B-B Center to Top (mm)	375	435	500
Top-Tube Length, Horizontal (mm)	583	607	620
B-B Drop (mm)	70	70	70
Chain-Stay Length (mm)	445	445	445
Seat-Tube Angle (deg)	73	73	73
Head-Tube Angle (deg)	70	70	70
Fork Rake (mm)	51	51	51
Trail (mm)	75	75	75
Front-Center (mm)	660	682	697
Wheelbase (mm)	1096	1118	1133
Stand-Over Height (mm)	512	532	567
Head-Tube Length (mm)	160	180	210
Reach (mm)	410	425	430
Stack (mm)	566	594	622
Handlebar Width (mm)	640	640	640
Stem Length (mm)	60	70	90
Saddle Width (mm)	175	175	175
Seat Post Length (mm)	350	350	350
Crank Length (mm)	165	170	175

PART NO.	DESCRIPTION	COLOR	SIZE
B6617-6402	ALIBI SPORT STEP THROUGH	LTTUR/GLD	SM
B6617-6403			MD
B6617-6404			LG
B6617-6502	ALIBI SPORT STEP THROUGH	MRN/LTCRL	SM
B6617-6503			MD
B6617-6504			LG



MRNBLU/HYP



TARBLK/LTTUR

How many times have you been ready to ride, only to be confronted with a flat tire? Well, our Alibi wants you to be pumped up to ride, not pumping up your tires. That's why it comes with tires that don't need any air at all.

- The hard-working & sturdy A1 Premium Aluminum frame is light and durable, and it also features rack and fender mounts for easy portage and dry riding in wet conditions. You'll also find that it's engineered with our Fitness Geometry, meaning that you'll go fast with maximum efficiency, but without the discomfort of an aggressive ride position. After all, the more comfortable you are, the longer you'll ride.
- The Alibi's anti-rust chain keeps rolling smoothly, even after a couple of confrontations with the elements, so you can spend more time riding and less time fixing.
- There's never a good time for a puncture, which is why the Nimbus Airless tires feature a puncture-proof core, offering incredible traction without the hassle of changing a tube.

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, formed tubes, fender/rack mounts
FORK	Hi-Ten, V-brake mounts
STEM	Forged Alloy, 17-degree rise, 31.8mm clamp
HANDLEBARS	640mm width, 15-degree backsweep, 55mm drop, 31.8mm
TAPE	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	V-brake, linear pull
REAR BRAKE	V-brake, linear pull
REAR DERAILLEUR	Shimano Tourney, 7-speed
SHIFT LEVERS	Shimano Altus, 7-speed, with gear display
CASSETTE	Shimano Tourney freewheel, 7-speed, 14-34t
CHAIN	KMC Z51 EPT, 6-/7-speed w/reusable MissingLink
CRANKSET	Cold-forged alloy crankarms, 3-piece construction, 130mm BCD spider, 5-arm w/steel chainring, 42T w/steel chainguard
CHAINRINGS	42T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
FRONT WHEEL	Alibi V-brake
REAR WHEEL	Alibi V-brake
FRONT TIRE	Nimbus Airless, 700x38mm
REAR TIRE	Nimbus Airless, 700x38mm
SADDLE	Milano, steel rails, 175mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

ALIBI	S	M	L	XL
Seat-Tube Length, B-B Center to Top (mm)	390	439	476	532
Top-Tube Length, Horizontal (mm)	585	607	628	652
B-B Drop (mm)	70	70	65	65
Chain-Stay Length (mm)	445	445	445	445
Seat-Tube Angle (deg)	73	73	73	73
Head-Tube Angle (deg)	70	70	70	70
Fork Rake (mm)	51	51	51	51
Trail (mm)	75	75	75	75
Front-Center (mm)	661	684	707	732
Wheelbase (mm)	1096	1119	1144	1169
Stand-Over Height (mm)	714	766	790	834.5
Head-Tube Length (mm)	160	185	210	240
Reach (mm)	405	420	435	450
Stack (mm)	575	599	617	645
Handlebar Width (mm)	640	640	640	640
Stem Length (mm)	60	70	90	100
Saddle Width (mm)	175	175	175	175
Seat Post Length (mm)	350	350	350	350
Crank Length (mm)	165	170	175	175

PART NO.	DESCRIPTION	COLOR	SIZE
B6617-7002	ALIBI	MRNBLU/HYP	SM
B6617-7003			MD
B6617-7004			LG
B6617-7005			XL
B6617-7102	ALIBI	TARBLK/LTTUR	SM
B6617-7103			MD
B6617-7104			LG
B6617-7105			XL

ALIBI STEP THROUGH



NRDCRED/LTTUR



TARBLK/CHRM



PRP/NRDCRED

How many times have you been ready to ride, only to be confronted with a flat tire? Well, our Alibi Step Through wants you to be pumped up to ride, not pumping up your tires. That's why it comes with tires that don't need any air at all, plus a step through design that makes getting on and off the bike a breeze.

- The hard-working & sturdy A1 Premium Aluminum frame is light and durable, and it also features rack and fender mounts for easy portage and dry riding in wet conditions. You'll also find that it's engineered with our Fitness Geometry, meaning that you'll go fast with maximum efficiency, but without the discomfort of an aggressive ride position. After all, the more comfortable you are, the longer you'll ride.
- The Alibi's anti-rust chain keeps rolling smoothly, even after a couple of confrontations with the elements, so you can spend more time riding and less time fixing.
- There's never a good time for a puncture, which is why the Nimbus Airless tires feature a puncture-proof core, offering incredible traction without the hassle of changing a tube.

ALIBI STEP THROUGH			
SIZE	S	M	L
Seat-Tube Length, B-B Center to Top (mm)	375	435	500
Top-Tube Length, Horizontal (mm)	583	607	620
B-B Drop (mm)	70	70	70
Chain-Stay Length (mm)	445	445	445
Seat-Tube Angle (deg)	73	73	73
Head-Tube Angle (deg)	70	70	70
Fork Rake (mm)	51	51	51
Trail (mm)	75	75	75
Front-Center (mm)	660	682	697
Wheelbase (mm)	1096	1118	1133
Stand-Over Height (mm)	512	532	567
Head-Tube Length (mm)	160	180	210
Reach (mm)	410	425	430
Stack (mm)	566	594	622
Handlebar Width (mm)	640	640	640
Stem Length (mm)	60	70	90
Saddle Width (mm)	175	175	175
Seat Post Length (mm)	350	350	350
Crank Length (mm)	165	170	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, step through design, formed tubes, fender/rack mounts
FORK	Hi-Ten, V-brake mounts
STEM	Forged Alloy, 17-degree rise, 31.8mm clamp
HANDLEBARS	31.8mm, 640mm width, 15-degree backsweep, 55mm drop
TAPE	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	V-brake, linear pull
REAR BRAKE	V-brake, linear pull
REAR DERAILLEUR	Shimano Tourney, 7-speed
SHIFT LEVERS	Shimano Altus, 7-speed, with gear display
CASSETTE	Shimano Tourney freewheel, 7-speed, 14-34t
CHAIN	KMC Z51 EPT, 6-/7-speed w/reusable MissingLink
CRANKSET	Cold-forged alloy crankarms, 3-piece construction, 130mm BCD spider, 5-arm w/steel chainring, 42T w/steel chainguard
CHAINRINGS	42T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
FRONT WHEEL	Alibi V-brake
REAR WHEEL	Alibi V-brake
FRONT TIRE	Nimbus Airless, 700x38mm
REAR TIRE	Nimbus Airless, 700x38mm
SADDLE	Milano, steel rails, 175mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
B6617-7302	ALIBI STEP THROUGH	NRDCRED/LTTUR	SM
B6617-7303			MD
B6617-7304			LG
B6617-7402	ALIBI STEP THROUGH	TARBLK/CHRM	SM
B6617-7403			MD
B6617-7404			LG
B6617-7202	ALIBI STEP THROUGH	PRP/NRDCRED	SM
B6617-7203			MD
B6617-7204			LG



CHAR/BLK

There are always more reasons not to exercise than to actually do it, and when it comes to getting a ride in, one of the most common complaints that we hear is about how tough it is in the city. If this sounds familiar, we have the solution to your problem—the Roll City.

- Shimano hydraulic disc brakes provide reliable stopping power, regardless of the conditions. This way, rain or shine, you'll be able to have full confidence in your ability to react to the road.
- Wide diameter, 650bx2.3" Nimbus Sport Reflective tires provide excellent traction, stability, and cushioning, which creates a safer, more reliable, and more comfortable ride on either paved or dirt roads. Plus, the reflective accents of the tire are sure to increase your visibility to motorists in low-light conditions.
- A Milano Sport saddle allows you to ride in comfort for mile-after-mile, while its integrated SWAT™ mount opens the door to a wide world of on-the-bike storage options.

ROLL			
SIZE	S	M	L
Stack (mm)	586	619	647
Reach (mm)	346	352	370
Head-Tube Length (mm)	155	185	215
Head-Tube Angle (deg)	68	69	69
B-B Height (mm)	285	285	285
B-B Drop (mm)	70	70	70
Trail (mm)	84	77	77
Fork Length (full) (mm)	420	420	420
Fork Rake/Offset (mm)	55	55	55
Front-Center (mm)	618	626	654
Chain-Stay Length (mm)	480	480	480
Wheelbase (mm)	1089	1097	1126
Top-Tube Length (horizontal) (mm)	595	615	645
Bike Stand-Over Height (mm)	702.2	764.3	806
Seat-Tube Length (mm)	375	440	480
Seat-Tube Angle (deg)	67	67	67
Handlebar Width (mm)	700	700	700
Stem Length (mm)	60	60	60
Saddle Width (mm)	175	175	175
Seat Post Length (mm)	350	350	350
Crank Length (mm)	165	170	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Ground Control Positioning, formed tubes, disc mount, fender/rack mounts, reflective paint
FORK	A1 Premium Aluminum, Cr-Mo steerer, post disc mount, fender/rack mounts, reflective paint
STEM	Specialized Flowset, 3D-forged alloy, 12-degree rise, 31.8mm clamp
HANDLEBARS	Specialized, alloy, 10-degree backsweep 31.8mm
GRIPS	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	Shimano Acera, hydraulic disc, resin pads, 160mm rotor
REAR BRAKE	Shimano Acera, hydraulic disc, resin pads, 160mm rotor
REAR DERAILLEUR	Shimano Deore, Shadow Plus design, SGS cage, 10-speed
SHIFT LEVERS	Shimano Deore, 10-speed
CASSETTE	Sunrace, 10-speed, 11-40t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	Single crank, 130mm BCD spider
CHAINRINGS	42T w/aluminum chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	Specialized Roll, double-wall, 33mm inner width, disc
FRONT HUB	Specialized disc, double-sealed, loose ball bearings, 9mm QR
REAR HUB	Specialized disc, loose ball bearings, for Shimano 10-speed cassette, QR
SPOKES	Stainless, 14g
FRONT TIRE	Nimbus Sport Reflective, 650bx2.3", 60TPI
REAR TIRE	Nimbus Sport Reflective, 650bx3.0", 60TPI
SADDLE	Milano Sport, steel rails
SEATPOST	Alloy, 12mm offset, 2-bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
96117-7702	ROLL CITY	CHAR/BLK	SM
96117-7703			MD
96117-7704			LG

ROLL COMP X1



BLK/CHAR/TI

Don't confuse simple with simpleminded—our Roll Comp X1 might take offence. That's because we designed it to be the hassle-free, no-fuss, no-excuses bike to help you hit your fitness goals. It's a tall order, sure, but with its one-by gearing, you'll never have to worry about weird gearing or dropping your chain.

- Wide diameter, 650bx2.3" Nimbus Sport Reflective tires provide excellent traction, stability, and cushioning, which creates a safer, more reliable, and more comfortable ride on either paved or dirt roads. Plus, the reflective accents of the tire are sure to increase your visibility to motorists in low-light conditions.
- Equipped with our Body Geometry The Cup saddle, you can expect a supreme level of comfort anywhere you take the Roll. It delivers on these expectations by "cupping" your sit bones, which reduces pressure without feeling obtrusive or constraining.
- A spring suspension seatpost takes the sting out of rough terrain, giving you an extra bit of "cushion" that'll have you riding longer and more comfortably.

ROLL			
SIZE	S	M	L
Stack (mm)	586	619	647
Reach (mm)	346	352	370
Head-Tube Length (mm)	155	185	215
Head-Tube Angle (deg)	68	69	69
B-B Height (mm)	285	285	285
B-B Drop (mm)	70	70	70
Trail (mm)	84	77	77
Fork Length (full) (mm)	420	420	420
Fork Rake/Offset (mm)	55	55	55
Front-Center (mm)	618	626	654
Chain-Stay Length (mm)	480	480	480
Wheelbase (mm)	1089	1097	1126
Top-Tube Length (horizontal) (mm)	595	615	645
Bike Stand-Over Height (mm)	702.2	764.3	806
Seat-Tube Length (mm)	375	440	480
Seat-Tube Angle (deg)	67	67	67
Handlebar Width (mm)	680	680	680
Stem Length (mm)	60	60	60
Saddle Width (mm)	245	245	245
Seat Post Length (mm)	350	350	350
Crank Length (mm)	165	170	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Ground Control Positioning, formed tubes, disc mount, fender/rack mounts
FORK	A1 Premium Aluminum, Cr-Mo steerer, post disc mount, fender/rack mounts
STEM	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Roll, 6061 alloy, 15-degree backsweep, 5-degree upsweep, 125mm rise, 31.8mm
GRIPS	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	Tektro Auriga, hydraulic disc, organic pads, 160mm rotor
REAR BRAKE	Tektro Auriga, hydraulic disc, organic pads, 160mm rotor
REAR DERAILLEUR	Shimano Deore, Shadow Plus design, SGS cage, 10-speed
SHIFT LEVERS	Shimano Deore, 10-speed
CASSETTE	Sunrace, 10-speed, 11-40t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	104mm BCD spider
CHAINRINGS	42T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	Specialized Roll, double-wall, 33mm inner width, disc
FRONT HUB	Specialized disc, double-sealed, loose ball bearings, 9mm QR
REAR HUB	Specialized disc, loose ball bearings, for Shimano cassettes, QR
SPOKES	Stainless, 14g
FRONT TIRE	Nimbus Sport Reflective, 650bx2.3", 60TPI w/BlackBelt Protection
REAR TIRE	Nimbus Sport Reflective, 650bx2.3", 60TPI w/BlackBelt Protection
SADDLE	Body Geometry The Cup, 6-degree rise, elastomer base, steel rails, SWAT™ compatible mounts, 245mm
SEATPOST	Suspension Plus, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
86117-5002	ROLL COMP X1	BLK/CHAR/TI	SM
86117-5003			MD
86117-5004			LG

ROLL COMP X1 LOW ENTRY



BLK/CHAR/TI

Don't confuse simple with simpleminded—our Roll Comp X1 Low Entry might take offence. That's because we designed it to be the hassle-free, no-excuses bike to help you hit your fitness goals. It's a tall order, sure, but with its one-by gearing and low entry, you'll never have to worry about weird gearing or struggling to get on or off the bike.

- Wide diameter, 650bx2.3" Nimbus Sport Reflective tires provide excellent traction, stability, and cushioning, which creates a safer, more reliable, and more comfortable ride on either paved or dirt roads. Plus, the reflective accents of the tire are sure to increase your visibility to motorists in low-light conditions.
- Equipped with our Body Geometry The Cup saddle, you can expect a supreme level of comfort anywhere you take the Roll. It delivers on these expectations by "cupping" your sit bones, which reduces pressure without feeling obtrusive or constraining.
- A spring suspension seatpost takes the sting out of rough terrain, giving you an extra bit of "cushion" that'll have you riding longer and more comfortably.

ROLL LOW ENTRY

SIZE	S	L
Stack (mm)	586	647
Reach (mm)	346	360
Head-Tube Length (mm)	155	215
Head-Tube Angle (deg)	68	69
B-B Height (mm)	285	285
B-B Drop (mm)	70	70
Trail (mm)	84	77
Fork Length (full) (mm)	420	420
Fork Rake/Offset (mm)	55	55
Front-Center (mm)	618	645
Chain-Stay Length (mm)	480	480
Wheelbase (mm)	1089	1116
Top-Tube Length (horizontal) (mm)	595	635
Bike Stand-Over Height (mm)	496.2	495.3
Seat-Tube Length (mm)	370	480
Seat-Tube Angle (deg)	67	67
Handlebar Width (mm)	680	680
Stem Length (mm)	60	60
Saddle Width (mm)	245	245
Seat Post Length (mm)	350	350
Crank Length (mm)	165	170

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Ground Control Positioning, formed tubes, disc mount, fender/rack mounts
FORK	A1 Premium Aluminum, Cr-Mo steerer, post disc mount, fender/rack mounts
STEM	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Roll, 6061 alloy, 15-degree backsweep, 5-degree upsweep, 125mm rise, 31.8mm
GRIPS	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	Tektro Auriga, hydraulic disc, organic pads, 160mm rotor
REAR BRAKE	Tektro Auriga, hydraulic disc, organic pads, 160mm rotor
REAR DERAILLEUR	Shimano Deore, Shadow Plus design, SGS cage, 10-speed
SHIFT LEVERS	Shimano Deore, 10-speed
CASSETTE	Sunrace, 10-speed, 11-40t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	104mm BCD spider
CHAINRINGS	42T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	Specialized Roll, double-wall, 33mm inner width, disc
FRONT HUB	Specialized disc, double-sealed, loose ball bearings, 9mm QR
REAR HUB	Specialized disc, loose ball bearings, for Shimano cassettes, QR
SPOKES	Stainless, 14g
FRONT TIRE	Nimbus Sport Reflective, 650bx2.3", 60TPI w/BlackBelt Protection
REAR TIRE	Nimbus Sport Reflective, 650bx2.3", 60TPI w/BlackBelt Protection
SADDLE	Body Geometry The Cup, 6-degree rise, elastomer base, steel rails, SWAT™ compatible mounts, 245mm
SEATPOST	Suspension Plus, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
86117-5102	ROLL COMP X1 LOW ENTRY	BLK/CHAR/TI	SM
86117-5104			LG

ROLL ELITE



BLK/TNT/RNBW/GUN/TI/BLK



CLGRY/LTTUR/CRL

There are two types of personal trainers in the world—drill sergeants and cheerleaders. The Roll Elite is the latter kind, in bicycle form.

- Wide diameter, 650bx2.3" Nimbus Sport tires provide excellent traction, stability, and cushioning, which creates a safer, more reliable, and more comfortable ride on either paved or dirt roads.
- Equipped with our Body Geometry The Cup saddle, you can expect a supreme level of comfort anywhere you take the Roll. It delivers on these expectations by "cupping" your sit bones, which reduces pressure without feeling obtrusive or constraining.
- A spring suspension seatpost takes the sting out of rough terrain, giving you an extra bit of "cushion" that'll have you riding longer and more comfortably.

ROLL			
SIZE	S	M	L
Stack (mm)	586	619	647
Reach (mm)	346	352	370
Head-Tube Length (mm)	155	185	215
Head-Tube Angle (deg)	68	69	69
B-B Height (mm)	285	285	285
B-B Drop (mm)	70	70	70
Trail (mm)	84	77	77
Fork Length (full) (mm)	420	420	420
Fork Rake/Offset (mm)	55	55	55
Front-Center (mm)	618	626	654
Chain-Stay Length (mm)	480	480	480
Wheelbase (mm)	1089	1097	1126
Top-Tube Length (horizontal) (mm)	595	615	645
Bike Stand-Over Height (mm)	702.2	764.3	806
Seat-Tube Length (mm)	375	440	480
Seat-Tube Angle (deg)	67	67	67
Handlebar Width (mm)	680	680	680
Stem Length (mm)	60	60	60
Saddle Width (mm)	245	245	245
Seat Post Length (mm)	350	350	350
Crank Length (mm)	165	170	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Ground Control Positioning, formed tubes, disc mount, fender/rack mounts
FORK	A1 Premium Aluminum, Cr-Mo steerer, post disc mount, fender/rack mounts
STEM	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Roll, 6061 alloy, 15-degree backsweep, 5-degree upsweep, 125mm rise, 31.8mm
GRIPS	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	Tektro, mechanical disc, resin pads, 160mm rotor
REAR BRAKE	Tektro, mechanical disc, resin pads, 160mm rotor
FRONT DERAILLEUR	Shimano Tourney, top swing, 31.8mm band clamp
REAR DERAILLEUR	Shimano Altus, SGS cage
SHIFT LEVERS	Shimano Altus, EZ Fire Plus, 8-speed
CASSETTE	Sunrace, 8-speed, 11-34t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Stout, forged alloy
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	Specialized Roll, double-wall, disc
FRONT HUB	Specialized disc, double-sealed, loose ball bearings, 9mm QR
REAR HUB	Specialized disc, loose ball bearings, for Shimano 8-/9-speed cassettes, QR
SPOKES	Stainless, 14g
FRONT TIRE	Nimbus Sport Reflective, 650bx2.3", 60TPI w/BlackBelt Protection
REAR TIRE	Nimbus Sport Reflective, 650bx2.3", 60TPI w/BlackBelt Protection
SADDLE	Body Geometry The Cup, 6-degree rise, elastomer base, steel rails, SWAT™ compatible mounts, 245mm
SEATPOST	Suspension Plus, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
86116-4002	ROLL ELITE	BLK/TNT/RNBW/GUN/TI/BLK	SM
86116-4003			MD
86116-4004			LG
86117-4002	ROLL ELITE	CLGRY/LTTUR/CRL	SM
86117-4003			MD
86117-4004			LG

ROLL ELITE LOW ENTRY



CLGRY/DPNDGO/HYP



PRTR/GRY/CRM/BLU



PDRGRN/BLK/TUR/LTTUR

There are two types of personal trainers in the world—drill sergeants and cheerleaders. The Roll Elite Low Entry is the latter kind, in bicycle form. And with its low entry design, it's a breeze to get on and off the bike.

- Wide diameter, 650bx2.3" Nimbus Sport tires provide excellent traction, stability, and cushioning, which creates a safer, more reliable, and more comfortable ride on either paved or dirt roads.
- Equipped with our Body Geometry The Cup saddle, you can expect a supreme level of comfort anywhere you take the Roll. It delivers on these expectations by "cupping" your sit bones, which reduces pressure without feeling obtrusive or constricting.
- A spring suspension seatpost takes the sting out of rough terrain, giving you an extra bit of "cushion" that'll have you riding longer and more comfortably.

ROLL LOW ENTRY

SIZE	S	L
Stack (mm)	586	647
Reach (mm)	346	360
Head-Tube Length (mm)	155	215
Head-Tube Angle (deg)	68	69
B-B Height (mm)	285	285
B-B Drop (mm)	70	70
Trail (mm)	84	77
Fork Length (full) (mm)	420	420
Fork Rake/Offset (mm)	55	55
Front-Center (mm)	618	645
Chain-Stay Length (mm)	480	480
Wheelbase (mm)	1089	1116
Top-Tube Length (horizontal) (mm)	595	635
Bike Stand-Over Height (mm)	496.2	495.3
Seat-Tube Length (mm)	370	480
Seat-Tube Angle (deg)	67	67
Handlebar Width (mm)	680	680
Stem Length (mm)	60	60
Saddle Width (mm)	245	245
Seat Post Length (mm)	350	350
Crank Length (mm)	165	170

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Ground Control Positioning, formed tubes, disc mount, fender/rack mounts
FORK	A1 Premium Aluminum, Cr-Mo steerer, post disc mount, fender/rack mounts
STEM	Specialized Flowset, 3D-forged alloy, 20-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Roll, 6061 alloy, 15-degree backsweep, 5-degree upsweep, 125mm rise, 31.8mm
GRIPS	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	Tektro, mechanical disc, resin pads, 160mm rotor
REAR BRAKE	Tektro, mechanical disc, resin pads, 160mm rotor
FRONT DERAILLEUR	Shimano Tourney, top swing, 31.8mm band clamp
REAR DERAILLEUR	Shimano Altus, SGS cage
SHIFT LEVERS	Shimano Altus, EZ Fire Plus, 8-speed
CASSETTE	Sunrace, 8-speed, 11-34t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	Stout, forged alloy
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	Specialized Roll, double-wall, disc
FRONT HUB	Specialized disc, double-sealed, loose ball bearings, 9mm QR
REAR HUB	Specialized disc, loose ball bearings, for Shimano 8-/9-speed cassettes, QR
SPOKES	Stainless, 14g
FRONT TIRE	Nimbus Sport, 60TPI, 650bx2.3", BlackBelt protection
REAR TIRE	Nimbus Sport, 60TPI, 650bx2.3", BlackBelt protection
SADDLE	Body Geometry The Cup, 6-degree rise, elastomer base, steel rails, SWAT™ compatible mounts, 245mm
SEATPOST	Suspension Plus, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
86117-4202	ROLL ELITE LOW ENTRY	CLGRY/DPNDGO/HYP	SM
86117-4204			LG
86116-4302	ROLL ELITE LOW ENTRY	PRTR/GRY/CRM/BLU	SM
86116-4304			LG
86116-4202	ROLL ELITE LOW ENTRY	PDRGRN/BLK/TUR/LTTUR	SM
86116-4204			LG

ROLL SPORT EQ



OAKGRN/PDRGRN/SPR

In a world of infomercials and crash diets, we understand the hesitation that surrounds anything promising fitness. But we believe in a simple tenet: you get back what you put in. And within the scope of bikes, you'd be hard-pressed to get more out of a machine than with our Roll Sport EQ.

- Wide diameter, 650bx2.3" Nimbus Sport Reflective tires provide excellent traction, stability, and cushioning, which creates a safer, more reliable, and more comfortable ride on either paved or dirt roads. Plus, the reflective accents of the tire are sure to increase your visibility to motorists in low-light conditions.
- Equipped with our Body Geometry The Cup saddle, you can expect a supreme level of comfort anywhere you take the Roll. It delivers on these expectations by "cupping" your sit bones, which reduces pressure without feeling obtrusive or constraining.
- A sturdy alloy seatpost features a 12mm offset for the perfect position on the bike, and its anodized finish will resist corrosion and wear over the long haul.

ROLL			
SIZE	S	M	L
Stack (mm)	586	619	647
Reach (mm)	346	352	370
Head-Tube Length (mm)	155	185	215
Head-Tube Angle (deg)	68	69	69
B-B Height (mm)	285	285	285
B-B Drop (mm)	70	70	70
Trail (mm)	84	77	77
Fork Length (full) (mm)	420	420	420
Fork Rake/Offset (mm)	55	55	55
Front-Center (mm)	618	626	654
Chain-Stay Length (mm)	480	480	480
Wheelbase (mm)	1089	1097	1126
Top-Tube Length (horizontal) (mm)	595	615	645
Bike Stand-Over Height (mm)	702.2	764.3	806
Seat-Tube Length (mm)	375	440	480
Seat-Tube Angle (deg)	67	67	67
Handlebar Width (mm)	680	680	680
Stem Length (mm)	60	60	60
Saddle Width (mm)	245	245	245
Seat Post Length (mm)	350	350	350
Crank Length (mm)	165	170	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Ground Control Positioning, formed tubes, fender/rack mounts
FORK	Roll Disc Steel, fender/rack mounts
STEM	Forged alloy, 17-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Roll, 6061 alloy, 15-degree backsweep, 5-degree upsweep, 125mm rise, 31.8mm
GRIPS	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	Tekro V-brake, linear pull
REAR BRAKE	Tekro V-brake, linear pull
FRONT DERAILLEUR	Shimano Altus, top swing, dual pull, 31.8mm band clamp
REAR DERAILLEUR	Shimano Altus, SGS cage, 9-speed
SHIFT LEVERS	microSHIFT MTB, 9-speed
CASSETTE	Shimano, 9-speed, 11-34t
CHAIN	SRAM PC-971 w/PowerLink
CRANKSET	Alpha Drive, JIS Interface, 9-/10-speed, forged 6061 aluminum, direct-mount
CHAINRINGS	44/32T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	650b double-wall
FRONT HUB	Specialized V-brake, alloy, loose ball bearings, 9mm, QR
REAR HUB	Specialized, 8-/9-speed cassette body, QR
SPOKES	Stainless, 14g
FRONT TIRE	Nimbus Sport Reflective, 650bx2.3", 60TPI w/BlackBelt Protection
REAR TIRE	Nimbus Sport Reflective, 650bx2.3", 60TPI w/BlackBelt Protection
SADDLE	Body Geometry The Cup, steel rails, 155mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
96117-6802	ROLL SPORT EQ	OAKGRN/PDRGRN/SPR	SM
96117-6803			MD
96117-6804			LG

ROLL SPORT EQ LOW ENTRY



OAKGRN/PDRGRN/SPR

In a world of infomercials and crash diets, we understand the hesitation that surrounds anything promising fitness. But we believe in a simple tenet: you get back what you put in. And within the scope of bikes, you'd be hard-pressed to get more out of a machine than with our Roll Sport EQ Low Entry.

- Wide diameter, 650bx2.3" Nimbus Sport Reflective tires provide excellent traction, stability, and cushioning, which creates a safer, more reliable, and more comfortable ride on either paved or dirt roads. Plus, the reflective accents of the tire are sure to increase your visibility to motorists in low-light conditions.
- Equipped with our Body Geometry The Cup saddle, you can expect a supreme level of comfort anywhere you take the Roll. It delivers on these expectations by "cupping" your sit bones, which reduces pressure without feeling obtrusive or constraining.
- A sturdy alloy seatpost features a 12mm offset for the perfect position on the bike, and its anodized finish will resist corrosion and wear over the long haul.

ROLL LOW ENTRY		
SIZE	S	L
Stack (mm)	586	647
Reach (mm)	346	360
Head-Tube Length (mm)	155	215
Head-Tube Angle (deg)	68	69
B-B Height (mm)	285	285
B-B Drop (mm)	70	70
Trail (mm)	84	77
Fork Length (full) (mm)	420	420
Fork Rake/Offset (mm)	55	55
Front-Center (mm)	618	645
Chain-Stay Length (mm)	480	480
Wheelbase (mm)	1089	1116
Top-Tube Length (horizontal) (mm)	595	635
Bike Stand-Over Height (mm)	496.2	495.3
Seat-Tube Length (mm)	370	480
Seat-Tube Angle (deg)	67	67
Handlebar Width (mm)	680	680
Stem Length (mm)	60	60
Saddle Width (mm)	245	245
Seat Post Length (mm)	350	350
Crank Length (mm)	165	170

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Ground Control Positioning, formed tubes, disc mount, fender/rack mounts
FORK	Roll Disc Steel, fender/rack mounts
STEM	Forged alloy, 17-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Roll, 6061 alloy, 15-degree backsweep, 5-degree upsweep, 125mm rise, 31.8mm
GRIPS	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	Tektro V-brake, linear pull
REAR BRAKE	Tektro V-brake, linear pull
FRONT DERAILLEUR	Shimano Altus, top swing, dual pull, 31.8mm band clamp
REAR DERAILLEUR	Shimano Altus, SGS cage, 9-speed
SHIFT LEVERS	microSHIFT MTB, 9-speed
CASSETTE	Shimano, 9-speed, 11-34t
CHAIN	SRAM PC-971 w/PowerLink
CRANKSET	Alpha Drive, JIS Interface, 9-/10-speed, forged 6061 aluminum, direct-mount
CHAINRINGS	44/32T
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	650b double-wall
FRONT HUB	Specialized V-brake, alloy, loose ball bearings, 9mm, QR
REAR HUB	Specialized, 8-/9-speed cassette body, QR
SPOKES	Stainless, 14g
FRONT TIRE	Nimbus Sport Reflective, 650bx2.3", 60TPI w/BlackBelt Protection
REAR TIRE	Nimbus Sport Reflective, 650bx2.3", 60TPI w/BlackBelt Protection
SADDLE	Body Geometry The Cup, steel rails, 245mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
96117-6902	ROLL SPORT EQ LOW ENTRY	OAKGRN/PDRGRN/SPR	SM
96117-6904			LG



BBYBLU/INK/NRDCRED



MRN/NRDCRED/CRL



MXORG/RED/METWHTSIL



OAKGRN/PDRGRN/SPR

Have you ever been described as having caviar taste on a hotdog budget? We've all been there, but we don't think you should have to sacrifice on any of the bells and whistles that get you excited to ride along your path to personal fitness. Meet the Roll Sport.

- Wide diameter, 650bx2.3" Nimbus Sport Reflective tires provide excellent traction, stability, and cushioning, which creates a safer, more reliable, and more comfortable ride on either paved or dirt roads. These tires will also increase your visibility to motorists in low-light conditions.
- Equipped with our Body Geometry The Cup saddle, you can expect a supreme level of comfort anywhere you take the Roll. It delivers on these expectations by "cupping" your sit bones, which reduces pressure without feeling obtrusive or constricting.
- A spring suspension seatpost takes the sting out of rough terrain, giving you an extra bit of "cushion" that'll have you riding longer and more comfortably.

ROLL			
SIZE	S	M	L
Stack (mm)	586	619	647
Reach (mm)	346	352	370
Head-Tube Length (mm)	155	185	215
Head-Tube Angle (deg)	68	69	69
B-B Height (mm)	285	285	285
B-B Drop (mm)	70	70	70
Trail (mm)	84	77	77
Fork Length (full) (mm)	420	420	420
Fork Rake/Offset (mm)	55	55	55
Front-Center (mm)	618	626	654
Chain-Stay Length (mm)	480	480	480
Wheelbase (mm)	1089	1097	1126
Top-Tube Length (horizontal) (mm)	595	615	645
Bike Stand-Over Height (mm)	702.2	764.3	806
Seat-Tube Length (mm)	375	440	480
Seat-Tube Angle (deg)	67	67	67
Handlebar Width (mm)	680	680	680
Stem Length (mm)	60	60	60
Saddle Width (mm)	245	245	245
Seat Post Length (mm)	350	350	350
Crank Length (mm)	165	170	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Ground Control Positioning, formed tubes, disc mount, fender/rack mounts
FORK	Roll Disc Steel, fender/rack mounts
STEM	Forged alloy, 17-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Roll, 6061 alloy, 15-degree backsweep, 5-degree upsweep, 125mm rise, 31.8mm
GRIPS	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	Tektro, mechanical disc, resin pads, 160mm rotor
REAR BRAKE	Tektro, mechanical disc, resin pads, 160mm rotor
FRONT DERAILLEUR	Shimano Tourney, top swing, 31.8mm band clamp
REAR DERAILLEUR	Shimano Tourney, 7-speed
SHIFT LEVERS	Shimano EF51, EZ Fire Plus, 7-speed
CASSETTE	Shimano Tourney freewheel, 7-speed, 14-34t
CHAIN	KMC Z51, 7-speed
CRANKSET	Stout, forged alloy
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	Specialized Roll, double-wall, disc
FRONT HUB	Specialized disc, double-sealed, loose ball bearings, 9mm QR
REAR HUB	Specialized disc, loose ball bearings, QR
SPOKES	Stainless, 14g
FRONT TIRE	Nimbus Sport Reflective, 650bx2.3", 60TPI w/BlackBelt Protection
REAR TIRE	Nimbus Sport Reflective, 650bx2.3", 60TPI w/BlackBelt Protection
SADDLE	Body Geometry The Cup, steel rails, 245mm
SEATPOST	Dual-Bolt Diecast Head, AL6061 Post, Spring Suspension

PART NO.	DESCRIPTION	COLOR	SIZE
86117-6002	ROLL SPORT	BBYBLU/INK/NRDCRED	SM
86117-6003			MD
86117-6004			LG
86117-6102	ROLL SPORT	MRN/NRDCRED/CRL	SM
86117-6103			MD
86117-6104			LG
86117-6602	ROLL SPORT	MXORG/RED/METWHTSIL	SM
86117-6603			MD
86117-6604			LG
86117-6202	ROLL SPORT	OAKGRN/PDRGRN/SPR	SM
86117-6203			MD
86117-6204			LG

ROLL SPORT LOW ENTRY



LTCLR/TUR/BBYBLU



LME/OAKGRN/TI



OAKGRN/PDRGRN/SPR



TUR/LTTUR/LTCRL

Have you ever been described as having caviar taste on a hotdog budget? We've all been there, but we don't think you should have to sacrifice on any of the bells and whistles that get you excited to ride along your path to personal fitness. Meet the Roll Sport Low Entry.

- Wide diameter, 650bx2.3" Nimbus Sport tires provide excellent traction, stability, and cushioning, which creates a safer, more reliable, and more comfortable ride on either paved or dirt roads.
- Equipped with our Body Geometry The Cup saddle, you can expect a supreme level of comfort anywhere you take the Roll. It delivers on these expectations by "cupping" your sit bones, which reduces pressure without feeling obtrusive or constricting.
- A spring suspension seatpost takes the sting out of rough terrain, giving you an extra bit of "cushion" that'll have you riding longer and more comfortably.

ROLL LOW ENTRY

SIZE	S	L
Stack (mm)	586	647
Reach (mm)	346	360
Head-Tube Length (mm)	155	215
Head-Tube Angle (deg)	68	69
B-B Height (mm)	285	285
B-B Drop (mm)	70	70
Trail (mm)	84	77
Fork Length (full) (mm)	420	420
Fork Rake/Offset (mm)	55	55
Front-Center (mm)	618	645
Chain-Stay Length (mm)	480	480
Wheelbase (mm)	1089	1116
Top-Tube Length (horizontal) (mm)	595	635
Bike Stand-Over Height (mm)	496.2	495.3
Seat-Tube Length (mm)	370	480
Seat-Tube Angle (deg)	67	67
Handlebar Width (mm)	680	680
Stem Length (mm)	60	60
Saddle Width (mm)	245	245
Seat Post Length (mm)	350	350
Crank Length (mm)	165	170

SPECS

All specs are subject to change without notice.

FRAME	Specialized A1 Premium Aluminum, Ground Control Positioning, formed tubes, disc mount, fender/rack mounts
FORK	Roll Disc Steel, fender/rack mounts
STEM	Forged alloy, 17-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Roll, 6061 alloy, 15-degree backsweep, 5-degree upsweep, 125mm rise, 31.8mm
GRIPS	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	Tektro, mechanical disc, resin pads, 160mm rotor
REAR BRAKE	Tektro, mechanical disc, resin pads, 160mm rotor
FRONT DERAILLEUR	Shimano Tourney, top swing, 31.8mm band clamp
REAR DERAILLEUR	Shimano Tourney, 7-speed
SHIFT LEVERS	Shimano EF51, EZ Fire Plus, 7-speed
CASSETTE	Shimano Tourney freewheel, 7-speed, 14-34t
CHAIN	KMC Z51, 7-speed
CRANKSET	Stout, forged alloy
CHAINRINGS	48/38/28T w/chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	Specialized Roll, double-wall, disc
FRONT HUB	Specialized disc, double-sealed, loose ball bearings, 9mm QR
REAR HUB	Specialized disc, loose ball bearings, QR
SPOKES	Stainless, 14g
FRONT TIRE	Nimbus Sport Reflective, 650bx2.3", 60TPI w/BlackBelt Protection
REAR TIRE	Nimbus Sport Reflective, 650bx2.3", 60TPI w/BlackBelt Protection
SADDLE	Body Geometry The Cup, steel rails, 245mm
SEATPOST	Dual-Bolt Diecast Head, AL6061 Post, Spring Suspension

PART NO.	DESCRIPTION	COLOR	SIZE
86117-6302	ROLL SPORT LOW ENTRY	LTCLR/TUR/BBYBLU	SM
86117-6304	ROLL SPORT LOW ENTRY	LME/OAKGRN/TI	LG
86117-6702	ROLL SPORT LOW ENTRY	OAKGRN/PDRGRN/SPR	SM
86117-6704	ROLL SPORT LOW ENTRY	OAKGRN/PDRGRN/SPR	LG
86117-6402	ROLL SPORT LOW ENTRY	TUR/LTTUR/LTCRL	SM
86117-6404	ROLL SPORT LOW ENTRY	TUR/LTTUR/LTCRL	LG
86117-6502	ROLL SPORT LOW ENTRY	TUR/LTTUR/LTCRL	SM
86117-6504	ROLL SPORT LOW ENTRY	TUR/LTTUR/LTCRL	LG



CNDYRED/MRN/BBYBLU



DOP/VALORG/SPR



LME/OAKGRN/TI



TARBLK/HYP/CHAR

They say that every journey begins with a single step, but when that journey is related to exercise, that first step can sure be a doozy. Don't worry, though—we have your back with the Roll. It has everything you need to help you along your journey of being the fitter, better you.

- Our Roll Bar handlebars feature plenty of rise and backsweep to keep your hands and body in the perfect position on the bike. This increases comfort dramatically, and hey, they look pretty darn cool, too.
- Wide diameter, 650bx2.3" Nimbus Sport tires provide excellent traction, stability, and cushioning, which creates a safer, more reliable, and more comfortable ride on either paved or dirt roads.
- Equipped with our Body Geometry The Cup saddle, you can expect a supreme level of comfort anywhere you take the Roll. It delivers on these expectations by "cupping" your sit bones, which reduces pressure without feeling obtrusive or constraining.

ROLL			
SIZE	S	M	L
Stack (mm)	586	619	647
Reach (mm)	346	352	370
Head-Tube Length (mm)	155	185	215
Head-Tube Angle (deg)	68	69	69
B-B Height (mm)	285	285	285
B-B Drop (mm)	70	70	70
Trail (mm)	84	77	77
Fork Length (full) (mm)	420	420	420
Fork Rake/Offset (mm)	55	55	55
Front-Center (mm)	618	626	654
Chain-Stay Length (mm)	480	480	480
Wheelbase (mm)	1089	1097	1126
Top-Tube Length (horizontal) (mm)	595	615	645
Bike Stand-Over Height (mm)	702.2	764.3	806
Seat-Tube Length (mm)	375	440	480
Seat-Tube Angle (deg)	67	67	67
Handlebar Width (mm)	680	680	680
Stem Length (mm)	60	60	60
Saddle Width (mm)	245	245	245
Seat Post Length (mm)	350	350	350
Crank Length (mm)	165	170	175

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, Ground Control Positioning, formed tubes, fender/rack mounts
FORK	Roll Disc Steel, fender/rack mounts
STEM	Forged alloy, 17-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Roll, 6061 alloy, 15-degree backsweep, 5-degree upsweep, 125mm rise, 31.8mm
GRIPS	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	Tekro V-brake, linear pull
REAR BRAKE	Tekro V-brake, linear pull
REAR DERAILLEUR	Shimano Tourney, 7-speed
SHIFT LEVERS	Shimano Altus, 7-speed
CASSETTE	Shimano Tourney freewheel, 7-speed, 14-34t
CHAIN	KMC Z51, 7-speed
CRANKSET	Cold-forged alloy crankarms, 3-piece construction, 104mm BCD spider, 4-arm w/steel chainring
CHAINRINGS	42T w/steel chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	650b double-wall
FRONT HUB	Specialized V-brake, alloy, loose ball bearings, 9mm, QR
REAR HUB	Specialized V-brake, loose ball bearings, QR, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Nimbus Sport, 60TPI, 650bx2.3", BlackBelt protection
REAR TIRE	Nimbus Sport, 60TPI, 650bx2.3", BlackBelt protection
SADDLE	Body Geometry The Cup, steel rails, 245mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
86117-7002	ROLL	CNDYRED/MRN/BBYBLU	SM
86117-7003			MD
86117-7004			LG
86117-7102	ROLL	DOP/VALORG/SPR	SM
86117-7103			MD
86117-7104			LG
86117-7602	ROLL	LME/OAKGRN/TI	SM
86117-7603			MD
86117-7604			LG
86117-7202	ROLL	TARBLK/HYP/CHAR	SM
86117-7203			MD
86117-7204			LG

ROLL LOW ENTRY



LTTUR/BRTPNK/CHAR



NRDCRED/LTTUR/FLKSIL



WRMCHAR/DPFUS/DPNDGO

They say that every journey begins with a single step, but when that journey is related to exercise, that first step can sure be a doozy. Don't worry, though—we have your back with the Roll Low Entry. It has everything you need to help you along your journey of being the fitter, better you.

- Our Roll Bar handlebars feature plenty of rise and backsweep to keep your hands and body in the perfect position on the bike. This increases comfort dramatically, and hey, they look pretty darn cool, too.
- Wide diameter, 650bx2.3" Nimbus Sport tires provide excellent traction, stability, and cushioning, which creates a safer, more reliable, and more comfortable ride on either paved or dirt roads.
- Equipped with our Body Geometry The Cup saddle, you can expect a supreme level of comfort anywhere you take the Roll. It delivers on these expectations by "cupping" your sit bones, which reduces pressure without feeling obtrusive or constraining.

ROLL LOW ENTRY

SIZE	S	L
Stack (mm)	586	647
Reach (mm)	346	360
Head-Tube Length (mm)	155	215
Head-Tube Angle (deg)	68	69
B-B Height (mm)	285	285
B-B Drop (mm)	70	70
Trail (mm)	84	77
Fork Length (full) (mm)	420	420
Fork Rake/Offset (mm)	55	55
Front-Center (mm)	618	645
Chain-Stay Length (mm)	480	480
Wheelbase (mm)	1089	1116
Top-Tube Length (horizontal) (mm)	595	635
Bike Stand-Over Height (mm)	496.2	495.3
Seat-Tube Length (mm)	370	480
Seat-Tube Angle (deg)	67	67
Handlebar Width (mm)	680	680
Stem Length (mm)	60	60
Saddle Width (mm)	245	245
Seat Post Length (mm)	350	350
Crank Length (mm)	165	170

SPECS

All specs are subject to change without notice.

FRAME	Specialized A1 Premium Aluminum, Ground Control Positioning, formed tubes, disc mount, fender/rack mounts
FORK	Roll Disc Steel, fender/rack mounts
STEM	Forged alloy, 17-degree rise, 31.8mm clamp
HANDLEBARS	Specialized Roll, 6061 alloy, 15-degree backsweep, 5-degree upsweep, 125mm rise, 31.8mm
GRIPS	Specialized Body Geometry Contour, lock-on
FRONT BRAKE	Tekro V-brake, linear pull
REAR BRAKE	Tekro V-brake, linear pull
REAR DERAILLEUR	Shimano Tourney, 7-speed
SHIFT LEVERS	Shimano Altus, 7-speed
CASSETTE	Shimano Tourney freewheel, 7-speed, 14-34t
CHAIN	KMC Z51, 6-/7-speed
CRANKSET	Cold-forged alloy crankarms, 3-piece construction, 104mm BCD spider, 4-arm w/steel chainring
CHAINRINGS	42T w/steel chainguard
BOTTOM BRACKET	BSA, square taper, cartridge bearings
RIMS	650b double-wall
FRONT HUB	Specialized V-brake, alloy, loose ball bearings, 9mm, QR
REAR HUB	Specialized V-brake, loose ball bearings, QR, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Nimbus Sport, 60TPI, 650bx2.3", BlackBelt protection
REAR TIRE	Nimbus Sport, 60TPI, 650bx2.3", BlackBelt protection
SADDLE	Body Geometry The Cup, steel rails, 245mm
SEATPOST	Alloy, 12mm offset, 2-bolt clamp, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
86117-7302	ROLL LOW ENTRY	LTTUR/BRTPNK/CHAR	SM
86117-7304			LG
86117-7402	ROLL LOW ENTRY	NRDCRED/LTTUR/FLKSIL	SM
86117-7404			LG
86117-7502	ROLL LOW ENTRY	WRMCHAR/DPFUS/DPNDGO	SM
86117-7504			LG

RIPROCK EXPERT 24



NRDCRED/PRLTUR/PRLTTUR



CHAR/BLK/HYP/NRDCRED

Traction, control, confidence, and fun—the Riprock 20's super-wide tires make it the perfect bike for your kid to start ripping on.

- The A1 Premium Aluminum frame is lightweight and built to withstand the tough use by kids, while the geometry features an ultra-low standover that makes it easy for your little ones to fit on and grow with the bike.
- Custom SR Suntour XCT fork features 70mm of smooth, air-sprung travel for rough terrain, while a hydraulic lockout will make climbing significantly easier for your little one.
- Shimano Deore hydraulic disc brakes are easy for little hands to reach and deliver a degree of stopping power that adults would be jealous of.

RIPROCK 24	
SIZE	11
Seat Tube Length, Center to Top (mm)	567
Top Tube Length (Horizontal) (mm)	510
Bottom Bracket Drop (mm)	61
Bottom Bracket Height (mm)	264
Chainstay Length (mm)	420
Seat Tube Angle (deg)	73
Head Tube Angle (deg)	69
Rake (mm)	40
Wheel Base (mm)	989
Standover Height (mm)	608
Head Tube Length (mm)	115
Reach (mm)	336.5
Handlebar Width (mm)	600
Stem Length (mm)	60
Seat Post Length (mm)	300
Crank Length (mm)	152

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, single butted, ZeroStack head tube, 135mm rear hub spacing, forged dropouts, replaceable derailleur hanger
FORK	Custom SR Suntour XCT, custom Multi-Circuit Damping, air spring, 70mm of travel, hydraulic lockout, 1-1/8" steerer, aluminum crown and lowers, 28mm aluminum stanchions, post mount only
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise, 31.8mm clamp, 60mm
HANDLEBARS	Specialized, alloy, 9-degree backsweep, 4-degree upsweep, 600mm width, 31.8mm
GRIPS	Specialized Body Geometry XCT lock-on
FRONT BRAKE	Shimano Deore, hydraulic disc, resin pads, 160mm rotor
REAR BRAKE	Shimano Deore, hydraulic disc, resin pads, 160mm rotor
REAR DERAILLEUR	Shimano Deore XT, GS cage, 10-speed
SHIFT LEVERS	Shimano Deore, 10-speed
CASSETTE	Sunrace, 10-speed, 11-36t
CHAIN	KMC X10, 10-speed w/reusable MissingLink
CRANKSET	Forged alloy, 104mm BCD spider
CHAINRINGS	32T w/chainguard
BOTTOM BRACKET	Square taper, cartridge bearing
RIMS	24", double-wall aluminum, 28h
FRONT HUB	Alloy disc, 110mm spacing, 6-bolt, sealed cartridge bearings, QR, 28h
REAR HUB	Alloy disc, 135mm spacing, 6-bolt disc, 10-speed freehub, sealed cartridge bearings, QR, 28h
SPOKES	Stainless, 14g
FRONT TIRE	Big Roller, 24x2.8", 60TPI, wire bead
REAR TIRE	Big Roller, 24x2.8", 60TPI, wire bead,
SADDLE	Specialized Kids' Henge
SEATPOST	Alloy, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
B6516-3111	RIPROCK EXPERT 24	NRDCRED/PRLTUR/PRLTTUR	11
B6516-3011	RIPROCK EXPERT 24	CHAR/BLK/HYP/NRDCRED	11

RIPROCK COMP 24



BLUFLKPUR/FLKSIL/PRLDPFUS



NEON BLU/HYP/BLK

Bikes were made for fun, and you'd be hard pressed to find a bike that delivers more entertainment to kids than our all-new Riprock 24 Comp.

- The premium A1 aluminum frame is lightweight and built to withstand the tough use by kids, while the geometry features an ultra-low standover that makes it easy for your little ones to fit on and grow with the bike.
- Custom SR Suntour XCT fork features 70mm of smooth, air-sprung travel for rough terrain, while a hydraulic lockout will make climbing significantly easier for your little one.
- Tektro Auriga hydraulic disc brakes provide superior stopping power for increased safety on the road and trail.

RIPROCK 24	
SIZE	11
Seat Tube Length, Center to Top (mm)	567
Top Tube Length (Horizontal) (mm)	510
Bottom Bracket Drop (mm)	61
Bottom Bracket Height (mm)	264
Chainstay Length (mm)	420
Seat Tube Angle (deg)	73
Head Tube Angle (deg)	69
Rake (mm)	40
Wheel Base (mm)	989
Standover Height (mm)	608
Head Tube Length (mm)	115
Reach (mm)	336.5
Handlebar Width (mm)	600
Stem Length (mm)	60
Seat Post Length (mm)	300
Crank Length (mm)	152

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, single butted, ZeroStack head tube, 135mm rear hub spacing, forged dropouts, replaceable derailleur hanger
FORK	Custom SR Suntour XCT, custom Multi-Circuit Damping, air spring, 70mm of travel, hydraulic lockout, 1-1/8" steerer, aluminum crown and lowers, 28mm Hi-Ten stanchions, post mount only
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise, 31.8mm clamp, 60mm
HANDLEBARS	Specialized, alloy, 9-degree backsweep, 4-degree upsweep, 600mm width, 31.8mm
GRIPS	Specialized Body Geometry XCT lock-on
FRONT BRAKE	Tektro Auriga, hydraulic disc, resin pads, post mount, 160mm rotor
REAR BRAKE	Tektro Auriga, hydraulic disc, resin pads, 160mm rotor
REAR DERAILLEUR	Shimano Alivio, Shadow design, 9-speed
SHIFT LEVERS	Shimano Alivio, RapidFire Plus, 9-speed
CASSETTE	Sunrace, 9-speed, 11-36t
CHAIN	KMC X9, 9-speed w/reusable MissingLink
CRANKSET	Forged alloy, 152mm
CHAINRINGS	30T w/chainguard
BOTTOM BRACKET	Square taper
RIMS	24", double-wall aluminum, 32h
FRONT HUB	Alloy disc, loose ball bearing, Cr-Mo axle, 32h
REAR HUB	Alloy disc, loose ball bearings, 6-bolt disc, 135mm spacing, 9-speed freehub
SPOKES	Stainless, 14g
FRONT TIRE	Big Roller, 24x2.8", 60TPI, wire bead
REAR TIRE	Big Roller, 24x2.8", 60TPI, wire bead,
SADDLE	Specialized Kids'
SEATPOST	Alloy, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
B6516-5011	RIPROCK COMP 24	BLUFLKPUR/FLKSIL/PRLDPFUS	11
B6516-5111	RIPROCK COMP 24	NEON BLU/HYP/BLK	11

RIPROCK 24



CNDYRED/HYP/BLK



METWHT/RFPNK/PRLNDGO



SIL/MXORG/BLK



PRLTUR/PRLTTUR/PRLHYP

Big tires make for big fun. The Riprock 24 features 2.8-inch tires, 70mm of coil-sprung suspension, and reliable disc brakes for a ride that can handle anything Junior can throw at it.

- The premium A1 aluminum frame is lightweight and built to withstand the tough use by kids, while the geometry features an ultra-low standover that makes it easy for your little ones to fit on and grow with the bike.
- Custom SR Suntour XCT fork features a sturdy construction and a coil spring that delivers 70mm of bump absorbing travel.
- Super wide Big Roller 24x2.8" tires deliver tons of traction, comfort, stability, and fun over all types of terrain.

RIPROCK 24	
SIZE	11
Seat Tube Length, Center to Top (mm)	567
Top Tube Length (Horizontal) (mm)	510
Bottom Bracket Drop (mm)	61
Bottom Bracket Height (mm)	264
Chainstay Length (mm)	420
Seat Tube Angle (deg)	73
Head Tube Angle (deg)	69
Rake (mm)	40
Wheel Base (mm)	989
Standover Height (mm)	608
Head Tube Length (mm)	115
Reach (mm)	336.5
Handlebar Width (mm)	600
Stem Length (mm)	60
Seat Post Length (mm)	300
Crank Length (mm)	152

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, single butted, ZeroStack head tube, 135mm rear hub spacing, forged dropouts, replaceable derailleur hanger
FORK	Custom SR Suntour XCT, coil spring, 70mm of travel, preload adjust, 1-1/8" steerer, alloy crown and lowers, 28mm Hi-Ten stanchions, post mount only
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise, 25.4mm clamp, 60mm
HANDLEBARS	Specialized, double-buttressed alloy, 5-degree backsweep, 600mm width, 25.4mm
GRIPS	Specialized, Kraton, Revo type
FRONT BRAKE	Tektro Aries, mechanical disc, organic pads, 160mm rotor
REAR BRAKE	Tektro Aries, mechanical disc, organic pads, 160mm rotor
REAR DERAILLEUR	Shimano Tourney TX, 8-speed
SHIFT LEVERS	Shimano Tourney, Revo-style, 8-Speed
CASSETTE	Sunrace, 8-speed, 11-34t
CHAIN	KMC Z7, 8-speed w/reusable MissingLink
CRANKSET	Forged alloy, 152mm
CHAINRINGS	30T w/chainguard
BOTTOM BRACKET	Square taper
RIMS	24", double-wall aluminum, 32h
FRONT HUB	Alloy disc, loose ball bearing, Cr-Mo axle, 6-bolt disc, 32h
REAR HUB	Alloy disc, loose ball bearings, 6-bolt disc, 135mm spacing, 9-speed freehub, 28h
SPOKES	Stainless, 14g
FRONT TIRE	Big Roller, 24x2.8", 60TPI, wire bead
REAR TIRE	Big Roller, 24x2.8", 60TPI, wire bead,
SADDLE	Specialized Kids'
SEATPOST	Alloy, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
B6516-7411	RIPROCK 24	CNDYRED/HYP/BLK	11
B6516-7511	RIPROCK 24	METWHT/RFPNK/PRLNDGO	11
B6516-7711	RIPROCK 24	SIL/MXORG/BLK	11
B6516-7611	RIPROCK 24	PRLTUR/PRLTTUR/PRLHYP	11

RIPROCK 20



CARBGRY/HYP/CLGRY



PDRGRN/TUR/LTTUR



RFPNK/PRLTUR/PRLTTUR



RYLBLU/MXORG/WHT

Traction, control, confidence, and fun—the Riprock 20's super-wide tires make it the perfect bike for your kid to start ripping on.

- The premium A1 aluminum frame is lightweight and built to withstand the tough use by kids, while the geometry features an ultra-low standover that makes it easy for your little ones to fit on and grow with the bike.
- Custom SR Suntour XCT fork features a sturdy construction and a coil spring that delivers 60mm of bump absorbing travel.
- Super wide Big Roller 20x2.8" tires deliver tons of traction, comfort, stability, and fun over all types of terrain.

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, single butted, ZeroStack head tube, 135mm rear hub spacing, forged dropouts, replaceable derailleur hanger
FORK	Custom SR Suntour XCT, coil spring, 60mm of travel, preload adjust, 1-1/8" steerer, alloy crown and lowers, 28mm Hi-Ten stanchions, post mount only
STEM	Specialized, 3D-forged alloy, 4-bolt, 6-degree rise, 25.4mm clamp, 60mm
HANDLEBARS	Specialized, double-buttressed alloy, 5-degree backsweep, 600mm width, 25.4mm
GRIPS	Specialized, Kraton, Revo type
FRONT BRAKE	Tektro Aries, mechanical disc, organic pads, 160mm rotor
REAR BRAKE	Tektro Aries, mechanical disc, organic pads, 160mm rotor
REAR DERAILLEUR	Shimano Tourney TX, 8-speed
SHIFT LEVERS	Shimano Tourney, Revo-style, 7-Speed
CASSETTE	Sunrace, 7-speed, 11-34t
CHAIN	KMC Z51, 6-/7-speed
CRANKSET	Forged alloy, 127mm
CHAINRINGS	30T w/chainguard
BOTTOM BRACKET	Square taper
RIMS	24", double-wall aluminum, 32h
FRONT HUB	Alloy disc, loose ball bearings, Cr-Mo axle, 6-bolt disc, 32h
REAR HUB	Alloy disc, loose ball bearings, 6-bolt disc, 135mm spacing, 9-speed freehub, 28h
SPOKES	Stainless, 14g
FRONT TIRE	Big Roller, 20x2.8", 60TPI, wire bead
REAR TIRE	Big Roller, 20x2.8", 60TPI, wire bead
SADDLE	Specialized Kids'
SEATPOST	Alloy, single bolt, 27.2mm

RIPROCK 20	
SIZE	9
Seat Tube Length, Center to Top (mm)	279
Top Tube Length (Horizontal) (mm)	465
Bottom Bracket Drop (mm)	37.5
Bottom Bracket Height (mm)	237
Chainstay Length (mm)	390
Seat Tube Angle (deg)	73
Head Tube Angle (deg)	69
Rake (mm)	40
Wheel Base (mm)	909.5
Standover Height (mm)	528
Head Tube Length (mm)	115
Reach (mm)	306
Handlebar Width (mm)	580
Stem Length (mm)	60
Seat Post Length (mm)	300
Crank Length (mm)	127

PART NO.	DESCRIPTION	COLOR	SIZE
B6516-7009	RIPROCK 20	CARBGRY/HYP/CLGRY	9
B6516-7109	RIPROCK 20	PDRGRN/TUR/LTTUR	9
B6516-7209	RIPROCK 20	RFPNK/PRLTUR/PRLTTUR	9
B6516-7309	RIPROCK 20	RYLBLU/MXORG/WHT	9

RIPROCK COASTER 20



MONGRN/NRDCRED/BLK



RFPNK/DPFUS/METWHTSIL



RYLBLU/MXORG/WHT



TUR/HYP/LTTUR



STRLGRV/NRDCRED/HYP

Riding a bike is all about freedom, so no kid should ever have to feel inhibited by where they can and can't ride their bike. With the Riprock 20 Coaster, however, your little one will be able to rip and ride on any terrain that they come across—especially with the easy-to-use coaster brake.

- The premium A1 aluminum frame is lightweight and built to withstand the tough use by kids, while the geometry features an ultra-low standover that makes it easy for your little ones to fit on and grow with the bike.
- Steel coaster brake is a reliable, easy to use brake perfect for safe stops and awesome skids.
- 20x2.3" Rhythm Lite tires deliver tons of traction, comfort, stability, and fun over all types of terrain.

RIPROCK COASTER 20

SIZE	20
Seat-Tube Length, B-B Center to Top (mm)	250
Top-Tube Length, Horizontal (mm)	449
B-B Drop (mm)	42
Chain-Stay Length (mm)	386
Seat-Tube Angle (deg)	72
Head-Tube Angle (deg)	70
Fork Rake (mm)	23
Trail (mm)	71
Front-Center (mm)	476
Wheelbase (mm)	858
Stand-Over Height (mm)	477
Head-Tube Length (mm)	80
Reach (mm)	315
Stack (mm)	413
Handlebar Width (mm)	560
Stem Length (mm)	37
Seat Post Length (mm)	220
Crank Length (mm)	114

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum
FORK	HiTen, 1-1/8" steerer
STEM	Ahead, alloy, 1-1/8" steerer, 22.2mm clamp, 37mm extension
HANDLEBARS	BMX, steel, 10-degree backsweep, 4-degree upsweep, 130mm rise, 560mm width, 22.2mm
GRIPS	Specialized, dual colored
REAR BRAKE	V-brake, alloy, linear pull
CHAIN	KMC Z510, single-speed, anti-drop, 1/2"x1/8"
CRANKSET	Hi-Ten steel, OPC
CHAINRINGS	36T
BOTTOM BRACKET	Steel, loose ball bearings
RIMS	20", alloy single wall, 36h
FRONT HUB	Steel, 3/8" axle, 36h
REAR HUB	Rear coaster brake, 3/8" Cr-Mo axle, loose ball bearings, 18T cog, 36h
SPOKES	Stainless, 14g
FRONT TIRE	Rhythm Lite, 20x2.3", 30TPI, wire bead, directional tread
REAR TIRE	Rhythm Lite, 20x2.3", 30TPI, wire bead, directional tread
SADDLE	Specialized Kids'
SEATPOST	Steel, 25.4mm

PART NO.	DESCRIPTION	COLOR	SIZE
B6517-9009	RIPROCK COASTER 20	MONGRN/NRDCRED/BLK	9
B6517-9109	RIPROCK COASTER 20	RFPNK/DPFUS/METWHTSIL	9
B6517-9209	RIPROCK COASTER 20	RYLBLU/MXORG/WHT	9
B6517-9409	RIPROCK COASTER 20	TUR/HYP/LTTUR	9
B6517-9309	RIPROCK COASTER 20	STRLGRV/NRDCRED/HYP	9

RIPROCK COASTER 16



BLKGLDPRL/HYP/RFPNK



CHAR/RFPNK/NENBLU



LTTUR/NRDCRED/BLK



RFPNK/TUR/LTTUR



BLKHYPCKL/EMDGRN/HYP



LTSIL/MXORG/BLK

With our Riprock Coaster 16, riding gets boiled down to its simplest element—fun. And to make sure of it, we designed the bike with tons of cool features that our easy for your little ones to use, like a coaster brake for simple stopping and wide 16x2.3" tires that increase stability and confidence.

- The premium A1 aluminum frame is lightweight and built to withstand the tough use by kids, while the geometry features an ultra-low standover that makes it easy for your little ones to fit on and grow with the bike.
- Steel coaster brake is a reliable, easy to use brake perfect for safe stops and awesome skids.
- 16x2.3" Rhythm Lite tires deliver tons of traction, comfort, stability, and fun over all types of terrain.

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum
FORK	HiTen, 1-1/8" steerer
STEM	Ahead, alloy, 1-1/8" steerer, 22.2mm clamp, 37mm extension
HANDLEBARS	BMX, steel, 10-degree backsweep, 4-degree upsweep, 115mm rise, 520mm width, 22.2mm
GRIPS	Specialized, dual colored
CHAIN	KMC Z510, single-speed, anti-drop, 1/2"x1/8"
CRANKSET	Hi-Ten steel
CHAINRINGS	26T
BOTTOM BRACKET	Steel, loose ball bearings
RIMS	16", alloy single wall, pin joint, 28h
FRONT HUB	Steel, nutted axle, 36h
REAR HUB	Rear coaster brake, 3/8" Cr-Mo axle, loose ball bearings, 16T cog, 28h
SPOKES	Stainless, 14g
FRONT TIRE	Rhythm Lite, 16x2.3", 30TPI, wire bead, directional tread
REAR TIRE	Rhythm Lite, 16x2.3", 30TPI, wire bead, directional tread
SADDLE	Specialized Kids'
SEATPOST	Steel, 25.4mm

RIPROCK COASTER 16	
SIZE	16
Seat-Tube Length, B-B Center to Top (mm)	210
Top-Tube Length, Horizontal (mm)	395
B-B Drop (mm)	27
Chain-Stay Length (mm)	310
Seat-Tube Angle (deg)	71
Head-Tube Angle (deg)	70
Fork Rake (mm)	5
Trail (mm)	72
Front-Center (mm)	399
Wheelbase (mm)	707
Stand-Over Height (mm)	405
Head-Tube Length (mm)	80
Reach (mm)	272
Stack (mm)	358
Handlebar Width (mm)	520
Stem Length (mm)	37
Seat Post Length (mm)	230
Crank Length (mm)	3.5

PART NO.	DESCRIPTION	COLOR	SIZE
B6517-9007	RIPROCK COASTER 16	BLKGLDPRL/HYP/RFPNK	7
B6517-9207	RIPROCK COASTER 16	CHAR/RFPNK/NENBLU	7
B6517-9407	RIPROCK COASTER 16	LTTUR/NRDCRED/BLK	7
B6517-9507	RIPROCK COASTER 16	RFPNK/TUR/LTTUR	7
B6517-9107	RIPROCK COASTER 16	BLKHYPCKL/EMDGRN/HYP	7
B6517-9307	RIPROCK COASTER 16	LTSIL/MXORG/BLK	7

RIPROCK COASTER 12



CNDYRED/HYP



NRDCRED/LTNDGO/METWHTSIL



METWHTSIL/RFPNK/MXORG



LME/NENBLU/BLK

With our Riprock Coaster 12, riding gets boiled down to its simplest element—fun. And to make sure of it, we designed the bike with tons of cool features that our easy for your little ones to use, like a coaster brake for simple stopping and wide 16x2.3" tires that increase stability and confidence.

- The premium A1 aluminum frame is lightweight and built to withstand the tough use by kids, while the geometry features an ultra-low standover that makes it easy for your little ones to fit on and grow with the bike.
- Steel coaster brake is a reliable, easy to use brake perfect for safe stops and awesome skids.
- 12x2.3" Rhythm Lite tires deliver tons of traction, comfort, stability, and fun over all types of terrain.

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum
FORK	HiTen, 1" threaded steerer
STEM	Quill, alloy, 22.2mm clamp
HANDLEBARS	Specialized Kids', steel, 10-degree backsweep, 4-degree upsweep, 55mm rise, 22.2mm
GRIPS	Specialized, dual colored
CHAIN	KMC Z510, single-speed, anti-drop, 1/2"x1/8"
CRANKSET	Hi-Ten steel
CHAINRINGS	26T
BOTTOM BRACKET	Steel, loose ball bearings
RIMS	12", aluminum, single wall, 16H
FRONT HUB	Steel, 3/8" axle, 16h
REAR HUB	Rear coaster brake, 3/8" Cr-Mo axle, loose ball bearings, 16T cog, 16h
SPOKES	Stainless, 14g
FRONT TIRE	Rhythm Lite, 12x2.3", 30TPI, wire bead, directional tread
REAR TIRE	Rhythm Lite, 12x2.3, 30TPI, wire bead, directional tread
SADDLE	Specialized Kids'
SEATPOST	Alloy, 25.4mm

RIPROCK COASTER 12	
SIZE	12
Seat-Tube Length, B-B Center to Top (mm)	170
Top-Tube Length, Horizontal (mm)	350
B-B Drop (mm)	11
Chain-Stay Length (mm)	272
Seat-Tube Angle (deg)	71
Head-Tube Angle (deg)	70
Fork Rake (mm)	5
Trail (mm)	53
Front-Center (mm)	331
Wheelbase (mm)	603
Stand-Over Height (mm)	365
Head-Tube Length (mm)	80
Reach (mm)	222
Stack (mm)	274
Handlebar Width (mm)	470
Stem Length (mm)	35
Seat Post Length (mm)	190
Crank Length (mm)	3

PART NO.	DESCRIPTION	COLOR	SIZE
B6517-9006	RIPROCK COASTER 12	CNDYRED/HYP	6
B6517-9306	RIPROCK COASTER 12	NRDCRED/LTNDGO/METWHTSIL	6
B6517-9206	RIPROCK COASTER 12	METWHTSIL/RFPNK/MXORG	6
B6517-9106	RIPROCK COASTER 12	LME/NENBLU/BLK	6

HOTROCK 24 XC PRO



RKTRED/BLK/WHT

The Hotrock 24 XC Pro is the ultimate kid-sized, singletrack shredder. It comes equipped with plenty of features that adults would be stoked on, so it's sure to take any young ripper's riding to the next level—right out of the box.

- Tough, light, and durable, the A1 Premium Aluminum frame is built to stand up to years of tough riding.
- A custom SR Suntour XCR-AIR suspension fork with Multi-Circuit Damping offers high-level performance for smooth compression and rebound, no matter the terrain.

HOTROCK 24 XC		
SIZE	S	L
Stack (mm)	504	516
Reach (mm)	335	372
Head-Tube Length (mm)	90	110
Head-Tube Angle (deg)	70	70
B-B Height (mm)	263.5	271
B-B Drop (mm)	45	37
Trail (mm)	73	73
Fork Length (full) (mm)	402	402
Fork Rake/Offset (mm)	37	37
Front-Center (mm)	544	587
Chain-Stay Length (mm)	420	420
Wheelbase (mm)	960	1005
Top-Tube Length (horizontal) (mm)	490	530
Bike Stand-Over Height (mm)	610	643
Seat-Tube Length (mm)	305	342
Seat-Tube Angle (deg)	73	73
Handlebar Width (mm)	640.0	
Stem Length (mm)	75.0	
Seat Post Length (mm)	300	
Crank Length (mm)	160.0	

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, double-butt, formed down tube/top tube, externally relieved head tube, forged dropouts w/replaceable hanger, disc mount
FORK	Custom SR Suntour XCR-AIR, custom Multi-Circuit Damping, air spring, 63mm of travel, preload adjust, 1-1/8" steerer, mag lowers, Hi-Ten 28mm stanchions, disc mount
STEM	Syntace F109, 6-degree rise, 31.8mm clamp
HANDLEBARS	Specialized flat bar, carbon, 8-degree backsweep, 640mm width, 31.8mm
GRIPS	Specialized Body Geometry XC Contour, lock-on w/gel
FRONT BRAKE	Shimano Deore, hydraulic disc, resin pads, 160mm rotor
REAR BRAKE	Shimano Deore, hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	SRAM X7, high-clamp 31.8mm, bottom pull, 2x10
REAR DERAILLEUR	Shimano Deore XT, Shadow Plus, GS cage, 10-speed
SHIFT LEVERS	Shimano Deore, RapidFire, 1-spec, 10-speed
CASSETTE	Sunrace, 10-speed, 11-36t
CHAIN	KMC X10L, 10-speed w/reusable MissingLink
CRANKSET	Custom SRAM S-1255, 2 pc., 10-speed XC double
CHAINRINGS	36/22T
BOTTOM BRACKET	SRAM GXP, 73mm
RIMS	24" disc, alloy double-wall, sleeve joint, 23mm inner width
FRONT HUB	Specialized Stout XC Pro, Hi Lo disc, alloy, sealed cartridge bearings, QR, 24h
REAR HUB	Specialized Stout XC Pro, Hi Lo disc, alloy, sealed cartridge bearings, QR, 28h
SPOKES	Stainless, 14g
FRONT TIRE	Fast Trak LK Sport, 24x1.8", 60TPI, wire bead
REAR TIRE	Fast Trak LK Sport, 24x1.8", 60TPI, wire bead
SADDLE	Specialized Youth, steel rails
SEATPOST	S-Works FACT carbon, 20mm offset, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
94015-0013	HOTROCK 24 XC PRO	RKTRED/BLK/WHT	13

HOTROCK 24 XC DISC



BLK/GRN/WHT

Kid-sized for shredding singletrack, the Hotrock 24 XC Disc comes equipped with everything your little ripper needs to start riding with the big kids, including hydraulic disc brakes.

- Tough, light, and durable, the A1 Premium Aluminum frame is built to stand up to years of tough riding.
- SR Suntour suspension fork offers 63mm of coil-sprung travel that smooths out bumpy, rough terrain

HOTROCK 24 XC		
SIZE	S	L
Stack (mm)	504	516
Reach (mm)	335	372
Head-Tube Length (mm)	90	110
Head-Tube Angle (deg)	70	70
B-B Height (mm)	263.5	271
B-B Drop (mm)	45	37
Trail (mm)	73	73
Fork Length (full) (mm)	402	402
Fork Rake/Offset (mm)	37	37
Front-Center (mm)	544	587
Chain-Stay Length (mm)	420	420
Wheelbase (mm)	960	1005
Top-Tube Length (horizontal) (mm)	490	530
Bike Stand-Over Height (mm)	610	643
Seat-Tube Length (mm)	305	342
Seat-Tube Angle (deg)	73	73
Handlebar Width (mm)	620	620
Stem Length (mm)	70	80
Seat Post Length (mm)	300	350
Crank Length (mm)	152	160

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, double-buttet, formed down tube/top tube, externally relieved head tube, forged dropouts w/replaceable hanger, disc mount
FORK	SR Suntour, coil spring w/preload adjust, 63mm of travel, 1-1/8" steel steerer, 9mm axle
STEM	Forged alloy, 20 degree rise, 4 bolt, 25.4mm clamp diameter
HANDLEBARS	Specialized, 8-degree backsweep, 4-degree upsweep, 25mm rise, 620mm width, 25.4mm
GRIPS	Specialized, Kraton w/gel
FRONT BRAKE	Tektro Auriga, hydraulic disc, resin pads, 160mm rotor
REAR BRAKE	Tektro Auriga, hydraulic disc, resin pads, 160mm rotor
FRONT DERAILLEUR	SR Suntour, 31.8mm clamp, high-mount
REAR DERAILLEUR	Shimano Acera, Shadow design
SHIFT LEVERS	Shimano RapidFire Plus, 8-speed
CASSETTE	Sunrace, 8-speed, 11-34t
CHAIN	KMC X8, 8-speed w/reusable MissingLink
CRANKSET	SR Suntour XCT-JR, replaceable outer ring, 42/32/22T w/chainguard
CHAINRINGS	42/32/22T
BOTTOM BRACKET	Square taper, cartridge bearings, 68mm
RIMS	24", aluminum double-wall, 32h
FRONT HUB	Specialized disc, loose ball bearings, 9mm QR, 32h
REAR HUB	Specialized disc, 6-bolt disc mount, loose ball bearings, for Shimano 8-/9-speed cassettes, QR, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Specialized Fast Trak LK Sport, 60TPI, wire bead, 24x1.8"
REAR TIRE	Specialized Fast Trak LK Sport, 60TPI, wire bead, 24x1.8"
SADDLE	Specialized Youth, steel rails
SEATPOST	Alloy, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
94016-7311	HOTROCK 24 XC DISC	BLK/GRN/WHT	11
94016-7313			13

BOY'S HOTROCK 24 XC



BLK/RED/WHT

Kid-sized for shredding singletrack, the Boy's Hotrock 24 XC comes equipped with everything your little ripper needs to start riding with the big kids.

- Tough, light, and durable, the A1 Premium Aluminum frame is built to stand up to years of tough riding.
- SR Suntour suspension fork offers 50mm of coil-sprung travel that smooths out bumpy, rough terrain

HOTROCK 24 XC		
SIZE	S	L
Stack (mm)	504	516
Reach (mm)	335	372
Head-Tube Length (mm)	90	110
Head-Tube Angle (deg)	70	70
B-B Height (mm)	263.5	271
B-B Drop (mm)	45	37
Trail (mm)	73	73
Fork Length (full) (mm)	402	402
Fork Rake/Offset (mm)	37	37
Front-Center (mm)	544	587
Chain-Stay Length (mm)	420	420
Wheelbase (mm)	960	1005
Top-Tube Length (horizontal) (mm)	490	530
Bike Stand-Over Height (mm)	610	643
Seat-Tube Length (mm)	305	342
Seat-Tube Angle (deg)	73	73
Handlebar Width (mm)	620	620
Stem Length (mm)	70	80
Seat Post Length (mm)	300	350
Crank Length (mm)	152	160

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, double-butt, formed down tube/top tube, externally relieved head tube, forged dropouts w/replaceable hanger, disc mount
FORK	SR Suntour, coil spring w/preload adjust, 50mm of travel, 1-1/8" steel steerer, 9mm axle
STEM	Forged alloy, 20 degree rise, 4 bolt, 25.4mm clamp diameter
HANDLEBARS	Specialized, 8-degree backsweep, 4-degree upsweep, 25mm rise, 620mm width, 25.4mm
GRIPS	Specialized, Kraton
FRONT BRAKE	V-brake, alloy, linear pull
REAR BRAKE	V-brake, alloy, linear pull
FRONT DERAILLEUR	SR Suntour, 31.8mm clamp, high-mount
REAR DERAILLEUR	SRAM X3, direct mount
SHIFT LEVERS	SRAM 3.0 Comp, Grip Shift, 7-speed
CASSETTE	Shimano Tourney freewheel, 7-speed, 14-34t
CHAIN	KMC Z51, 7-speed
CRANKSET	SR Suntour XCT-JR, replaceable outer ring w/chainguard
CHAINRINGS	42/32/22T
BOTTOM BRACKET	Square taper, cartridge bearings, 68mm
RIMS	24", aluminum double-wall, 32h
FRONT HUB	Front hub, 5mm QR, steel axle, loose ball bearings, dual lock nuts w/17mm contact side, 32h
REAR HUB	Rear, 5mm QR, loose ball bearings, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Specialized Fast Trak LK Sport, 60TPI, wire bead, 24x1.8"
REAR TIRE	Specialized Fast Trak LK Sport, 60TPI, wire bead, 24x1.8"
SADDLE	Specialized Youth, steel rails
SEATPOST	Alloy, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
94E0-7111	HOTROCK 24 XC BOY	BLK/RED/WHT	11
94E0-7113			13

GIRL'S HOTROCK 24 XC



BLK/PNK/WHT

She might be your little princess, but she's a trail-riding machine. That's why we designed the Girl's Hotrock 24 XC to come with everything your girl needs to start riding with the big kids.

- Tough, light, and durable, the A1 Premium Aluminum frame is built to stand up to years of tough riding.
- SR Suntour suspension fork offers 50mm of coil-sprung travel that smooths out bumpy, rough terrain

HOTROCK 24 XC		
SIZE	S	L
Stack (mm)	504	516
Reach (mm)	335	372
Head-Tube Length (mm)	90	110
Head-Tube Angle (deg)	70	70
B-B Height (mm)	263.5	271
B-B Drop (mm)	45	37
Trail (mm)	73	73
Fork Length (full) (mm)	402	402
Fork Rake/Offset (mm)	37	37
Front-Center (mm)	544	587
Chain-Stay Length (mm)	420	420
Wheelbase (mm)	960	1005
Top-Tube Length (horizontal) (mm)	490	530
Bike Stand-Over Height (mm)	610	643
Seat-Tube Length (mm)	305	342
Seat-Tube Angle (deg)	73	73
Handlebar Width (mm)	620	620
Stem Length (mm)	70	80
Seat Post Length (mm)	300	350
Crank Length (mm)	152	160

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, double-buttet, formed down tube/top tube, externally relieved head tube, forged dropouts w/replaceable hanger, disc mount
FORK	SR Suntour, coil spring w/preload adjust, 50mm of travel, 1-1/8" steel steerer, 9mm axle
STEM	Forged alloy, 20 degree rise, 4 bolt, 25.4mm clamp diameter
HANDLEBARS	Specialized, 8-degree backsweep, 4-degree upsweep, 25mm rise, 620mm width, 25.4mm
GRIPS	Specialized, Kraton
FRONT BRAKE	V-brake, alloy, linear pull
REAR BRAKE	V-brake, alloy, linear pull
FRONT DERAILLEUR	SR Suntour, 31.8mm clamp, high-mount
REAR DERAILLEUR	SRAM X3, direct mount
SHIFT LEVERS	SRAM 3.0 Comp, Grip Shift, 7-speed
CASSETTE	Shimano Tourney freewheel, 7-speed, 14-34t
CHAIN	KMC Z51, 7-speed
CRANKSET	SR Suntour XCT-JR, replaceable outer ring w/chainguard
CHAINRINGS	42/32/22T
BOTTOM BRACKET	Square taper, cartridge bearings, 68mm
RIMS	24", aluminum double-wall, 32h
FRONT HUB	Front hub, 5mm QR, steel axle, loose ball bearings, dual lock nuts w/17mm contact side, 32h
REAR HUB	Rear, 5mm QR, loose ball bearings, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Specialized Fast Trak LK Sport, 60TPI, wire bead, 24x1.8"
REAR TIRE	Specialized Fast Trak LK Sport, 60TPI, wire bead, 24x1.8"
SADDLE	Specialized Youth, steel rails
SEATPOST	Alloy, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
94E0-7211	HOTROCK 24 XC GIRL	BLK/PNK/WHT	11
94E0-7213			13

BOY'S 21-SPEED HOTROCK 24



BLK/WHT/CYAN



NRDCRED/HYP

Little legs love to climb as big ones, which is why we made the Boy's 21-Speed Hotrock 24. It has wide gear range that puts any hill within reach, which means that they'll spend more time smiling and less time sulking on the side of the trail.

- Tough, light, and durable, the A1 Premium Aluminum frame is built to stand up to years of tough riding.
- SR Suntour suspension fork offers 50mm of coil-sprung travel that smooths out bumpy, rough terrain

HOTROCK 24 BOY	
SIZE	BOYS
Stack (mm)	495
Reach (mm)	354
Head-Tube Length (mm)	130
Head-Tube Angle (deg)	69
B-B Height (mm)	221.5
B-B Drop (mm)	35
Trail (mm)	56
Fork Length (full) (mm)	376
Fork Rake/Offset (mm)	40
Front-Center (mm)	574
Chain-Stay Length (mm)	410
Wheelbase (mm)	982
Top-Tube Length (horizontal) (mm)	505
Bike Stand-Over Height (mm)	615
Seat-Tube Length (mm)	312
Seat-Tube Angle (deg)	73
Handlebar Width (mm)	600
Stem Length (mm)	70
Seat Post Length (mm)	300
Crank Length (mm)	152

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, formed top tube/down tube, forged dropouts, replaceable alloy derailleur hanger
FORK	SR Suntour, coil spring w/preload adjust, 50mm of travel, 1-1/8" steel steerer, 9mm axle
STEM	Forged alloy, 20 degree rise, 4 bolt, 25.4mm clamp diameter
HANDLEBARS	Specialized, 6-degree backsweep, 4-degree upsweep, 25.4mm
GRIPS	Specialized, Kraton, Revo type
FRONT BRAKE	V-brake, alloy, linear pull
REAR BRAKE	V-brake, alloy, linear pull
FRONT DERAILLEUR	Shimano Tourney, top swing, 31.8mm band clamp
REAR DERAILLEUR	Shimano Tourney, 7-speed
SHIFT LEVERS	Shimano Tourney, Revo-style, 7-speed
CASSETTE	Shimano, 7-speed, 14-28T
CHAIN	KMC HV500, 1/2x3/32"
CRANKSET	Forged alloy arms w/chainguard
CHAINRINGS	42/34/24T w/chainguard
BOTTOM BRACKET	68x119mm, semi-cartridge
RIMS	24", alloy single wall, pin joint, 32h
FRONT HUB	Alloy, 3/8" axle, loose ball bearings, dual lock nuts, 17mm contact side, nutted, 32h
REAR HUB	Alloy, loose ball, dual lock nuts, 17mm contact side, steel nutted axle, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Roller, 24x2.125", 30TPI, wire bead
REAR TIRE	Roller, 24x2.125", 30TPI, wire bead
SADDLE	Specialized Kids', 7mm rails w/bumper
SEATPOST	Alloy, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
B4E0-7111	HOTROCK 24 21-SPEED BOY	BLK/WHT/CYAN	11
B4017-7011	HOTROCK 24 21-SPEED BOY	NRDCRED/HYP	11

GIRL'S 21-SPEED HOTROCK 24



BLU



RFPNK/LTTUR/TUR

Little legs love to climb as big ones, which is why we made the Girl's 21-Speed Hotrock 24. It has wide gear range that puts any hill within reach, which means that they'll spend more time smiling and less time sulking on the side of the trail.

- Tough, light, and durable, the A1 Premium Aluminum frame is built to stand up to years of tough riding.
- SR Suntour suspension fork offers 50mm of coil-sprung travel that smooths out bumpy, rough terrain

HOTROCK 24 GIRL	
SIZE	GIRLS
Stack (mm)	495
Reach (mm)	354
Head-Tube Length (mm)	130
Head-Tube Angle (deg)	69
B-B Height (mm)	221.5
B-B Drop (mm)	35
Trail (mm)	56
Fork Length (full) (mm)	376
Fork Rake/Offset (mm)	40
Front-Center (mm)	574
Chain-Stay Length (mm)	410
Wheelbase (mm)	982
Top-Tube Length (horizontal) (mm)	505
Bike Stand-Over Height (mm)	559
Seat-Tube Length (mm)	312
Seat-Tube Angle (deg)	73
Handlebar Width (mm)	600
Stem Length (mm)	70
Seat Post Length (mm)	300
Crank Length (mm)	152

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, formed top tube/down tube, forged dropouts, replaceable alloy derailleur hanger
FORK	SR Suntour, coil spring w/preload adjust, 50mm of travel, 1-1/8" steel steerer, 9mm axle
STEM	Forged alloy, 20 degree rise, 4 bolt, 25.4mm clamp diameter
HANDLEBARS	Specialized, 6-degree backsweep, 4-degree upsweep, 25.4mm
GRIPS	Specialized, Kraton, Revo type
FRONT BRAKE	V-brake, alloy, linear pull
REAR BRAKE	V-brake, alloy, linear pull
FRONT DERAILLEUR	Shimano Tourney, top swing, 31.8mm band clamp
REAR DERAILLEUR	Shimano Tourney, 7-speed
SHIFT LEVERS	Shimano Tourney, Revo-style, 7-speed
CASSETTE	Shimano, 7-speed, 14-28T
CHAIN	KMC HV500, 1/2x3/32"
CRANKSET	Forged alloy arms w/chainguard
CHAINRINGS	42/34/24T w/chainguard
BOTTOM BRACKET	68x119mm, semi-cartridge
RIMS	24", alloy single wall, pin joint, 32h
FRONT HUB	Alloy, 3/8" axle, loose ball bearings, dual lock nuts, 17mm contact side, nutted, 32h
REAR HUB	Alloy, loose ball, dual lock nuts, 17mm contact side, steel nutted axle, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Roller, 24x2.125", 30TPI, wire bead
REAR TIRE	Roller, 24x2.125", 30TPI, wire bead
SADDLE	Specialized Kids', 7mm rails w/bumper
SEATPOST	Alloy, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
B4E0-7211	HOTROCK 24 21-SPEED GIRL	BLU	11
B4017-7111	HOTROCK 24 21-SPEED GIRL	RFPNK/LTTUR/TUR	11

BOY'S 7-SPEED HOTROCK 24



BLK/RED/WHT



CHAR/RED/YEL



MONGRN/NRDCRE

Your little guy might love to ride, but that doesn't mean he'll be doing Trans-Provence this summer. That's why we made our Boy's 7-Speed Hotrock 24 with plenty of gear range to tackle the neighborhood hills.

- Tough, light, and durable, the A1 Premium Aluminum frame is built to stand up to years of tough riding.
- SR Suntour suspension fork offers 50mm of coil-sprung travel that smooths out bumpy, rough terrain

HOTROCK 24 BOY	
SIZE	BOYS
Stack (mm)	495
Reach (mm)	354
Head-Tube Length (mm)	130
Head-Tube Angle (deg)	69
B-B Height (mm)	221.5
B-B Drop (mm)	35
Trail (mm)	56
Fork Length (full) (mm)	376
Fork Rake/Offset (mm)	40
Front-Center (mm)	574
Chain-Stay Length (mm)	410
Wheelbase (mm)	982
Top-Tube Length (horizontal) (mm)	505
Bike Stand-Over Height (mm)	615
Seat-Tube Length (mm)	312
Seat-Tube Angle (deg)	73
Handlebar Width (mm)	600
Stem Length (mm)	70
Seat Post Length (mm)	300
Crank Length (mm)	152

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, formed top tube/down tube, forged dropouts, replaceable alloy derailleur hanger
FORK	SR Suntour, coil spring w/preload adjust, 50mm of travel, 1-1/8" steel steerer, 9mm axle
STEM	Forged alloy, 20 degree rise, 4 bolt, 25.4mm clamp diameter
HANDLEBARS	Specialized, 6-degree backsweep, 4-degree upsweep, 25.4mm
GRIPS	Specialized, Kraton, Revo type
FRONT BRAKE	V-brake, alloy, linear pull
REAR BRAKE	V-brake, alloy, linear pull
REAR DERAILLEUR	Shimano Tourney, 7-speed
SHIFT LEVERS	Shimano Tourney, Revo-style, 7-speed
CASSETTE	Shimano, 7-speed, 14-28T
CHAIN	KMC HV500, 1/2x3/32"
CRANKSET	Forged alloy arms w/single outer chainguard
CHAINRINGS	36T w/chainguard
BOTTOM BRACKET	68x118mm, semi-cartridge, E-type
RIMS	24", alloy single wall, pin joint, 32h
FRONT HUB	Alloy, 3/8" axle, loose ball bearings, dual lock nuts, 17mm contact side, nutted, 32h
REAR HUB	Alloy, loose ball, dual lock nuts, 17mm contact side, steel nutted axle, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Roller, 24x2.125", 30TPI, wire bead
REAR TIRE	Roller, 24x2.125", 30TPI, wire bead
SADDLE	Specialized Kids', 7mm rails w/bumper
SEATPOST	Alloy, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
B4E0-6611	HOTROCK 24 7-SPEED BOY	BLK/RED/WHT	11
B4016-6811	HOTROCK 24 7-SPEED BOY	CHAR/RED/YEL	11
B4017-6011	HOTROCK 24 7-SPEED BOY	MONGRN/NRDCRE	11

GIRL'S 7-SPEED HOTROCK 24



NVY/LTTUR/BRTPNK



TUR/LTTUR/HYP

Your little girl might love to ride, but that doesn't mean she'll be riding the Continental Divide this summer. That's why we made our Girl's 7-Speed Hotrock 24 with plenty of gear range to tackle the neighborhood hills.

- Tough, light, and durable, the A1 Premium Aluminum frame is built to stand up to years of tough riding.
- SR Suntour suspension fork offers 50mm of coil-sprung travel that smooths out bumpy, rough terrain

HOTROCK 24 GIRL	
SIZE	GIRLS
Stack (mm)	495
Reach (mm)	354
Head-Tube Length (mm)	130
Head-Tube Angle (deg)	69
B-B Height (mm)	221.5
B-B Drop (mm)	35
Trail (mm)	56
Fork Length (full) (mm)	376
Fork Rake/Offset (mm)	40
Front-Center (mm)	574
Chain-Stay Length (mm)	410
Wheelbase (mm)	982
Top-Tube Length (horizontal) (mm)	505
Bike Stand-Over Height (mm)	559
Seat-Tube Length (mm)	312
Seat-Tube Angle (deg)	73
Handlebar Width (mm)	600
Stem Length (mm)	70
Seat Post Length (mm)	300
Crank Length (mm)	152

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, formed top tube/down tube, forged dropouts, replaceable alloy derailleur hanger
FORK	SR Suntour, coil spring w/preload adjust, 50mm of travel, 1-1/8" steel steerer, 9mm axle
STEM	Forged alloy, 20 degree rise, 4 bolt, 25.4mm clamp diameter
HANDLEBARS	Specialized, 6-degree backsweep, 4-degree upsweep, 25.4mm
GRIPS	Specialized, Kraton, Revo type
FRONT BRAKE	V-brake, alloy, linear pull
REAR BRAKE	V-brake, alloy, linear pull
SHIFT LEVERS	Shimano Tourney, Revo-style, 7-speed
CASSETTE	Shimano, 7-speed, 14-28T
CHAIN	KMC HV500, 1/2x3/32"
CRANKSET	Forged alloy arms w/single outer chainguard
CHAINRINGS	36T w/chainguard
BOTTOM BRACKET	68x118mm, semi-cartridge, E-type
RIMS	24", alloy single wall, pin joint, 32h
FRONT HUB	Alloy, 3/8" axle, loose ball bearings, dual lock nuts, 17mm contact side, nutted, 32h
REAR HUB	Alloy, loose ball, dual lock nuts, 17mm contact side, steel nutted axle, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Roller, 24x2.125", 30TPI, wire bead
REAR TIRE	Roller, 24x2.125", 30TPI, wire bead
SADDLE	Specialized Kids', 7mm rails w/bumper
SEATPOST	Alloy, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
B4016-6411	HOTROCK 24 7-SPEED GIRL	NVY/LTTUR/BRTPNK	11
B4017-6111	HOTROCK 24 7-SPEED GIRL	TUR/LTTUR/HYP	11

BOY'S HOTROCK 24 STREET



LTSIL/MXORG

Junior might not be ready or interested in riding trails, but what kid doesn't want to cruise the neighborhood on a miniature performance machine that would make Mom and Dad jealous? Good question. Let his bike be the next topic of conversation in the tree fort with the Boy's Hotrock 24 Street.

- Tough, light, and durable, the A1 Premium Aluminum frame is built to stand up to years of tough riding.
- A straight blade alloy fork is strong and durable, so it will withstand your little ones trying to catch air for the first time.

HOTROCK 24 BOY	
SIZE	BOYS
Stack (mm)	495
Reach (mm)	354
Head-Tube Length (mm)	130
Head-Tube Angle (deg)	69
B-B Height (mm)	221.5
B-B Drop (mm)	35
Trail (mm)	56
Fork Length (full) (mm)	376
Fork Rake/Offset (mm)	40
Front-Center (mm)	574
Chain-Stay Length (mm)	410
Wheelbase (mm)	982
Top-Tube Length (horizontal) (mm)	505
Bike Stand-Over Height (mm)	615
Seat-Tube Length (mm)	312
Seat-Tube Angle (deg)	73
Handlebar Width (mm)	600
Stem Length (mm)	70
Seat Post Length (mm)	300
Crank Length (mm)	152

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, formed top tube/down tube, forged dropouts, replaceable alloy derailleur hanger
FORK	Alloy, 1-1/8" steerer, straight blades
STEM	Forged alloy, 20-degree rise, 4-bolt, 25.4mm clamp diameter
HANDLEBARS	Specialized, 6-degree backsweep, 4-degree upsweep, 25.4mm
GRIPS	Specialized, Kraton, Revo type
FRONT BRAKE	V-brake, alloy, linear pull
REAR BRAKE	V-brake, alloy, linear pull
FRONT DERAILLEUR	Shimano Tourney, top swing, 31.8mm band clamp
REAR DERAILLEUR	Shimano Tourney, 7-speed
SHIFT LEVERS	Shimano Tourney, Revo-style, 7-speed
CASSETTE	Shimano, 7-speed, 14-28t
CHAIN	KMC HV500, 1/2x3/32"
CRANKSET	Forged alloy arms w/chainguard
CHAINRINGS	42/34/24T w/chainguard
BOTTOM BRACKET	68x118mm, semi-cartridge
RIMS	24", alloy single wall, pin joint, 32h
FRONT HUB	Alloy, 3/8" axle, loose ball bearings, dual lock nuts, 17mm contact side, nutted, 32h
REAR HUB	Alloy, loose ball, dual lock nuts, 17mm contact side, steel nutted axle, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Nimbus, 24x1.5", 30TPI, wire bead, Flak Jacket protection
REAR TIRE	Nimbus, 24x1.5", 30TPI, wire bead, Flak Jacket protection
SADDLE	Specialized Kids', 7mm rails w/bumper
SEATPOST	Alloy, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
B4017-7411	HOTROCK 24 STREET BOY	LTSIL/MXORG	11

GIRL'S HOTROCK 24 STREET



BLK/PNK

Your little girl might not be ready or interested in riding trails, but what kid doesn't want to cruise the neighborhood on a miniature performance machine that would make Mom and Dad jealous? Good question. Let her bike be the next topic of conversation at the clubhouse with the Girl's Hotrock 24 Street.

- Tough, light, and durable, the A1 Premium Aluminum frame is built to stand up to years of tough riding.
- A straight blade alloy fork is strong and durable, so it will withstand your little ones trying to catch air for the first time.

HOTROCK 24 GIRL	
SIZE	GIRLS
Stack (mm)	495
Reach (mm)	354
Head-Tube Length (mm)	130
Head-Tube Angle (deg)	69
B-B Height (mm)	221.5
B-B Drop (mm)	35
Trail (mm)	56
Fork Length (full) (mm)	376
Fork Rake/Offset (mm)	40
Front-Center (mm)	574
Chain-Stay Length (mm)	410
Wheelbase (mm)	982
Top-Tube Length (horizontal) (mm)	505
Bike Stand-Over Height (mm)	559
Seat-Tube Length (mm)	312
Seat-Tube Angle (deg)	73
Handlebar Width (mm)	600
Stem Length (mm)	70
Seat Post Length (mm)	300
Crank Length (mm)	152

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, formed top tube/down tube, forged dropouts, replaceable alloy derailleur hanger
FORK	Alloy, 1-1/8" steerer, straight blades
STEM	Forged alloy, 20-degree rise, 4-bolt, 25.4mm clamp diameter
HANDLEBARS	Specialized, 6-degree backsweep, 4-degree upsweep, 25.4mm
GRIPS	Specialized, Kraton, Revo type
FRONT BRAKE	V-brake, alloy, linear pull
REAR BRAKE	V-brake, alloy, linear pull
FRONT DERAILLEUR	Shimano Tourney, top swing, 31.8mm band clamp
REAR DERAILLEUR	Shimano Tourney, 7-speed
SHIFT LEVERS	Shimano Tourney, Revo-style, 7-speed
CASSETTE	Shimano, 7-speed, 14-28t
CHAIN	KMC HV500, 1/2x3/32"
CRANKSET	Forged alloy arms w/chainguard
CHAINRINGS	42/34/24T w/chainguard
BOTTOM BRACKET	68x118mm, semi-cartridge
RIMS	24", alloy single wall, pin joint, 32h
FRONT HUB	Alloy, 3/8" axle, loose ball bearings, dual lock nuts, 17mm contact side, nutted, 32h
REAR HUB	Alloy, loose ball, dual lock nuts, 17mm contact side, steel nutted axle, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Nimbus, 24x1.5", 30TPI, wire bead, Flak Jacket protection
REAR TIRE	Nimbus, 24x1.5", 30TPI, wire bead, Flak Jacket protection
SADDLE	Specialized Kids', 7mm rails w/bumper
SEATPOST	Alloy, single bolt, 27.2mm

PART NO.	DESCRIPTION	COLOR	SIZE
B4E0-8111	HOTROCK 24 STREET GIRL	BLK/PNK	11

BOY'S 6-SPEED HOTROCK 20



BLU/WHT/BLK



BLKHYPCKL/EMDGRN



RED/WHT/BLK

Your little tike might love to ride, but given that they're still growing like a weed, the big kid trail shredder bike can probably wait a few years. That's why we made our Boy's 6-Speed Hotrock 20 with plenty of gear range to tackle the neighborhood trails.

- Tough, light, and durable, the A1 Premium Aluminum frame is built to stand up to years of tough riding.
- SR Suntour suspension fork offers 40mm of coil-sprung travel that smooths out bumpy, rough terrain

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, 20", formed top tube/down tube, forged dropouts, replaceable alloy derailleur hanger
FORK	SR Suntour, coil spring w/preload adjust, 40mm of travel, 1-1/8" steel steerer, 9mm axle
STEM	Forged alloy, 20-degree rise, 4-bolt, 25.4mm clamp diameter
HANDLEBARS	Specialized Kids', steel, 10-degree backsweep, 4-degree upsweep, 25mm rise, 25.4mm
GRIPS	Specialized, Kraton, Revo type
FRONT BRAKE	V-brake, alloy, linear pull
REAR BRAKE	V-brake, alloy, linear pull
REAR DERAILLEUR	V-brake, alloy, linear pull
SHIFT LEVERS	Shimano Revo-Shift
CASSETTE	Shimano Tourney freewheel, 6-speed, 14-28t
CHAIN	KMC HV500, 1/2x3/32"
CRANKSET	Forged alloy arms w/single outer chainguard
CHAINRINGS	36T w/chainguard
BOTTOM BRACKET	68mmx118mm, semi-cartridge, E-type
RIMS	20", alloy single wall, pin joint, 32h
FRONT HUB	Alloy, 3/8" axle, loose ball bearings, dual lock nuts, 17mm contact side, nutted, 32h
REAR HUB	Alloy, loose ball, dual lock nuts, 17mm contact side, steel nutted axle, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Roller, 20x2.125", 30TPI, wire bead
REAR TIRE	Roller, 20x2.125", 30TPI, wire bead
SADDLE	Specialized Kids', 7mm rails w/bumper
SEATPOST	Alloy, single bolt, 27.2mm

HOTROCK 20 6SPD BOY	
SIZE	6-SPD BOY
Seat Tube Length, Center to Top (mm)	279
Top Tube Length (Horizontal) (mm)	465
Top Tube Length (Actual) (mm)	449
Bottom Bracket Drop (mm)	20
Bottom Bracket Height (mm)	237
Chainstay Length (mm)	390
Seat Tube Angle (deg)	72
Head Tube Angle (deg)	69
Rake (mm)	40
Wheel Base (mm)	916
Standover Height (mm)	555
Head Tube Length (mm)	110
Handlebar Width (mm)	600
Stem Length (mm)	70
Seat Post Length (mm)	300
Crank Length (mm)	127

PART NO.	DESCRIPTION	COLOR	SIZE
B4E0-4109	HOTROCK 20 6-SPEED BOY	BLU/WHT/BLK	9
B4017-3009	HOTROCK 20 6-SPEED BOY	BLKHYPCKL/EMDGRN	9
B4015-4209	HOTROCK 20 6-SPEED BOY	RED/WHT/BLK	9

GIRL'S 6-SPEED HOTROCK 20



PNK



PRP/NENBLU/WHT

Your little girl might love to ride, but given that they're still growing like a bean sprout, the big girl trail shredder bike can probably wait a few years. That's why we made our Girl's 6-Speed Hotrock 20 with plenty of gear range to tackle the neighborhood trails.

- Tough, light, and durable, the A1 Premium Aluminum frame is built to stand up to years of tough riding.
- SR Suntour suspension fork offers 40mm of coil-sprung travel that smooths out bumpy, rough terrain

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, 20", formed top tube/down tube, forged dropouts, replaceable alloy derailleur hanger
FORK	SR Suntour, coil spring w/preload adjust, 40mm of travel, 1-1/8" steel steerer, 9mm axle
STEM	Forged alloy, 20-degree rise, 4-bolt, 25.4mm clamp diameter
HANDLEBARS	Specialized Kids', steel, 10-degree backsweep, 4-degree upsweep, 25mm rise, 25.4mm
GRIPS	Specialized, Kraton, Revo type
FRONT BRAKE	V-brake, alloy, linear pull
REAR BRAKE	V-brake, alloy, linear pull
REAR DERAILLEUR	Shimano Tourney, 6-speed
SHIFT LEVERS	Shimano Revo-Shift
CASSETTE	Shimano Tourney freewheel, 6-speed, 14-28t
CHAIN	KMC HV500, 1/2x3/32"
CRANKSET	Forged alloy arms w/single outer chainguard
CHAINRINGS	36T w/chainguard
BOTTOM BRACKET	68mmx118mm, semi-cartridge, E-type
RIMS	20", alloy single wall, pin joint, 32h
FRONT HUB	Alloy, 3/8" axle, loose ball bearings, dual lock nuts, 17mm contact side, nutted, 32h
REAR HUB	Alloy, loose ball, dual lock nuts, 17mm contact side, steel nutted axle, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Roller, 20x2.125", 30TPI, wire bead
REAR TIRE	Roller, 20x2.125", 30TPI, wire bead
SADDLE	Specialized Kids', 7mm rails w/bumper
SEATPOST	Alloy, single bolt, 27.2mm

HOTROCK 20 6SPD GIRL	
SIZE	6-SPD GIRL
Seat Tube Length, Center to Top (mm)	279
Top Tube Length (Horizontal) (mm)	465
Top Tube Length (Actual) (mm)	463
Bottom Bracket Drop (mm)	20
Bottom Bracket Height (mm)	237
Chainstay Length (mm)	390
Seat Tube Angle (deg)	72
Head Tube Angle (deg)	69
Rake (mm)	40
Wheel Base (mm)	916
Standover Height (mm)	514
Head Tube Length (mm)	110
Handlebar Width (mm)	600
Stem Length (mm)	70
Seat Post Length (mm)	300
Crank Length (mm)	127

PART NO.	DESCRIPTION	COLOR	SIZE
B4E0-4209	HOTROCK 20 6-SPEED GIRL	PNK	9
B4017-3109	HOTROCK 20 6-SPEED GIRL	PRP/NENBLU/WHT	9

BOY'S HOTROCK 20 STREET



GRN/WHT/BLK

Your little dude might not be ready or interested in riding trails, but what kid doesn't want to cruise the neighborhood on a miniature performance machine that would make Mom and Dad jealous? Good question. Let his bike be the next topic of conversation at the tree fort with the Boy's Hotrock 20 Street.

- Tough, light, and durable, the A1 Premium Aluminum frame is built to stand up to years of tough riding.
- A straight blade alloy fork is strong and durable, so it will withstand your little ones trying to catch air for the first time.

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, 20", formed top tube/down tube, forged dropouts, replaceable alloy derailleur hanger
FORK	Alloy, 1-1/8" steerer, straight blades
STEM	Forged alloy, 20-degree rise, 4-bolt, 25.4mm clamp diameter
HANDLEBARS	Specialized Kids', steel, 10-degree backsweep, 4-degree upsweep, 25mm rise, 25.4mm
GRIPS	Specialized, Kraton, Revo type
FRONT BRAKE	V-brake, alloy, linear pull
REAR BRAKE	V-brake, alloy, linear pull
SHIFT LEVERS	Shimano Revo-Shift
CASSETTE	Shimano, 6-speed, 14-28t
CHAIN	KMC HV500, 1/2x3/32"
CRANKSET	Forged alloy arms w/chainguard
CHAINRINGS	36T w/chainguard
BOTTOM BRACKET	68mmx118mm, semi-cartridge
RIMS	20", alloy single wall, pin joint, 32h
FRONT HUB	Alloy, 3/8" axle, loose ball bearings, dual lock nuts, 17mm contact side, nutted, 32h
REAR HUB	Alloy, loose ball, dual lock nuts, 17mm contact side, steel nutted axle, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Nimbus, 20x1.5", 30TPI, wire bead, Flak Jacket protection
REAR TIRE	Nimbus, 20x1.5", 30TPI, wire bead, Flak Jacket protection
SADDLE	Specialized Kids', 7mm rails w/bumper
SEATPOST	Alloy, single bolt, 27.2mm

HOTROCK 20 6SPD BOY	
SIZE	6-SPD BOY
Seat Tube Length, Center to Top (mm)	279
Top Tube Length (Horizontal) (mm)	465
Top Tube Length (Actual) (mm)	449
Bottom Bracket Drop (mm)	20
Bottom Bracket Height (mm)	237
Chainstay Length (mm)	390
Seat Tube Angle (deg)	72
Head Tube Angle (deg)	69
Rake (mm)	40
Wheel Base (mm)	916
Standover Height (mm)	555
Head Tube Length (mm)	110
Handlebar Width (mm)	600
Stem Length (mm)	70
Seat Post Length (mm)	300
Crank Length (mm)	127

PART NO.	DESCRIPTION	COLOR	SIZE
B4E0-5109	HOTROCK 20 STREET BOY	GRN/WHT/BLK	9

GIRL'S HOTROCK 20 STREET



PNK/BLU

Your little girl might not be ready or interested in riding trails, but what kid doesn't want to cruise the neighborhood on a miniature performance machine that would make Mom and Dad jealous? Good question. Let her bike be the next topic of conversation at the clubhouse with the Girl's Hotrock 20 Street.

- Tough, light, and durable, the A1 Premium Aluminum frame is built to stand up to years of tough riding.
- A straight blade alloy fork is strong and durable, so it will withstand your little ones trying to catch air for the first time.

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, 20", formed top tube/down tube, forged dropouts, replaceable alloy derailleur hanger
FORK	Alloy, 1-1/8" steerer, straight blades
STEM	Forged alloy, 20-degree rise, 4-bolt, 25.4mm clamp diameter
HANDLEBARS	Specialized Kids', steel, 10-degree backsweep, 4-degree upsweep, 25mm rise, 25.4mm
GRIPS	Specialized, Kraton, Revo type
FRONT BRAKE	V-brake, alloy, linear pull
REAR BRAKE	V-brake, alloy, linear pull
SHIFT LEVERS	Shimano Revo-Shift
CASSETTE	Shimano, 6-speed, 14-28t
CHAIN	KMC HV500, 1/2x3/32"
CRANKSET	Forged alloy arms w/chainguard
CHAINRINGS	36T w/chainguard
BOTTOM BRACKET	68mmx118mm, semi-cartridge
RIMS	20", alloy single wall, pin joint, 32h
FRONT HUB	Alloy, 3/8" axle, loose ball bearings, dual lock nuts, 17mm contact side, nutted, 32h
REAR HUB	Alloy, loose ball, dual lock nuts, 17mm contact side, steel nutted axle, 32h
SPOKES	Stainless, 14g
FRONT TIRE	Nimbus, 20x1.5", 30TPI, wire bead, Flak Jacket protection
REAR TIRE	Nimbus, 20x1.5", 30TPI, wire bead, Flak Jacket protection
SADDLE	Specialized Kids', 7mm rails w/bumper
SEATPOST	Alloy, single bolt, 27.2mm

HOTROCK 20 6SPD GIRL	
SIZE	6-SPD GIRL
Seat Tube Length, Center to Top (mm)	279
Top Tube Length (Horizontal) (mm)	465
Top Tube Length (Actual) (mm)	463
Bottom Bracket Drop (mm)	20
Bottom Bracket Height (mm)	237
Chainstay Length (mm)	390
Seat Tube Angle (deg)	72
Head Tube Angle (deg)	69
Rake (mm)	40
Wheel Base (mm)	916
Standover Height (mm)	514
Head Tube Length (mm)	110
Handlebar Width (mm)	600
Stem Length (mm)	70
Seat Post Length (mm)	300
Crank Length (mm)	127

PART NO.	DESCRIPTION	COLOR	SIZE
B4E0-5209	HOTROCK 20 STREET GIRL	PNK/BLU	9

BOY'S HOTROCK 20 COASTER



BLK/WHT/BLU



RED/WHT/BLK



WHT/BLU/BLK

Chances are, your first bike had a coaster brake. They're easy to use, and honestly, you can't beat the awesome skids that you can do with them. If you're feeling overwhelmed with nostalgia right now, don't worry—Junior can get one, too, with the Boy's Hotrock 20 Coaster.

- Tough, light, and durable, the A1 Premium Aluminum frame is built to stand up to years of tough riding.
- A Hi-Ten steel fork is strong and durable, so it will withstand your little ones trying to catch air for the first time.

SPECS

All specs are subject to change without notice.

FRAME	Specialized A1 Premium Aluminum, 20" singlespeed coaster, formed top tube/down tube, forged horizontal dropouts
FORK	Hi-Ten steel, 1-1/8" threadless steerer, 3/8" axle dropouts
STEM	Ahead, alloy, 1-1/8" steerer, 22.2mm clamp, 37mm extension
HANDLEBARS	BMX, steel, 10-degree backsweep, 4-degree upsweep, 130mm rise, 560mm width, 22.2mm
GRIPS	Specialized, Kraton, closed end, 105mm
BRAKE	Rear V-brake, alloy, linear pull w/rear coaster brake
CHAIN	KMC Z510, single-speed, anti-drop, 1/2"x1/8"
CRANKSET	Hi-Ten steel, OPC
CHAINRINGS	36T
BOTTOM BRACKET	Steel, loose ball bearings
RIMS	20", alloy single wall, pin joint, 32h
FRONT HUB	Steel, nutted axle, 36h
REAR HUB	Steel, coaster brake, nutted axle, 36h
SPOKES	Stainless, 14g
FRONT TIRE	Specialized Rhythm Lite, 20x2.0", 30TPI, wire bead
REAR TIRE	Specialized Rhythm Lite, 20x2.0"
SADDLE	Specialized Kids', 7mm rails w/clamp
SEATPOST	Steel, 25.4mm

PART NO.	DESCRIPTION	COLOR	SIZE
B4E0-3609	HOTROCK 20 COASTER BOY	BLK/WHT/BLU	9
B4E0-3909	HOTROCK 20 COASTER BOY	RED/WHT/BLK	9
B4016-3009	HOTROCK 20 COASTER BOY	WHT/BLU/BLK	9

HOTROCK 20 COASTER BOY

SIZE	BOYS
Seat Tube Length, Center to Top (mm)	241
Top Tube Length (Horizontal) (mm)	456
Top Tube Length (Actual) (mm)	438
Bottom Bracket Height (mm)	227
Chainstay Length (mm)	386
Seat Tube Angle (deg)	72
Head Tube Angle (deg)	70
Rake (mm)	23.5
Standover Height (mm)	505
Head Tube Length (mm)	80
Handlebar Width (mm)	560
Stem Length (mm)	37
Seat Post Length (mm)	220
Crank Length (mm)	114

GIRL'S HOTROCK 20 COASTER



PNK/WHT



METWHT/MXORG/CYN



PUR/WHT

Chances are, your first bike had a coaster brake. They're easy to use, and honestly, you can't beat the awesome skids that you can do with them. If you're feeling overwhelmed with nostalgia right now, don't worry—your little girl can get one, too, with the Girl's Hotrock 20 Coaster.

- Tough, light, and durable, the A1 Premium Aluminum frame is built to stand up to years of tough riding.
- A Hi-Ten steel fork is strong and durable, so it will withstand your little ones trying to catch air for the first time.

SPECS

All specs are subject to change without notice.

FRAME	Specialized A1 Premium Aluminum, 20" singlespeed coaster, formed top tube/down tube, forged horizontal dropouts
FORK	Hi-Ten steel, 1-1/8" threadless steerer, 3/8" axle dropouts
STEM	Ahead, alloy, 1-1/8" steerer, 22.2mm clamp, 37mm extension
HANDLEBARS	BMX, steel, 10-degree backsweep, 4-degree upsweep, 130mm rise, 560mm width, 22.2mm
GRIPS	Specialized, Kraton, closed end, 105mm
BRAKE	Rear V-brake, alloy, linear pull w/rear coaster brake
CHAIN	KMC Z510, single-speed, anti-drop, 1/2"x1/8"
CRANKSET	Hi-Ten steel, OPC
CHAINRINGS	36T
BOTTOM BRACKET	Steel, loose ball bearings
RIMS	20", alloy single wall, pin joint, 32h
FRONT HUB	Steel, nudded axle, 36h
REAR HUB	Steel, coaster brake, nudded axle, 36h
SPOKES	Stainless, 14g
FRONT TIRE	Specialized Rhythm Lite, 20x2.0", 30TPI, wire bead
REAR TIRE	Specialized Rhythm Lite, 20x2.0", 30TPI, wire bead
SADDLE	Specialized Kids', 7mm rails w/clamp
SEATPOST	Steel, 25.4mm

PART NO.	DESCRIPTION	COLOR	SIZE
B4E0-3109	HOTROCK 20 COASTER GIRL	PNK/WHT	9
B4016-3209	HOTROCK 20 COASTER GIRL	METWHT/MXORG/CYN	9
B4E0-3209	HOTROCK 20 COASTER GIRL	PUR/WHT	9

HOTROCK 20 COASTER GIRL

SIZE	GIRLS
Seat Tube Length, Center to Top (mm)	241
Top Tube Length (Horizontal) (mm)	456
Top Tube Length (Actual) (mm)	446
Bottom Bracket Height (mm)	227
Chainstay Length (mm)	386
Seat Tube Angle (deg)	72
Head Tube Angle (deg)	70
Rake (mm)	23.5
Standover Height (mm)	476
Head Tube Length (mm)	80
Handlebar Width (mm)	560
Stem Length (mm)	37
Seat Post Length (mm)	220
Crank Length (mm)	114

BOY'S HOTROCK 16 COASTER



BLK/CYAN/ORG



CYN/HYP/BLK



RED/WHT/BLK

Chances are, your first bike had a coaster brake. They're easy to use, and honestly, you can't beat the awesome skids that you can do with them. If you're feeling overwhelmed with nostalgia right now, don't worry—Junior can get one, too, with the Boy's Hotrock 16 Coaster.

- Tough, light, and durable, the A1 Premium Aluminum frame is built to stand up to years of tough riding.
- A steel coaster brake makes slowing down and stopping as easy as can be.

SPECS

All specs are subject to change without notice.

FRAME	Specialized A1 Premium Aluminum, 16" singlespeed coaster, formed tubes, kickstand mount, horizontal dropouts
FORK	Hi-Ten steel, 1-1/8" threaded steerer, 3/8" axle dropouts
STEM	Ahead, alloy, 1-1/8" steerer, 22.2mm clamp, 37mm extension
HANDLEBARS	BMX, steel, 10-degree backsweep, 4-degree upsweep, 115mm rise, 520mm width, 22.2mm
GRIPS	Specialized, Kraton, closed end, 105mm
BRAKE	Rear coaster brake
CHAIN	KMC Z510, single-speed, anti-drop, 1/2"x1/8"
CRANKSET	Hi-Ten steel, OPC
CHAINRINGS	26T
BOTTOM BRACKET	Steel, loose ball bearings
RIMS	16", alloy single wall, pin joint, 28h
FRONT HUB	Steel, nutted axle, 28h
REAR HUB	Steel, coaster brake, nutted axle, 28h
SPOKES	Stainless, 14g
FRONT TIRE	Rhythm Lite, 16x2.0", 30TPI, wire bead
REAR TIRE	Rhythm Lite, 16x2.0", 30TPI, wire bead
SADDLE	Specialized Kids', integrated handle, 25.4mm integrated steel seatpost
SEATPOST	Steel, 25.4mm, integrated w/ saddle

PART NO.	DESCRIPTION	COLOR	SIZE
B4E0-2107	HOTROCK 16 COASTER BOY	BLK/CYAN/ORG	7
B4016-2007	HOTROCK 16 COASTER BOY	CYN/HYP/BLK	7
B4E0-2707	HOTROCK 16 COASTER BOY	RED/WHT/BLK	7

HOTROCK COASTER 16 BOY

SIZE	16 BOY
Seat Tube Length, Center to Top (mm)	210
Top Tube Length (Horizontal) (mm)	395
Top Tube Length (Actual) (mm)	377
Bottom Bracket Height (mm)	189
Chainstay Length (mm)	310
Seat Tube Angle (deg)	71
Head Tube Angle (deg)	70
Rake (mm)	5
Standover Height (mm)	426
Head Tube Length (mm)	80
Handlebar Width (mm)	520
Stem Length (mm)	37
Seat Post Length (mm)	230
Crank Length (mm)	3.5

GIRL'S HOTROCK 16 COASTER



PNK/PUR/WHT



PRLTTUR/TUR/GLDORG



PUR/WHT

Chances are, your first bike had a coaster brake. They're easy to use, and honestly, you can't beat the awesome skids that you can do with them. If you're feeling overwhelmed with nostalgia right now, don't worry—your little girl can get one, too, with the Girl's Hotrock 16 Coaster.

- Tough, light, and durable, the A1 Premium Aluminum frame is built to stand up to years of tough riding.
- A steel coaster brake makes slowing down and stopping as easy as can be.

SPECS

All specs are subject to change without notice.

FRAME	Specialized A1 Premium Aluminum, 16" singlespeed coaster, formed tubes, kickstand mount, horizontal dropouts
FORK	Hi-Ten steel, 1-1/8" threaded steerer, 3/8" axle dropouts
STEM	Ahead, alloy, 1-1/8" steerer, 22.2mm clamp, 37mm extension
HANDLEBARS	BMX, steel, 10-degree backsweep, 4-degree upsweep, 115mm rise, 520mm width, 22.2mm
GRIPS	Specialized, Kraton, closed end, 105mm
BRAKE	Rear coaster brake
CHAIN	KMC Z510, single-speed, anti-drop, 1/2"x1/8"
CRANKSET	Hi-Ten steel, OPC
CHAINRINGS	26T
BOTTOM BRACKET	Steel, loose ball bearings
RIMS	16", alloy single wall, pin joint, 32h
FRONT HUB	Steel, nutted axle, 28h
REAR HUB	Steel, coaster brake, nutted axle, 28h
SPOKES	Stainless, 14g
FRONT TIRE	Rhythm Lite, 16x2.0", 30TPI, wire bead
REAR TIRE	Rhythm Lite, 16x2.0", 30TPI, wire bead
SADDLE	Specialized Kids', integrated handle, 25.4mm integrated steel seatpost
SEATPOST	Steel, 25.4mm, integrated w/ saddle

PART NO.	DESCRIPTION	COLOR	SIZE
B4E0-2207	HOTROCK 16 COASTER GIRL	PNK/PUR/WHT	7
B4016-2407	HOTROCK 16 COASTER GIRL	PRLTTUR/TUR/GLDORG	7
B4E0-2607	HOTROCK 16 COASTER GIRL	PUR/WHT	7

HOTROCK COASTER 16 GIRL

SIZE	16 GIRL
Seat Tube Length, Center to Top (mm)	210
Top Tube Length (Horizontal) (mm)	395
Top Tube Length (Actual) (mm)	387
Bottom Bracket Height (mm)	189
Chainstay Length (mm)	310
Seat Tube Angle (deg)	71
Head Tube Angle (deg)	70
Rake (mm)	5
Standover Height (mm)	393
Head Tube Length (mm)	80
Handlebar Width (mm)	520
Stem Length (mm)	37
Seat Post Length (mm)	230
Crank Length (mm)	3.5

BOY'S HOTROCK 12 COASTER



BLU/WHT/BLK



ORG/WHT/BLK

Chances are, your first bike had a coaster brake. They're easy to use, and honestly, you can't beat the awesome skids that you can do with them. If you're feeling overwhelmed with nostalgia right now, don't worry—Junior can get one, too, with the Boy's Hotrock 12 Coaster.

- Tough, light, and durable, the A1 Premium Aluminum frame is built to stand up to years of tough riding.
- A steel coaster brake makes slowing down and stopping as easy as can be.

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, 12" singlespeed coaster, formed tubes, horizontal dropouts
FORK	Hi-Ten steel, 1" threaded steerer, 3/8" axle dropouts
STEM	Quill, alloy, 22.2mm clamp
HANDLEBARS	Specialized Kids', steel, 10-degree backsweep, 4-degree upsweep, 55mm rise, 22.2mm
GRIPS	Specialized, Kraton, closed end, 105mm
BRAKE	Rear coaster brake
CHAIN	KMC Z510, single-speed, anti-drop, 1/2"x1/8"
CRANKSET	Hi-Ten steel, OPC
CHAINRINGS	26T
BOTTOM BRACKET	Steel, loose ball bearings
RIMS	12", alloy single wall, pin joint, 32h
FRONT HUB	Steel, nutted axle, 36h
REAR HUB	Steel, coaster brake, nutted axle, 28h
SPOKES	Stainless, 14g
FRONT TIRE	Rhythm Lite, 12x2.0", 30TPI, wire bead
REAR TIRE	Rhythm Lite, 12x2.0", 30TPI, wire bead
SADDLE	Specialized Kids', integrated handle, 25.4mm integrated steel seatpost
SEATPOST	Steel, 25.4mm, integrated w/ saddle

PART NO.	DESCRIPTION	COLOR	SIZE
B4E0-1106	HOTROCK 12 COASTER BOY	BLU/WHT/BLK	6
B4E0-1706	HOTROCK 12 COASTER BOY	ORG/WHT/BLK	6

HOTROCK COASTER 12 BOY

SIZE	12 BOY
Seat Tube Length, Center to Top (mm)	169
Top Tube Length (Horizontal) (mm)	349
Top Tube Length (Actual) (mm)	331
Bottom Bracket Height (mm)	173
Chainstay Length (mm)	272
Seat Tube Angle (deg)	71
Head Tube Angle (deg)	70
Rake (mm)	5
Standover Height (mm)	352
Head Tube Length (mm)	80
Handlebar Width (mm)	470
Stem Length (mm)	35
Seat Post Length (mm)	190
Crank Length (mm)	3

GIRL'S HOTROCK 12 COASTER



PNK/WHT



WHT/PUR

Chances are, your first bike had a coaster brake. They're easy to use, and honestly, you can't beat the awesome skids that you can do with them. If you're feeling overwhelmed with nostalgia right now, don't worry—your little girl can get one, too, with the Girl's Hotrock 12 Coaster.

- Tough, light, and durable, the A1 Premium Aluminum frame is built to stand up to years of tough riding.
- A steel coaster brake makes slowing down and stopping as easy as can be.

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, 12" singlespeed coaster, formed tubes, horizontal dropouts
FORK	Hi-Ten steel, 1" threaded steerer, 3/8" axle dropouts
STEM	Quill, alloy, 22.2mm clamp
HANDLEBARS	Specialized Kids', steel, 10-degree backsweep, 4-degree upsweep, 55mm rise, 22.2mm
GRIPS	Specialized, Kraton, closed end, 105mm
BRAKE	Rear coaster brake
CHAIN	KMC Z510, single-speed, anti-drop, 1/2"x1/8"
CRANKSET	Hi-Ten steel, OPC
CHAINRINGS	26T
BOTTOM BRACKET	Steel, loose ball bearings
RIMS	12", alloy single wall, pin joint, 16h
FRONT HUB	Steel, nutted axle, 16h
REAR HUB	Steel, coaster brake, nutted axle, 16h
SPOKES	Stainless, 14g
FRONT TIRE	Rhythm Lite, 12x2.0", 30TPI, wire bead
REAR TIRE	Rhythm Lite, 12x2.0", 30TPI, wire bead
SADDLE	Specialized Kids', integrated handle, 25.4mm integrated steel seatpost
SEATPOST	Steel, 25.4mm, integrated w/ saddle

PART NO.	DESCRIPTION	COLOR	SIZE
B4E0-1206	HOTROCK 12 COASTER GIRL	PNK/WHT	6
B4E0-1606	HOTROCK 12 COASTER GIRL	WHT/PUR	6

HOTROCK COASTER 12 GIRL

SIZE	12 GIRL
Seat Tube Length, Center to Top (mm)	169
Top Tube Length (Horizontal) (mm)	349
Top Tube Length (Actual) (mm)	338
Bottom Bracket Height (mm)	173
Chainstay Length (mm)	272
Seat Tube Angle (deg)	71
Head Tube Angle (deg)	70
Rake (mm)	5
Standover Height (mm)	323
Head Tube Length (mm)	80
Handlebar Width (mm)	470
Stem Length (mm)	35
Seat Post Length (mm)	190
Crank Length (mm)	3

BOY'S HOTWALK



MONGRN/NRDCCRED



RED/WHT/BLK

If we were to stop and think about it, learning to ride back in the day bordered on a traumatic event. The crashes, oh the crashes. These days, however, kids have it easy with awesome little bikes like our Boy's Hotwalk.

- Durable and tough, the A1 Premium Aluminum walking frame is designed specifically for little ones to scoot around safely.
- A Hi-Ten steel fork is strong and durable, so it will withstand your little ones trying to catch air for the first time.

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, 12" walking bike, formed tubes, horizontal dropouts
FORK	Hi-Ten steel, 1" threaded steerer, 3/8" axle dropouts
STEM	Quill, alloy, 22.2mm clamp
HANDLEBARS	Specialized Kids', steel, 10-degree backsweep, 4-degree upsweep, 22.2mm
GRIPS	Specialized, Kraton, closed end, 105mm
RIMS	12", alloy single wall, pin joint, 16h
FRONT HUB	Steel, nutted axle, 16h
REAR HUB	Steel, nutted axle, 16h
SPOKES	Stainless, 14g
FRONT TIRE	Rhythm Lite, 12x2.0", 30TPI, wire bead
REAR TIRE	Rhythm Lite, 12x2.0", 30TPI, wire bead
SADDLE	Specialized Kids', 22.2mm integrated steel seatpost
SEATPOST	Steel, 22.2mm, integrated w/ saddle

PART NO.	DESCRIPTION	COLOR	SIZE
B4017-0005	HOTWALK BOY	MONGRN/NRDCCRED	5
B4E0-0605	HOTWALK BOY	RED/WHT/BLK	5

HOTWALK BOY

SIZE	BOY
Seat Tube Length, Center to Top (mm)	157
Top Tube Length (Horizontal) (mm)	295
Top Tube Length (Actual) (mm)	288
Chainstay Length (mm)	222
Seat Tube Angle (deg)	71
Head Tube Angle (deg)	69
Wheel Base (mm)	520
Rake (mm)	5
Standover Height (mm)	275
Head Tube Length (mm)	70
Handlebar Width (mm)	400
Stem Length (mm)	35
Seat Post Length (mm)	190

GIRL'S HOTWALK



LTTUR/HYP/TUR



PNK

If we were to stop and think about it, learning to ride back in the day bordered on a traumatic event. The crashes, oh the crashes. These days, however, kids have it easy with awesome little bikes like our Girl's Hotwalk.

- Durable and tough, the A1 Premium Aluminum walking frame is designed specifically for little ones to scoot around safely.
- A Hi-Ten steel fork is strong and durable, so it will withstand your little ones trying to catch air for the first time.

SPECS	All specs are subject to change without notice.
FRAME	Specialized A1 Premium Aluminum, 12" walking bike, formed tubes, horizontal dropouts
FORK	Hi-Ten steel, 1" threaded steerer, 3/8" axle dropouts
STEM	Quill, alloy, 22.2mm clamp
HANDLEBARS	Specialized Kids', steel, 10-degree backsweep, 4-degree upsweep, 22.2mm
GRIPS	Specialized, Kraton, closed end, 105mm
RIMS	12", alloy single wall, pin joint, 16h
FRONT HUB	Steel, nutted axle, 16h
REAR HUB	Steel, nutted axle, 16h
SPOKES	Stainless, 14g
FRONT TIRE	Rhythm Lite, 12x2.0", 30TPI, wire bead
REAR TIRE	Rhythm Lite, 12x2.0", 30TPI, wire bead
SADDLE	Specialized Kids', 22.2mm integrated steel seatpost

PART NO.	DESCRIPTION	COLOR	SIZE
B4017-0105	HOTWALK GIRL	LTTUR/HYP/TUR	5
B4E0-0105	HOTWALK GIRL	PNK	5

HOTWALK GIRL

SIZE	GIRL
Seat Tube Length, Center to Top (mm)	157
Top Tube Length (Horizontal) (mm)	295
Top Tube Length (Actual) (mm)	0
Chainstay Length (mm)	222
Seat Tube Angle (deg)	71
Head Tube Angle (deg)	69
Wheel Base (mm)	520
Rake (mm)	5
Standover Height (mm)	226
Head Tube Length (mm)	70
Handlebar Width (mm)	400
Stem Length (mm)	35
Seat Post Length (mm)	190