



# دهانات الجوهرة ALJAWHARA PAINTS

## EMULSION PUTTY

it is emulsion putty based on special polymer which gives flexibility & smoothing and filling for fine cracks, used for interior walls.

### PHYSICAL DATA

Appearance	: Matt putty
Color	: white
Density	: 1.6 Kg / Ltr.
Drying Time	{ Dust Dry: 1 hours } { Hard Dry: 2 hours } } Depends on Temperature & Humidity
Flammability	: Non Flammable

### APPLICATION DATA

Tools	: Trowel or putty knife.
Thinning	: By water
Coverage	: 2 - 2.5 sq.m / Ltr. (at 200 microns DFT) Depends on nature of surface.
Storage	: 18 months in a cool place away from direct sunshine.

### BEFORE PAINTING OPERATION:

- The surface to be painted must be clean, free from dirt, loose materials, dust and grease
- Suitable for use on all interior cementinous surfaces
- To ensure good results, apply several layers
- Do not over use of putty. A thick layer of putty may cause crack in the top coat after dry ing.
- Cleaning of used tools By water



الشركة الكيماوية للتشكيلات الملونة المحدودة  
Chemical Company for Colour Assortement LTD.

[www.aljawharapaints.com](http://www.aljawharapaints.com)

[info@aljawharapaints.com](mailto:info@aljawharapaints.com)

Kingdom of Saudi Arabia TollFree 920000008

المملكة العربية السعودية الرقم الموحد: ٩٢٠٠٠٠٠٠٨

